

SAKURA AI Engine RAG API (2026-06-29)

Download OpenAPI specification:[Download OpenAPI Spec\(YAML\)](#)[Download OpenAPI Spec\(JSON\)](#)

SAKURA AI Engine RAG API

đôçűń ěňť' _łĩ Ț

AUTHORIZATIONS:

BearerAuth

QUERY PARAMETERS

model	string
name	string
page	integer A page number within the paginated result set.
page_size	integer Number of results to return per page.
tag	string

Responses

200

RESPONSE SCHEMA: application/json

meta	object
required	
results	Array of objects (DocumentList)

required

GET /v1/documents/

Response samples

200

Content-Type

application/json

```
{
  "meta": {
    "page": 0,
    "page_size": 0,
    "total_pages": 0,
    "count": 0,
    "next": "http://example.com",
    "previous": "http://example.com"
  },
  "results": [
    {}
  ]
}
```

document_id

AUTHORIZATIONS:

BearerAuth

PATH PARAMETERS

id

required

string <uuid>

A UUID string identifying this document.

Responses

200

RESPONSE SCHEMA: application/json

id	string <uuid>
required	
created_at	string <date-time>
required	
status	string (ステータス) Enum: "pending" "processing" "available" "deleted" "error" • pending - Pending • processing - Processing • available - Available • deleted - Deleted • error - Error
required	
name	string <= 255 characters
required	
model	string
required	
chunk_size	integer
required	
chunk_count	integer
required	
tags	Array of strings
content	string
required	
error_message	string

required

GET /v1/documents/{id}/

Response samples

200

Content-Type

application/json

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "created_at": "2019-08-24T14:15:22Z",
  "status": "pending",
  "name": "string",
  "model": "string",
  "chunk_size": 0,
  "chunk_count": 0,
  "tags": [
    "string"
  ],
  "content": "string",
  "error_message": "string"
}
```

đồ cưỡi ể n' _ư đặ

AUTHORIZATIONS:

BearerAuth

PATH PARAMETERS

id

string <uuid>

required

A UUID string identifying this document.

REQUEST BODY SCHEMA: application/json

REQUIRED

name	string <= 255 characters
required	
tags	Array of strings

Responses

200

RESPONSE SCHEMA: application/json

id	string <uuid>
required	
created_at	string <date-time>
required	
status	string (ステータス) Enum: "pending" "processing" "available" "deleted" "error" • pending - Pending • processing - Processing • available - Available • deleted - Deleted • error - Error
required	
name	string <= 255 characters
required	
model	string
required	

chunk_size	integer
required	
chunk_count	integer
required	
tags	Array of strings
content	string
required	
error_message	string
required	

PUT /v1/documents/{id}/

Request samples

Payload

Content-Type

application/json

```
{
  "name": "string",
  "tags": [
    "string"
  ]
}
```

Response samples

200

Content-Type

application/json

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "created_at": "2019-08-24T14:15:22Z",
```

```
"status": "pending",
"name": "string",
"model": "string",
"chunk_size": 0,
"chunk_count": 0,
"tags": [
  "string"
],
"content": "string",
"error_message": "string"
```

```
}
```

đôçűń ěňť' _ďě' țrôÿ

AUTHORIZATIONS:

BearerAuth

PATH PARAMETERS

id

required

string <uuid>

A UUID string identifying this document.

Responses

204

No response body

ĐĚĽĚŤĚ/v1/documents/{id}/

çĥűňκ'

đôçűń ěňť_çĥűňκ' _ļ' ț

ViewSet for chunk list/single acquisition under the document.

- list: /documents/{document_id}/chunks/
- retrieve: /documents/{document_id}/chunks/{index}/ ← Retrieved by index

AUTHORIZATIONS:

BearerAuth

PATH PARAMETERS

document_pk	string
required	

QUERY PARAMETERS

page	integer A page number within the paginated result set.
page_size	integer Number of results to return per page.

Responses

200

RESPONSE SCHEMA: application/json

meta	object
required	
results	Array of objects (DocumentChunk)
required	

GET /v1/documents/{document_pk}/chunks/

Response samples

200
Content type application/json <pre>{ "meta": {</pre>


```
"page": 0,
"page_size": 0,
"total_pages": 0,
"count": 0,
"next": "http://example.com",
"previous": "http://example.com"
},
"results": [
  {}
]
```

```
}
```

đôçűń ěňť_čhűnk' _řěťřěvě

ViewSet for chunk list/single acquisition under the document.

- list: /documents/{document_id}/chunks/
- retrieve: /documents/{document_id}/chunks/{index}/ ← Retrieved by index

AUTHORIZATIONS:

BearerAuth

PATH PARAMETERS

document_pk

required

string

index

required

string^{^¥d+\$}

Responses

200

RESPONSE SCHEMA: application/json

document

object

<code>required</code>	
<code>chunk_index</code>	<code>integer</code>
<code>required</code>	
<code>content</code>	<code>string</code>
<code>required</code>	
<code>metadata</code>	<code>object or null</code>
<code>required</code>	

GET/v1/documents/{document_pk}/chunks/{index}/

Response samples

200

Content type

application/json

```
{
  "document": {
    "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
    "created_at": "2019-08-24T14:15:22Z",
    "status": "pending",
    "name": "string",
    "model": "string",
    "chunk_size": 0,
    "chunk_count": 0,
    "tags": [],
    "error_message": "string"
  },
  "chunk_index": 0,
  "content": "string",
  "metadata": {
    "property1": null,
    "property2": null
  }
}
```

chất

độc ứn ể ấ' _chất

AUTHORIZATIONS:

BearerAuth

REQUEST BODY SCHEMA: application/json

REQUIRED

distance_type

string

Default: "cosine"

Enum: "cosine" "l2"

Distance metric used for similarity calculation.

- cosine: cosine distance
- l2: L2 distance (Euclidean distance)
- cosine - cosine
- l2 - l2

model

string <= 255 characters

Default: "multilingual-e5-large"

Specifies the embedding model to use for search. Generates query and document embeddings with the specified model to perform a similarity search. (Please check the Control Panel or relevant documentation for available models.)

chat_model

string <= 255 characters

required

Specifies the chat model to use for answer generation.

Based on the search results, this model is used to generate answer sentences. (Please check the control panel etc. for available models.)

query

string <= 1000 characters

required

Specify the question text.

The specified query is used for both searching and answer generation.

prompt	string <= 2000 characters Specify a custom instruction text that will be added to `system_prompt` when generating an answer. It can be used to specify the tone and control the answer format. If unspecified, the default system_prompt will be used.
tags	Array of strings[items <= 255 characters] Specify the tag to search for. Only documents containing the specified tags will be searched. If multiple tags are specified, only documents in which all tags are specified will be targeted.
top_k	integer [1 .. 100] Default: 5 Specify the maximum number of items to be retrieved as search results. This number of documents will be used in descending order of similarity.
threshold	number <double> [0 .. 2] Default: 0.3 Vector distance threshold. Documents with a distance greater than this distance will be excluded from the search results.
use_full_content	boolean Default: false If true, use the full document as context. If false, searches and answers will be generated in divided chunks.

Responses

200

RESPONSE SCHEMA: application/json

answer	string
required	
sources	Array of QueryResultChunk (object) or QueryResultDocument (object)
required	(ChatResultSource)

POST /v1/documents/chat/

Request samples

Payload

Content-Type

application/json

```
{
  "distance_type": "cosine",
  "model": "multilingual-e5-large",
  "chat_model": "string",
  "query": "string",
  "prompt": "string",
  "tags": [
    "string"
  ],
  "top_k": 5,
  "threshold": 0.3,
  "use_full_content": false
}
```

Response samples

200

Content-Type

application/json

```
{
  "answer": "string",
```

```
"sources": [
  {}
]
}
```

ř ůěřŷ

đôçŭń ěňť! _ř ůěřŷ

AUTHORIZATIONS:

BearerAuth

QUERY PARAMETERS

model	string
name	string
tag	string

REQUEST BODY SCHEMA: application/json

REQUIRED

model	string <= 255 characters Default: "multilingual-e5-large" Model used for query vectorization.
query	string <= 1000 characters
tags	Array of strings[items <= 255 characters] Only documents with all tags are included.
top_k	integer [1 .. 100] Default: 3 Maximum number of search results to return.

threshold

number <double> [0 .. 2]

Default: 0.3

Vector distance threshold. Documents with a distance greater than this distance will be excluded from the search results.

distance_type

string

Default: "cosine"

Enum: "cosine" "l2"

Distance metric used for similarity calculation.

- **cosine**: Cosine distance. It is suitable for text similarity measurements and values range from 0 to 2 (0 being an exact match).
- **l2**: L2 distance (Euclidean distance). Straight line distance in vector space, suitable for measuring similarity of numerical data. Values range from 0 to 2 (0 being an exact match).
- **cosine** - cosine
- **l2** - l2

Responses

200

RESPONSE SCHEMA: application/json

results

Array of objects (QueryResultChunk)

required

Array

document

object

required

chunk_index

integer

required

distance	number <double>
required	

content	string
required	

metadata	object
required	

POST /v1/documents/query/

Request samples

Payload

Content-Type

application/json

```
{
  "model": "multilingual-e5-large",
  "query": "string",
  "tags": [
    "string"
  ],
  "top_k": 3,
  "threshold": 0.3,
  "distance_type": "cosine"
}
```

Response samples

200

Content-Type

application/json

```
{
  "results": [
    {}
  ]
}
```



```
}  
    _r l_ăđ  
  
đôç_ưn ẻnặ' _ư l_ăđ
```

AUTHORIZATIONS:

BearerAuth

REQUEST BODY SCHEMA:

n ửlặr ắặ/ặn -đắắ
 ắ r lặắặặặ/ặ-ặặặ-ặn -ửặặặặặặ
 n ửlặr ắặ/ặn -đắắ
REQUIRED

file	string <uri>
required	
name	string <= 255 characters If not specified, the uploaded file name will be used.
tags	Array of strings
model	string Enum: "multilingual-e5-large" "preview/Qwen3-Embedding-4B-FP16" Model used for vectorization. - multilingual-e5-large - multilingual-e5-large - preview/Qwen3-Embedding-4B-FP16 - preview/Qwen3-Embedding-4B-FP16
chunk_size	integer The maximum value varies depending on the model. If not specified, the model default value will be set.

Responses

200

RESPONSE SCHEMA: application/json

id	string <uuid>
required	
status	string (ステータス)
required	Enum: "pending" "processing" "available" "deleted" "error" - pending - Pending - processing - Processing - available - Available - deleted - Deleted - error - Error
content	string
required	
name	string <= 255 characters
	If not specified, the uploaded file name will be used.
tags	Array of strings
model	string
	Enum: "multilingual-e5-large" "preview/Qwen3-Embedding-4B-FP16"
	Model used for vectorization.
	- multilingual-e5-large - multilingual-e5-large - preview/Qwen3-Embedding-4B-FP16 - preview/Qwen3-Embedding-4B-FP16
chunk_size	integer
	The maximum value varies depending on the model. If not specified,

the model default value will be set.

RÖ' T/v1/documents/upload/

Response samples

200

ÇöntentÄyr ě

ăr r lřčăřîön/j' ôñ

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "status": "pending",
  "content": "string",
  "name": "string",
  "tags": [
    "string"
  ],
  "model": "multilingual-e5-large",
  "chunk_size": 0
}
```