

A FULL-STACK PLATFORM FOR RECRUITMENT AND APPLICATION MANAGEMENT-SOURCE CODES

Application.java

```
package com.project.recruitment;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class Application {
    public static void main(String[] args) {
        SpringApplication.run(Application.class, args);
    }
}
```

User.java

```
package com.project.recruitment.model;

import jakarta.persistence.*;

@Entity
public class User {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private Long id;

    private String name;
    private String email;
    private String password;
    private String role;

    public Long getId() {
        return id;
    }

    public String getName() {
```

```

        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) {
        this.email = email;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }

    public String getRole() {
        return role;
    }

    public void setRole(String role) {
        this.role = role;
    }
}

```

Job.java

```

package com.project.recruitment.model;

import jakarta.persistence.*;

@Entity
public class Job {

```

```
@Id
@GeneratedValue(strategy = GenerationType.IDENTITY)
private Long id;

private String title;
private String description;
private String location;

public Long getId() {
    return id;
}

public String getTitle() {
    return title;
}

public void setTitle(String title) {
    this.title = title;
}

public String getDescription() {
    return description;
}

public void setDescription(String description) {
    this.description = description;
}

public String getLocation() {
    return location;
}

public void setLocation(String location) {
    this.location = location;
}
}
```

ApplicationEntity.java

```
package com.project.recruitment.model;
```

```
import jakarta.persistence.*;
```

```
@Entity
```

```
public class ApplicationEntity {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.IDENTITY)
```

```
    private Long id;
```

```
    private String applicantName;
```

```
    private String email;
```

```
    private String resume;
```

```
    private String status;
```

```
    @ManyToOne
```

```
    private Job job;
```

```
    public Long getId() {
```

```
        return id;
```

```
    }
```

```
    public String getApplicantName() {
```

```
        return applicantName;
```

```
    }
```

```
    public void setApplicantName(String applicantName) {
```

```
        this.applicantName = applicantName;
```

```
    }
```

```
    public String getEmail() {
```

```
        return email;
```

```
    }
```

```
    public void setEmail(String email) {
```

```
        this.email = email;
```

```
    }
```

```
    public String getResume() {
```

```
        return resume;
```

```
    }
```

```

    public void setResume(String resume) {
        this.resume = resume;
    }

    public String getStatus() {
        return status;
    }

    public void setStatus(String status) {
        this.status = status;
    }

    public Job getJob() {
        return job;
    }

    public void setJob(Job job) {
        this.job = job;
    }
}

```

UserRepository.java

```

package com.project.recruitment.repository;

import com.project.recruitment.model.User;
import org.springframework.data.jpa.repository.JpaRepository;

public interface UserRepository extends JpaRepository<User, Long> {
    User findByEmail(String email);
}

```

JobRepository.java

```

package com.project.recruitment.repository;

import com.project.recruitment.model.Job;
import org.springframework.data.jpa.repository.JpaRepository;

public interface JobRepository extends JpaRepository<Job, Long> {
}

```

ApplicationRepository.java

```
package com.project.recruitment.repository;

import com.project.recruitment.model.ApplicationEntity;
import org.springframework.data.jpa.repository.JpaRepository;

public interface ApplicationRepository extends
JpaRepository<ApplicationEntity, Long> {
}
```

AuthController.java

```
package com.project.recruitment.controller;

import com.project.recruitment.model.User;
import com.project.recruitment.repository.UserRepository;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;

@RestController
@RequestMapping("/auth")
public class AuthController {

    @Autowired
    private UserRepository userRepo;

    @PostMapping("/register")
    public String register(@RequestBody User user) {
        userRepo.save(user);
        return "Registered";
    }

    @PostMapping("/login")
    public String login(@RequestBody User user) {
        User u = userRepo.findByEmail(user.getEmail());
        if (u != null && u.getPassword().equals(user.getPassword())) {
            return "Success";
        }
        return "Invalid";
    }
}
```

```
}  
}
```

JobController.java

```
package com.project.recruitment.controller;  
  
import com.project.recruitment.model.Job;  
import com.project.recruitment.repository.JobRepository;  
import org.springframework.beans.factory.annotation.Autowired;  
import org.springframework.web.bind.annotation.*;  
  
import java.util.List;  
  
@RestController  
@RequestMapping("/jobs")  
public class JobController {  
  
    @Autowired  
    private JobRepository jobRepo;  
  
    @GetMapping  
    public List<Job> getJobs() {  
        return jobRepo.findAll();  
    }  
  
    @PostMapping  
    public Job addJob(@RequestBody Job job) {  
        return jobRepo.save(job);  
    }  
  
    @DeleteMapping("/{id}")  
    public void deleteJob(@PathVariable Long id) {  
        jobRepo.deleteById(id);  
    }  
}
```

ApplicationController.java

```
package com.project.recruitment.controller;  
  
import com.project.recruitment.model.ApplicationEntity;
```

```

import com.project.recruitment.repository.ApplicationRepository;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;

import java.util.List;

@RestController
@RequestMapping("/applications")
public class ApplicationController {

    @Autowired
    private ApplicationRepository appRepo;

    @GetMapping
    public List<ApplicationEntity> getAll() {
        return appRepo.findAll();
    }

    @PostMapping
    public ApplicationEntity apply(@RequestBody ApplicationEntity app) {
        app.setStatus("Applied");
        return appRepo.save(app);
    }
}

```

MailService.java

```

package com.project.recruitment.service;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.mail.SimpleMailMessage;
import org.springframework.mail.javamail.JavaMailSender;
import org.springframework.stereotype.Service;

@Service
public class MailService {

    @Autowired
    private JavaMailSender sender;

    public void sendMail(String to, String subject, String text) {

```



```

        SimpleMailMessage msg = new SimpleMailMessage();
        msg.setTo(to);
        msg.setSubject(subject);
        msg.setText(text);
        sender.send(msg);
    }
}

```

SecurityConfig.java

```

package com.project.recruitment.config;

import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import
org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.web.SecurityFilterChain;

@Configuration
public class SecurityConfig {

    @Bean
    public SecurityFilterChain filterChain(HttpSecurity http) throws Exception {
        http
            .csrf().disable()
            .authorizeHttpRequests()
            .anyRequest().permitAll();

        return http.build();
    }
}

```

application.properties

```

spring.datasource.url=jdbc:mysql://localhost:3306/recruitment
spring.datasource.username=root
spring.datasource.password=

spring.jpa.hibernate.ddl-auto=update
spring.jpa.show-sql=true

spring.mail.host=smtp.gmail.com

```

```
spring.mail.port=587
spring.mail.username=your_email@gmail.com
spring.mail.password=your_password
spring.mail.properties.mail.smtp.auth=true
spring.mail.properties.mail.smtp.starttls.enable=true
```