

JOB PORTAL MANAGEMENT SYSTEM – SOURCE CODE

1. MAIN APPLICATION CLASS

```
package com.jobportal;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class JobPortalApplication {

    public static void main(String[] args) {

        SpringApplication.run(JobPortalApplication.class, args);

    }

}
```

2. ENTITY CLASSES

2.1 USER ENTITY

```
package com.jobportal.model;

import jakarta.persistence.*;

@Entity

public class User {

    @Id

    @GeneratedValue(strategy = GenerationType.IDENTITY)

    private Long id;

    private String name;

    private String email;

    private String password;

    private String role;

    public Long getId() { return id; }

    public void setId(Long id) { this.id = id; }

    public String getName() { return name; }

    public void setName(String name) { this.name = name; }

    public String getEmail() { return email; }

    public void setEmail(String email) { this.email = email; }

    public String getPassword() { return password; }
```

```
public void setPassword(String password) { this.password = password; }

public String getRole() { return role; }

public void setRole(String role) { this.role = role; }

}
```

2.2 JOB ENTITY

```
package com.jobportal.model;

import jakarta.persistence.*

@Entity

public class Job {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)

    private Long id;

    private String company;

    private String title;

    private String location;

    private double salary;

    private String skills;

    public Long getId() { return id; }

    public void setId(Long id) { this.id = id; }

    public String getCompany() { return company; }

    public void setCompany(String company) { this.company = company; }

    public String getTitle() { return title; }

    public void setTitle(String title) { this.title = title; }

    public String getLocation() { return location; }

    public void setLocation(String location) { this.location = location; }

    public double getSalary() { return salary; }

    public void setSalary(double salary) { this.salary = salary; }

    public String getSkills() { return skills; }

    public void setSkills(String skills) { this.skills = skills; }

}
```

2.3 APPLICATION ENTITY

```
package com.jobportal.model;

import jakarta.persistence.*;

@Entity

public class Application {

    @Id

    @GeneratedValue(strategy = GenerationType.IDENTITY)

    private Long id;

    private Long userId;

    private Long jobId;

    private String status;

    public Long getId() { return id; }

    public void setId(Long id) { this.id = id; }

    public Long getUserId() { return userId; }

    public void setUserId(Long userId) { this.userId = userId; }

    public Long getJobId() { return jobId; }

    public void setJobId(Long jobId) { this.jobId = jobId; }

    public String getStatus() { return status; }

    public void setStatus(String status) { this.status = status; }

}
```

3. REPOSITORY LAYE

3.1 USER REPOSITORY

```
package com.jobportal.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.jobportal.model.User;

public interface UserRepository extends JpaRepository<User, Long> {

    User findByEmail(String email);

}
```

3.2 JOB REPOSITORY

```
package com.jobportal.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.jobportal.model.Job;
```

```
public interface JobRepository extends JpaRepository<Job, Long> {  
}
```

3.3 APPLICATION REPOSITORY

```
package com.jobportal.repository;  
  
import org.springframework.data.jpa.repository.JpaRepository;  
import com.jobportal.model.Application;  
  
public interface ApplicationRepository extends JpaRepository<Application, Long> {  
}
```

4. SERVICE LAYER

```
package com.jobportal.service;  
  
import org.springframework.beans.factory.annotation.Autowired;  
import org.springframework.stereotype.Service;  
import com.jobportal.model.User;  
import com.jobportal.repository.UserRepository;  
  
@Service  
public class UserService {  
  
    @Autowired  
    private UserRepository repo;  
  
    public User register(User user) {  
        return repo.save(user);  
    }  
  
    public User login(String email, String password) {  
        User user = repo.findByEmail(email);  
        if (user != null && user.getPassword().equals(password)) {  
            return user;  
        }  
        return null;  
    }  
}
```

5. CONTROLLER LAYER

5.1 AUTH CONTROLLER

```
package com.jobportal.controller;
```

```

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;
import com.jobportal.model.User;
import com.jobportal.service.UserService;

@RestController
@RequestMapping("/api/auth")
@CrossOrigin
public class AuthController {

    @Autowired
    private UserService service;

    @PostMapping("/register")
    public User register(@RequestBody User user) {
        return service.register(user);
    }

    @PostMapping("/login")
    public User login(@RequestBody User user) {
        return service.login(user.getEmail(), user.getPassword());
    }
}

```

5.2 JOB CONTROLLER

```

package com.jobportal.controller;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;
import com.jobportal.model.Job;
import com.jobportal.repository.JobRepository;
import java.util.List;

@RestController
@RequestMapping("/api/jobs")
@CrossOrigin
public class JobController {

    @Autowired
    private JobRepository repo;
}

```

```

@GetMapping
public List<Job> getAllJobs() {
    return repo.findAll();
}

@PostMapping
public Job addJob(@RequestBody Job job) {
    return repo.save(job);
}
}

```

6. FRONTEND CODE

6.1 LOGIN PAGE

```

<!DOCTYPE html>

<html>

<body>

<h2>Login</h2>

<input type="email" id="email" placeholder="Email">

<input type="password" id="password" placeholder="Password">

<button onclick="login()">Login</button>

<script>

function login() {
    fetch("http://localhost:8080/api/auth/login", {
        method: "POST",
        headers: {"Content-Type": "application/json"},
        body: JSON.stringify({
            email: document.getElementById("email").value,
            password: document.getElementById("password").value
        })
    })
    .then(res => res.json())
    .then(data => alert("Login Success"));
}

</script>

```

```
</body>
```

```
</html>
```

6.2 JOB LISTING PAGE

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>Job Listings</h2>
```

```
<div id="jobs"></div>
```

```
<script>
```

```
fetch("http://localhost:8080/api/jobs")
```

```
.then(res => res.json())
```

```
.then(data => {
```

```
  let output = "";
```

```
  data.forEach(job => {
```

```
    output += `<p>${job.title} - ${job.company}</p>`;
```

```
  });
```

```
  document.getElementById("jobs").innerHTML = output;
```

```
});
```

```
</script>
```

```
</body>
```

```
</html>
```

7. DATABASE (MYSQL)

```
CREATE DATABASE jobportal;
```

```
USE jobportal;
```

```
CREATE TABLE user (
```

```
  id BIGINT AUTO_INCREMENT PRIMARY KEY,
```

```
  name VARCHAR(100),
```

```
  email VARCHAR(100),
```

```
  password VARCHAR(100),
```

```
  role VARCHAR(20)
```

```
);
```

```
CREATE TABLE job (
```

```
id BIGINT AUTO_INCREMENT PRIMARY KEY,  
company VARCHAR(100),  
title VARCHAR(100),  
location VARCHAR(100),  
salary DOUBLE,  
skills VARCHAR(200)  
);
```

```
CREATE TABLE application (  
id BIGINT AUTO_INCREMENT PRIMARY KEY,  
user_id BIGINT,  
job_id BIGINT,  
status VARCHAR(50)  
);
```

8. APPLICATION.PROPERTIES

```
spring.datasource.url=jdbc:mysql://localhost:3306/jobportal  
spring.datasource.username=root  
spring.datasource.password=root  
spring.jpa.hibernate.ddl-auto=update  
spring.jpa.show-sql=true  
spring.jpa.database-platform=org.hibernate.dialect.MySQL8Dialect  
server.port=8080
```