```java
package edu.Task_8;

import org.springframework.context.ApplicationContext;

public class App {

    public static void main(String[] args) {

        ApplicationContext context =
                new AnnotationConfigApplicationContext(AppConfig.class);

        EmployeeService service = context.getBean(EmployeeService.class);

        service.addEmployee(101, "Anand", "CSE");
        service.addEmployee(102, "Divya", "ECE");
        service.addEmployee(103, "Ravi", "IT");

        System.out.println("All Employees:");
        service.getAllEmployees().forEach(System.out::println);

        System.out.println("\nFind Employee 102:");
        System.out.println(service.getEmployee(102));

        System.out.println("\nDelete Employee 101:");
        System.out.println("Deleted? " + service.removeEmployee(101));

        System.out.println("\nAll Employees After Delete:");
        service.getAllEmployees().forEach(System.out::println);
    }
}
```

```java
package edu.Task_8;

import org.springframework.context.annotation.ComponentScan;

@Configuration
@ComponentScan(basePackages = "edu.Task_8")
public class AppConfig {

}
```

```java
package edu.Task_8;

public class Employee {

    private int id;
    private String name;
    private String department;

    public Employee() {}

    public Employee(int id, String name, String department) {
        this.id = id;
        this.name = name;
        this.department = department;
    }

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getDepartment() {
        return department;
```

```java
package edu.Task_8;

import java.util.*;

@Component
public class EmployeeRepository {

    private final Map<Integer, Employee> store = new HashMap<>();

    public void save(Employee e) {
        store.put(e.getId(), e);
    }

    public Employee findById(int id) {
        return store.get(id);
    }

    public List<Employee> findAll() {
        return new ArrayList<>(store.values());
    }

    public boolean deleteById(int id) {
        return store.remove(id) != null;
    }
}
```

```java
package edu.Task_8;

import org.springframework.beans.factory.annotation.Autowired;

@Component
public class EmployeeService {

    private final EmployeeRepository repo;

    @Autowired
    public EmployeeService(EmployeeRepository repo) {
        this.repo = repo;
    }

    public void addEmployee(int id, String name, String dept) {
        repo.save(new Employee(id, name, dept));
    }

    public Employee getEmployee(int id) {
        return repo.findById(id);
    }

    public List<Employee> getAllEmployees() {
        return repo.findAll();
    }

    public boolean removeEmployee(int id) {
        return repo.deleteById(id);
    }
}
```

```
All Employees:
Employee{id=101, name='Anand', dept='CSE'}
Employee{id=102, name='Divya', dept='ECE'}
Employee{id=103, name='Ravi', dept='IT'}

Find Employee 102:
Employee{id=102, name='Divya', dept='ECE'}

Delete Employee 101:
Deleted? true

All Employees After Delete:
Employee{id=102, name='Divya', dept='ECE'}
Employee{id=103, name='Ravi', dept='IT'}
```