An Explainable Multimodal AI System for Clinical Trial Protocol Complexity Profiling and Prolonged-Duration Risk Prediction

Dr. D. Rajesh
Professor
Computer Science and Engineering
Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology
drrajeshd@veltech.edu.in

Dr. J. Swapna
Assistant Professor
Computer Science and Engineering
Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology
swapnaj@veltech.edu.in

Malepati Prem Kumar Reddy
4th Year B.Tech
Computer Science and Engineering
Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology
vtu26418@veltech.edu.in

Cherukula Lokeshwara Reddy
4th Year B.Tech
Computer Science and Engineering
Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology
vtu26381@veltech.edu.in

***Abstract*— Clinical trial registries combine structured study characteristics with protocol descriptions, but their use for duration prediction requires careful control of outcome availability. This paper presents Clinical Trial Intelligence, a research workbench for protocol complexity profiling and retrospective duration analysis. The implemented pipeline validates registry records, constructs structured and TF–IDF text representations, compares unimodal and multimodal predictors, and preserves model and data provenance. A frozen ClinicalTrials.gov API snapshot contains 800 completed interventional drug studies. Eligibility checks retain 312 records; temporal purging leaves 105 training, nine tuning, 11 calibration, and 64 test records. Prolonged duration is defined as more than 1,101 days, the training-set upper quartile. On the test set, the text-only model achieves a duration mean absolute error of 314.70 days and a prolonged-duration AUROC of 0.8075; early multimodal fusion achieves 333.00 days and 0.7615. These comparisons do not establish a fusion advantage. A nominal 90% interval from the duration-selected median baseline covers 75% of test outcomes, indicating substantial undercoverage. A separate fixed-reference Protocol Complexity Index combines six explicitly normalized components. A FastAPI and React workbench exposes predictions, provenance, uncertainty, and model-appropriate explanations. Saved prediction replay reproduces the reported point metrics. The experiment uses a small, completed-only convenience cohort and current registry descriptions whose baseline availability is unverified. Its results support reproducible retrospective analysis, rather than prospective clinical validation.**

***Index Terms*— clinical trial informatics, protocol complexity, multimodal machine learning, duration prediction, temporal evaluation, explainability, research reproducibility.**

I. INTRODUCTION

Clinical trial planning brings together recruitment, participant eligibility, intervention schedules, outcome measurement, and follow-up. These requirements differ across protocols, and no single registry field describes their combined operational burden. ClinicalTrials.gov provides structured study characteristics alongside brief summaries, detailed descriptions, and eligibility text [1]. These records make it possible to examine relationships between trial design and recorded duration, provided that their reporting limitations are considered. They describe registered studies rather than direct observations of every operational event.

Increasing protocol complexity has been documented in registry-based analyses [2]. Duration prediction has also been investigated using statistical and machine-learning methods [3]. This work therefore addresses an existing research problem. Its contribution is an inspectable implementation that links a frozen dataset, explicit cohort rules, comparable model branches, complexity calculations, and an analyst interface. The workbench makes it possible to follow a displayed result back to the corresponding data version and saved model artifact.

Structured and textual information can offer complementary descriptions of a study. Enrollment and outcome counts summarize scale, whereas narrative fields may describe treatment schedules, eligibility restrictions, or study procedures. Multimodal learning provides a framework for combining such representations [4]. Complementarity, however, is a hypothesis to test. Adding a text branch or combining two predictors does not itself demonstrate an improvement in generalization, particularly when development and evaluation cohorts are small.

The research question is whether combining registry characteristics and protocol language improves retrospective prediction of recorded duration and prolonged-duration status under a common temporal evaluation procedure. A second question concerns how an explicit complexity profile can be presented alongside model outputs without confusing a descriptive index with a validated clinical score. The system keeps the complexity calculation, duration estimate, and binary-risk definition separately identifiable so that each result can be interpreted in its own terms. Duration regression estimates a quantity in days, whereas the classifier estimates membership in a training-defined upper-duration group. These objectives can favor different models. A complexity score supplies a third, descriptive view whose numeric range cannot be interpreted as a probability. Reporting

their definitions together reduces ambiguity when an analyst compares trials.

Registry studies face two distinct leakage problems. An outcome may occur after the start of a later evaluation period, and a registry field may have been revised after the intended prediction date. A temporal split with outcome purging addresses the first problem. It does not reconstruct historical versions of enrollment or protocol text. Leakage can substantially distort machine-learning evidence [5]; the present study consequently records the absence of verified baseline feature provenance and limits its claims to the frozen retrospective snapshot.

The implementation uses scikit-learn pipelines for fitted preprocessing and predictive models [6]. Structured-only, text-only, and fusion branches use the same retained records and target definition. Their comparison is accompanied by a constant baseline, which supplies a useful check against unnecessary model complexity. Tuning selects separate recommendations for duration and risk; test metrics are reserved for descriptive evaluation. The model displayed in the workbench remains identified by its saved bundle rather than by an unspecified claim of best performance.

The main contributions are as follows:

1. A reproducible registry-processing workflow with source checksums, explicit inclusion rules, whole-date temporal partitioning, and outcome-availability purging.
2. A fixed-reference Protocol Complexity Index (PCI) with documented component ceilings, weights, rounding, and missing-value behavior.
3. Comparable structured, TF–IDF text, early-fusion, and late-fusion branches, with recorded preprocessing and task-specific tuning objectives.
4. A retrospective experiment that reports measured results from an authentic frozen registry cohort and retains individual held-out predictions for verification.
5. A model-aware explanation interface that distinguishes constant predictions, supported feature evidence, and optional attribution methods.
6. A browser workbench linking trial profiles, data-quality warnings, saved predictions, source evidence, and downloadable research records.
7. A verification procedure that replays saved artifacts and checks numerical results without retraining or altering the frozen experiment.

The empirical results reported here come from the 800-record ClinicalTrials.gov snapshot. They are not AACT results, population estimates, or evidence that the system predicts trial success. The reported endpoint is elapsed time between recorded start and actual completion dates. A long elapsed duration may be intentional, and the prolonged-duration label does not measure delay against a planned deadline. For example, a protocol with long planned follow-up can exceed the duration threshold while remaining on schedule. Conversely, a shorter study can miss its planned completion date while remaining below the threshold. Registry duration alone does not distinguish these cases, so the interface and manuscript retain the endpoint definition alongside every risk interpretation.

II. SYSTEM ARCHITECTURE

Fig. 1 shows the implemented Clinical Trial Intelligence architecture. The evidence path begins with saved ClinicalTrials.gov API responses and a canonical trial table. The registry snapshot, its acquisition metadata, and checksums are retained together. Optional protocol-document ingestion and source-search tools support research use of the application, but their outputs are not silently added to the frozen model experiment. The empirical dataset and predictor inputs are specified independently of interface capabilities.

The processing layer validates identifiers, dates, study status, and required fields before constructing a duration cohort. Duplicate identifiers and invalid targets are checked explicitly. Cohort exclusions and temporal exclusions are written as separate artifacts, allowing reviewers to distinguish an ineligible record from an otherwise eligible record removed because its outcome was unavailable at a later split boundary. Source metadata records that the available features come from the retrieved registry state.

The modeling layer separates numerical and categorical trial characteristics from protocol text. Numerical inputs pass through a fitted median imputer and scaling; categorical fields use one-hot encoding. The text branch constructs TF–IDF unigram and bigram features. These representations support independent baselines and early concatenation. Additional structured tree ensembles and a late-fusion branch expand the comparison without changing the held-out test records or target. Learned preprocessing remains attached to the saved model pipeline.

The PCI service supplies a transparent descriptive profile. Its fixed-reference score is defined by a fixed formula configuration and does not require model fitting. The training workflow also stores a different training-relative complexity index; these definitions are distinguished in Section IV. Neither index is a calibrated probability, and neither should be substituted for the learned duration or risk output.

The experiment writes a manifest, point metrics, held-out predictions, exclusions, and serialized pipelines. Duration and risk recommendations are selected separately on tuning data. The deployed research bundle illustrated here is the duration-selected median baseline, which includes its constant training-prevalence risk output. The offline text-model risk recommendation is a separate result. Identifying this distinction prevents the interface screenshot from being mistaken for a text-model prediction.

A FastAPI backend serves stored datasets, model evidence, saved prediction records, authentication, and project access controls. A React interface provides data import, exploration, prediction, comparison, source evidence, and monitoring views. The application also supports optional provider-based assistant streaming. That assistant is a research interface capability; it is not the predictive estimator used to produce the reported duration metrics.

The explanation layer reports only information supported by the selected model and available dependencies. For a constant baseline, it identifies the training statistic and explains why feature-specific contributions are undefined. The interface also exposes missing-input and retrospective-provenance warnings. This design makes a numerical prediction reviewable alongside its limitations rather than treating a polished dashboard as evidence of scientific validity.




Figure 1. Implemented architecture, separating frozen research evidence, model execution, and workbench services.




Figure 2. Recorded cohort construction and temporal evaluation; counts refer to the frozen registry experiment.

III. DATASET AND DATA SCIENCE PIPELINE

The empirical source is a frozen ClinicalTrials.gov API snapshot acquired on October 7, 2026. It contains 800 unique completed interventional drug studies, with 200 API-returned records from each start-year stratum: 2000–2005, 2006–2011, 2012–2017, and 2018–2023. The acquisition retained eight raw response pages and a canonical CSV file. Selecting the first returned records within each stratum produces a convenience cohort, not a random or representative sample of registered trials.

Fig. 2 summarizes cohort construction and temporal evaluation. Duration eligibility requires a completed study, an actual completion date, day-level precision for both start and completion, and a strictly positive elapsed interval. Applying these rules retains 312 records and excludes 488. The canonical snapshot is preserved unchanged; filtering produces derived artifacts so that exclusions can be traced to the original identifiers and recorded reasons.

For each eligible record, duration d_i is the actual completion date minus the start date, expressed in days. The binary target is $y_i = \mathbf{1}[d_i > q_{0.75}^{\text{train}}]$. The upper quartile of the retained training durations is 1,101 days; equality to this value remains in the negative class. This threshold is derived from training outcomes alone and is fixed for tuning, calibration, and test evaluation. It does not use a planned completion date or an external clinical definition of delay.

The initial chronological partition uses whole start-calendar-day groups in a 60/20/20 allocation. These proportions apply to date groups, not necessarily to record counts. Training records whose outcomes reach or exceed the validation cutoff are purged; the corresponding rule removes validation outcomes at or beyond the test cutoff. The procedure removes 123 eligible records. The retained validation period is then separated chronologically into tuning and calibration subsets, again without splitting a start-date group.

Table 1. Core Feature Groups

Group	Recorded inputs	Role
Study design	Study type and phase	Categorical inputs
Scale	Enrollment and arm count	Numerical inputs
Outcomes	Primary and secondary outcome counts	Numerical inputs
Eligibility	Criterion count	Numerical input
Protocol text	Title, summary, description, eligibility	TF–IDF inputs
PCI	Versioned normalized components	Separate profile

The resulting partitions contain 105 training, nine tuning, 11 calibration, and 64 test records. The initial validation cutoff is October 10, 2019; the calibration cutoff is July 12, 2020; and the test cutoff is September 14, 2021. There are 26 prolonged-duration outcomes in training and six in the test set. Both tuning and calibration contain zero positive cases, an important constraint on discrimination assessment and probability calibration.

Table 1 lists the actual predictor groups. Identifiers, status, start date, completion date, duration, and the derived target are excluded from the predictive features. Numerical imputation, standardization, categorical encoding, and text vocabulary construction are fitted on training data. Unknown categories are ignored at transformation, and empty numerical columns are

retained by the imputer. Missing text receives a documented sentinel. Both the criterion-count and text-complexity columns are missing in all 800 source records. The criterion-count predictor therefore becomes a constant zero column after the training imputer. These controls prevent cross-partition preprocessing leakage, while unverified historical availability of registry descriptions remains an unresolved limitation.

IV. PROTOCOL COMPLEXITY INDEX

The workbench implements a fixed-reference descriptive PCI score. For component j, a finite nonnegative raw value x_j is normalized as $z_j = \min(1, \max(0, x_j/c_j))$, where c_j is the configured ceiling. Missing or invalid values contribute zero and are disclosed; this handling does not establish that the corresponding burden is absent. The score is

$$PCI = 100(0.25C + 0.20O_p + 0.20O_s + 0.15A + 0.10E + 0.10T), \quad (1)$$

where C, O_p, O_s, A, E, and T are the normalized eligibility-count, primary-outcome-count, secondary-outcome-count, arm-count, enrollment, and text-complexity inputs, respectively.

Table 2 gives the fixed weights and raw-value ceilings. The supplied text-complexity input is a numeric project field; it is not automatically a validated readability grade or a biomedical embedding. Fig. 3 visualizes the weight allocation.

Table 2. Fixed PCI Weights and Normalization Ceilings

Component (raw ceiling)	Weight
Eligibility count (C; 40)	0.25
Primary-outcome count (O_p; 10)	0.20
Secondary-outcome count (O_s; 20)	0.20
Arm count (A; 8)	0.15
Enrollment (E; 1,000)	0.10
Text-complexity input (T; 20)	0.10
Total	**1.00**

The score lies in $[0, 100]$. The implementation sums unrounded component contributions and applies decimal half-up rounding to two places. Categories use this rounded score: Low below 40, Medium from 40 through 70, and High above 70. These are project-defined descriptive categories, not established clinical or regulatory thresholds. A higher score does not establish a causal increase in duration.

The frozen training artifact separately records an equal-weight index over five numerical inputs. Its imputation and min–max limits are learned from the training set; constant components contribute zero, and transformed values are clipped to $[0, 1]$. This training-relative index omits the text-complexity component. In this run, criterion count is constant zero, limiting this index to at most 80. It must not be presented as the six-component fixed-reference score or as a controlled sensitivity experiment, because both the normalization and component definitions differ.

V. BIOMEDICAL NATURAL LANGUAGE PROCESSING

The executed text branch concatenates the title, brief summary, detailed description, and eligibility criteria. It uses TF–IDF unigrams and bigrams [7] with sublinear term frequency and a maximum vocabulary of 20,000 features. Vocabulary and inverse-document-frequency statistics are fitted on the training partition. This representation encodes lexical associations rather than biomedical knowledge or causal protocol constraints.




Figure 3. Configured weights of the six-component fixed-reference PCI.

BioBERT provides an established biomedical language representation [8] and is an optional extension in the project. The frozen experiment does not contain an executed BioBERT comparison. Accordingly, no transformer accuracy, chunking result, or embedding advantage is attributed to the reported models. The present comparison concerns structured variables and the implemented TF–IDF representation under a shared cohort and evaluation procedure.

VI. MACHINE LEARNING AND MULTIMODAL FUSION

The experiment contains nine branches: a median/prevalence baseline; structured, text, and early multimodal linear pipelines; four structured tree-ensemble pipelines; and late fusion. The linear branches pair Ridge regression for duration with logistic classification for prolonged duration. The additional structured branches use extra trees, random forests, gradient boosting, and histogram gradient boosting [9–11]. Each branch retains its own fitted preprocessing and estimators.

Fig. 4 shows the input and fusion relationships. Early fusion concatenates standardized numerical, one-hot categorical, and sparse TF–IDF features. It does not use transformer embeddings or a claimed dimensionality-reduction stage.

Each branch fits its duration estimator and risk classifier separately. They share the recorded input groups and partition membership but optimize different objectives. The comparison does not use trial status, completion dates, or duration as predictor fields. PCI is retained as a descriptive output and is not silently appended to the specified predictor matrix.

Late fusion averages predictions from histogram gradient boosting and the text model. The selected weight is 0.25 for the structured branch and 0.75 for text, for both duration and risk. Thus $\hat{d} = 0.25\hat{d}_s + 0.75\hat{d}_t$ and $\hat{p} = 0.25\hat{p}_s + 0.75\hat{p}_t$. The weights are tuned separately for the two tasks using the tuning subset; the saved component models are not refitted on the test set.

Table 3 groups the nine branches by purpose. The duration recommendation minimizes tuning RMSE and selects the median baseline; the risk recommendation minimizes raw tuning Brier

Nine implemented experiment branches

Structured: 5 numeric + 2 categorical | Text: 4 fields → TF–IDF

Branch	Input	Combination
Median / prevalence baseline	**None**	Constant
Structured linear	**S**	—
Text linear	**T**	—
Multimodal linear	**S + T**	Early concat.
Extra Trees; Random Forest	**S**	—
Gradient; histogram boosting	**S**	—
Text + histogram boosting	**S + T**	Late fusion

S: impute, scale, one-hot · T: unigrams + bigrams (≤20,000)

Figure 4. Executed unimodal and multimodal branches using shared retained records and targets.

Table 3. Experimental Design

ID	Input	Model	Purpose
E1	Training outcomes	Median / prevalence	Constant control
E2	Structured fields	Linear + four ensembles	Structured controls
E3	TF–IDF text	Ridge / logistic	Text control
E4	Structured + text	Concatenated linear	Early fusion
E5	E2 + E3 outputs	Weighted average	Late fusion

score and selects the text model. These choices are distinct from ranking models by test performance. The small tuning subset makes both recommendations uncertain, especially because it contains no prolonged-duration outcomes.

VII. EXPLAINABILITY AND CLINICAL TRIAL INTELLIGENCE WORKBENCH

The workbench associates explanation evidence with the selected model. SHAP is an optional attribution method [12]; its availability does not establish that a SHAP analysis was executed for every saved model. In particular, the duration-selected median baseline produces a constant estimate and has no feature-specific attribution. The interface states this explicitly. Attributions for supported nonconstant models describe their fitted behavior and do not establish causal effects of changing a protocol field.




Figure 5. Actual project prediction view: constant duration bundle, raw prevalence risk, uncertainty, and provenance warnings.

Fig. 5 is a capture of the running project using imported registry records. It shows the median duration of 482 days, raw training prevalence of $26/105$ (displayed as 24.8%), and the saved 37–927-day duration interval. The displayed records illustrate interface behavior; they are not additional test observations or evidence of individual predictive validity.

The FastAPI and React application connects trial selection, complexity profiles, prediction evidence, source records, and exports. User authentication and project controls govern stored workspaces. Source-search and assistant features support exploration, while the prediction evidence identifies the model, source dataset, and warnings needed to interpret a research output.

VIII. FROZEN REGISTRY EXPERIMENT

The frozen experiment uses the authentic registry cohort described in Section III. Its retained test set contains 64 studies, including six with duration above 1,101 days. Randomized estimators and bootstrap summaries use seed 42. The saved models, manifests, and prediction rows are retained so that the reported values can be checked without rerunning acquisition or choosing a new cohort.

Table 4 reports the structured linear, text, and early-fusion branches on the same test records. Duration errors are in days. AP denotes average precision, not trapezoidal area under a precision–recall curve. Brier score evaluates the raw prolonged-duration probabilities. Table values are rounded for presentation; the saved project predictions retain full precision.

Table 4. Held-Out Registry Results ($n = 64$; Errors in Days)

Model	MAE	RMSE	R^2	Brier	AUROC	AP
Structured	372.68	432.38	−.117	.1196	.6121	.1546
TF–IDF text	314.70	366.98	.196	.0776	.8075	.3481
Early fusion	333.00	399.28	.048	.0934	.7615	.2877

The constant baseline has test MAE 351.19 days, RMSE 419.23 days, and $R^2 = -0.050$. Late fusion achieves MAE 317.13 days, RMSE 374.88 days, AUROC 0.7557, and Brier score 0.0877. Text has lower duration error than both fusion branches in this test sample. These descriptive differences do not establish statistical superiority or justify changing the preselected duration recommendation after inspecting test outcomes.

The duration baseline's nominal 90% split-conformal interval covers 48 of 64 test outcomes, or 75%, with a mean width of 890 days. This observed undercoverage is reported as a limitation rather than presented as calibrated 90% performance. All reported comparisons use the same retained registry test records.

IX. EVALUATION PROTOCOL FOR THE REGISTRY STUDY

Model selection and fusion-weight selection use tuning data. The separate calibration subset supplies absolute duration residuals for split-conformal uncertainty [13]. With $n_c = 11$ and $\alpha = 0.10$, the residual rank is $\lceil (n_c + 1)(1 - \alpha) \rceil = 11$. For the median baseline, the selected residual is 445 days. Centering on 482 days gives the interval [37, 927]. Temporal distribution shift can violate the exchangeability conditions underlying nominal coverage.

Regression is evaluated with MAE, RMSE, and R^2. Binary-risk evaluation uses AUROC, average precision, and Brier score, with $\text{Brier} = n^{-1} \sum_i (\hat{p}_i - y_i)^2$. F1 is not reported because no operational probability cutoff is specified for this experiment. The prolonged-duration outcome threshold is distinct from any

threshold that might later convert a probability into an operational decision.

Tuning and calibration each contain one outcome class. Their AUROC and average precision are therefore unavailable under the project's evaluation policy. The saved risk scores are raw probabilities; a fitted two-class sigmoid calibrator is unavailable. The experiment also stores percentile bootstrap intervals using 200 resamples and seed 42. These summaries condition on fixed models and independent trial resampling; they omit model-fitting uncertainty, site clustering, and multiple-comparison adjustment.

For duration errors $e_i = \hat{d}_i - d_i$, the reported definitions are $\mathrm{MAE} = n^{-1}\sum_i |e_i|$ and $\mathrm{RMSE} = \sqrt{n^{-1}\sum_i e_i^2}$. The coefficient of determination is $R^2 = 1 - \sum_i e_i^2 / \sum_i (d_i - \bar{d})^2$ and can be negative. A constant risk score gives test AUROC 0.5 and average precision equal to the observed positive fraction, $6/64 = 0.09375$. These controls make the ranking metrics interpretable under the small test prevalence. The selected duration baseline has tuning RMSE 288.77 days, while the selected raw text-risk model has tuning Brier score 0.01966. Neither tuning value is reported as test performance.

X. RESULTS REPORTING AND REPRODUCIBILITY

The project retains the canonical CSV, raw response pages, acquisition metadata, cohort exclusions, temporal exclusions, feature definitions, model manifest, saved pipelines, and held-out predictions. The canonical CSV SHA-256 begins `d096795e303b5a10`; the complete digest is retained with the project data. This identifies the precise source bytes rather than an evolving live registry query.

Fig. 6 summarizes the 312 duration-eligible records before temporal purging. Its threshold marker is derived from the 105 retained training records. The histogram describes the source cohort; it is not a plot of test prediction errors or an additional model-performance comparison.




Figure 6. Observed durations of 312 eligible records before temporal purging; the marker is the training-derived prolonged-duration threshold.

Verification replays all 756 saved held-out duration predictions across nine branches and recomputes the saved point metrics. The maximum absolute prediction difference is below 5×10^{-13} in the recorded environment. This confirms consistency of artifacts, code, and reported numbers; it does not measure prospective accuracy or eliminate dataset bias.

The saved research outputs connect each metric to its model branch, target definition, split membership, and trial identifier. A result displayed for an imported trial is therefore distinguishable from a held-out evaluation result. The project retains both the source records and derived prediction rows, supporting inspection of numerical errors and missing-data warnings without repeating acquisition.

The duration distribution contains a substantial right tail. Among the 312 eligible studies, recorded durations range from 16 to 8,719 days, with a median of 736.5 days and a mean of 1,026.15 days. The upper quartile of this entire eligible cohort is 1,363 days. This descriptive value differs from the 1,101-day threshold calculated on retained training records. The latter remains the target definition because using the full cohort to set the threshold would allow later outcomes to influence development. The histogram displays the entire eligible cohort, including observations subsequently removed by temporal purging.

Missingness affects the interpretation of both predictive features and complexity profiles. Detailed descriptions are unavailable for 346 of the 800 source records, or 43.25%, while titles, brief summaries, and eligibility text are present. Criterion count and the supplied text-complexity input are absent for every source record. A nonempty eligibility narrative therefore does not imply an observed numeric criterion count. The text model can use the narrative while the corresponding structured column remains constant after imputation. This difference in available information is relevant to the comparison of text and structured branches, although it does not establish why an individual prediction is accurate.

The additional structured ensembles show that changing model family does not consistently resolve the observed errors. Extra trees attain test MAE 354.22 days, RMSE 418.79 days, and AUROC 0.6710. Random forests attain MAE 350.55 days, RMSE 428.37 days, and AUROC 0.6724. Gradient boosting attains MAE 372.39 days, RMSE 491.10 days, and AUROC 0.5431. Histogram gradient boosting attains MAE 447.14 days, RMSE 589.99 days, and AUROC 0.5747. These values come from the same 64 test records as the linear and fusion results. They provide additional controls rather than separate replications with independent test data.

The text model has the lowest test MAE and RMSE among the nine saved branches. Its bootstrap 95% intervals are 265.32–359.60 days for MAE, 319.72–414.26 days for RMSE, and 0.5976–0.9626 for AUROC. Early fusion has intervals of 282.40–383.69 days for MAE and 0.5287–0.9356 for AUROC. These broad ranges indicate that point estimates should be interpreted with care. Individual metric intervals do not directly test the difference between two models, and overlap or nonoverlap should not be substituted for the saved paired comparison.

For the text model, the paired test MAE difference relative to the median baseline is -36.49 days, with a bootstrap 95% interval from -93.52 to 23.50 days. Late fusion has a difference of -34.06 days, with an interval from -102.01 to 31.01 days. Both intervals include zero. The corresponding early-fusion difference is -18.19 days, with an interval from -78.04 to 44.28 days. These results do not provide a clear conditional duration-error advantage over the constant reference, despite favorable candidate point estimates. The comparisons preserve trial pairing and condition on the already fitted models.

The raw-probability comparison gives a different view. Text has a Brier-score difference of -0.0311 relative to the prevalence baseline, with a paired interval from -0.0430 to -0.0165. Late fusion has a difference of -0.0209, with an interval from -0.0330 to -0.0070. These recorded conditional comparisons favor the candidate scores in this test sample. They are not corrected for comparing multiple candidate models and do not establish external probability calibration. A Brier improvement also does not imply that a particular decision threshold provides acceptable false-positive or false-negative rates.

The displayed baseline illustrates the distinction between a usable software output and an individualized estimator. Every eligible record evaluated through that bundle receives the same 482-day duration center and the same raw prevalence risk of $26/105$. The latter reflects a training positive fraction of approximately 24.76%, whereas the held-out fraction is $6/64$, or 9.375%. The screenshot rounds the training fraction to 24.8%. Differences between trial descriptions do not change this constant output. The interface therefore identifies its explanation as a training baseline instead of presenting unsupported feature contributions. The separate offline text-risk recommendation should not be inferred from this display.

Interval errors can also be inspected directly. Of the 64 test durations, one lies below the 37-day lower endpoint and 15 lie above the 927-day upper endpoint. The 48 covered observations account for the reported 75% empirical coverage. The 890-day interval width follows from twice the saved 445-day calibration residual. This width is a property of the chosen calibration procedure and model; it is not a clinically determined tolerance. The sample shows that a substantial interval can still underrepresent the upper-duration tail when development and test periods differ.

The fixed-reference PCI requires similar attention to input completeness. If the unmodified snapshot rows are passed to its calculator, the absent criterion-count and text-complexity inputs contribute zero under the documented policy. Their configured weights total 35 points, so the remaining observed components can contribute at most 65 points even if all reach their ceilings. The configured High category above 70 is consequently unattainable for those unfilled rows. This is a consequence of missing source inputs, not evidence that the actual protocols lack eligibility or textual burden. Manually completed or separately derived inputs would need explicit provenance before being compared with the original snapshot scores.

These results support a consistent analyst workflow. A trial is first inspected for source completeness and recorded study characteristics, then for its descriptive PCI definition, and finally for the selected model's duration, probability semantics, and uncertainty evidence. A comparison between trials uses the same target and model branch. A change in imported data or predictor selection requires its own saved evidence rather than inheriting the metrics of the frozen cohort. This sequence keeps registry observations, model outputs, and operational interpretation connected without treating them as interchangeable measurements.

XI. LIMITATIONS, ETHICS, AND RESPONSIBLE USE

The cohort includes completed studies only, excluding ongoing or discontinued trials from the duration analysis. Convenience sampling, date-precision filtering, and temporal purging further restrict its scope. The test set has only six positive outcomes, while tuning and calibration have none. These sample sizes limit discrimination estimates, calibration, subgroup analysis, and the stability of model selection.

The snapshot contains the latest retrieved registry descriptions, not verified pre-start versions. Actual enrollment and revised narrative fields may encode post-start information. Outcome purging cannot remove this feature-provenance uncertainty. The PCI weights and categories are explicit research choices with no claimed clinical validation, and missing inputs can lower the fixed-reference score. Explanations are model evidence, not causal recommendations.

The experiment also does not model right censoring: its duration target is available only after an actual completion date is recorded. A model for ongoing studies would require a different outcome design, such as an explicitly specified time-to-event analysis. Sponsor, site, and therapeutic-area clustering may produce dependencies between records, while the saved bootstrap treats trials as independently resampled units. The current evidence cannot quantify these sources of uncertainty or establish performance for an unseen institution.

The system supports research and operational exploration rather than diagnosis, treatment selection, or regulatory decisions. Public registry data do not establish individual patient benefit. External validation on historically versioned records and prospectively defined prediction times remains necessary. The workbench presents these restrictions alongside the prediction evidence so that analysts can assess the scope of each result.

XII. CONCLUSION

Clinical Trial Intelligence connects registry validation, explicit complexity scoring, unimodal and multimodal modeling, and a browser research workbench. The experiment reports reproducible measurements from a frozen ClinicalTrials.gov cohort, with exact target and temporal-split definitions. A replay of saved predictions confirms the numerical consistency of the reported results.

On the 64-record test set, TF–IDF text has lower duration error than early and late fusion. Tuning nevertheless selects the constant median model for duration, illustrating why test performance and model-selection evidence must remain distinct. The nominal 90% duration interval attains only 75% observed coverage, and historical feature availability is unverified.

The project establishes an auditable retrospective workflow. Stronger scientific claims require larger independent cohorts, historical registry features, adequate positive outcomes, and a predefined prospective evaluation. These requirements define the next research stage without treating software functionality as clinical validation.

ACKNOWLEDGMENT

The authors acknowledge the U.S. National Library of Medicine for ClinicalTrials.gov and the open-source software used by the project. OpenAI Codex assisted in revising manuscript text and writing figure-rendering and verification scripts. Assistance affected Sections I–XII and the code for Figs. 1–4 and 6; Fig. 5 is a project browser capture. The authors retain responsibility for checking the content and references.

REFERENCES

[1] National Library of Medicine, "ClinicalTrials.gov API," accessed Oct. 12, 2026. [Online]. Available: https://clinicaltrials.gov/data-api/api

[2] N. Markey, B. Howitt, I. El-Mansouri, C. Schwartzenberg, O. Kotova, and C. Meier, "Clinical trials are becoming more complex: A machine learning analysis of data from over 16,000 trials," *Sci. Rep.*, vol. 14, no. 1, Art. no. 3514, Feb. 2024, doi: 10.1038/s41598-024-53211-z.

[3] J. Cho, Q. Xu, C. H. Wong, and A. W. Lo, "Predicting clinical trial duration via statistical and machine learning models," *Contemp. Clin. Trials Commun.*, vol. 45, Art. no. 101473, Jun. 2025, doi: 10.1016/j.conctc.2025.101473.

[4] T. Baltrušaitis, C. Ahuja, and L.-P. Morency, "Multimodal machine learning: A survey and taxonomy," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 41, no. 2, pp. 423–443, Feb. 2019, doi: 10.1109/TPAMI.2018.2798607.

[5] S. Kapoor and A. Narayanan, "Leakage and the reproducibility crisis in machine-learning-based science," *Patterns*, vol. 4, no. 9, Art. no. 100804, Sep. 2023, doi: 10.1016/j.patter.2023.100804.

[6] F. Pedregosa *et al.*, "Scikit-learn: Machine learning in Python," *J. Mach. Learn. Res.*, vol. 12, pp. 2825–2830, 2011.

[7] G. Salton and C. Buckley, "Term-weighting approaches in automatic text retrieval," *Inf. Process. Manage.*, vol. 24, no. 5, pp. 513–523, 1988, doi: 10.1016/0306-4573(88)90021-0.

[8] J. Lee *et al.*, "BioBERT: A pre-trained biomedical language representation model for biomedical text mining," *Bioinformatics*, vol. 36, no. 4, pp. 1234–1240, Feb. 2020, doi: 10.1093/bioinformatics/btz682.

[9] P. Geurts, D. Ernst, and L. Wehenkel, "Extremely randomized trees," *Mach. Learn.*, vol. 63, no. 1, pp. 3–42, Apr. 2006, doi: 10.1007/s10994-006-6226-1.

[10] L. Breiman, "Random forests," *Mach. Learn.*, vol. 45, no. 1, pp. 5–32, Oct. 2001, doi: 10.1023/A:1010933404324.

[11] J. H. Friedman, "Greedy function approximation: A gradient boosting machine," *Ann. Statist.*, vol. 29, no. 5, pp. 1189–1232, Oct. 2001, doi: 10.1214/aos/1013203451.

[12] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems*, vol. 30, 2017, pp. 4765–4774.

[13] A. N. Angelopoulos and S. Bates, "Conformal prediction: A gentle introduction," *Found. Trends Mach. Learn.*, vol. 16, no. 4, pp. 494–591, 2023, doi: 10.1561/2200000101.