

Problem List

Accepted

Editor

Constraints:

n == names.length == heights.length

1 <= n <= 10⁵

1 <= names[i].length <= 20

1 <= heights[i] <= 10⁵

names[i] consists of lower and upper case English letters.

All the values of heights are distinct.

Seen this question in a real interview before?

Yes

No

Accepted

394,782 / 465.5K

Acceptance Rate

84.8%

1.9K

180

Code

Java

Auto

```
1 import java.util.Arrays;
2
3 class Solution {
4     public String[] sortPeople(String[] names, int[] heights) {
5         int n = names.length;
6
7         Integer[] indices = new Integer[n];
8         for (int i = 0; i < n; i++) {
9             indices[i] = i;
10        }
11    }
12 }
```

Saved

Ln 7, Col 5

Test Result

TestCase

Accepted

Runtime: 1 ms

Case 1

Case 2

Input

names =

["Mary", "John", "Emma"]

heights =

[180, 165, 170]

Output

Nifty bank

-0.95%

Search

ENG IN

11:30 AM

8/4/2026

Problem List

Accepted

Editor

Constraints:

n == names.length == heights.length

1 <= n <= 10⁵

1 <= names[i].length <= 20

1 <= heights[i] <= 10⁵

names[i] consists of lower and upper case English letters.

All the values of heights are distinct.

Seen this question in a real interview before?

Yes

No

Accepted

394,782 / 465.5K

Acceptance Rate

84.8%

1.9K

180

Code

Java

Auto

1

import java.util.Arrays;

2

3

class Solution {

4

public String[] sortPeople(String[] names, int[] heights) {

5

int n = names.length;

6

7

8

Integer[] indices = new Integer[n];

9

for (int i = 0; i < n; i++) {

10

indices[i] = i;

11

}

Test Result

Testcase

Accepted

Runtime: 1 ms

Case 1

Case 2

Input

names =

["Mary", "John", "Emma"]

heights =

[180, 165, 170]

Output

Nifty bank

-0.95%

Search

ENG

IN

11:30 AM

8/4/2026

Problem

Submissions

Leaderboard

Discussions

HackerRank

PrepareJavaData StructuresJava Comparator

Exit Full Screen View

Comparators are used to compare two objects. In this challenge, you'll create a comparator and use it to sort an array.

The Player class is provided for you in your editor. It has 2 fields: a **name** String and a **score** integer.

Given an array of **n** Player objects, write a comparator that sorts them in order of decreasing score; if 2 or more players have the same score, sort those players alphabetically by name. To do this, you must create a Checker class that implements the Comparator interface, then write an int compare(Player a, Player b) method implementing the `Comparator.compare(T o1, T o2)` method.

Input Format

Input from stdin is handled by the locked stub code in the Solution class.

The first line contains an integer, **n**, denoting the number of players.

Each of the **n** subsequent lines contains a player's **name** and **score**, respectively.

Constraints

- $0 \leq \text{score} \leq 1000$
- 2 players can have the same name.
- Player names consist of lowercase English letters.

Output Format

You are not responsible for printing any output to stdout. The locked stub code in Solution will create a Checker object, use it to sort the Player array, and print each sorted element.

```
36 Arrays.sort(player, checker);
37 for(int i = 0; i < player.length; i++){
38     System.out.printf("%s %s\n", player[i].name, player[i].score);
39 }
40 }
41 }
```

Line: 9 Col: 2

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends?



Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Compiler Message

Success

Input (stdin)

1	5
2	amy 100

Download

Hot days ahead
31°C



ENG
IN



11:27 AM
8/4/2026

Description | Accepted X | Editor

179. Largest Number

Medium Topics Companies

Given a list of non-negative integers `nums`, arrange them such that they form the largest number and return the result as a string.

Since the result may be very large, so you need to return a string instead of an integer.

Example 1:

Input: `nums = [10,2]`
Output: `"210"`

Example 2:

Input: `nums = [3,30,34,5,9]`
Output: `"9534330"`

Constraints:

- $1 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 10^9$

9.5K 227 ☆ ↗ ⓘ

Breaking news
Udhayanidhi Stal...

Code

Java Auto

```
4 public String largestNumber(int[] nums) {  
5     String[] strNums = new String[nums.length];  
6     for (int i = 0; i < nums.length; i++) {  
7         strNums[i] = String.valueOf(nums[i]);  
8     }  
9  
10  
11     Arrays.sort(strNums, (a, b) -> (b + a).compareTo(a + b));  
12  
13  
14     if (strNums[0].equals("0")) {
```

Saved

Ln 4, Col 46

Test Result | Testcase

Accepted Runtime: 1 ms

Case 1 Case 2

Input

nums =
[10,2]

Output

"210"

Expected



Search



ENG
IN



11:25 AM
8/4/2026

Sometimes it's better to use dynamic size arrays. Java's [Arraylist](#) can provide you this feature. Try to solve this problem using Arraylist.

You are given n lines. In each line there are zero or more integers. You need to answer a few queries where you need to tell the number located in y^{th} position of x^{th} line.

Take your input from System.in.

Input Format

The first line has an integer n . In each of the next n lines there will be an integer d denoting number of integers on that line and then there will be d space-separated integers. In the next line there will be an integer q denoting number of queries. Each query will consist of two integers x and y .

Constraints

- $1 \leq n \leq 20000$
- $0 \leq d \leq 50000$
- $1 \leq q \leq 1000$
- $1 \leq x \leq n$

Each number will fit in signed integer.

Total number of integers in n lines will not cross 10^5 .

Output Format

In each line, output the number located in y^{th} position of x^{th} line. If there is no such position, just print "ERROR!"

Sample Input

☐ Test against custom input



You have earned 10.00 points!

You are now 27 points away from the 4th star for your java badge.

61%

123/150

Congratulations

You solved this challenge. Would you like to challenge your friends?



Test case 0

Test case 1

Test case 2

Test case 3

Compiler Message

Success

Input (stdin)

Download

```
1 5
2 5 41 77 74 22 44
3 1 12
```

In computer science, a priority queue is an abstract data type which is like a regular queue, but where additionally each element has a "priority" associated with it. In a priority queue, an element with high priority is served before an element with low priority. - [Wikipedia](#)

In this problem we will test your knowledge on [Java Priority Queue](#).

There are a number of students in a school who wait to be served. Two types of events, ENTER and SERVED, can take place which are described below.

- ENTER: A student with some priority enters the queue to be served.
- SERVED: The student with the highest priority is served (removed) from the queue.

A unique id is assigned to each student entering the queue. The queue serves the students based on the following criteria (priority criteria):

1. The student having the highest Cumulative Grade Point Average (CGPA) is served first.
2. Any students having the same CGPA will be served by name in ascending case-sensitive alphabetical order.
3. Any students having the same CGPA and name will be served in ascending order of the id.

Create the following two classes:

- The Student class should implement:
 - The constructor `Student(int id, String name, double cgpa)`.
 - The method `int getID()` to return the id of the student.
 - The method `String getName()` to return the name of the student.
 - The method `double getCGPA()` to return the CGPA of the student.

```

39  class Priorities {
40      public List<Student> getStudents(List<String> events) {
41          java.util.PriorityQueue<Student> pq = new java.util.PriorityQueue<>();
42
43          for (String event : events) {
44              String[] parts = event.split(" ");
45              if (parts[0].equals("ENTER")) {
46                  String name = parts[1];
47                  double cgpa = Double.parseDouble(parts[2]);
48                  int id = Integer.parseInt(parts[3]);
49                  pq.add(new Student(id, name, cgpa));
50              } else if (parts[0].equals("SERVED")) {
51                  pq.poll();
52              }
53          }
54
55          List<Student> students = new ArrayList<>();
56          while (!pq.isEmpty()) {
57              students.add(pq.poll());
58          }
59
60          return students;
61      }
62  }
63
64  >

```

Line: 63 Col: 2

☐ Test against custom input

DescriptionAccepted × Editions

values {"Sunday", "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday", "Sunday"}

Note: January 1, 1971 was a Friday.

Example 1:
Input: day = 31, month = 8, year = 1971
Output: "Saturday"

Example 2:
Input: day = 18, month = 7, year = 1971
Output: "Sunday"

Example 3:
Input: day = 15, month = 8, year = 1971
Output: "Sunday"

Constraints:
• The given dates are valid dates between the years 1971 and 2100.

461 44 ☆ ↗ ↻

Code

Java Auto

```
1 import java.time.LocalDate;
2 import java.time.format.TextStyle;
3 import java.util.Locale;
4
5 class Solution {
6     public String dayOfTheWeek(int day, int month, int year) {
7         return LocalDate.of(year, month, day).getDayOfWeek().getDisplayName(TextStyle.FULL, Locale.ENGLISH);
8     }
9 }
```

SavedLn 9, Col 2

Test ResultTestcase

AcceptedRuntime: 11 ms

Case 1Case 2Case 3

Input

day = 31

month = 8

year =

WhatsApp

 VTRH G1
~ Hemelatha D Thiagarajan: 5KM FEMALE
NOT RECEIVED PRIZE WINNERS
VEL TECH RUN FOR HER BELOW PRIZE W

31°C
Partly sunny

Search

ENG IN 11:11 AM
8/4/2026

Problem List

1154. Day of the Year

Easy

Topics

Companies

Hint

Given a string `date` representing a [Gregorian calendar](#) date formatted as `YYYY-MM-DD`, return the day number of the year.

Example 1:
Input: `date = "2019-01-09"`
Output: `9`
Explanation: Given date is the 9th day of the year in 2019.

Example 2:
Input: `date = "2019-02-10"`
Output: `41`

Constraints:

- `date.length == 10`
- `date[4] == date[7] == '-',` and all other characters are digits.

517 35

Code

Java

Auto

Ln 26, Col 2

```
1 class Solution {
2     public int dayOfYear(String date) {
3         int year = Integer.parseInt(date.substring(0, 4));
4         int month = Integer.parseInt(date.substring(5, 7));
5         int day = Integer.parseInt(date.substring(8, 10));
6
7         int[] daysInMonth = {0, 31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31};
8         int totalDays = 0;
9
10        for (int i = 1; i < month; i++) {
11            totalDays += daysInMonth[i];
12        }
13        totalDays += day;
14        return totalDays;
15    }
16 }
```

Test Result

Testcase

Accepted Runtime: 0 ms

Case 1 Case 2

Input

date = "2019-01-09"

Output

9

Expected

RELIANCE -1.29%

Search

ENG IN

11:08 AM 8/4/2026

Description

Accepted

1360. Number of Days Between Two Dates

EasyTopicsCompaniesHint

Write a program to count the number of days between two dates.

The two dates are given as strings, their format is `MM-DD` as shown in the examples.

Example 1:

Input: date1 = "2019-06-29", date2 = "2019-06-30"

Output: 1

Example 2:

Input: date1 = "2020-01-15", date2 = "2019-12-31"

Output: 15

Constraints:

44342

Code

Java

```
1 import java.time.LocalDate;
2 import java.time.temporal.ChronoUnit;
3
4 class Solution {
5     public int daysBetweenDates(String date1, String date2) {
6
7         LocalDate d1 = LocalDate.parse(date1);
8         LocalDate d2 = LocalDate.parse(date2);
9         return (int) Math.abs(ChronoUnit.DAYS.between(d1, d2));
10    }
11 }
```

SavedLn 1, Col 1

Test ResultTestcase

AcceptedRuntime: 5 ms

Case 1Case 2

Input

date1 =
"2019-06-29"

date2 =
"2019-06-30"

Output

Problem

Submissions

Leaderboard

Discussions

The `Calendar` class is an abstract class that provides methods for converting between a specific instant in time and a set of calendar fields such as YEAR, MONTH, DAY_OF_MONTH, HOUR, and so on, and for manipulating the calendar fields, such as getting the date of the next week.

You are given a date. You just need to write the method, `getDay`, which returns the day on that date. To simplify your task, we have provided a portion of the code in the editor.

Example

`month = 8`
`day = 14`
`year = 2017`

The method should return `MONDAY` as the day on that date.

AUGUST 2017

SUN	MON	TUE	WED	THU	FRI	SAT
		1	2	3	4	5
6	7	8	9	10	11	12
13	14	15	16	17	18	19



You have earned 15.00 points!
You are now 57 points away from the 4th star for your java badge.

19% 93/150

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

Next Challenge

Test case 0

Compiler Message

Success

Test case 1

Test case 2

Input (stdin)

08 05 2015

Download

Test case 3

Test case 4

Expected Output

WEDNESDAY

Download

Test case 5