

## 1704. Determine if String Halves Are Alike

Solved 

[Easy](#)
[Topics](#)
[Companies](#)
[Hint](#)

You are given a string `s` of even length. Split this string into two halves of equal lengths, and let `a` be the first half and `b` be the second half.

Two strings are **alike** if they have the same number of vowels (`'a'`, `'e'`, `'i'`, `'o'`, `'u'`, `'A'`, `'E'`, `'I'`, `'O'`, `'U'`). Notice that `s` contains uppercase and lowercase letters.

Return `true` if `a` and `b` are **alike**. Otherwise, return `false`.

### Example 1:

**Input:** `s = "book"`

**Output:** `true`

**Explanation:** `a = "bo"` and `b = "ok"`. `a` has 1 vowel and `b` has 1 vowel. Therefore, they are alike.

### Example 2:

**Input:** `s = "textbook"`

**Output:** `false`

**Explanation:** `a = "text"` and `b = "book"`. `a` has 1 vowel whereas `b` has 2. Therefore, they are not alike. Notice that the vowel `o` is counted twice.

### Constraints:

 2.3K
 
 108
 



5 Online

### </> Code

Java  Auto

```

1 class Solution {
2     public boolean halvesAreAlike(String s) {
3         int mid = s.length() / 2;
4         int countA = 0;
5         int countB = 0;
6
7         for (int i = 0; i < mid; i++) {
8             if (isVowel(s.charAt(i))) {
9                 countA++;
10            }
11        }
12
13        for (int i = mid; i < s.length(); i++) {

```

Saved

Ln 1, Col 1

☒ Testcase
 
☒ Test Result

Accepted Runtime: 0 ms

☒ Case 1
 ☒ Case 2

Input

`s =`  
`"book"`

Output

`true`

Expected

`true`

Determine if String Halves Are... × | vtu28261-a11y/PSJ---LAB × | Compare the Triplets | Hacker × | hackerrank.com/rest/contests × | +

← → ↺ 🌐 hackerrank.com/challenges/compare-the-triplets/problem ☆ 📁 🎯 ⋮

## Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

✔ Sample Test case 0

Input (stdin)

Download

|   |        |
|---|--------|
| 1 | 5 6 7  |
| 2 | 3 6 10 |

✔ Sample Test case 1

Your Output (stdout)

Download

|   |     |
|---|-----|
| 1 | 1 1 |
|---|-----|

Expected Output

Download

|   |     |
|---|-----|
| 1 | 1 1 |
|---|-----|

[Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Helpdesk](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#)



## 217. Contains Duplicate

Solved ✓

Easy

Topics

Companies

Given an integer array `nums`, return `true` if any value appears **at least twice** in the array, and return `false` if every element is distinct.

### Example 1:

Input: `nums = [1,2,3,1]`

Output: `true`

#### Explanation:

The element 1 occurs at the indices 0 and 3.

### Example 2:

Input: `nums = [1,2,3,4]`

Output: `false`

#### Explanation:

All elements are distinct.

### Example 3:

Input: `nums = [1,1,1,3,3,4,3,2,4,2]`

Output: `true`

14.2K



469



365 Online

### Code

Java Auto

```
1 import java.util.HashSet;
2
3 class Solution {
4     public boolean containsDuplicate(int[] nums) {
5         HashSet<Integer> set = new HashSet<>();
6
7         for (int num : nums) {
8             if (set.contains(num)) {
9                 return true;
10            }
11            set.add(num);
12        }
13    }
14 }
```

Saved

Ln 16, Col 2

### Testcase Test Result

Accepted Runtime: 0 ms

✓ Case 1

✓ Case 2

✓ Case 3

#### Input

`nums =`  
`[1,2,3,1]`



#### Output

`true`

#### Expected

`true`

# Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

## ✔ Sample Test case 0

Input (stdin)

Download

|   |            |
|---|------------|
| 1 | 07:05:45PM |
|---|------------|

Your Output (stdout)

|   |          |
|---|----------|
| 1 | 19:05:45 |
|---|----------|

Expected Output

Download

|   |          |
|---|----------|
| 1 | 19:05:45 |
|---|----------|

[Description](#)
[Editorial](#)
[Solutions](#)
[Submissions](#)

## 283. Move Zeroes

Solved 

[Easy](#)
[Topics](#)
[Companies](#)
[Hint](#)

Given an integer array `nums`, move all `0`'s to the end of it while maintaining the relative order of the non-zero elements.

**Note** that you must do this in-place without making a copy of the array.

### Example 1:

Input: `nums = [0,1,0,3,12]`

Output: `[1,3,12,0,0]`

### Example 2:

Input: `nums = [0]`

Output: `[0]`

### Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

**Follow up:** Could you minimize the total number of operations done?

`</>` Code

Java  Auto

```

1 class Solution {
2     public void moveZeroes(int[] nums) {
3         int index = 0;
4
5         for (int i = 0; i < nums.length; i++) {
6             if (nums[i] != 0) {
7                 nums[index] = nums[i];
8                 index++;
9             }
10        }
11
12        while (index < nums.length) {
13            nums[index] = 0;
14        }
15    }
16}
```

Saved

Ln 1, Col 1

☒ Testcase
 [Test Result](#)

Accepted Runtime: 0 ms

☒ Case 1
 ☒ Case 2

Input

nums =  
`[0,1,0,3,12]`

Output

`[1,3,12,0,0]`

Expected

# Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

## ✔ Sample Test case 0

Input (stdin)

Download

|   |          |
|---|----------|
| 1 | 3        |
| 2 | 11 2 4   |
| 3 | 4 5 6    |
| 4 | 10 8 -12 |

Your Output (stdout)

|   |    |
|---|----|
| 1 | 15 |
|---|----|

Expected Output

Download

|   |    |
|---|----|
| 1 | 15 |
|---|----|

## 867. Transpose Matrix

Solved ✓

Easy Topics Companies Hint

Given a 2D integer array `matrix`, return *the transpose of* `matrix`.

The **transpose** of a matrix is the matrix flipped over its main diagonal, switching the matrix's row and column indices.

|     |    |    |
|-----|----|----|
| 2   | 4  | -1 |
| -10 | 5  | 11 |
| 18  | -7 | 6  |

→

|    |     |    |
|----|-----|----|
| 2  | -10 | 18 |
| 4  | 5   | -7 |
| -1 | 11  | 6  |

### Example 1:

Input: `matrix = [[1,2,3],[4,5,6],[7,8,9]]`  
 Output: `[[1,4,7],[2,5,8],[3,6,9]]`

### Example 2:

Input: `matrix = [[1,2,3],[4,5,6]]`  
 Output: `[[1,4],[2,5],[3,6]]`

### Constraints:

- `m == matrix.length`

4.3K 133 ☆ ↗ ?

30 Online

### Code

Java Auto

```
1 class Solution {
2     public int[][] transpose(int[][] matrix) {
3         int m = matrix.length;
4         int n = matrix[0].length;
5
6         int[][] result = new int[n][m];
7
8         for (int i = 0; i < m; i++) {
9             for (int j = 0; j < n; j++) {
10                 result[j][i] = matrix[i][j];
11             }
12         }
13     }
14 }
```

Saved

Ln 16, Col 2

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

matrix =  
[[1,2,3],[4,5,6],[7,8,9]]

Output

[[1,4,7],[2,5,8],[3,6,9]]

Expected

[[1,4,7],[2,5,8],[3,6,9]]

Problem List

<

>

Description

Editorial

Solutions

Submissions

1314. Matrix Block Sum

Solved

Medium

Topics

Companies

Hint

Given a  $m \times n$  matrix `mat` and an integer `k`, return a matrix `answer` where each `answer[i][j]` is the sum of all elements `mat[r][c]` for:

$i - k \leq r \leq i + k,$

$j - k \leq c \leq j + k,$  and

$(r, c)$  is a valid position in the matrix.

Example 1:

Input: `mat = [[1,2,3],[4,5,6],[7,8,9]]`, `k = 1`

Output: `[[12,21,16],[27,45,33],[24,39,28]]`

Example 2:

Input: `mat = [[1,2,3],[4,5,6],[7,8,9]]`, `k = 2`

Output: `[[45,45,45],[45,45,45],[45,45,45]]`

Constraints:

$m == \text{mat.length}$

$n == \text{mat}[i].\text{length}$

$1 \leq m, n, k \leq 100$

$1 \leq \text{mat}[i][j] \leq 100$

2.6K

52

20 Online

Submit

Code

Java

Auto

```
1 class Solution {
2     public int[][] matrixBlockSum(int[][] mat, int k) {
3         int m = mat.length;
4         int n = mat[0].length;
5
6         int[][] answer = new int[m][n];
7
8         for (int i = 0; i < m; i++) {
9             for (int j = 0; j < n; j++) {
10
11                 int sum = 0;
12
13                 int r1 = Math.max(0, i - k);
```

Saved

Ln 30, Col 2

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Input

mat =

`[[1,2,3],[4,5,6],[7,8,9]]`

k =

`1`

Output

`[[12,21,16],[27,45,33],[24,39,28]]`



# Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

✓ **Sample Test case 0**

✓ Sample Test case 1

✓ Sample Test case 2

✓ Sample Test case 3

Input (stdin)

Download

|   |             |
|---|-------------|
| 1 | 4 4 1       |
| 2 | 1 2 3 4     |
| 3 | 5 6 7 8     |
| 4 | 9 10 11 12  |
| 5 | 13 14 15 16 |

Your Output (stdout)

|   |            |
|---|------------|
| 1 | 2 3 4 8    |
| 2 | 1 7 11 12  |
| 3 | 5 6 10 16  |
| 4 | 9 13 14 15 |

## Compilation Completed

### • Case 1

Input:  

**n =**

3

**mat1[][] =**

1 1 1  
1 1 1

**mat2[][] =**

1 1 1  
1 1 1

Expected Output:

[[3, 3, 3],  
[3, 3, 3],  
[3, 3, 3]]