

Task 5

Writing Join Queries, Equivalent, and/or Recursive Queries

Case study : Online Food Ordering System

Objective : To perform advanced query processing and test its heuristics by designing optimized complex queries, for the online food ordering system.

1. Join Queries

Query1: Retrieve all orders along with the corresponding Customer's name.

```
SELECT o.Order_ID, o.order_date, o.order_total, c.cust_Name  
FROM OrderTable o  
JOIN Customer c ON o.cust_ID = c.cust_ID;
```

Query2: Retrieve all menu items along with the restaurant name that offers them.

```
SELECT m.Item_Name, m.Price, r.Rest_Name  
FROM Menu_Item m  
JOIN Restaurant r ON m.Rest = r.Rest_ID;
```

Query3: Retrieve all orders and their delivery status

```
SELECT o.Order_ID, o.Order_Total, d.Delivery_status, d.Delivery-  
Time.
```

```
FROM OrderTable o
```

```
LEFT JOIN Delivery d ON o.Order_ID = d.Order_ID;
```

Order-ID	Order-date	Order-total	Cust-Name
1	2025-01-20	800	Alice
2	2025-01-21	500	Bob
3	2025-01-22	700	Charlie

Item-Name	Price	Rest-Name
Pizza	450	Food Paradise
Burger	270	Food Paradise
Sushi	720	Tasty Treats
Pasta	360	Food Paradise
Noodles	315	Global Eats

Order-ID	Order-Total	Delivery-status	Delivery-Time
1	800	Delivered	2025-01-20 14:30
2	500	Pending	NULL
3	700	Delivered	2025-01-22 16:00

Order-ID	Order-Date	Order-Total	Cust-Name
1	2025-01-20	800	Alice
2	2025-01-21	500	Bob
3	2025-01-22	700	Charlie

Cust-Name	Order-ID	Order-Total
Alice	1	800
Bob	2	500
Charlie	3	700

Order-ID	Order-Total	Cust-Name
1	800	Alice
2	500	Bob
3	700	Charlie

Cust-Name	Order-ID	Order-Total
Alice	1	800
Bob	2	500
Charlie	3	700

Cust-Name	Item-Name	Price
Alice	Pizza	450
Alice	Burger	270
Alice	Sushi	720
Alice	Pasta	360
Alice	Noodles	315
Bob	Pizza	450
Bob	Burger	270
Bob	Sushi	720
Bob	Pasta	360
Bob	Noodles	315

Inner Join

An Inner Join retrieves records that have matching values in both tables.

Query : Retrieves all orders along with their customer names.

```
SELECT o.Order_ID, o.Order_Date, o.Order_Total, c.cust_Name  
FROM OrderTable o  
INNER JOIN customer c ON o.cust_ID = c.cust_ID;
```

LEFT OUTER JOIN :

A left outer join retrieves all records from the left table and the matched records from the right table. If no match is found, NULL is returned for columns from the right table.

Query : Retrieve all customers, even those who haven't placed any orders.

```
SELECT c.cust_Name, o.Order_ID, o.Order_Total  
FROM customer c  
LEFT JOIN OrderTable o ON c.cust_ID = o.cust_ID;
```

RIGHT OUTER JOIN

A right outer join retrieves all records from the right table and the matched records from the left table. If no match is found, NULL is returned for columns from the left table.

Item1	Item2	Rest_Name
Pizza	Burger	FoodParadise
Pizza	Pasta	FoodParadise
Burger	Pizza	FoodParadise
Burger	Pasta	FoodParadise
Pasta	Pizza	FoodParadise
Pasta	Burger	FoodParadise

Cat_ID	Cat_Name	Parent_Cat_ID
4	Pizza	2
2	Italian	1
1	Food	NULL

Query: Retrieve all orders and the names of customers who placed them. Include orders even if the customer details are missing.

```
SELECT o.Order-ID, o.Order-Total, c.Cust-Name  
FROM OrderTable o  
Right JOIN Customer c ON o.Cust-ID = c.Cust-ID;
```

Full Outer Join :-

A full outer join retrieves all records from both tables. If no match is found, NULL is returned for unmatched rows from either table.

Query: Retrieve all customers and all orders, even if there is no match.

```
SELECT c.Cust-Name, o.Order-ID, o.Order-Total  
FROM Customer c
```

```
FULL OUTER JOIN OrderTable o ON c.Cust-ID = o.Cust-ID;
```

CROSS JOIN:

A cross join returns the cartesian product of the two tables. Every row from the first table is combined with every row from the second table.

Query: Retrieve all possible combinations of customers and menu items.

```
SELECT c.Cust-Name, m.Item-Name, m.Price  
FROM Customer c
```

```
CROSS JOIN Menu-Item m;
```

SELF JOIN

A self join joins a table with itself. It is used for hierarchical or comparison data.

Query: Retrieve all menu items that belong to the same restaurant as another item.

```
SELECT m1.Item_Name AS Item1, m2.Item_Name AS Item2, r.Rest_Name.
```

```
FROM Menu_Item m1.
```

```
JOIN Menu_Item AS Item1, m2.Item_Name AS Item2, r.Rest_Name
```

```
JOIN Restaurant r ON m1.Rest_ID = r.Rest_ID;
```

2. Equivalent Queries:

Query 1: Retrieve all customers who placed orders using a join.

Using Join:

```
SELECT DISTINCT c.cust_name
```

```
FROM customer c
```

```
JOIN OrderTable o ON c.cust_ID = o.cust_ID;
```

Equivalent Subquery:

```
SELECT cust_Name
```

```
FROM customer
```

```
WHERE cust_ID IN (SELECT cust_ID FROM OrderTable);
```


Query 2: Retrieve the restaurant offering the most expensive menu item.

Using Join:

```
SELECT r.Rest_Name, MAX(m.Price) AS MAX_Price  
FROM Menu_Item m  
JOIN Restaurant r ON m.Rest_ID = r.Rest_ID  
GROUP BY r.Rest_Name  
HAVING MAX(m.Price) = (SELECT MAX(Price) FROM Menu_Item);
```

Equivalent Subquery:

```
SELECT Rest_Name  
FROM Restaurant  
WHERE Rest_ID = (  
    SELECT Rest_ID  
    FROM Menu_Item  
    WHERE Price = (SELECT MAX(Price) FROM Menu_Item)  
);
```

Recursive Queries:

Oracle SQL supports recursion using the WITH clause for hierarchical data.

Query 1: Generate a recursive query to find all ancestors of a given category in a hypothetical "MenuCategory" Table.


```
CREATE TABLE Menu-Category (
    Cat_ID INT PRIMARY KEY,
    Cat_Name VARCHAR(50),
    Parent_Cat_ID INT
);
```

Sample Data :

```
INSERT INTO Menu-Category (Cat_ID, Cat_Name, Parent_Cat_ID)
VALUES (1, 'Food', NULL);
```

```
INSERT INTO Menu-Category (Cat_ID, Cat_Name, Parent_Cat_ID)
VALUES (2, 'Italian', 1);
```

```
INSERT INTO Menu-Category (Cat_ID, Cat_Name, Parent_Cat_ID)
VALUES (3, 'Chinese', 1);
```

```
INSERT INTO Menu-Category (Cat_ID, Cat_Name, Parent_Cat_ID)
VALUES (4, 'Pizza', 2);
```

4. Optimizing Complex Queries

Query 1: Find customers who placed orders totalling more than 1000 across all their orders.

```
SELECT c.cust_Name, SUM(o.Order_Total) AS Total_Spent
```

```
FROM customers c
```

```
JOIN orders o ON c.cust_ID = o.cust_ID
```

```
GROUP BY c.cust_Name
```

```
HAVING SUM(o.Order_Total) > 1000 ;
```