

Task - 2

The SQL commands to create, insert, select and display a table for an online food ordering system.

1. Create Tables

a) Customer Table :

Create Table

```
Customers (customerID INT PRIMARY KEY, Name VARCHAR(100),  
Email VARCHAR(100), phone number VARCHAR(15),  
Address VARCHAR(255) );
```

b) FoodItems Table :

Create Table

```
FoodItems (FoodID INT PRIMARY KEY, FoodName VARCHAR(100),  
Price DECIMAL(10,2), Category VARCHAR(50) );
```

This is the sample how your commands are executed in the fig.

c) Orders Table :

```
Create Table Orders (OrderID INT PRIMARY KEY, CustomerID INT,  
Orderdate DATE, Total Amount DECIMAL(10,2),  
Foreign key (customerID) REFERENCES customers  
(customerID) );
```

d) Order details Table

Create Table Orderdetails (

Order detailsID INT

PRIMARY KEY, OrderID INT, FoodID INT, Quantity INT

Subtotal DECIMAL (10,2), Foreignkey (OrderID)
REFERENCES orders (OrderID), Foreign key
(FoodID) REFERENCES
FoodItems (FoodID));

2. Insert Records

a) Insert into customers Table

INSERT

INTO customers (customerID, Name, Email, PhoneNumber, Address)
VALUES (1, 'John Doe', 'john.doe@example.com', '1234567890', '123 Elm
street');

INSERT INTO customers (customerID, Name, Email, PhoneNumber, Address)
VALUES (2, 'Jane Smith', 'jane.smith@example.com', '9876543210', '456
Oak Avenue');

SELECT * FROM customers;

b) Insert into foodItems Table

INSERT

INTO FoodItems (FoodID, FoodName, Price, Category) VALUES (1, 'cheese
Pizza', 8.99, 'Pizza');

INSERT

INTO FoodItems (FoodID, FoodName, Price, Category) VALUES (2, 'Chicken
Burger', 5.49, 'Burger');

```
INSERT INTO FoodItems (FoodID, FoodName, Price, Category) VALUES (3, 'Veggie Salad', 4.99, 'Salad');
```

```
INSERT INTO FoodItems (FoodID, FoodName, Price, Category) VALUES (4, 'Chocolate Cake', 3.99, 'Dessert');
```

```
SELECT * FROM FoodItems;
```

c) Insert into Orders Table

```
INSERT INTO Orders (OrderID, CustomerID, Order date, TotalAmount) VALUES (1, 1, DATE '2025-01-03', 18.47);
```

```
INSERT INTO Orders (OrderID, CustomerID, Order date, TotalAmount) VALUES (2, 2, DATE '2025-01-03', 9.48);
```

```
SELECT * FROM Orders;
```

d) Insert into Order Details Table

```
INSERT INTO OrderDetails (OrderDetailID, OrderID, FoodID, Quantity, Subtotal) VALUES (1, 1, 1, 2, 17.98);
```

```
INSERT INTO OrderDetails (OrderDetailID, OrderID, FoodID, Quantity, Subtotal) VALUES (2, 1, 4, 1, 3.99);
```

```
INSERT INTO OrderDetails (OrderDetailID, OrderID, FoodID, Quantity, Subtotal) VALUES (3, 2, 2, 1, 5.49);
```


Order ID	Customer ID	Order Name	Total Amount
1	1	2025-01-03	18.47
2	2	2025-01-03	9.48

Order Detail ID	Order ID	Food ID	Quantity	Subtotal
1	1	1	2	17.98
2	2	4	1	3.99
3	3	2	1	6.49
4	4	3	1	4.99

VEL TECH	
EX NO.	2
PERFORMANCE (5)	5
RESULT AND ANALYSIS (5)	5
VIVA VOCE (5)	1
RECORD (5)	1
TOTAL (20)	1
SIGN WITH DATE	1

VEL TECH - USE	
EX NO.	
PERFORMANCE (5)	
RESULT AND ANALYSIS (5)	
VIVA VOCE (5)	
RECORD (5)	
TOTAL (20)	
SIGN WITH DATE	

```
INSERT INTO Orderdetails (OrderDetailID, OrderID, FoodID, Quantity, Subtotal)
VALUES (4, 2, 3, 1, 4.99);
```

```
SELECT * FROM OrderDetails;
```

3. Select Data

a) Select All Customers;

```
SELECT * FROM Customers;
```

b) Select All foodItems;

```
SELECT * FROM FoodItems;
```

c) Select All Orders;

```
SELECT * FROM Orders;
```

d) Select All Orderdetails;

```
SELECT * FROM OrderDetails;
```

FoodID	FoodName	Price	Category
1)	Cheese Pizza	8.99	Pizza
2)	Chicken Burger	5.49	Burger
3)	Veggie Salad	4.99	Salad
4)	Chocolate Cake	3.99	Dessert