

New tab

leetcode problems - Search

Running Sum of 1d Array - LeetCo

leetcode problems - Search

+

https://leetcode.com/problems/running-sum-of-1d-array/

Chat

Problem List

Submit

80 Online

Description

Editorial

Solutions

Submissions

1480. Running Sum of 1d Array

Solved

Easy

Topics

Companies

Hint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]...nums[i])`.

Return the running sum of `nums`.

Example 1:

Input: `nums = [1,2,3,4]`
Output: `[1,3,6,10]`
Explanation: Running sum is obtained as follows: `[1, 1+2, 1+2+3, 1+2+3+4]`.

Example 2:

Input: `nums = [1,1,1,1,1]`
Output: `[1,2,3,4,5]`
Explanation: Running sum is obtained as follows: `[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]`.

Example 3:

Input: `nums = [3,1,2,10,1]`
Output: `[3,4,6,16,17]`

8.9K | 222 | ☆ | ↗ | ⌂

Code

Java

Auto

```
class Solution {
    public int[] runningSum(int[] nums) {
        for (int i = 1; i < nums.length; i++) {
            nums[i] = nums[i] + nums[i - 1];
        }
        return nums;
    }
}
```

Saved

Ln 10, Col 5

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Input

nums =

[1,2,3,4]

Output

[1,3,6,10]

Expected

31°C

Partly cloudy

Search

ENG

IN

20:07

12-08-2026

New tab

leetcode problems - Search

Shuffle the Array - LeetCode

leetcode problems - Search

+

https://leetcode.com/problems/shuffle-the-array/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

1470. Shuffle the Array

Solved

Easy

Topics

Companies

Hint

Given the array `nums` consisting of `2n` elements in the form `[x1, x2, ..., xn, y1, y2, ..., yn]`.

Return the array in the form `[x1, y1, x2, y2, ..., xn, yn]`.

Example 1:

Input: `nums = [2,5,1,3,4,7], n = 3`
Output: `[2,3,5,4,1,7]`
Explanation: Since `x1=2, x2=5, x3=1, y1=3, y2=4, y3=7` then the answer is `[2,3,5,4,1,7]`.

Example 2:

Input: `nums = [1,2,3,4,4,3,2,1], n = 4`
Output: `[1,4,2,3,3,2,4,1]`

Example 3:

Input: `nums = [1,1,2,2], n = 2`
Output: `[1,2,1,2]`

Constraints:

6.5K16660 Online

Code

Java

Auto

```
1 class Solution {
2     public int[] shuffle(int[] nums, int n) {
3         int[] result = new int[nums.length];
4
5         int j = 0;
6
7         for (int i = 0; i < n; i++) {
8             result[j++] = nums[i];
9             result[j++] = nums[i + n];
10        }
11
12        return result;
13    }
14 }
```

SavedLn 14, Col 2

Testcase

Test Result

nums =

[2,5,1,3,4,7]

n =

3

Output

[2,3,5,4,1,7]

Expected

2

Search

ENG IN

20:12 12-09-2026

New tab

leetcode problems - Search

Remove Element - LeetCode

leetcode problems - Search

+

https://leetcode.com/problems/remove-element/

Problem List

Submit

0

Chat

Premium

Description

Editorial

Solutions

Submissions

27. Remove Element

Solved

EasyTopicsCompaniesHint

Given an integer array `nums` and an integer `val`, remove all occurrences of `val` in `nums` **in-place**. The order of the elements may be changed. Then return the *number of elements in `nums` which are not equal to `val`*.

Consider the number of elements in `nums` which are not equal to `val` be `k`, to get accepted, you need to do the following things:

- Change the array `nums` such that the first `k` elements of `nums` contain the elements which are not equal to `val`. The remaining elements of `nums` are not important as well as the size of `nums`.
- Return `k`.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int val = ...; // Value to remove
int[] expectedNums = [...]; // The expected answer with correct length.
// It is sorted with no values equaling val.

int k = removeElement(nums, val); // Calls your implementation

assert k == expectedNums.length;
sort(nums, 0, k); // Sort the first k elements of nums
```

5.3K984329 Online

Code

JavaAuto

```
1 class Solution {
2     public int removeElement(int[] nums, int val) {
3         int k = 0;
4
5         for (int i = 0; i < nums.length; i++) {
6             if (nums[i] != val) {
7                 nums[k] = nums[i];
8                 k++;
9             }
10        }
11
12        return k;
13    }
14 }
```

SavedLn 14, Col 2

Testcase

Test Result

Input

nums =
[3,2,2,3]

val =
3

Output

[2,2]

2

Search

ENG IN

20:13 12-09-2026

New tab

leetcode problems - Search

Remove Duplicates from Sorted Array

leetcode problems - Search

https://leetcode.com/problems/remove-duplicates-from-sorted-array/

Problem List

26. Remove Duplicates from Sorted Array

Solved

Description

Editorial

Solutions

Submissions

Easy

Topics

Companies

Hint

Given an integer array `nums` sorted in **non-decreasing order**, remove the duplicates **in-place** such that each unique element appears only **once**. The **relative order** of the elements should be kept the **same**.

Consider the number of **unique elements** in `nums` to be `k`. After removing duplicates, return the number of unique elements `k`.

The first `k` elements of `nums` should contain the unique numbers in **sorted order**. The remaining elements beyond index `k - 1` can be ignored.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int[] expectedNums = [...]; // The expected answer with correct length

int k = removeDuplicates(nums); // Calls your implementation

assert k == expectedNums.length;
for (int i = 0; i < k; i++) {
    assert nums[i] == expectedNums[i];
}
```

19.6K 1.1K 658 Online

Code

Java

Auto

```
1 class Solution {
2     public int removeDuplicates(int[] nums) {
3         int k = 1;
4
5         for (int i = 1; i < nums.length; i++) {
6             if (nums[i] != nums[i - 1]) {
7                 nums[k] = nums[i];
8                 k++;
9             }
10        }
11
12        return k;
13    }
14 }
```

Saved

Ln 12, Col 18

Testcase

Test Result

Input

nums =

[1,1,2]

Output

[1,2]

Expected

[1,2]

2

Search

12-09-2026

20:16

Problem List

53. Maximum Subarray

Description

Editorial

Solutions

Submissions

Medium

Topics

Companies

Given an integer array `nums`, find the **subarray** with the largest sum, and return *its sum*.

Example 1:

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]`
Output: 6
Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.

Example 2:

Input: `nums = [1]`
Output: 1
Explanation: The subarray `[1]` has the largest sum 1.

Example 3:

Input: `nums = [5,4,-1,7,8]`
Output: 23
Explanation: The subarray `[5,4,-1,7,8]` has the largest sum 23.

Constraints:

Code

```
1 class Solution {
2     public int maxSubArray(int[] nums) {
3         int currentSum = nums[0];
4         int maxSum = nums[0];
5
6         for (int i = 1; i < nums.length; i++) {
7             currentSum = Math.max(nums[i], currentSum + nums[i]);
8             maxSum = Math.max(maxSum, currentSum);
9         }
10
11         return maxSum;
12     }
13 }
```

Testcase

Test Result

Input

`nums = [-2,1,-3,4,-1,2,1,-5,4]`

Output

6

Expected

6

38.2K

573

494 Online

Problem List

49. Group Anagrams

Medium

Topics

Companies

Given an array of strings `strs`, group the **anagrams** together. You can return the answer in **any order**.

Example 1:

Input: `strs = ["eat","tea","tan","ate","nat","bat"]`

Output: `[["bat"],["nat","tan"],["ate","eat","tea"]]`

Explanation:

- There is no string in `strs` that can be rearranged to form `"bat"`.
- The strings `"nat"` and `"tan"` are anagrams as they can be rearranged to form each other.
- The strings `"ate"`, `"eat"`, and `"tea"` are anagrams as they can be rearranged to form each other.

Example 2:

Input: `strs = [""]`

Output: `[[""]]`

22.4K 426 498 Online

Code

Java

```
1 class Solution {
2     public List<List<String>> groupAnagrams(String[] strs) {
3         HashMap<String, List<String>> map = new HashMap<>();
4
5         for (String s : strs) {
6             char[] ch = s.toCharArray();
7             Arrays.sort(ch);
8
9             String key = new String(ch);
10
11             if (!map.containsKey(key)) {
12                 map.put(key, new ArrayList<>());
13             }
14
15             map.get(key).add(s);
16         }
17
18         return new ArrayList<>(map.values());
19     }
20 }
```

Saved

ln 20, Col 2

Testcase

Test Result

Input

strs =

["eat","tea","tan","ate","nat","bat"]

Output

[["eat","tea","ate"],["bat"],["tan","nat"]]

Search

20:23 12-09-2026

Problem List

Description

Editorial

Solutions

Submissions

• $1 \leq \text{words.length} \leq 500$

• $1 \leq \text{words}[i].\text{length} \leq 10$

• $\text{words}[i]$ consists of lowercase English letters.

• k is in the range $[1, \text{The number of unique words}[\text{words}[i]]]$

Follow-up: Could you solve it in $O(n \log(k))$ time and $O(n)$ extra space?

ASSISTA AGORA

SO NO RESPOSTA

YouTube

Instagram

Facebook

Twitter

LinkedIn

WhatsApp

Telegram

Medium

Dev.to

Codecademy

Udemy

Coursera

edX

FutureLearn

Blackboard

Moodle

Canvas LMS

FutureLearn

Blackboard

Moodle

Canvas LMS

Seen this question in a real interview before?

1/6

Yes

No

Accepted 8,19,173/1.4M

Acceptance Rate 60.5%

Topics

Companies

Similar Questions

8.1K

73

54 Online

Code

Java

Auto

```
1 class Solution {
2     public List<String> topKFrequent(String[] words, int k) {
3         HashMap<String, Integer> map = new HashMap<>();
4         for (String word : words) {
5             map.put(word, map.getOrDefault(word, 0) + 1);
6         }
7         List<String> list = new ArrayList<>(map.keySet());
8         list.sort((a, b) -> {
9             if (map.get(a) != map.get(b)) {
10                 return map.get(b) - map.get(a);
11             }
12             return a.compareTo(b);
13         });
14         return list.subList(0, k);
15     }
16 }
```

Testcase

Test Result

words =

["i","love","leetcode","i","love","coding"]

k =

2

Output

["i","love"]

Search

20:31 12-09-2026

Shuffle the Array

Online Java Compiler - Program

Ask Gemini

programiz.com/java-programming/online-compiler/

Ask Google

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz

Online Java Compiler

AMC

Your Trading Edge

Amplify Your Forex Trades

Leverage up to 1:5000

Trade Now

Trading derivatives involves high risk to your capital.

Programiz PRO

Main.java

Run

Output

```
1 import java.util.*;
2
3 public class Main {
4     public static void main(String[] args) {
5
6         Deque<Integer> dq = new ArrayDeque<>();
7
8         // Add elements
9         dq.addLast(10);
10        dq.addLast(20);
11        dq.addLast(30);
12
13        System.out.println(dq);
14
15        // Remove from front
16        System.out.println(dq.removeFirst());
17
18        // Remove from back
19        System.out.println(dq.removeLast());
20
21        System.out.println(dq);
22    }
23 }
```

```
[10, 20, 30]
10
30
[20]

=== Code Execution Successful ===
```

"Hello World!"

Search

ENG IN

20:40 12-09-2026

Shuffle the Array

Online Java Compiler - online c

Ask Gemini

onlinegdb.com/online_java_compiler

OnlineGDB

online compiler and debugger for c/c++

code, compile, run, debug, share.

IDE

My Projects

Classroom new

Learn Programming

Programming Questions

Sign Up

Login

1- import java.util.*;

2-

3- public class Main {

4- public static void main(String[] args) {

5-

6- HashSet<Integer> set = new HashSet<>();

7-

8- set.add(10);

9- set.add(20);

10- set.add(30);

11- set.add(10);

12-

13- System.out.println(set);

14- System.out.println("Size: " + set.size());

15-

16- if (set.contains(20)) {

17- System.out.println("20 is present");

18- }

19-

20- set.remove(30);

21-

22- System.out.println(set);

23-

24- }

Run

Debug

Stop

Share

Save

Beautify

Language Java

close ad [x]

Put your style in the spotlight with Lens Blur.

Learn more

Generate images, video and audio. All in one place.

Learn more

Adobe Firefly

Input

[20, 10, 30]

Size: 3

20 is present

[20, 10]

...Program finished with exit code 0

Press ENTER to exit console.

About • FAQ • Docs • Blog • Terms of Use • Contact Us

• GDB Tutorial • Credits • Privacy

© 2016 - 2026 GDB Online

Search

ENG IN

20:50 12-09-2026

PROBLEM SOLVING AND TESTING USING JAVA

WEEK 1

Java Lambda Expressions

```
import java.util.*;
interface PerformOperation {
    boolean check(int n);
}
public class Main {
    static PerformOperation isOdd() {
        return n -> n % 2 != 0;
    }
    static PerformOperation isPrime() {
        return n -> {
            if (n < 2) return false;
            for (int i = 2; i * i <= n; i++)
                if (n % i == 0) return false;
            return true;
        };
    }
    static PerformOperation isPalindrome() {
        return n -> {
            int x = n, rev = 0;
            while (n > 0) {
                rev = rev * 10 + n % 10;
                n /= 10;
            }
            return x == rev;
        };
    }
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int t = sc.nextInt();
        while (t-- > 0) {
            int type = sc.nextInt();
            int n = sc.nextInt();
            if (type == 1)
                System.out.println(isOdd().check(n) ? "ODD" : "EVEN");
            else if (type == 2)
                System.out.println(isPrime().check(n) ? "PRIME" : "COMPOSITE");
            else
                System.out.println(isPalindrome().check(n) ? "PALINDROME" : "NOT PALINDROME");
        }
    }
}
```

Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.

D:\>javac Main.java

D:\>java Main

5
1 4
EVEN
2 5
PRIME
3 898
PALINDROME
1 3
ODD
2 12
COMPOSITE

D:\>|

Java Comparator

```
import java.util.*;
class Player {
    String name;
    int score;
    Player(String name, int score) {
        this.name = name;
        this.score = score;
    }
}
class Checker implements Comparator<Player> {
    public int compare(Player a, Player b) {
        if (a.score != b.score)
            return b.score - a.score;
        return a.name.compareTo(b.name);
    }
}
public class Sample {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        Player[] players = new Player[n];
        for (int i = 0; i < n; i++) {
            String name = sc.next();
            int score = sc.nextInt();
            players[i] = new Player(name, score);
        }
        Arrays.sort(players, new Checker());
        for (Player p : players) {
            System.out.println(p.name + " " + p.score);
        }
        sc.close();
    }
}
```

```
C:\Windows\System32\cmd.e  X + v
Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.

D:\>javac Sample.java

D:\>java Sample
5
amy 100
david 100
heraldo 50
aakansha 75
aleksa 150
aleksa 150
amy 100
david 100
aakansha 75
heraldo 50

D:\>|
```

Java Sort

```
import java.util.*;
class Student {
    int id;
    String name;
    double cgpa;
    Student(int id, String name, double cgpa) {
        this.id = id;
        this.name = name;
        this.cgpa = cgpa;
    }
}
class Checker implements Comparator<Student> {
    public int compare(Student a, Student b) {
        if (a.cgpa != b.cgpa)
            return Double.compare(b.cgpa, a.cgpa);
        if (a.name.equals(b.name))
            return a.name.compareTo(b.name);
        return Integer.compare(a.id, b.id);
    }
}
public class Sort {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        Student[] students = new Student[n];
        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String name = sc.next();
            double cgpa = sc.nextDouble();
            students[i] = new Student(id, name, cgpa);
        }
        Arrays.sort(students, new Checker());
        for (Student s : students) {
            System.out.println(s.name);
        }
        sc.close();
    }
}
```

```
C:\Windows\System32\cmd.e  X + v
Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.
```

```
D:\>javac Sort.java
```

```
D:\>java Sort
5
33 rumpa 3.68
85 ashis 3.85
56 samiha 3.75
19 samara 3.75
22 fahim 3.76
ashis
fahim
samara
samiha
rumpa
```

```
D:\>|
```

Running Sum of 1D Array

1480. Running Sum of 1d Array

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0..i])`.

Return the running sum of `nums`.

Example 1:

Input: `nums = [1,2,3,4]`
Output: `[1,3,6,10]`
Explanation: Running sum is obtained as follows: `[1, 1+2, 1+2+3, 1+2+3+4]`.

Example 2:

Input: `nums = [1,1,1,1,1]`
Output: `[1,2,3,4,5]`
Explanation: Running sum is obtained as follows: `[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]`.

Example 3:

Input: `nums = [3,1,2,10,1]`
Output: `[3,4,6,16,17]`

Constraints:

- `1 <= nums.length <= 1000`
- `-106 <= nums[i] <= 106`

```
class Solution {
    public int[] runningSum(int[] nums) {
        for (int i = 1; i < nums.length; i++) {
            nums[i] = nums[i] + nums[i - 1];
        }
        return nums;
    }
}
```

Testcase 1: Test Result

Accepted Runtime: 0 ms

Case 1 **Case 2** **Case 3**

Input:

`nums =`
`[1,2,3,4]`

Output:

`[1,3,6,10]`

Expected:

`[1,3,6,10]`

Richest Customer Wealth

The screenshot shows the LeetCode interface for problem 1672, "Richest Customer Wealth". The left pane contains the problem description, which states: "You are given an $n \times n$ integer grid `accounts` where `accounts[i][j]` is the amount of money the i^{th} customer has in the j^{th} bank. Return the wealth that the richest customer has." It also defines a customer's wealth as the sum of money in all their bank accounts and provides three examples. Example 1: Input `accounts = [[1,2,3],[3,2,1]]`, Output `6`. Example 2: Input `accounts = [[1,5],[7,3],[3,5]]`, Output `10`. Example 3: Input `accounts = [[2,8,7],[7,1,3],[1,9,5]]`, Output `17`. The right pane shows a Java solution using a nested loop to calculate the wealth for each customer and then finding the maximum. The test result pane shows the solution is "Accepted" with a runtime of 0 ms for the provided test case.

1672. Richest Customer Wealth

You are given an $n \times n$ integer grid `accounts` where `accounts[i][j]` is the amount of money the i^{th} customer has in the j^{th} bank. Return the wealth that the richest customer has.

A customer's **wealth** is the amount of money they have in all their bank accounts. The richest customer is the customer that has the maximum wealth.

Example 1:

Input: `accounts = [[1,2,3],[3,2,1]]`
Output: `6`
Explanation:
1st customer has wealth = 1 + 2 + 3 = 6
2nd customer has wealth = 3 + 2 + 1 = 6
Both customers are considered the richest with a wealth of 6 each, so return 6.

Example 2:

Input: `accounts = [[1,5],[7,3],[3,5]]`
Output: `10`
Explanation:
1st customer has wealth = 6
2nd customer has wealth = 10
3rd customer has wealth = 8
The 2nd customer is the richest with a wealth of 10.

Example 3:

Input: `accounts = [[2,8,7],[7,1,3],[1,9,5]]`
Output: `17`

Constraints:

- $n == \text{accounts.length}$

```
class Solution {
    public int maximumWealth(int[][] accounts) {
        int maxWealth = 0;

        for (int[] customer : accounts) {
            int wealth = 0;
            for (int money : customer) {
                wealth += money;
            }
            maxWealth = Math.max(maxWealth, wealth);
        }

        return maxWealth;
    }
}
```

Testcase: **Accepted** Runtime: 0 ms

Case 1 Case 2 Case 3

Input: `accounts = [[1,2,3],[3,2,1]]`

Output: `6`

Expected: `6`

Squares of a Sorted Array

The screenshot shows the LeetCode interface for problem 977, "Squares of a Sorted Array". The left pane contains the problem description, which states: "Given an integer array `nums` sorted in non-decreasing order, return an array of the squares of each number sorted in non-decreasing order." It provides two examples. Example 1: Input `nums = [-4,-1,0,3,10]`, Output `[0,1,9,16,100]`. Example 2: Input `nums = [-7,-3,2,3,11]`, Output `[4,9,9,49,121]`. The right pane shows a Java solution using a two-pointer approach to compare the squares of elements from both ends of the array and place the larger square in the result array. The test result pane shows the solution is "Accepted" with a runtime of 0 ms for the provided test case.

977. Squares of a Sorted Array

Given an integer array `nums` sorted in non-decreasing order, return an array of the squares of each number sorted in non-decreasing order.

Example 1:

Input: `nums = [-4,-1,0,3,10]`
Output: `[0,1,9,16,100]`
Explanation: After squaring, the array becomes `[16,1,0,9,100]`. After sorting, it becomes `[0,1,9,16,100]`.

Example 2:

Input: `nums = [-7,-3,2,3,11]`
Output: `[4,9,9,49,121]`

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- `nums` is sorted in non-decreasing order.

Follow up: Squaring each element and sorting the new array is very trivial, could you find an $O(n)$ solution using a different approach?

Discover more Computer Science

Solve this question in a real interview before? 1/6

```
class Solution {
    public int[] sortedSquares(int[] nums) {
        int n = nums.length;
        int[] result = new int[n];

        int left = 0;
        int right = n - 1;
        int index = n - 1;

        while (left <= right) {
            int leftSquare = nums[left] * nums[left];
            int rightSquare = nums[right] * nums[right];

            if (leftSquare > rightSquare) {
                result[index] = leftSquare;
                left++;
            } else {
                result[index] = rightSquare;
                right--;
            }

            index--;
        }

        return result;
    }
}
```

Testcase: **Accepted** Runtime: 0 ms

Input: `nums = [-4,-1,0,3,10]`

Output: `[0,1,9,16,100]`

Expected: `[0,1,9,16,100]`

Find Pivot Index

724. Find Pivot Index

Easy Topics Compare Hint

Given an array of integers `nums`, calculate the **pivot index** of this array.

The **pivot index** is the index where the sum of all the numbers **strictly** to the left of the index is equal to the sum of all the numbers **strictly** to the index's right.

If the index is on the left edge of the array, then the left sum is `0` because there are no elements to the left. This also applies to the right edge of the array.

Return the **leftmost pivot index**. If no such index exists, return `-1`.

Example 1:

Input: `nums = [1,7,3,6,5,6]`
Output: `3`
Explanation:
The pivot index is 3.
Left sum = `nums[0] + nums[1] + nums[2] = 1 + 7 + 3 = 11`
Right sum = `nums[4] + nums[5] = 5 + 6 = 11`

Example 2:

Input: `nums = [1,2,3]`
Output: `-1`
Explanation:
There is no index that satisfies the conditions in the problem statement.

Example 3:

Input: `nums = [2,1,-1]`
Output: `0`
Explanation:
The pivot index is 0.
Left sum = `0` (no elements to the left of index 0)
Right sum = `nums[1] + nums[2] = 1 + -1 = 0`

3.5K 277 119 Online

Code

Java Auto

```
3 int totalSum = 0;
4
5 // Calculate total sum
6 for (int num : nums) {
7     totalSum += num;
8 }
9
10 int leftSum = 0;
11
12 // Find pivot index
13 for (int i = 0; i < nums.length; i++) {
14     int rightSum = totalSum - leftSum - nums[i];
15
16     if (leftSum == rightSum) {
17         return i;
18     }
19     leftSum += nums[i];
20 }
21
22 return -1;
```

Send

Ln 25, Col 1

Testcase Test Result

Input

nums =
[1,7,3,6,5,6]

Output

3

Expected

3

Contribute a testcase

```
29 public class Solution {
30     public static void main(String[] args) throws IOException {
31         BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
32         BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv(
33             "OUTPUT_PATH")));
34
35         String[] firstMultipleInput = bufferedReader.readLine().replaceAll("\\s+$", "").split("
36
37         int month = Integer.parseInt(firstMultipleInput[0]);
38
39         int day = Integer.parseInt(firstMultipleInput[1]);
40
41         int year = Integer.parseInt(firstMultipleInput[2]);
42
43         String res = Result.findDay(month, day, year);
44
45         bufferedWriter.write(res);
46         bufferedWriter.newLine();
47
48         bufferedReader.close();
49         bufferedWriter.close();
50     }
51 }
```

1154. Day of the Year

Easy Topics Companies Hint

Given a string `date` representing a [Gregorian calendar](#) date formatted as `YYYY-MM-DD`, return *the day number of the year*.

Example 1:

Input: `date = "2019-01-09"`
Output: 9
Explanation: Given date is the 9th day of the year in 2019.

Example 2:

Input: `date = "2019-02-10"`
Output: 41

Constraints:

- `date.length == 10`
- `date[4] == date[7] == '-'`, and all other `date[i]`'s are digits
- `date` represents a calendar date between Jan 1st, 1900 and Dec 31st, 2019.



Seen this question in a real interview before? 1/6

Yes No

Accepted 102,396/203.8K Acceptance Rate 50.2%

518 36

12 Online

Code

Java Auto

```
1 class Solution {
2     public int dayOfYear(String date) {
3         int year = Integer.parseInt(date.substring(0, 4));
4         int month = Integer.parseInt(date.substring(5, 7));
5         int day = Integer.parseInt(date.substring(8));
6
7         int[] days = {31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31};
8
9         // Check for leap year
10        boolean isLeap = (year % 400 == 0) || (year % 4 == 0 && year % 100 != 0);
11        if (isLeap && month > 2) {
12            day += 1;
13        }
14
15        // Add days of previous months
16        for (int i = 0; i < month - 1; i++) {
17            day += days[i];
18        }
19    }
20 }
```

Saved

Ln 23, Col 1

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

`date = "2019-01-09"`

Output

9

Expected

9

Contribute a testcase

1360. Number of Days Between Two Dates

Easy Topics Companies Hint

Write a program to count the number of days between two dates.

The two dates are given as strings, their format is YYYY-MM-DD as shown in the examples.

Example 1:

Input: date1 = "2019-06-29", date2 = "2019-06-30"

Output: 1

Example 2:

Input: date1 = "2020-01-15", date2 = "2019-12-31"

Output: 15

Constraints:

- The given dates are valid dates between the years 1971 and 2100.

UNLOCK EXPERIENCES

Prepare your network for
today and tomorrow

HPE

Seen this question in a real interview before? 1/6

Yes No

Accepted 77,896/146.2K Acceptance Rate 53.3%

Topics

443 42



Hot weather
Now

Java Auto

```
1 import java.time.LocalDate;
2 import java.time.temporal.ChronoUnit;
3
4 class Solution {
5     public int daysBetweenDates(String date1, String date2) {
6         LocalDate d1 = LocalDate.parse(date1);
7         LocalDate d2 = LocalDate.parse(date2);
8         return (int) Math.abs(ChronoUnit.DAYS.between(d1, d2));
9     }
10 }
11
```

Saved

Ln 11, Col 1

Testcase Test Result

Accepted Runtime: 6 ms

Case 1 Case 2

Input

date1 =
"2019-06-29"

date2 =
"2019-06-30"

Output

1

Expected

1

Copilot

16 Online



Search

ENG
IN11:22
14-08-2026

1185. Day of the Week

Easy 🔖 Topics 🏷️ Companies 🏢 Hint 📖

Given a date, return the corresponding day of the week for that date.

The input is given as three integers representing the `day`, `month` and `year` respectively.

Return the answer as one of the following values `["Sunday", "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday"]`.

Note: January 1, 1971 was a Friday.

Example 1:

Input: `day = 31, month = 8, year = 2019`
Output: `"Saturday"`

Example 2:

Input: `day = 18, month = 7, year = 1999`
Output: `"Sunday"`

Example 3:

Input: `day = 15, month = 8, year = 1993`
Output: `"Sunday"`

Constraints:

- The given dates are valid dates between the years 1971 and 2100.

 Great ideas deserve a great domain name

```
Java 📄 Auto
1 import java.time.LocalDate;
2
3 class Solution {
4     public String dayOfTheWeek(int day, int month, int year) {
5         LocalDate date = LocalDate.of(year, month, day);
6         String weekDay = date.getDayOfWeek().name();
7         // Capitalize first letter and lowercase the rest
8         return weekDay.charAt(0) + weekDay.substring(1).toLowerCase();
9     }
10 }
11
```

Saved

Ln 11, Col 1

Accepted Runtime: 5 ms

✅ Case 1 ✅ Case 2 ✅ Case 3

Input

`day =`
`31`

`month =`
`8`

`year =`
`2019`

Output

`"Saturday"`

```
17 ArrayList<ArrayList<Integer>> times = new ArrayList<>();
18
19 ✓
20 int d = scan.nextInt();
21 ArrayList<Integer> row = new ArrayList<>();
22 ✓ for (int j = 0; j < d; j++) {
23     row.add(scan.nextInt());
24 }
25
```

Line: 49 Col: 1



Upload Code as File



Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.



Sample Test case 0



Sample Test case 1

Input (stdin)

```
1 5
2 5 41 77 74 22 44
3 1 12
4 4 37 34 36 53
```

Download

```
1  import java.util.*;
2
3  class Student{
4      private int id;
5      private String fname;
6      private double cgpa;
7      public Student(int id, String fname, double cgpa) {
8          super();
9          this.id = id;
10         this.fname = fname;
11         this.cgpa = cgpa;
12     }
13     public int getId() {
14         return id;
15     }
16     public String getFname() {
17         return fname;
18     }
19     public double getCgpa() {
20         return cgpa;
21     }
22 }
23
24 //Complete the code
25 public class Solution
```

Line: 51 Col: 1

451. Sort Characters By Frequency

Medium Topics Companies

Given a string *s*, sort it in **decreasing order** based on the **frequency** of the characters. The **frequency** of a character is the number of times it appears in the string.

Return *the sorted string*. If there are multiple answers, return *any of them*.

Example 1:

Input: *s* = "tree"
Output: "eert"
Explanation: 'e' appears twice while 'r' and 't' both appear once. So 'e' must appear before both 'r' and 't'. Therefore "eetr" is also a valid answer.

Example 2:

Input: *s* = "cccaaa"
Output: "aaaccc"
Explanation: Both 'c' and 'a' appear three times, so both "cccaaa" and "aaaccc" are valid answers. Note that "cacaca" is incorrect, as the same characters must be together.

Example 3:

Input: *s* = "Aabb"
Output: "bbAa"
Explanation: "bbaA" is also a valid answer, but "Aabb" is incorrect. Note that 'A' and 'a' are treated as two different characters.

Constraints:

- 1 ≤ *s*.length ≤ 5 × 10⁵
- s* consists of uppercase and lowercase English letters and digits.

9.4K 193 ☆ 📄 🗨️

76 Online

Contribute a testcase

```
Java Auto
1 class Solution {
2     public String frequencySort(String s) {
3         // Step 1: Count the frequency of each character
4         Map<Character, Integer> map = new HashMap<>();
5         for (char c : s.toCharArray()) {
6             map.put(c, map.getOrDefault(c, 0) + 1);
7         }
8
9         // Step 2: Create a list of characters from the map keys
10        List<Character> list = new ArrayList<>(map.keySet());
11
12        // Step 3: Sort characters by frequency in descending order
13        list.sort((a, b) -> map.get(b) - map.get(a));
14
15        // Step 4: Build the result string
16        StringBuilder sb = new StringBuilder();
17        for (Character c : list) {
18            sb.append(c.repeat(map.get(c)));
19        }
20        return sb.toString();
21    }
22 }
```

Testcase Test Result

Accepted Runtime: 1 ms

Case 1 Case 2 Case 3

Input

s = "tree"

Output

"eert"

Expected

"eert"

```
4 // Write your Checker class here
5
6 class Player{
7     String name;
8     int score;
9
10    Player(String name, int score){
11        this.name = name;
12        this.score = score;
13    }
14 }
15
16 class Solution {
17     public static void main(String[] args) {
18         Scanner scan = new Scanner(System.in);
19         int n = scan.nextInt();
20
21         Player[] player = new Player[n];
22         Checker checker = new Checker();
23
24         for(int i = 0; i < n; i++){
25             player[i] = new Player(scan.next(), scan.nextInt());
26         }
```

Line: 2 Col: 1

179. Largest Number

Medium Topics Companies

Given a list of non-negative integers `nums`, arrange them such that they form the largest number and return it.

Since the result may be very large, so you need to return a string instead of an integer.

Example 1:

Input: `nums = [10,2]`
Output: `"210"`

Example 2:

Input: `nums = [3,30,34,5,9]`
Output: `"9534330"`

Constraints:

- $1 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 10^9$

Discover more

Number Theory Problems

Seen this question in a real interview before? 1/6

Yes No

Accepted 865,103/2M Acceptance Rate 43.6%

Topics

9.6K 228 ☆ ↗ ⌚

66 Online

Code

Java Auto

```
1 import java.util.Arrays;
2
3 class Solution {
4     public String largestNumber(int[] nums) {
5         String[] arr = new String[nums.length];
6         for (int i = 0; i < nums.length; i++) {
7             arr[i] = String.valueOf(nums[i]);
8         }
9
10        // Custom sort: compare combinations (s2 + s1) vs (s1 + s2)
11        Arrays.sort(arr, (s1, s2) -> (s2 + s1).compareTo(s1 + s2));
12
13        // Edge case: If the highest number is "0", the whole array is 0
14        if (arr[0].equals("0")) {
15            return "0";
16        }
17    }
18 }
```

Saved

Ln 26, Col 1

Testcase Test Result

Accepted Runtime: 2 ms

Case 1 Case 2

Input

`nums =`
`[10,2]`

Output

`"210"`

Expected

`"210"`

Contribute a testcase

```
8  ✓
9  public class Solution {
10     private final static Scanner scan = new Scanner(System.in);
11     private final static Priorities priorities = new Priorities();
12
13     public static void main(String[] args) {
14         int totalEvents = Integer.parseInt(scan.nextLine());
15         List<String> events = new ArrayList<>();
16
17         while (totalEvents-- != 0) {
18             String event = scan.nextLine();
19             events.add(event);
20         }
21
22         List<Student> students = priorities.getStudents(events);
23
24         if (students.isEmpty()) {
25             System.out.println("EMPTY");
26         } else {
27             for (Student st: students) {
28                 System.out.println(st.getName());
29             }
30         }
31     }
```

Line: 7 Col: 1