

1.Java Dequeue

```
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        /* Enter your code here. Read input from STDIN. Print output
to STDOUT. Your class should be named Solution. */
        Scanner in = new Scanner(System.in);
        Deque deque = new ArrayDeque<>();
        int n = in.nextInt();
        int m = in.nextInt();

        int[] freq = new int[10000001];
        int unique=0;
        int maxUnique=0;
        for (int i = 0; i < n; i++) {
            int num = in.nextInt();

            freq[num]++;
            deque.addLast(num);
            if(freq[num]==1) unique++;

            if(deque.size()==m){
                if(unique>maxUnique)maxUnique=unique;
                int removed = (int)deque.removeFirst();
                freq[removed]--;
                if (freq[removed] == 0) {
                    unique--;
                }
            }
        }

        System.out.println(maxUnique);
    }
}
```

```
}
```

2. Java Hashset

```
import java.io.*;
```

```
import java.util.*;
```

```
public class Solution {
```

```
    public static void main(String[] args) {
```

```
        /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class  
        should be named Solution. */
```

```
        Scanner s = new Scanner(System.in);
```

```
        int t = s.nextInt();
```

```
        String[] pair_left = new String[t];
```

```
        String[] pair_right = new String[t];
```

```
        HashSet<String> dataGuest = new HashSet<>(t);
```

```
        for(int i = 0; i < t; i++){
```

```
            pair_left[i] = s.next();
```

```
            pair_right[i] = s.next();
```

```
        }
```

```
        for(int a = 0; a < t; a++){
```

```
            String pasangan = pair_left[a] + " " + pair_right[a];
```

```
            dataGuest.add(pasangan);
```

```
            System.out.println(dataGuest.size());
```

```
        }
```

```
    }
```

```
}
```

