

New tab

leetcode problems - Search

Running Sum of 1d Array - LeetCo

leetcode problems - Search

+

https://leetcode.com/problems/running-sum-of-1d-array/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

1480. Running Sum of 1d Array

Solved

EasyTopicsCompaniesHint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]...nums[i])`.

Return the running sum of `nums`.

Example 1:

Input: `nums = [1,2,3,4]`
Output: `[1,3,6,10]`
Explanation: Running sum is obtained as follows: `[1, 1+2, 1+2+3, 1+2+3+4]`.

Example 2:

Input: `nums = [1,1,1,1,1]`
Output: `[1,2,3,4,5]`
Explanation: Running sum is obtained as follows: `[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]`.

Example 3:

Input: `nums = [3,1,2,10,1]`
Output: `[3,4,6,16,17]`

8.9K22280 Online

Code

JavaAuto

```
1
2
3
4
5
6
7
8
9
10
class Solution {
    public int[] runningSum(int[] nums) {
        for (int i = 1; i < nums.length; i++) {
            nums[i] = nums[i] + nums[i - 1];
        }
        return nums;
    }
}
```

SavedLn 10, Col 5

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

nums =

[1,2,3,4]

Output

[1,3,6,10]

Expected

31°CPartly cloudy

Search

12-08-202620:07

New tab

leetcode problems - Search

Shuffle the Array - LeetCode

leetcode problems - Search

+

https://leetcode.com/problems/shuffle-the-array/

Problem List

Submit

0

Chat

Premium

Description

Editorial

Solutions

Submissions

1470. Shuffle the Array

Solved

EasyTopicsCompaniesHint

Given the array `nums` consisting of `2n` elements in the form $[x_1, x_2, \dots, x_n, y_1, y_2, \dots, y_n]$.

Return the array in the form $[x_1, y_1, x_2, y_2, \dots, x_n, y_n]$.

Example 1:

Input: `nums = [2,5,1,3,4,7], n = 3`
Output: `[2,3,5,4,1,7]`
Explanation: Since $x_1=2, x_2=5, x_3=1, y_1=3, y_2=4, y_3=7$ then the answer is `[2,3,5,4,1,7]`.

Example 2:

Input: `nums = [1,2,3,4,4,3,2,1], n = 4`
Output: `[1,4,2,3,3,2,4,1]`

Example 3:

Input: `nums = [1,1,2,2], n = 2`
Output: `[1,2,1,2]`

Constraints:

6.5K16660 Online

Code

Java

```
1 class Solution {
2     public int[] shuffle(int[] nums, int n) {
3         int[] result = new int[nums.length];
4
5         int j = 0;
6
7         for (int i = 0; i < n; i++) {
8             result[j++] = nums[i];
9             result[j++] = nums[i + n];
10        }
11
12        return result;
13    }
14 }
```

SavedLn 14, Col 2

Testcase

Test Result

nums =

[2,5,1,3,4,7]

n =

3

Output

[2,3,5,4,1,7]

Expected

2

Search

ENG IN

20:12 12-09-2026

New tab

leetcode problems - Search

Remove Element - LeetCode

leetcode problems - Search

+

https://leetcode.com/problems/remove-element/

Problem List

Submit

0

Chat

Premium

Description

Editorial

Solutions

Submissions

27. Remove Element

Solved

EasyTopicsCompaniesHint

Given an integer array `nums` and an integer `val`, remove all occurrences of `val` in `nums` **in-place**. The order of the elements may be changed. Then return the *number of elements in `nums` which are not equal to `val`*.

Consider the number of elements in `nums` which are not equal to `val` be `k`, to get accepted, you need to do the following things:

- Change the array `nums` such that the first `k` elements of `nums` contain the elements which are not equal to `val`. The remaining elements of `nums` are not important as well as the size of `nums`.
- Return `k`.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int val = ...; // Value to remove
int[] expectedNums = [...]; // The expected answer with correct length.
// It is sorted with no values equaling val.

int k = removeElement(nums, val); // Calls your implementation

assert k == expectedNums.length;
sort(nums, 0, k); // Sort the first k elements of nums
```

5.3K984329 Online

Code

JavaAuto

```
1 class Solution {
2     public int removeElement(int[] nums, int val) {
3         int k = 0;
4
5         for (int i = 0; i < nums.length; i++) {
6             if (nums[i] != val) {
7                 nums[k] = nums[i];
8                 k++;
9             }
10        }
11
12        return k;
13    }
14 }
```

SavedLn 14, Col 2

Testcase

Test Result

Input

nums =
[3,2,2,3]

val =
3

Output

[2,2]

2

Search

ENG IN

20:13 12-09-2026

26. Remove Duplicates from Sorted Array

Easy

Topics

Companies

Hint

Given an integer array `nums` sorted in **non-decreasing order**, remove the duplicates **in-place** such that each unique element appears only **once**. The **relative order** of the elements should be kept the **same**.

Consider the number of **unique elements** in `nums` to be `k`. After removing duplicates, return the number of unique elements `k`.

The first `k` elements of `nums` should contain the unique numbers in **sorted order**. The remaining elements beyond index `k - 1` can be ignored.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int[] expectedNums = [...]; // The expected answer with correct length

int k = removeDuplicates(nums); // Calls your implementation

assert k == expectedNums.length;
for (int i = 0; i < k; i++) {
    assert nums[i] == expectedNums[i];
}
```

19.6K1.1K658 Online

Code

JavaAuto

```
1 class Solution {
2     public int removeDuplicates(int[] nums) {
3         int k = 1;
4
5         for (int i = 1; i < nums.length; i++) {
6             if (nums[i] != nums[i - 1]) {
7                 nums[k] = nums[i];
8                 k++;
9             }
10        }
11
12        return k;
13    }
14 }
```

SavedLn 12, Col 18

TestcaseTest Result

Input

nums =

[1,1,2]

Output

[1,2]

Expected

[1,2]

20:16

12-09-2026

Problem List

53. Maximum Subarray

Description

Editorial

Solutions

Submissions

Medium

Topics

Companies

Given an integer array `nums`, find the **subarray** with the largest sum, and return *its sum*.

Example 1:

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]`
Output: 6
Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.

Example 2:

Input: `nums = [1]`
Output: 1
Explanation: The subarray `[1]` has the largest sum 1.

Example 3:

Input: `nums = [5,4,-1,7,8]`
Output: 23
Explanation: The subarray `[5,4,-1,7,8]` has the largest sum 23.

Constraints:

Code

```
1 class Solution {
2     public int maxSubArray(int[] nums) {
3         int currentSum = nums[0];
4         int maxSum = nums[0];
5
6         for (int i = 1; i < nums.length; i++) {
7             currentSum = Math.max(nums[i], currentSum + nums[i]);
8             maxSum = Math.max(maxSum, currentSum);
9         }
10
11         return maxSum;
12     }
13 }
```

Testcase

Test Result

Input

`nums = [-2,1,-3,4,-1,2,1,-5,4]`

Output

6

Expected

6

Problem List

49. Group Anagrams

Medium

Topics

Companies

Given an array of strings `strs`, group the anagrams together. You can return the answer in any order.

Example 1:

Input: `strs = ["eat","tea","tan","ate","nat","bat"]`

Output: `[["bat"],["nat","tan"],["ate","eat","tea"]]`

Explanation:

- There is no string in `strs` that can be rearranged to form `"bat"`.
- The strings `"nat"` and `"tan"` are anagrams as they can be rearranged to form each other.
- The strings `"ate"`, `"eat"`, and `"tea"` are anagrams as they can be rearranged to form each other.

Example 2:

Input: `strs = [""]`

Output: `[[""]]`

22.4K 426 498 Online

Code

Java

```
1 class Solution {
2     public List<List<String>> groupAnagrams(String[] strs) {
3         HashMap<String, List<String>> map = new HashMap<>();
4
5         for (String s : strs) {
6             char[] ch = s.toCharArray();
7             Arrays.sort(ch);
8
9             String key = new String(ch);
10
11             if (!map.containsKey(key)) {
12                 map.put(key, new ArrayList<>());
13             }
14
15             map.get(key).add(s);
16         }
17
18         return new ArrayList<>(map.values());
19     }
20 }
```

Saved

ln 20, Col 2

Testcase

Test Result

Input

strs =

["eat","tea","tan","ate","nat","bat"]

Output

[["eat","tea","ate"],["bat"],["tan","nat"]]

Search

20:23 12-09-2026

Problem List

Description

Editorial

Solutions

Submissions

• $1 \leq \text{words.length} \leq 500$

• $1 \leq \text{words}[i].\text{length} \leq 10$

• $\text{words}[i]$ consists of lowercase English letters.

• k is in the range $[1, \text{The number of unique words}[\text{words}[i]]]$

Follow-up: Could you solve it in $O(n \log(k))$ time and $O(n)$ extra space?

ASSISTA AGORA

SO NO RESCORT

YouTube

Instagram

Facebook

Twitter

Seen this question in a real interview before? 1/6

Yes

No

Accepted 8,19,173/1.4M

Acceptance Rate 60.5%

Topics

Companies

Similar Questions

8.1K

73

54 Online

Code

Java

Auto

```
1 class Solution {
2     public List<String> topKFrequent(String[] words, int k) {
3         HashMap<String, Integer> map = new HashMap<>();
4         for (String word : words) {
5             map.put(word, map.getOrDefault(word, 0) + 1);
6         }
7         List<String> list = new ArrayList<>(map.keySet());
8         list.sort((a, b) -> {
9             if (map.get(a) != map.get(b)) {
10                 return map.get(b) - map.get(a);
11             }
12             return a.compareTo(b);
13         });
14         return list.subList(0, k);
15     }
16 }
```

Testcase 1

Test Result

words =

["i","love","leetcode","i","love","coding"]

k =

2

Output

["i","love"]

Search

20:31

12-09-2026

Shuffle the Array

Online Java Compiler - Program

Ask Gemini

programiz.com/java-programming/online-compiler/

Ask Google

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz

Online Java Compiler

AMC

Your Trading Edge

Amplify Your Forex Trades

Leverage up to 1:5000

Trade Now

Trading derivatives involves high risk to your capital.

Programiz PRO

Main.java

Run

Output

```
1 import java.util.*;
2
3 public class Main {
4     public static void main(String[] args) {
5
6         Deque<Integer> dq = new ArrayDeque<>();
7
8         // Add elements
9         dq.addLast(10);
10        dq.addLast(20);
11        dq.addLast(30);
12
13        System.out.println(dq);
14
15        // Remove from front
16        System.out.println(dq.removeFirst());
17
18        // Remove from back
19        System.out.println(dq.removeLast());
20
21        System.out.println(dq);
22    }
23 }
```

```
[10, 20, 30]
10
30
[20]

=== Code Execution Successful ===
```

"Hello World!"

Search

ENG IN

20:40 12-09-2026

Shuffle the Array

Online Java Compiler - online c

Ask Gemini

onlinegdb.com/online_java_compiler

OnlineGDB

online compiler and debugger for c/c++

code, compile, run, debug, share.

IDE

My Projects

Classroom new

Learn Programming

Programming Questions

Sign Up

Login

1- import java.util.*;

2-

3- public class Main {

4- public static void main(String[] args) {

5-

6- HashSet<Integer> set = new HashSet<>();

7-

8- set.add(10);

9- set.add(20);

10- set.add(30);

11- set.add(10);

12-

13- System.out.println(set);

14- System.out.println("Size: " + set.size());

15-

16- if (set.contains(20)) {

17- System.out.println("20 is present");

18- }

19-

20- set.remove(30);

21-

22- System.out.println(set);

23-

24- }

Run

Debug

Stop

Share

Save

{ } Beautify

+

-

Language Java

close ad [x]

Put your style in the spotlight with Lens Blur.

Learn more

Generate images, video and audio. All in one place.

Learn more

Adobe Firefly

Input

[20, 10, 30]

Size: 3

20 is present

[20, 10]

...Program finished with exit code 0

Press ENTER to exit console.

About • FAQ • Docs • Blog • Terms of Use • Contact Us

• GDB Tutorial • Credits • Privacy

© 2016 - 2026 GDB Online

Search

ENG IN

20:50 12-09-2026