

2. Find the Highest Altitude

There is a biker going on a road trip. The road trip consists of $n + 1$ points at various altitudes. The biker starts his trip on point 0 with altitude equal 0.

You are given an integer array `gain` of length n where `gain[i]` is the **net gain in altitude** between points i and $i + 1$ for all $(0 \leq i < n)$. Return *the highest altitude of a point*.

Example 1:

Input: `gain = [-5,1,5,0,-7]`

Output: 1

Explanation: The altitudes are `[0,-5,-4,1,1,-6]`. The highest is 1.

Example 2:

Input: `gain = [-4,-3,-2,-1,4,3,2]`

Output: 0

Explanation: The altitudes are `[0,-4,-7,-9,-10,-6,-3,-1]`. The highest is 0.

Constraints:

- $n == \text{gain.length}$
- $1 \leq n \leq 100$
- $-100 \leq \text{gain}[i] \leq 100$

PROGRAM

```
class Solution {  
  
    public int largestAltitude(int[] gain) {  
  
        int altitude = 0;  
  
        int highest = 0;  
  
        for (int i = 0; i < gain.length; i++) {  
  
            altitude += gain[i];  
  
            if (altitude > highest) {  
  
                highest = altitude;  
  
            }  
  
        }  
  
    }  
}
```

return highest;

}

}

OUTPUT

The screenshot shows a LeetCode submission for the problem "Find the Highest Altitude". The submission is accepted, with a runtime of 0 ms and memory usage of 0.00 MB. The code is in Java, and the test case input is [-5, 1, 5, 0, -7] with an expected output of 1.

Problem List < > <=>

Accepted

VTU30221 submitted at Sep 18, 2026 09:00

Analysis Solution

Unlock the Full LeetCode Experience

Company problems, Ask Leet, and expert editorials — all in one plan.

Runtime: 0 ms | Beats: -%

Memory: 0.00 MB | Beats: -%

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

gain = [-5, 1, 5, 0, -7]

Output

1

Expected