

2. Sort Array By Parity

Given an integer array `nums`, move all the even integers at the beginning of the array followed by all the odd integers.

Return *any array that satisfies this condition*.

Example 1:

Input: `nums = [3,1,2,4]`

Output: `[2,4,3,1]`

Explanation: The outputs `[4,2,3,1]`, `[2,4,1,3]`, and `[4,2,1,3]` would also be accepted.

Example 2:

Input: `nums = [0]`

Output: `[0]`

Constraints:

- $1 \leq \text{nums.length} \leq 5000$
- $0 \leq \text{nums}[i] \leq 5000$

PROGRAM

```
class Solution {  
  
    public int[] sortArrayByParity(int[] nums) {  
  
        int left = 0;  
  
        int right = nums.length - 1;  
  
        while (left < right) {  
  
            // Find an odd number from the left  
            while (left < right && nums[left] % 2 == 0) {  
                left++;  
            }  
  
            // Find an even number from the right  
            while (left < right && nums[right] % 2 != 0) {  
                right--;
```

```
}

// Swap them
if (left < right) {

    int temp = nums[left];

    nums[left] = nums[right];

    nums[right] = temp;

    left++;

    right--;

}

}

return nums;

}

}
```

OUTPUT

Sort Array By Parity - LeetCode

https://leetcode.com/problems/sort-array-by-parity/submissions/2139140589/

Problem List<>>Submit

Accepted 286 / 286 testcases passed
VTU90221 submitted at Sep 12, 2026 10:40
AnalysisSolution

Unlock the Full LeetCode Experience
₹583.25/mo
Company problems, Ask Leet, and expert editorials — all in one plan.

Runtime0 ms | Beats 100.00%
Memory20.50 MB | Beats 96.56%
100%
1ms2ms3ms4ms
1ms2ms3ms4ms

Code | C++
1class Solution {

23
24
25
26
27
28
29
};

Testcase | Test Result
Accepted Runtime: 0 ms
Case 1Case 2
Input
nums =
[3,1,2,4]
Output
[4,2,1,3]
Expected
[2,4,3,1]

32°C Mostly sunny
Search
ENG IN
10:40 12-09-2026