

Calculate the sum of similarities of a string S with each of its suffixes.

The first line contains the number of test cases t .

Each of the next t lines contains a string to process, s .

- $1 \leq t \leq 10$
- $1 \leq |s| \leq 100000$
- s is composed of characters in the range `ascii[a-z]`

Output t lines, each containing the answer for the corresponding test case.

2
ababaa
aa

11
3

Line: 83 Col: 1

 Upload Code as File☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

✔ Sample Test case 0

Input (stdin)

[Download](#)

Problem List

Submit

0

00:15:32

Premium

Description

Editorial

Solutions

Submissions

459. Repeated Substring Pattern

EasyTopicsCompanies

Given a string s , check if it can be constructed by taking a substring of it and appending multiple copies of the substring together.

Example 1:

Input: $s = \text{"abab"}$
Output: true
Explanation: It is the substring "ab" twice.

Example 2:

Input: $s = \text{"aba"}$
Output: false

Example 3:

Input: $s = \text{"abcabcabcabc"}$
Output: true
Explanation: It is the substring "abc" four times or the substring "abcabc" twice.

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of lowercase English letters.

6.9K

159

22 Online

Code

Java

Auto

```
1 class Solution {
2     public boolean repeatedSubstringPattern(String s) {
3         int n = s.length();
4
5         for (int len = 1; len <= n / 2; len++) {
6             if (n % len == 0) {
7                 String sub = s.substring(0, len);
8                 StringBuilder result = new StringBuilder();
9
10                for (int i = 0; i < n / len; i++) {
11                    result.append(sub);
12                }
13                if (result.toString().equals(s)) {
14                    return true;
15                }
16            }
17        }
18        return false;
19    }
20 }
```

Saved

Ln 1, Col 1

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Input

$s =$
 "abab"

Output

true

Expected

true

Given two strings, determine if they share a common substring. A substring may be as small as one character.

Example

$s1$ = 'and'

$s2$ = 'art'

These share the common substring **a**.

$s1$ = 'be'

$s2$ = 'cat'

These do not share a substring.

Function Description

Complete the function twoStrings in the editor below.

twoStrings has the following parameter(s):

- string $s1$: a string
- string $s2$: another string

Returns

- string: either YES or NO

Input Format

The first line contains a single integer p , the number of test cases.

The following p pairs of lines are as follows:

- The first line contains string $s1$.
- The second line contains string $s2$.

Constraints

```
52 String s2 = bufferedReader.readLine();
53
54 String result = Result.twoStrings(s1, s2);
55
56 bufferedWriter.write(result);
57 bufferedWriter.newLine();
58 }
59
60 bufferedReader.close();
61 bufferedWriter.close();
62 }
63
64 }
```

Line: 64 Col: 1

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Sample Test case 1

Sample Test case 2

Input (stdin)

Download

```
1 2
2 hello
3 world
```

Problem List

Submit

0

00:15:32

Premium

Description

Editorial

Solutions

Submissions

796. Rotate String

EasyTopicsCompanies

Given two strings `s` and `goal`, return `true` if and only if `s` can become `goal` after some number of **shifts** on `s`.

A **shift** on `s` consists of moving the leftmost character of `s` to the rightmost position.

- For example, if `s = "abcde"`, then it will be `"bcdea"` after one shift.

Example 1:

Input: `s = "abcde"`, `goal = "cdeab"`
Output: `true`

Example 2:

Input: `s = "abcde"`, `goal = "abced"`
Output: `false`

Constraints:

- `1 <= s.length, goal.length <= 100`
- `s` and `goal` consist of lowercase English letters.

</> Code

JavaAuto

```
1 class Solution {
2     public boolean rotateString(String s, String goal) {
3
4         // Lengths must be equal
5         if (s.length() != goal.length()) {
6             return false;
7         }
8
9         // goal must be a substring of s + s
10        String doubled = s + s;
11
12        return doubled.contains(goal);
13    }
14 }
```

SavedLn 14, Col 2

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

s =
"m"

goal =
"f"

Output

false

5.1K30239 Online

One platform. Infinite possibilities.

A space explorer's ship crashed on Mars! They send a series of SOS messages to Earth for help.



Letters in some of the SOS messages are altered by cosmic radiation during transmission. Given the signal received by Earth as a string, *s*, determine how many letters of the SOS message have been changed by radiation.

Example

s = 'SOSTOT'

```
22 for (int i = 0; i < s.length(); i++) {
23
24     if (s.charAt(i) != message.charAt(i % 3)) {
25         count++;
26     }
27 }
28
29 return count;
```

Line: 52 Col: 1

Upload Code as File

☐ Test against custom input

Run Code

Submit Code



You have earned 15.00 points!

You are now 140 points away from the 4th star for your problem solving badge.

49%

335/475

Congratulations

You solved this challenge. Would you like to challenge your friends?



Next Challenge

Test case 0

Compiler Message

Problem List

438. Find All Anagrams in a String

Medium

Topics

Companies

Description

Editorial

Solutions

Submissions

Run

Ctrl

Submit

13.4K

187

96 Online

438. Find All Anagrams in a String

Medium

Topics

Companies

Given two strings `s` and `p`, return an array of all the start indices of `p`'s *anagrams* in `s`. You may return the answer in **any order**.

Example 1:

Input: `s = "cbaebabacd"`, `p = "abc"`
Output: `[0,6]`
Explanation:
The substring with start index = 0 is "cba", which is an anagram of "abc".
The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab"`, `p = "ab"`
Output: `[0,1,2]`
Explanation:
The substring with start index = 0 is "ab", which is an anagram of "ab".
The substring with start index = 1 is "ba", which is an anagram of "ab".
The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- $1 \leq s.length, p.length \leq 3 \times 10^4$
- `s` and `p` consist of lowercase English letters.

Code

Java

Auto

```
1 import java.util.*;
2
3 class Solution {
4     public List<Integer> findAnagrams(String s, String p) {
5
6         List<Integer> result = new ArrayList<>();
7
8         if (s.length() < p.length()) {
9             return result;
10        }
11
12        int[] count = new int[26];
13    }
```

Saved

Ln 52, Col 2

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Input

`s =`
`"cbaebabacd"`
`p =`
`"abc"`

Output

`[0,6]`

Problem

Submissions

Leaderboard

Discussions

HackerRank

Prepare

Algorithms

Strings

Palindrome Index

Exit Full Screen View

Given a string of lowercase letters in the range `ascii[a-z]`, determine the index of a character that can be removed to make the string a **palindrome**. There may be more than one solution, but any will do. If the word is already a palindrome or there is no solution, return `-1`. Otherwise, return the index of a character to remove.

Example

`s = "bcbe"`

Either remove 'b' at index `0` or 'b' at index `3`.

Function Description

Complete the `palindromeIndex` function in the editor below.

`palindromeIndex` has the following parameter(s):

- string `s`: a string to analyze

Returns

- int: the index of the character to remove or `-1`

Input Format

The first line contains an integer `q`, the number of queries.

Each of the next `q` lines contains a query string `s`.

Constraints

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^5 + 5$
- All characters are in the range `ascii[a-z]`.

Sample Input

76

77

78

79

80

81

82

83

84

85

86

```
int result = Result.palindromeIndex(s);

bufferedWriter.write(String.valueOf(result));
bufferedWriter.newLine();

}

bufferedReader.close();
bufferedWriter.close();

}
```

Line: 86 Col: 1

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Problem Solving

You have earned 25.00 points!

You are now 115 points away from the 4th star for your problem solving badge.

58%

360/475

Congratulations

You solved this challenge. Would you like to challenge your friends?

[Twitter](#)[LinkedIn](#)

Next Challenge

Problem List

Submit

0

00:15:32

Premium

Description | Editorial | Solutions | Submissions

Easy | Topics | Companies

Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or `-1` if `needle` is not part of `haystack`.

Example 1:

Input: `haystack = "sadbutsad", needle = "sad"`
Output: `0`
Explanation: "sad" occurs at index 0 and 6. The first occurrence is at index 0, so we return 0.

Example 2:

Input: `haystack = "leetcode", needle = "leeto"`
Output: `-1`
Explanation: "leeto" did not occur in "leetcode", so we return -1.

Constraints:

- `1 <= haystack.length, needle.length <= 104`
- `haystack` and `needle` consist of only lowercase English characters.

DELL
Technologies

FESTIVE OFFERS
Built for every festive task
Cashback up to ₹15,000*
Dell 15

Shop Now
Intel® Core™
Ultra 7 processor

intel
core
ultra 7

Seen this question in a real interview before? 1/6

7.8K

577

142 Online

</> Code

Java | Auto

```
1 class Solution {
2     public int strStr(String haystack, String needle) {
3         return haystack.indexOf(needle);
4     }
5 }
```

Saved | Ln 3, Col 2

Testcase | Test Result

Accepted | Runtime: 0 ms

Case 1 | Case 2

Input

haystack =
"sadbutsad"

needle =
"sad"

Output

0

Problem List

Submit

0

00:15:32

Premium

Description

Editorial

Solutions

Submissions

5. Longest Palindromic Substring

MediumTopicsCompaniesHint

Given a string `s`, return the longest *palindromic substring* in `s`.

Example 1:

Input: `s = "babad"`
Output: `"bab"`
Explanation: `"aba"` is also a valid answer.

Example 2:

Input: `s = "cbbd"`
Output: `"bb"`

Constraints:

- `1 <= s.length <= 1000`
- `s` consist of only digits and English letters.

GoDaddy

Get email that looks as professional as your business is.

Seen this question in a real interview before? 1/5

33.1K675490 Online

</> Code

JavaAuto

```
1 class Solution {
2     public String longestPalindrome(String s) {
3
4         if (s.length() < 2) {
5             return s;
6         }
7
8         int start = 0;
9         int end = 0;
10
11         for (int i = 0; i < s.length(); i++) {
12
13             // Odd length palindrome
14             int left = i - 1;
15             int right = i + 1;
16             while (left >= 0 & right < s.length() & s.charAt(left) == s.charAt(right)) {
17                 left--;
18                 right++;
19             }
20             if (right - left - 1 > end - start) {
21                 start = left + 1;
22                 end = right - 1;
23             }
24
25             // Even length palindrome
26             left = i;
27             right = i + 1;
28             while (left < s.length() & right < s.length() & s.charAt(left) == s.charAt(right)) {
29                 left++;
30                 right++;
31             }
32             if (right - left > end - start) {
33                 start = left;
34                 end = right - 1;
35             }
36         }
37         return s.substring(start, end + 1);
38     }
39 }
```

SavedLn 42, Col 2

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1

Case 2

Input

`s =`
`"babad"`

Output

`"bab"`

Expected

`"bab"`

Problem

Submissions

Leaderboard

Discussions

HackerRank

Prepare > Algorithms > Strings > Circular Palindromes

Exit Full Screen View

A palindrome is a string that reads the same from left to right as it does from right to left.

Given a string, S , of N lowercase English letters, we define a k -length rotation as cutting the first k characters from the beginning of S and appending them to the end of S . For each S , there are N possible k -length rotations (where $0 \leq k < N$). See the Explanation section for examples.

Given N and S , find all N k -length rotations of S ; for each rotated string, S_k , print the maximum possible length of any palindromic substring of S_k on a new line.

Input Format

The first line contains an integer, N (the length of S).

The second line contains a single string, S .

Constraints

- $1 \leq N \leq 5 \times 10^5$
- $0 \leq k < N$
- S is comprised of lowercase English letters.

Output Format

There should be N lines of output, where each line k contains an integer denoting the maximum length of any palindromic substring of rotation S_k .

Sample Input 0

13
aaaaabbbbbaaaa

121

122

123

124

125

126

127

128

129

130

131

* there is a center whose Manacher radius

* is at least mid and which is at least

* mid away from both window boundaries.

*/

int queryLeft = left + mid;

int queryRight = rightBound - mid;

if (queryLeft <= queryRight) {

int maxRadius = rangeMax(

sparse,

Line: 214 Col: 1

Upload Code as File

Test against custom input

Run Code

Submit Code

Problem Solving

You have earned 120.00 points!

You are now 370 points away from the gold level for your problem solving badge, 1%

480/850

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge