

438. Find All Anagrams in a String

Medium Topics Companies

Given two strings `s` and `p`, return an array of all the start indices of `p`'s anagrams in `s`. You may return the answer in **any order**.

Example 1:

Input: `s = "cbaebabacd", p = "abc"`
Output: `[0,6]`
Explanation:
The substring with start index = 0 is "cba", which is an anagram of "abc".
The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab", p = "ab"`
Output: `[0,1,2]`
Explanation:
The substring with start index = 0 is "ab", which is an anagram of "ab".
The substring with start index = 1 is "ba", which is an anagram of "ab".
The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- `1 <= s.length, p.length <= 3 * 104`
- `s` and `p` consist of lowercase English letters.

 Google Gemini

Claim your free Gemini student plan

Sign up

Code

Java Auto

```
1 import java.util.*;
2
3 class Solution {
4     public List<Integer> findAnagrams(String s, String p) {
5         List<Integer> ans = new ArrayList<>();
6         int[] count = new int[26];
7
8         for (char c : p.toCharArray())
9             count[c - 'a']++;
10
11         int left = 0, right = 0, len = p.length();
12
13         while (right < s.length()) {
14             count[s.charAt(right) - 'a']--;
15             right++;
16
17             if (right - left == len) {
18                 boolean ok = true;
19
20                 for (int x : count)
21                     if (x != 0) {
22                         ok = false;
23                         break;
24                     }
25
26                 if (ok) ans.add(left);
27
28                 count[s.charAt(left) - 'a']++;
29                 left++;
30             }
31         }
32
33         return ans;
34     }
35 }
```

Saved

438. Find All Anagrams in a String

Medium Topics Companies

Given two strings `s` and `p`, return an array of all the start indices of `p`'s anagrams in `s`. You may return the answer in **any order**.

Example 1:

Input: `s = "cbaebabacd", p = "abc"`

Output: `[0,6]`

Explanation:

The substring with start index = 0 is "cba", which is an anagram of "abc".

The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab", p = "ab"`

Output: `[0,1,2]`

Explanation:

The substring with start index = 0 is "ab", which is an anagram of "ab".

The substring with start index = 1 is "ba", which is an anagram of "ab".

The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- $1 \leq s.length, p.length \leq 3 \times 10^4$
- `s` and `p` consist of lowercase English letters.

 **Claim your free Gemini student plan** [Sign up](#)

Code

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

`s =`
`"cbaebabacd"`

`p =`
`"abc"`

Output

`[0,6]`

Expected

`[0,6]`

[Contribute a testcase](#)