

Given a string of lowercase letters in the range `ascii[a-z]`, determine the index of a character that can be removed to make the string a **palindrome**. There may be more than one solution, but any will do. If the word is already a palindrome or there is no solution, return `-1`. Otherwise, return the index of a character to remove.

$$s = {}^nbcbcb^*$$
$$s = {}^nbcbcb^*$$

Either remove 'b' at index 0 or 'c' at index 3.

Complete the `palindromeindex` function in the editor below.

palindromeIndex has the following parameter(s):

- string s: a string to analyze

- `int`: the index of the character to remove or `-1`

- `int`: the index of the character to remove or `-1`

The first line contains an integer q , the number of queries.

Each of the next q lines contains a query string a .

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^4 + 5$
- All characters are in the range `ascii[a-z]`

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^4 + 5$
- All characters are in the range `ascii[a-z]`

STDM	Function
3	q = 3
aaab	s = 'aaab' (first query)
baa	s = 'baa' (second query)
aaa	s = 'aaa' (third query)

$$\begin{matrix} 3 \\ 0 \\ -1 \end{matrix}$$

Query 1: "asab"
Removing 'b' at index 3 results in a palindrome, so return 3.

Query 2: "baa"
Removing 'b' at index 0 results in a palindrome, so return 0.

Query 3: "aaa"
Removing 'a' at index 0 results in a palindrome, so return 0.

This string is clearly a *palindromum*, not rather -1 . Damascius' use now of this character would result in a *palindromum*, but this fact seems first

Author	arnitkgp
Difficulty	Easy
Cutoff Score	25.00
Max Score	25
Submitted By	103250

 [View discussions](#)

[View editorial](#)

 [View top submissions](#)

Palindrome

★★★★★

 Download problem statement

[Download sample test cases](#)

 [Suggest Edit](#)

CHOOSE A TRANSLATION

English



```
1 import java.util.*;
2
3 class Result {
4     static boolean isPal(String s, int l, int r) {
5         while (l < r) {
6             if (s.charAt(l++) != s.charAt(r--))
7                 return false;
8         }
9         return true;
10    }
11
12    public static int palindromeIndex(String s) {
13        int l = 0, r = s.length() - 1;
14
15        while (l < r) {
16            if (s.charAt(l) != s.charAt(r)) {
17                if (isPal(s, l + 1, r))
18                    return l;
19                if (isPal(s, l, r - 1))
20                    return r;
21                return -1;
22            }
23            l++;
24            r--;
25        }
26        return -1;
27    }
28 }
29
30 public class Solution {
31     public static void main(String[] args) {
32         Scanner sc = new Scanner(System.in);
33         int q = sc.nextInt();
34
35         while (q-- > 0)
36             System.out.println(Result.palindromeIndex(sc.next()));
37     }
38 }
```

Line: 38 Col: 2

 Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Compiler Message

Success

Input (stdin)

```
1 3
2 aaab
3 baa
4 aaa
```

[Download](#)

Your Output (stdout)

```
1 3
2 0
```