

1480. Running Sum of 1d Array

Easy Topics Companies Hint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]..nums[i])`.
Return the running sum of `nums`.

Example 1:

Input: `nums = [1,2,3,4]`
Output: `[1,3,6,10]`
Explanation: Running sum is obtained as follows: `[1, 1+2, 1+2+3, 1+2+3+4]`.

Example 2:

Input: `nums = [1,1,1,1,1]`
Output: `[1,2,3,4,5]`
Explanation: Running sum is obtained as follows: `[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]`.

Example 3:

Input: `nums = [3,1,2,10,1]`
Output: `[3,4,6,16,17]`

Constraints:

- `1 <= nums.length <= 1000`
- `-10^9 <= nums[i] <= 10^9`



Code

Java Auto

```
1 class Solution {
2     public int[] runningSum(int[] nums) {
3         int sum = 0;
4
5         for (int i = 0; i < nums.length; i++) {
6             sum += nums[i];
7             nums[i] = sum;
8         }
9
10        return nums;
11    }
12 }
13
```

Saved

Ln 1, Col 1

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2 Case 3

Input

`nums =`
`[1,2,3,4]`

Output

`[1,3,6,10]`

Expected

`[1,3,6,10]`

Contribute a testcase