

438. Find All Anagrams in a String

Medium Topics Companies

Given two strings `s` and `p`, return an array of all the start indices of `p`'s **anagrams** in `s`. You may return the answer in **any order**.

Example 1:

Input: `s = "cbaebabacd"`, `p = "abc"`

Output: `[0,6]`

Explanation:

The substring with start index = 0 is "cba", which is an anagram of "abc".

The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab"`, `p = "ab"`

Output: `[0,1,2]`

Explanation:

The substring with start index = 0 is "ab", which is an anagram of "ab".

The substring with start index = 1 is "ba", which is an anagram of "ab".

The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- $1 \leq s.length, p.length \leq 3 \times 10^4$
- `s` and `p` consist of lowercase English letters.

👍 13.4K 🗨️ 187 ☆ 📄 🔔

71 Online

Code

Java Auto

```
1 import java.util.*;
2
3 class Solution {
4     public List<Integer> findAnagrams(String s, String p) {
5
6         List<Integer> result = new ArrayList<>();
7
8         if (s.length() < p.length()) {
9             return result;
10        }
11
12        int[] pCount = new int[26];
13        int[] windowCount = new int[26];
14
15        // Count characters in p
```

Saved

Ln 49, Col 2

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

`s =`
`"cbaebabacd"`

`p =`
`"abc"`

Output

`[0,6]`

Expected