

[Description](#) | [Editorial](#) | [Solutions](#) | [Submissions](#)

1480. Running Sum of 1d Array

Easy Topics Companies Hint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]...nums[i])`.

Return the running sum of `nums`.

Example 1:

Input: nums = [1,2,3,4]

Output: [1,3,6,10]

Explanation: Running sum is obtained as follows: [1, 1+2, 1+2+3, 1+2+3+4].

Example 2:

Input: nums = [1,1,1,1,1]

Output: [1,2,3,4,5]

Explanation: Running sum is obtained as follows: $[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]$.

Example 3:

Input: nums = [3,1,2,10,1]

Output: [3, 4, 6, 16, 17]

Constraints:

- `1 <= nums.length <= 1000`
- `-10^6 <= nums[i] <= 10^6`

Solved

</> Code

Java   Auto

```
1 class Solution {
2     public int[] runningSum(int[] nums) {
3         for (int i = 1; i < nums.length; i++) {
4             nums[i] = nums[i] + nums[i - 1];
5         }
6
7         return nums;
8     }
9 }
```

Saved

Ln 10, Col 1

Testcase > Test Result

Accepted Runtime: 0 ms

✔ Case 1 ✔ Case 2 ✔ Case 3

Input

```
nums =
```

[1,2,3,4]

Output

[1,3,6,10]

Expected

[1,3,6,10]

♥ [Contribute a testcase](#)