

TASK 3: Using Clauses, Operators and Functions in queries:**CO2, CO5,****K3**

(Tool: SQL/ Oracle, ALM: Flipped classroom)

Aim: To Perform the query processing on databases for different retrieval results of queries using DML, DRL operations using aggregate, date, string, indent functions, set clauses and operators.

- To retrieve the location of a particular match conducted by its MatchID
- To retrieve the Players detail whose name start with ‘A’.
- Add a column Batting and Bowling in Player table.
- To count the number of right-hand batsman in a team.
- To display the CricketBoard details for the BoardIDs 'BID01', 'BID03', and 'BID06'.
- To select the names and IDs of players who are left-hand bowlers.
- To find the UmpireID of umpires who have not umpired any match.
- To list the PlayerIDs and the total number of matches each player has played.

Sample output:

1. Select location from Match where MatchID='MAC03';
2. Select * from Player where Name ='A%';
3. Alter table Player add Batting varchar(20), Bowling varchar(6);
4. Select count(*) from Players where Batting='right-hand';
5. Select * from CricketBoard where BoardID in('BID01', BID03','BID06');
6. Select PLayerID, Name for Player where Bowling='left-hand';

Queries:

1. Retrieve the location of a particular match by its MatchID

```
SELECT Location FROM Match WHERE MatchID = 'MAC03'; -- Filter for the required match
```

2. Retrieve the player details whose name starts with 'A'

```
SELECT * FROM Player WHERE UPPER(Name) LIKE 'A%'; -- 'A%' matches names starting with A (case-insensitive)
```

3. Add columns Batting and Bowling to the Player table

```
ALTER TABLE Player ADD ( Batting VARCHAR2(20), -- Stores batting style (e.g., right-hand, left-hand Bowling VARCHAR2(10)); -- Stores bowling style
```

4. Count the number of right-hand batsmen in a specific team

```
SELECT COUNT(*) AS NumRightBatsmen FROM Player WHERE LOWER(Batting) = 'right-hand' -- Match batting style AND TeamID = 'TID01'; -- Restrict to one team  
(change as needed)
```

5. Display CricketBoard details for specific BoardIDs

```
SELECT * FROM CricketBoard WHERE BoardID IN ('BID01','BID03','BID06');  
-- Matches any of the listed IDs
```

6. Select the PlayerID and Name of players who are left-hand bowlers

```
SELECT PlayerID, Name FROM Player WHERE LOWER(Bowling) = 'left-hand';  
-- Match bowling style
```

7. Find UmpireIDs of umpires who have not umpired any match

```
SELECT U.UmpireID, U.Name FROM Umpire U LEFT JOIN Match_Umpire MU  
ON U.UmpireID = MU.UmpireID -- Match umpires to matches  
WHERE MU.UmpireID IS NULL; -- Keep only those with no  
match records
```

8. List PlayerIDs and total number of matches each player has played

```
SELECT PlayerID, COUNT(DISTINCT MatchID) AS MatchesPlayed -- Count unique  
matches per player  
FROM Player_Match  
GROUP BY PlayerID; -- Group results by each player
```