



# Basic File IO with the NIO Library

Originals of Slides and Source Code for Examples:  
<http://courses.coreservlets.com/Course-Materials/java.html>



**Customized Java EE Training:** <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.



For live Java-related training,  
see <http://courses.coreservlets.com/>  
or email [hall@coreservlets.com](mailto:hall@coreservlets.com).



Taught by the author of *Core Servlets and JSP*, *More Servlets and JSP*, and this tutorial. Available at public venues, or customized versions can be held on-site at your organization.

- Courses developed and taught by Marty Hall
  - JSF 2, PrimeFaces, servlets/JSP, Ajax, jQuery, Android development, Java 7 or 8 programming, custom mix of topics
  - Courses available in any state or country. Maryland/DC area companies can also choose afternoon/evening courses.
- Courses developed and taught by [coreservlets.com](http://coreservlets.com) experts (edited by Marty)
  - Spring, Hibernate/JPA, GWT, Hadoop, HTML5, RESTful Web Services

Contact [hall@coreservlets.com](mailto:hall@coreservlets.com) for details



## Topics in This Section

- **More on try/catch blocks**
  - finally blocks
  - multcatch
  - try with resources
- **Path**
- **Simple file reading: all lines at once into List**
- **Simple file writing: all at once from a List**
- **Some simple file reading and writing utilities**
- **Faster and more flexible file reading**
- **Faster and more flexible file writing**

## Summary for Java 6 (and Earlier) Programmers

- **Use Path instead of File**
  - `Path p = Paths.get("/path/to/file.txt");`
- **Can read all file lines into a List in one call**
  - `List<String> lines = Files.readAllLines(somePath, someCharset);`
- **Can write List into a file in one call**
  - `Files.write(somePath, someList, someCharset);`
- **Use try that automatically closes resources**
  - `try(BufferedReader reader = ...) { ... } catch (...) { ... }`
- **Shortcuts to get high-performance classes**
  - `Files.newBufferedReader(somePath, someCharset)`
  - `Files.newBufferedWriter(somePath, someCharset)`



# More on try/catch Blocks



Customized Java EE Training: <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Summary

- **Covered earlier: basics**

```
try {  
    statement1;  
    statement2;  
    ...  
} catch(Eclass1 var1) {  
    ...  
} catch(Eclass2 var2) {  
    ...  
} catch(Eclass3 var3) {  
    ...  
}  
...
```

- **New: finally**

```
try {...  
} catch(...) {...  
} finally {  
    ...  
}
```

- **New: multicatch**

```
try {...  
} catch(Eclass1 | Eclass e) {  
    ...  
} ...
```

- **New: try with resources**

```
try (SomeAutoCloseable var = ...) {...  
} catch(...) { ...  
} ...
```

# Finally Blocks

- **Idea**

- The finally { ... } block at the end of a try/catch is called whether or not there is an exception

- **Motivation: resetting resources**

```
HugeDataStructure blah = ...;
try {
    doSomethingWith(blah);
    ...
} catch {
    ...
} finally {
    blah = null;
}
```

## Finally Blocks: Need

- **Question: difference between these two?**

Finally Block	Code After Entire try/catch
<pre>try { ... } catch(...) { ... } finally {     doSomeCleanup(); }</pre>	<pre>try { ... } catch(...) { ... } doSomeCleanup();</pre>

- **Answer: nested try/catch blocks**

- In the example on the right above, if the catch throws an exception and the entire try/catch block is inside another try/catch block, the cleanup code might not run.
  - So, usual practice for code that runs whether or not there is an exception is to put it below try/catch block, but finally block is sometimes necessary.

# Multicatch

- **Idea: can catch multiple exceptions using |**
  - In Java 7 and later, if two different catch blocks will do the same, you can catch more than one in the same catch clause (but also consider catching a parent type):
    - `try { ... } catch(Eclass1 | Eclass2 e) {...}`
- **Example**

Without Multicatch	With Multicatch
<pre>String strng = getSomeString(); int num; try {     num = Integer.parseInt(strng); } catch(NumberFormatException nfe) {     num = someDefault; } catch(NullPointerException npe) {     num = someDefault; }</pre>	<pre>String strng = getSomeString(); int num; try {     num = Integer.parseInt(strng); } catch(NumberFormatException   NullPointerException e) {     num = someDefault; }</pre>

# Try with Resources

- **Idea**
  - In Java 7 and later, you can declare variables that implement `AutoCloseable` in parens after try.
    - Scope of variable is scope of try/catch block
    - The “close” method of each variable is called at the end, whether or not there is an exception (i.e., as if the call to close were in a finally block)
    - Can declare multiple variables, separated by semicolon
- **Example**

```
try (BufferedReader reader = ...) {
    doSomeIOWith(reader);
    ...
} catch(...) {
    ...
}
```



# Try with Resources: Need

Without	With
<pre>BufferedReader reader; try {     reader = ...;     ... } catch (...) {     ... } finally {     reader.close(); }</pre>	<pre>try(BufferedReader reader = ...) {     ... } catch (...) {     ... }</pre>

- **Advantages of approach on right**
  - Shorter and simpler
  - Can't forget to call close
  - The reader variable is out of scope after the try/catch block finishes

© 2013 Marty Hall



## Paths



**Customized Java EE Training:** <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Idea

- **Path is flexible replacement for File**
  - And is main starting point for file IO operations
- **Get Path with Paths.get**
  - Path p1 = Paths.get("some-file");
  - Path p2 = Paths.get("/usr/local/gosling/some-file");
  - Path p3 =  
Paths.get("C:\\Users\\Gosling\\Documents\\some-file");
    - Notice the double backslashes because backslash already has meaning (escape next char) in Java strings.
- **Paths have convenient methods**
  - toAbsolutePath, startsWith, endsWith, getFileName, getName, getNameCount, subpath, getParent, getRoot, normalize, relativize

## Example

```
public class PathExamples {  
    public static void main(String[] args) {  
        Path p1 = Paths.get("InputFile.txt");  
        System.out.println("Simple Path");  
        System.out.printf("toString: %s%n", p1);  
        Path p2 = p1.toAbsolutePath();  
        System.out.println("Absolute Path");  
        System.out.printf("toString: %s%n", p2);  
        System.out.printf("getFileName: %s%n", p2.getFileName());  
        System.out.printf("getName(0): %s%n", p2.getName(0));  
        System.out.printf("getNameCount: %d%n", p2.getNameCount());  
        System.out.printf("subpath(0,2): %s%n", p2.subpath(0,2));  
        System.out.printf("getParent: %s%n", p2.getParent());  
        System.out.printf("getRoot: %s%n", p2.getRoot());  
    }  
}
```

# Example Output

## Simple Path

toString: InputFile.txt

## Absolute Path

toString: C:\eclipse-workspace\java\nio\InputFile.txt

getFileName: InputFile.txt

getName(0): eclipse-workspace

getNameCount: 4

subpath(0,2): eclipse-workspace\java

getParent: C:\eclipse-workspace\java\nio

getRoot: C:\

© 2013 Marty Hall



# Simple File Reading



Customized Java EE Training: <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.

Developed and taught by well-known author and developer. At public venues or onsite at *your* location.



## Idea

- **You can read all lines in one method call**
  - `List<String> lines = Files.readAllLines(somePath, someCharset);`
- **You can read all bytes in one method call**
  - `byte[] fileArray = Files.readAllBytes(file);`
    - Strings can easily be made from byte arrays:  
`String fileData = new String(Files.readAllBytes(file));`
- **Minor caveats**
  - You have to explicitly specify a Charset, even if you will use the default for the JDK
    - `Charset cset1 = Charset.defaultCharset();`
    - `Charset cset1 = Charset.forName("US-ASCII");`
  - You still have to catch `IOException`

## Example

```
public class ReadFile1 {  
    public static void main(String[] args) throws IOException {  
        String file = "InputFile.txt";  
        Charset characterSet = Charset.defaultCharset();  
        Path path = Paths.get(file);  
        List<String> lines =  
            Files.readAllLines(path, characterSet);  
        System.out.printf("Lines from %s: %s%n", file, lines);  
    }  
}
```

# Example Output

- **Source of InputFile.txt**

First line

Second line

Third line

Last line

- **Output of example code from previous slide**

Lines from InputFile.txt:

[First line, Second line, Third line, Last line]

© 2013 Marty Hall



# Simple File Writing



**Customized Java EE Training: <http://courses.coreservlets.com/>**

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.

Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Idea

- **You can write all lines in one method call**
  - `List<String> lines = ...;`
  - `Files.write(somePath, lines, someCharset);`
- **You can write all bytes in one method call**
  - `byte[] fileArray = ...;`
  - `Files.write(somePath, fileArray);`
- **OpenOption**
  - Both methods above optionally take an `OpenOption` as final argument
    - This specifies whether to create file if it doesn't exist, whether to append, and so forth
    - Default behavior is to create file if not there and to overwrite if it is there

## Example

```
public class WriteFile1 {  
    public static void main(String[] args) throws IOException {  
        Charset characterSet = Charset.defaultCharset();  
        Path path = Paths.get("OutputFile1.txt");  
        List<String> lines =  
            Arrays.asList("Line One", "Line Two", "Final Line");  
        Files.write(path, lines, characterSet);  
    }  
}
```

- **Source of OutputFile1.txt after execution**

```
Line One  
Line Two  
Final Line
```



# Some Simple Utilities



Customized Java EE Training: <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Two Static Methods

- **FileUtils.getLines("filename")**
  - Reading file into a List<String>
- **FileUtils.writeLines("filename", list)**
  - Writing file from a List<String>

```
public class FileUtils {  
    public static List<String> getLines(String file)  
        throws IOException {  
        Path path = Paths.get(file);  
        return(Files.readAllLines(path, Charset.defaultCharset()));  
    }  
  
    public static Path writeLines(String file, List<String> lines)  
        throws IOException {  
        Path path = Paths.get(file);  
        return(Files.write(path, lines, Charset.defaultCharset()));  
    }  
}
```

## Minor Variation of ReadFile1

```
public class ReadFile1A {  
    public static void main(String[] args) throws IOException {  
        String file = "InputFile.txt";  
        List<String> lines = FileUtils.getLines(file);  
        System.out.printf("Lines from %s: %s%n", file, lines);  
    }  
}
```

- **Output**

- Same as ReadFile1. E.g.:

Lines from InputFile.txt:

[First line, Second line, Third line, Last line]

## Minor Variation of WriteFile1

```
public class WriteFile1A {  
    public static void main(String[] args) throws IOException {  
        List<String> lines =  
            Arrays.asList("Line One", "Line Two", "Final Line");  
        FileUtils.writeLines("OutputFile1.txt", lines);  
    }  
}
```

- **Source of OutputFile1.txt after execution**

Line One

Line Two

Final Line





# Faster and More Flexible File Reading



Customized Java EE Training: <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Idea

- **You sometimes need only part of the file**
  - Files.readAllLines reads everything, with no way to stop reading if you find the info you need partway through
- **Need higher performance for very large files**
  - Buffered reading reads in blocks, and is faster for very large files.
- **Shortcut method for getting BufferedReader**
  - Files.newBufferedReader(somePath, someCharset)
- **BufferedReader has readLine method**
  - Returns a String. Can chop the String into pieces using StringTokenizer (weak but simple) or String.split (much more powerful).
    - Details on parsing in lectures on network programming.

# Example

```
public class ReadFile2 {  
    public static void main(String[] args) throws IOException {  
        String file = "InputFile.txt";  
        Charset characterSet = Charset.defaultCharset();  
        Path path = Paths.get(file);  
        try(BufferedReader reader =  
            Files.newBufferedReader(path, characterSet)) {  
            System.out.printf("Lines from %s:%n", file);  
            String line;  
            while ((line = reader.readLine()) != null) {  
                System.out.println(line);  
            }  
        } catch (IOException ioe) {  
            System.err.printf("IOException: %s%n", ioe);  
        }  
    }  
}
```

# Example Output

- **Source of InputFile.txt**

First line

Second line

Third line

Last line

- **Output of example code from previous slide**

Lines from InputFile.txt:

First line

Second line

Third line

Last line



# Faster and More Flexible File Writing



Customized Java EE Training: <http://courses.coreservlets.com/>

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Idea

- **You often need to format Strings**
  - Files.write does not let you format the Strings as you insert them into the file
- **Need higher performance for very large files**
  - Buffered writing writes in blocks, and is faster for very large files.
- **Shortcut method for getting BufferedWriter**
  - Files.newBufferedWriter(somePath, someCharset)
- **Can also use PrintWriter**
  - Writer has only simple write method, but you can do new PrintWriter(yourBufferedWriter), then use the print, println, and printf methods of PrintWriter
    - printf covered in lecture on More Syntax and Utilities

## Example 1: BufferedWriter Only

```
public class WriteFile2 {  
    public static void main(String[] args) throws IOException {  
        Charset characterSet = Charset.defaultCharset();  
        int numLines = 10;  
        Path path = Paths.get("OutputFile2.txt");  
        try (BufferedWriter writer =  
            Files.newBufferedWriter(path, characterSet)) {  
            for(int i=0; i<numLines; i++) {  
                writer.write("Number is " + 100 * Math.random());  
                writer.newLine();  
            }  
        } catch (IOException ioe) {  
            System.err.printf("IOException: %s%n", ioe);  
        }  
    }  
}
```

## Example Output

- Source of OutputFile2.txt after execution

```
Number is 81.4612317643326  
Number is 52.38736740877531  
Number is 71.76545597068544  
Number is 59.85194979902197  
Number is 17.25041924343985  
Number is 86.77057757498325  
Number is 30.570152355456926  
Number is 61.490142746576424  
Number is 35.59135386659128  
Number is 89.43130746540979
```

## Example 2: PrintWriter

```
public class WriteFile3 {  
    public static void main(String[] args) throws IOException {  
        Charset characterSet = Charset.defaultCharset();  
        int numLines = 10;  
        Path path = Paths.get("OutputFile3.txt");  
        try (PrintWriter out =  
            new PrintWriter(Files.newBufferedWriter(path,  
                characterSet))) {  
            for(int i=0; i<numLines; i++) {  
                out.printf("Number is %5.2f%n", 100 * Math.random());  
            }  
        } catch (IOException ioe) {  
            System.err.printf("IOException: %s%n", ioe);  
        }  
    }  
}
```

## Example Output

- Source of OutputFile3.txt after execution

```
Number is 71.95  
Number is 35.75  
Number is 39.52  
Number is 15.04  
Number is  2.50  
Number is 14.58  
Number is 63.06  
Number is 13.77  
Number is 96.51  
Number is  5.27
```





# Wrap-Up



**Customized Java EE Training: <http://courses.coreservlets.com/>**

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

## Summary: File IO Topics

- **Use Path instead of File**
  - Path p = Paths.get("/path/to/file.txt");
- **Can read all file lines into a List in one call**
  - List<String> lines =  
Files.readAllLines(somePath, someCharset);
- **Can write List into a file in one call**
  - Files.write(somePath, someList, someCharset);
- **Minor utilities (not builtin)**
  - List<String> lines = FileUtils.getLines("filename");
  - FileUtils.writeLines("filename", someList);
- **Shortcuts to get high-performance classes**
  - Files.newBufferedReader(somePath, someCharset)
    - To read, use readLine method
  - Files.newBufferedWriter(somePath, someCharset)
    - To write, use write method, or wrap in PrintWriter and use printf

# Summary: General Topics

- **finally blocks**

```
try {...  
} catch(...) {...  
} finally {  
    ...  
}
```

- **multicatch**

```
try {...  
} catch(Eclass1 | Eclass e) {  
    ...  
} ...
```

- **try with resources**

```
try (SomeAutoCloseable var = ...) {...  
} catch(...) { ...  
} ...
```

© 2013 Marty Hall



# Questions?

[JSF 2, PrimeFaces, Java 7 or 8, HTML5, Ajax, jQuery, Hadoop, RESTful Web Services, Android, Spring, Hibernate, Servlets, JSP, GWT, and other Java EE training.](#)



**Customized Java EE Training: <http://courses.coreservlets.com/>**

Java, JSF 2, PrimeFaces, HTML5, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.  
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.