

Figure 1: Object Dependency Graph

This document describes the plan and progress of the implementation of Vulkayes.

Synchronization

Most parameters in Vulkan require external synchronization. Synchronization is provided in two flavours: Single-thread and multi-thread. Single-thread synchronization primitives are noops, while multi-thread primitives provide actual multi-thread and multi-core synchronization. If single-thread synchronization is chosen, the Rust type system statically prevents use in multiple threads.

Externally Synchronized Parameters

- The `instance` parameter in `vkDestroyInstance`
  - Consequence of shared pointer usage
- The `device` parameter in `vkDestroyDevice`
  - Consequence of shared pointer usage
- The `queue` parameter in `vkQueueSubmit`
  - Synchronized internally
- The `fence` parameter in `vkQueueSubmit`
  - Synchronized internally
- The `queue` parameter in `vkQueueWaitIdle`
  - Synchronized internally
- The `memory` parameter in `vkFreeMemory`
  - Consequence of shared pointer usage
- The `memory` parameter in `vkMapMemory`
  - Synchronized internally
- The `memory` parameter in `vkUnmapMemory`
  - Synchronized internally
- The `buffer` parameter in `vkBindBufferMemory`
  - Handled by API design
- The `image` parameter in `vkBindImageMemory`
  - Handled by API design
- The `queue` parameter in `vkQueueBindSparse`
- The `fence` parameter in `vkQueueBindSparse`
- The `fence` parameter in `vkDestroyFence`
  - Consequence of shared pointer usage
- The `semaphore` parameter in `vkDestroySemaphore`
  - Consequence of shared pointer usage
- The `event` parameter in `vkDestroyEvent`
- The `event` parameter in `vkSetEvent`
- The `event` parameter in `vkResetEvent`
- The `queryPool` parameter in `vkDestroyQueryPool`
- The `buffer` parameter in `vkDestroyBuffer`
  - Consequence of shared pointer usage
- The `bufferView` parameter in `vkDestroyBufferView`
  - Consequence of shared pointer usage
- The `image` parameter in `vkDestroyImage`
  - Consequence of shared pointer usage
- The `imageView` parameter in `vkDestroyImageView`
  - Consequence of shared pointer usage
- The `shaderModule` parameter in `vkDestroyShaderModule`
- The `pipelineCache` parameter in `vkDestroyPipelineCache`
- The `dstCache` parameter in `vkMergePipelineCaches`
- The `pipeline` parameter in `vkDestroyPipeline`

- The pipelineLayout parameter in vkDestroyPipelineLayout
  - Consequence of shared pointer usage
- The sampler parameter in vkDestroySampler
  - Consequence of shared pointer usage
- The descriptorSetLayout parameter in vkDestroyDescriptorSetLayout
  - Consequence of shared pointer usage
- The descriptorPool parameter in vkDestroyDescriptorPool
  - Consequence of shared pointer usage
- The descriptorPool parameter in vkResetDescriptorPool
  - Synchronized internally
- The descriptorPool member of the pAllocateInfo parameter in vkAllocateDescriptorSets
  - Synchronized internally
- The descriptorPool parameter in vkFreeDescriptorSets
  - Synchronized internally
- The framebuffer parameter in vkDestroyFramebuffer
  - Consequence of shared pointer usage
- The renderPass parameter in vkDestroyRenderPass
  - Consequence of shared pointer usage
- The commandPool parameter in vkDestroyCommandPool
  - Consequence of shared pointer usage
- The commandPool parameter in vkResetCommandPool
  - Synchronized internally
- The commandPool member of the pAllocateInfo parameter in vkAllocateCommandBuffers
  - Synchronized internally
- The commandPool parameter in vkFreeCommandBuffers
  - Synchronized internally

- The commandBuffer parameter in vkBeginCommandBuffer
- The commandBuffer parameter in vkEndCommandBuffer
- The commandBuffer parameter in vkResetCommandBuffer
- The commandBuffer parameter in vkCmdBindPipeline
- The commandBuffer parameter in vkCmdSetViewport
- The commandBuffer parameter in vkCmdSetScissor
- The commandBuffer parameter in vkCmdSetLineWidth
- The commandBuffer parameter in vkCmdSetDepthBias
- The commandBuffer parameter in vkCmdSetBlendConstants
- The commandBuffer parameter in vkCmdSetDepthBounds
- The commandBuffer parameter in vkCmdSetStencilCompareMask
- The commandBuffer parameter in vkCmdSetStencilWriteMask
- The commandBuffer parameter in vkCmdSetStencilReference
- The commandBuffer parameter in vkCmdBindDescriptorSets
- The commandBuffer parameter in vkCmdBindIndexBuffer
- The commandBuffer parameter in vkCmdBindVertexBuffers
- The commandBuffer parameter in vkCmdDraw
- The commandBuffer parameter in vkCmdDrawIndexed
- The commandBuffer parameter in vkCmdDrawIndirect
- The commandBuffer parameter in vkCmdDrawIndexedIndirect
- The commandBuffer parameter in vkCmdDispatch
- The commandBuffer parameter in vkCmdDispatchIndirect
- The commandBuffer parameter in vkCmdCopyBuffer
- The commandBuffer parameter in vkCmdCopyImage
- The commandBuffer parameter in vkCmdBlitImage
- The commandBuffer parameter in vkCmdCopyBufferToImage
- The commandBuffer parameter in vkCmdCopyImageToBuffer

- The commandBuffer parameter in vkCmdUpdateBuffer
- The commandBuffer parameter in vkCmdFillBuffer
- The commandBuffer parameter in vkCmdClearColorImage
- The commandBuffer parameter in vkCmdClearDepthStencilImage
- The commandBuffer parameter in vkCmdClearAttachments
- The commandBuffer parameter in vkCmdResolveImage
- The commandBuffer parameter in vkCmdSetEvent
- The commandBuffer parameter in vkCmdResetEvent
- The commandBuffer parameter in vkCmdWaitEvents
- The commandBuffer parameter in vkCmdPipelineBarrier
- The commandBuffer parameter in vkCmdBeginQuery
- The commandBuffer parameter in vkCmdEndQuery
- The commandBuffer parameter in vkCmdResetQueryPool
- The commandBuffer parameter in vkCmdWriteTimestamp
- The commandBuffer parameter in vkCmdCopyQueryPoolResults
- The commandBuffer parameter in vkCmdPushConstants
- The commandBuffer parameter in vkCmdBeginRenderPass
- The commandBuffer parameter in vkCmdNextSubpass
- The commandBuffer parameter in vkCmdEndRenderPass
- The commandBuffer parameter in vkCmdExecuteCommands
- The commandBuffer parameter in vkCmdSetDeviceMask
- The commandBuffer parameter in vkCmdDispatchBase
- The commandPool parameter in vkTrimCommandPool
  - Internally synchronized
- The ycbcrConversion parameter in vkDestroySamplerYcbcrConversion
- The descriptorUpdateTemplate parameter in vkDestroyDescriptorUpdateTemplate
- The descriptorSet parameter in vkUpdateDescriptorSetWithTemplate
- The commandBuffer parameter in vkCmdDrawIndirectCount
- The commandBuffer parameter in vkCmdDrawIndexedIndirectCount
- The commandBuffer parameter in vkCmdBeginRenderPass2
- The commandBuffer parameter in vkCmdNextSubpass2
- The commandBuffer parameter in vkCmdEndRenderPass2
- The surface parameter in vkDestroySurfaceKHR
  - Consequence of shared pointer usage
- The surface member of the pCreateInfo parameter in vkCreateSwapchainKHR
  - Handled by a combination of API design and swapchain internal synchronization
- The oldSwapchain member of the pCreateInfo parameter in vkCreateSwapchainKHR
  - Internally synchronized
- The swapchain parameter in vkDestroySwapchainKHR
  - Consequence of shared pointer usage
- The swapchain parameter in vkAcquireNextImageKHR
  - Internally synchronized
- The semaphore parameter in vkAcquireNextImageKHR
  - Internally synchronized
- The fence parameter in vkAcquireNextImageKHR
  - Internally synchronized
- The queue parameter in vkQueuePresentKHR
  - Internally synchronized
- The surface parameter in vkGetDeviceGroupSurfacePresentModesKHR
- The surface parameter in vkGetPhysicalDevicePresentRectanglesKHR
- The display parameter in vkCreateDisplayModeKHR
- The mode parameter in vkGetDisplayPlaneCapabilitiesKHR
- The commandBuffer parameter in vkCmdSetDeviceMaskKHR
- The commandBuffer parameter in vkCmdDispatchBaseKHR

- The commandBuffer parameter in vkCmdPushDescriptorSetKHR
- The commandBuffer parameter in vkCmdPushDescriptorSetWithTemplateKHR
- The descriptorUpdateTemplate parameter in vkDestroyDescriptorUpdateTemplateKHR
- The descriptorSet parameter in vkUpdateDescriptorSetWithTemplateKHR
- The commandBuffer parameter in vkCmdBeginRenderPass2KHR
- The commandBuffer parameter in vkCmdNextSubpass2KHR
- The commandBuffer parameter in vkCmdEndRenderPass2KHR
- The swapchain parameter in vkGetSwapchainStatusKHR
- The ycbcrConversion parameter in vkDestroySamplerYcbcrConversionKHR
- The commandBuffer parameter in vkCmdDrawIndirectCountKHR
- The commandBuffer parameter in vkCmdDrawIndexedIndirectCountKHR
- The callback parameter in vkDestroyDebugReportCallbackEXT
- The object member of the pTagInfo parameter in vkDebugMarkerSetObjectTagEXT
- The object member of the pNameInfo parameter in vkDebugMarkerSetObjectNameEXT
- The commandBuffer parameter in vkCmdBindTransformFeedbackBuffersEXT
- The commandBuffer parameter in vkCmdBeginTransformFeedbackEXT
- The commandBuffer parameter in vkCmdEndTransformFeedbackEXT
- The commandBuffer parameter in vkCmdBeginQueryIndexedEXT
- The commandBuffer parameter in vkCmdEndQueryIndexedEXT
- The commandBuffer parameter in vkCmdDrawIndirectByteCountEXT
- The commandBuffer parameter in vkCmdDrawIndirectCountAMD
- The commandBuffer parameter in vkCmdDrawIndexedIndirectCountAMD
- The commandBuffer parameter in vkCmdBeginConditionalRenderingEXT
- The commandBuffer parameter in vkCmdEndConditionalRenderingEXT
- The commandBuffer parameter in vkCmdProcessCommandsNVX
- The commandBuffer parameter in vkCmdReserveSpaceForCommandsNVX
- The objectTable parameter in vkDestroyObjectTableNVX
- The objectTable parameter in vkRegisterObjectsNVX
- The objectTable parameter in vkUnregisterObjectsNVX
- The commandBuffer parameter in vkCmdSetViewportWScalingNV
- The swapchain parameter in vkGetRefreshCycleDurationGOOGLE
- The swapchain parameter in vkGetPastPresentationTimingGOOGLE
- The commandBuffer parameter in vkCmdSetDiscardRectangleEXT
- The objectHandle member of the pNameInfo parameter in vkSetDebugUtilsObjectNameEXT
- The objectHandle member of the pTagInfo parameter in vkSetDebugUtilsObjectTagEXT
- The messenger parameter in vkDestroyDebugUtilsMessengerEXT
- The commandBuffer parameter in vkCmdSetSampleLocationsEXT
- The validationCache parameter in vkDestroyValidationCacheEXT
- The dstCache parameter in vkMergeValidationCachesEXT
- The commandBuffer parameter in vkCmdBindShadingRateImageNV
- The commandBuffer parameter in vkCmdSetViewportShadingRatePaletteNV
- The commandBuffer parameter in vkCmdSetCoarseSampleOrderNV
- The commandBuffer parameter in vkCmdWriteBufferMarkerAMD
- The commandBuffer parameter in vkCmdDrawMeshTasksNV
- The commandBuffer parameter in vkCmdDrawMeshTasksIndirectNV
- The commandBuffer parameter in vkCmdDrawMeshTasksIndirectCountNV
- The commandBuffer parameter in vkCmdSetExclusiveScissorNV
- The commandBuffer parameter in vkCmdSetLineStippleEXT

Validations

There are two types of validations in Vulkan API: Implicit validations, which talk about technical aspects of the API usage, and explicit validations, which talk about semantical aspects. Vulkayes aims to solve all implicit validations in the core crate. External validations are not always trivial to solve, some of them are statically

fulfilled using the type system or the API design, others are left to the user.

External validations resolved statically are enclosed in blue boxes below. Validations optionally checked at runtime are in green boxes.

Implicit validations

Instance

Validations for `vkCreateInstance`:

1. `pCreateInfo` must be a valid pointer to a valid `VkInstanceCreateInfo` structure
   - Handled by API design (ash)
2. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design (ash)
3. `pInstance` must be a valid pointer to a `VkInstance` handle
   - Handled by API design (ash)

Validations for `VkInstanceCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_INSTANCE_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkDebugReportCallbackCreateInfoEXT`, `VkDebugUtilsMessengerCreateInfoEXT`, `VkValidationFeaturesEXT`, or `VkValidationFlagsEXT`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be `0`
   - Handled by API design (ash)
5. If `pApplicationInfo` is not `NULL`, `pApplicationInfo` must be a valid pointer to a valid `VkApplicationInfo` structure
   - Handled by API design (ash)
6. If `enabledLayerCount` is not `0`, `ppEnabledLayerNames` must be a valid pointer to an array of `enabledLayerCount` null-terminated UTF-8 strings
   - Returns error
7. If `enabledExtensionCount` is not `0`, `ppEnabledExtensionNames` must be a valid pointer to an array of `enabledExtensionCount` null-terminated UTF-8 strings
   - Returns error

Device

Validations for `vkCreateDevice`:

1. `physicalDevice` must be a valid `VkPhysicalDevice` handle
    - Handled by API design (ash)
2. `pCreateInfo` must be a valid pointer to a valid `VkDeviceCreateInfo` structure
    - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
    - Handled by API design (ash)
4. `pDevice` must be a valid pointer to a `VkDevice` handle
    - Handled by API design (ash)

Validations for `VkDeviceCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_DEVICE_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkDeviceDiagnosticsConfigCreateInfoNV`, `VkDeviceGroupDeviceCreateInfo`, `VkDeviceMemoryOverallocationCreateInfoAMD`, `VkPhysicalDevice16BitStorageFeatures`, `VkPhysicalDevice8BitStorageFeatures`, `VkPhysicalDeviceASTCDecodeFeaturesEXT`, `VkPhysicalDeviceBlendOperationAdvancedFeaturesEXT`, `VkPhysicalDeviceBufferDeviceAddressFeatures`, `VkPhysicalDeviceBufferDeviceAddressFeaturesEXT`, `VkPhysicalDeviceCoherentMemoryFeaturesAMD`, `VkPhysicalDeviceComputeShaderDerivativesFeaturesNV`, `VkPhysicalDeviceConditionalRenderingFeaturesEXT`, `VkPhysicalDeviceCooperativeMatrixFeaturesNV`, `VkPhysicalDeviceCornerSampledImageFeaturesNV`, `VkPhysicalDeviceCoverageReductionModeFeaturesNV`, `VkPhysicalDeviceDedicatedAllocationImageAliasingFeaturesNV`, `VkPhysicalDeviceDepthClipEnableFeaturesEXT`, `VkPhysicalDeviceDescriptorIndexingFeatures`, `VkPhysicalDeviceDeviceGeneratedCommandsFeaturesNV`, `VkPhysicalDeviceDiagnosticsConfigFeaturesNV`, `VkPhysicalDeviceExclusiveScissorFeaturesNV`, `VkPhysicalDeviceFeatures2`, `VkPhysicalDeviceFragmentDensityMapFeaturesEXT`, `VkPhysicalDeviceFragmentShaderBarycentricFeaturesNV`, `VkPhysicalDeviceFragmentShaderInterlockFeaturesEXT`, `VkPhysicalDeviceHostQueryResetFeatures`, `VkPhysicalDeviceImagelessFramebufferFeatures`, `VkPhysicalDeviceIndexTypeUint8FeaturesEXT`, `VkPhysicalDeviceInlineUniformBlockFeaturesEXT`, `VkPhysicalDeviceLineRasterizationFeaturesEXT`, `VkPhysicalDeviceMemoryPriorityFeaturesEXT`, `VkPhysicalDeviceMeshShaderFeaturesNV`, `VkPhysicalDeviceMultiviewFeatures`, `VkPhysicalDevicePerformanceQueryFeaturesKHR`, `VkPhysicalDevicePipelineCreationCacheControlFeaturesEXT`, `VkPhysicalDevicePipelineExecutablePropertiesFeaturesKHR`, `VkPhysicalDeviceProtectedMemoryFeatures`, `VkPhysicalDeviceRayTracingFeaturesKHR`, `VkPhysicalDeviceRepresentativeFragmentTestFeaturesNV`, `VkPhysicalDeviceSamplerYcbcrConversionFeatures`, `VkPhysicalDeviceScalarBlockLayoutFeatures`, `VkPhysicalDeviceSeparateDepthStencilLayoutsFeatures`, `VkPhysicalDeviceShaderAtomicInt64Features`, `VkPhysicalDeviceShaderClockFeaturesKHR`, `VkPhysicalDeviceShaderDemoteToHelperInvocationFeaturesEXT`, `VkPhysicalDeviceShaderDrawParametersFeatures`, `VkPhysicalDeviceShaderFloat16Int8Features`, `VkPhysicalDeviceShaderImageFootprintFeaturesNV`, `VkPhysicalDeviceShaderIntegerFunctions2FeaturesINTEL`, `VkPhysicalDeviceShaderSMBuiltinsFeaturesNV`, `VkPhysicalDeviceShaderSubgroupExtendedTypesFeatures`, `VkPhysicalDeviceShadingRateImageFeaturesNV`, `VkPhysicalDeviceSubgroupSizeControlFeaturesEXT`, `VkPhysicalDeviceTexelBufferAlignmentFeaturesEXT`, `VkPhysicalDeviceTextureCompressionASTCHDRFeaturesEXT`, `VkPhysicalDeviceTimelineSemaphoreFeatures`, `VkPhysicalDeviceTransformFeedbackFeaturesEXT`, `VkPhysicalDeviceUniformBufferStandardLayoutFeatures`, `VkPhysicalDeviceVariablePointersFeatures`, `VkPhysicalDeviceVertexAttributeDivisorFeaturesEXT`, `VkPhysicalDeviceVulkan11Features`, `VkPhysicalDeviceVulkan12Features`, `VkPhysicalDeviceVulkanMemoryModelFeatures`, or `VkPhysicalDeviceYcbcrImageArraysFeaturesEXT`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be `0`
   - Handled by API design (ash)
5. `pQueueCreateInfos` must be a valid pointer to an array of `queueCreateInfoCount` valid `VkDeviceQueueCreateInfo` structures
   - Handled by API design (ash)

6. If `enabledLayerCount` is not `0`, `ppEnabledLayerNames` must be a valid pointer to an array of `enabledLayerCount` null-terminated UTF-8 strings
   - Returns error
7. If `enabledExtensionCount` is not `0`, `ppEnabledExtensionNames` must be a valid pointer to an array of `enabledExtensionCount` null-terminated UTF-8 strings
   - Returns error
8. If `pEnabledFeatures` is not `NULL`, `pEnabledFeatures` must be a valid pointer to a valid `VkPhysicalDeviceFeatures` structure
   - Handled by API design (ash)
9. `queueCreateInfoCount` must be greater than `0`
   - Returns error

Queue

Validations for `VkDeviceQueueCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_DEVICE_QUEUE_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL` or a pointer to a valid instance of `VkDeviceQueueGlobalPriorityCreateInfoEXT`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkDeviceQueueCreateFlagBits` values
   - Handled by API design (ash)
5. `pQueuePriorities` must be a valid pointer to an array of `queueCount` `float` values
   - Handled by API design (ash)
6. `queueCount` must be greater than `0`
   - Returns error

Validations for `vkGetDeviceQueue`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pQueue` must be a valid pointer to a `VkQueue` handle
   - Handled by API design

Validations for `vkGetDeviceQueue2`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pQueueInfo` must be a valid pointer to a valid `VkDeviceQueueInfo2` structure
   - Handled by API design
3. `pQueue` must be a valid pointer to a `VkQueue` handle
   - Handled by API design

Validations for `VkDeviceQueueInfo2`:

1. `sType` must be `VK_STRUCTURE_TYPE_DEVICE_QUEUE_INFO_2`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `flags` must be a valid combination of `VkDeviceQueueCreateFlagBits` values
   - Handled by API design (ash)

Validations for `vkQueueSubmit`:

1. `queue` must be a valid `VkQueue` handle
   - Handled by API design
2. If `submitCount` is not `0`, `pSubmits` must be a valid pointer to an array of `submitCount` valid `VkSubmitInfo` structures
   - Handled by API design
3. If `fence` is not `VK_NULL_HANDLE`, `fence` must be a valid `VkFence` handle
   - Handled by API design
4. Both of `fence`, and `queue` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkDevice`
   - Returns error

Validations for `VkSubmitInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_SUBMIT_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkD3D12FenceSubmitInfoKHR`, `VkDeviceGroupSubmitInfo`, `VkPerformanceQuerySubmitInfoKHR`, `VkProtectedSubmitInfo`, `VkTimelineSemaphoreSubmitInfo`, `VkWin32KeyedMutexAcquireReleaseInfoKHR`, or `VkWin32KeyedMutexAcquireReleaseInfoNV`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. If `waitSemaphoreCount` is not `0`, `pWaitSemaphores` must be a valid pointer to an array of `waitSemaphoreCount` valid `VkSemaphore` handles
   - Handled by API design (ash)
5. If `waitSemaphoreCount` is not `0`, `pWaitDstStageMask` must be a valid pointer to an array of `waitSemaphoreCount` valid combinations of `VkPipelineStageFlagBits` values
   - Handled by API design (ash)
6. Each element of `pWaitDstStageMask` must not be `0`
   - Handled by API design
7. If `commandBufferCount` is not `0`, `pCommandBuffers` must be a valid pointer to an array of `commandBufferCount` valid `VkCommandBuffer` handles
   - Handled by API design (ash)
8. If `signalSemaphoreCount` is not `0`, `pSignalSemaphores` must be a valid pointer to an array of `signalSemaphoreCount` valid `VkSemaphore` handles
   - Handled by API design (ash)
9. Each of the elements of `pCommandBuffers`, the elements of `pSignalSemaphores`, and the elements of `pWaitSemaphores` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkDevice`
   - Returns error

Swapchain

Validations for `vkCreateSwapchainKHR`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design (ash)
2. `pCreateInfo` must be a valid pointer to a valid `VkSwapchainCreateInfoKHR` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design (ash)
4. `pSwapchain` must be a valid pointer to a `VkSwapchainKHR` handle
   - Handled by API design (ash)

Validations for `VkSwapchainCreateInfoKHR`:

1. `sType` must be `VK_STRUCTURE_TYPE_SWAPCHAIN_CREATE_INFO_KHR`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkDeviceGroupSwapchainCreateInfoKHR`, `VkImageFormatListCreateInfo`, `VkSurfaceFullScreenExclusiveInfoEXT`, `VkSurfaceFullScreenExclusiveWin32InfoEXT`, `VkSwapchainCounterCreateInfoEXT`, or `VkSwapchainDisplayNativeHdrCreateInfoAMD`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkSwapchainCreateFlagBitsKHR` values
   - Handled by API design (ash)
5. `surface` must be a valid `VkSurfaceKHR` handle
   - Handled by API design (ash)
6. `imageFormat` must be a valid `VkFormat` value
   - Handled by API design (ash)
7. `imageColorSpace` must be a valid `VkColorSpaceKHR` value
   - Handled by API design (ash)
8. `imageUsage` must be a valid combination of `VkImageUsageFlagBits` values
   - Handled by API design (ash)
9. `imageUsage` must not be `0`
   - Returns error

10. `imageSharingMode` must be a valid `VkSharingMode` value
    - Handled by API design (ash)
11. `preTransform` must be a valid `VkSurfaceTransformFlagBitsKHR` value
    - Handled by API design (ash)
12. `compositeAlpha` must be a valid `VkCompositeAlphaFlagBitsKHR` value
    - Handled by API design (ash)
13. `presentMode` must be a valid `VkPresentModeKHR` value
    - Handled by API design (ash)
14. If `oldSwapchain` is not `VK_NULL_HANDLE`, `oldSwapchain` must be a valid `VkSwapchainKHR` handle
    - Handled by API design (ash)
15. If `oldSwapchain` is a valid handle, it must have been created, allocated, or retrieved from `surface`
    - Handled by API design
16. Both of `oldSwapchain`, and `surface` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkInstance`
    - Handled by API design

Validations for `vkGetSwapchainImagesKHR`:

1. `device` must be a valid `VkDevice` handle
    - Handled by API design
2. `swapchain` must be a valid `VkSwapchainKHR` handle
    - Handled by API design
3. `pSwapchainImageCount` must be a valid pointer to a `uint32_t` value
    - Handled by API design (ash)
4. If the value referenced by `pSwapchainImageCount` is not `0`, and `pSwapchainImages` is not `NULL`, `pSwapchainImages` must be a valid pointer to an array of `pSwapchainImageCount` `VkImage` handles
    - Handled by API design (ash)
5. Both of `device`, and `swapchain` must have been created, allocated, or retrieved from the same `VkInstance`
    - Handled by API design

Validations for `vkQueuePresentKHR`:

1. `queue` must be a valid `VkQueue` handle
    - Handled by API design (ash)
2. `pPresentInfo` must be a valid pointer to a valid `VkPresentInfoKHR` structure
    - Handled by API design (ash)

Validations for `VkPresentInfoKHR`:

1. `sType` must be `VK_STRUCTURE_TYPE_PRESENT_INFO_KHR`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkDeviceGroupPresentInfoKHR`, `VkDisplayPresentInfoKHR`, `VkPresentFrameTokenGGP`, `VkPresentRegionsKHR`, or `VkPresentTimesInfoGOOGLE`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. If `waitSemaphoreCount` is not `0`, `pWaitSemaphores` must be a valid pointer to an array of `waitSemaphoreCount` valid `VkSemaphore` handles
   - Handled by API design (ash)
5. `pSwapchains` must be a valid pointer to an array of `swapchainCount` valid `VkSwapchainKHR` handles
   - Handled by API design (ash)
6. `pImageIndices` must be a valid pointer to an array of `swapchainCount` `uint32_t` values
   - Handled by API design (ash)
7. If `pResults` is not `NULL`, `pResults` must be a valid pointer to an array of `swapchainCount` `VkResult` values
   - Handled by API design (ash)
8. `swapchainCount` must be greater than `0`
   - Returns error
9. Both of the elements of `pSwapchains`, and the elements of `pWaitSemaphores` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkInstance`
   - Returns error

Validations for `vkAcquireNextImageKHR`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `swapchain` must be a valid `VkSwapchainKHR` handle
   - Handled by API design
3. If `semaphore` is not `VK_NULL_HANDLE`, `semaphore` must be a valid `VkSemaphore` handle
   - Handled by API design
4. If `fence` is not `VK_NULL_HANDLE`, `fence` must be a valid `VkFence` handle
   - Handled by API design
5. `pImageIndex` must be a valid pointer to a `uint32_t` value
   - Handled by API design (ash)
6. If `semaphore` is a valid handle, it must have been created, allocated, or retrieved from `device`
   - Returns error
7. If `fence` is a valid handle, it must have been created, allocated, or retrieved from `device`
   - Returns error
8. Both of `device`, and `swapchain` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkInstance`
   - Handled by API design

Command Buffer

Validations for `vkCreateCommandPool`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkCommandPoolCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pCommandPool` must be a valid pointer to a `VkCommandPool` handle
   - Handled by API design (ash)

Validations for `VkCommandPoolCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_COMMAND_POOL_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `flags` must be a valid combination of `VkCommandPoolCreateFlagBits` values
   - Handled by API design (ash)

Validations for `vkTrimCommandPool`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `commandPool` must be a valid `VkCommandPool` handle
   - Handled by API design
3. `flags` must be `0`
   - Handled by API design
4. `commandPool` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Validations for `vkResetCommandPool`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `commandPool` must be a valid `VkCommandPool` handle
   - Handled by API design
3. `flags` must be a valid combination of `VkCommandPoolResetFlagBits` values
   - Handled by API design
4. `commandPool` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Validations for `VkCommandBufferAllocateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_COMMAND_BUFFER_ALLOCATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `commandPool` must be a valid `VkCommandPool` handle
   - Handled by API design (ash)
4. `level` must be a valid `VkCommandBufferLevel` value
   - Handled by API design (ash)

Fence

Validations for `vkCreateFence`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design (ash)
2. `pCreateInfo` must be a valid pointer to a valid `VkFenceCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design (ash)
4. `pFence` must be a valid pointer to a `VkFence` handle
   - Handled by API design (ash)

Validations for `VkFenceCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_FENCE_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkExportFenceCreateInfo` or `VkExportFenceWin32HandleInfoKHR`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkFenceCreateFlagBits` values
   - Handled by API design (ash)

Validations for `vkGetFenceStatus`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `fence` must be a valid `VkFence` handle
   - Handled by API design
3. `fence` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Validations for `vkResetFences`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pFences` must be a valid pointer to an array of `fenceCount` valid `VkFence` handles
   - Handled by API design
3. `fenceCount` must be greater than `0`
   - Handled by API design
4. Each element of `pFences` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Validations for `vkWaitForFences`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pFences` must be a valid pointer to an array of `fenceCount` valid `VkFence` handles
   - Handled by API design
3. `fenceCount` must be greater than `0`
   - Handled by API design
4. Each element of `pFences` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Sempahore

Validations for `vkCreateSemaphore`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design (ash)
2. `pCreateInfo` must be a valid pointer to a valid `VkSemaphoreCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design (ash)
4. `pSemaphore` must be a valid pointer to a `VkSemaphore` handle
   - Handled by API design (ash)

Validations for `VkSemaphoreCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_SEMAPHORE_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkExportSemaphoreCreateInfo`, `VkExportSemaphoreWin32HandleInfoKHR`, or `VkSemaphoreTypeCreateInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be `0`
   - Handled by API design (ash)

Validations for `VkSemaphoreTypeCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_SEMAPHORE_TYPE_CREATE_INFO`
   - Handled by API design (ash)
2. `semaphoreType` must be a valid `VkSemaphoreType` value
   - Handled by API design (ash)

Image

Validations for `vkCreateImage`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkImageCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pImage` must be a valid pointer to a `VkImage` handle
   - Handled by API design (ash)

Validations for `VkImageCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_IMAGE_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkDedicatedAllocationImageCreateInfoNV`, `VkExternalFormatANDROID`, `VkExternalMemoryImageCreateInfo`, `VkExternalMemoryImageCreateInfoNV`, `VkImageDrmFormatModifierExplicitCreateInfoEXT`, `VkImageDrmFormatModifierListCreateInfoEXT`, `VkImageFormatListCreateInfo`, `VkImageStencilUsageCreateInfo`, or `VkImageSwapchainCreateInfoKHR`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkImageCreateFlagBits` values
   - Handled by API design
5. `imageType` must be a valid `VkImageType` value
   - Handled by API design (ash)
6. `format` must be a valid `VkFormat` value
   - Handled by API design (ash)
7. `samples` must be a valid `VkSampleCountFlagBits` value
   - Handled by API design (ash)
8. `tiling` must be a valid `VkImageTiling` value
   - Handled by API design (ash)
9. `usage` must be a valid combination of `VkImageUsageFlagBits` values
   - Handled by API design
10. `usage` must not be `0`
    - Returns error
11. `sharingMode` must be a valid `VkSharingMode` value
    - Handled by API design (ash)
12. `initialLayout` must be a valid `VkImageLayout` value
    - Handled by API design (ash)

Validations for `vkBindImageMemory`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `image` must be a valid `VkImage` handle
   - Handled by API design
3. `memory` must be a valid `VkDeviceMemory` handle
   - Handled by API design
4. `image` must have been created, allocated, or retrieved from `device`
   - Handled by API design
5. `memory` must have been created, allocated, or retrieved from `device`
   - Returns error

Validations for `vkCreateImageView`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkImageViewCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pView` must be a valid pointer to a `VkImageView` handle
   - Handled by API design (ash)

Validations for `VkImageViewCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_IMAGE_VIEW_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkImageViewASTCDecodeModeEXT`, `VkImageViewUsageCreateInfo`, or `VkSamplerYcbcrConversionInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkImageViewCreateFlagBits` values
   - Handled by API design
5. `image` must be a valid `VkImage` handle
   - Handled by API design
6. `viewType` must be a valid `VkImageViewType` value
   - Handled by API design
7. `format` must be a valid `VkFormat` value
   - Handled by API design
8. `components` must be a valid `VkComponentMapping` structure
   - Handled by API design
9. `subresourceRange` must be a valid `VkImageSubresourceRange` structure
   - Handled by API design

Buffer

Validations for `vkCreateBuffer`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkBufferCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pBuffer` must be a valid pointer to a `VkBuffer` handle
   - Handled by API design (ash)

Validations for `VkBufferCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_BUFFER_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkBufferDeviceAddressCreateInfoEXT`, `VkBufferOpaqueCaptureAddressCreateInfo`, `VkDedicatedAllocationBufferCreateInfoNV`, or `VkExternalMemoryBufferCreateInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkBufferCreateFlagBits` values
   - Handled by API design
5. `usage` must be a valid combination of `VkBufferUsageFlagBits` values
   - Handled by API design
6. `usage` must not be `0`
   - Return error
7. `sharingMode` must be a valid `VkSharingMode` value
   - Handled by API design

Validations for `vkBindBufferMemory`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `buffer` must be a valid `VkBuffer` handle
   - Handled by API design
3. `memory` must be a valid `VkDeviceMemory` handle
   - Handled by API design
4. `buffer` must have been created, allocated, or retrieved from `device`
   - Handled by API design
5. `memory` must have been created, allocated, or retrieved from `device`
   - Returns error

Validations for `vkCreateBufferView`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkBufferViewCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pView` must be a valid pointer to a `VkBufferView` handle
   - Handled by API design (ash)

Validations for `VkBufferViewCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_BUFFER_VIEW_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `flags` must be `0`
   - Handled by API design
4. `buffer` must be a valid `VkBuffer` handle
   - Handled by API design (ash)
5. `format` must be a valid `VkFormat` value
   - Handled by API design (ash)

Memory

Validations for `vkMapMemory`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `memory` must be a valid `VkDeviceMemory` handle
   - Handled by API design
3. `flags` must be `0`
   - Handled by API design
4. `ppData` must be a valid pointer to a pointer value
   - Handled by API design (ash)
5. `memory` must have been created, allocated, or retrieved from `device`
   - Handled by API design

Validations for `vkFlushMappedMemoryRanges`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pMemoryRanges` must be a valid pointer to an array of `memoryRangeCount` valid `VkMappedMemoryRange` structures
   - Handled by API design
3. `memoryRangeCount` must be greater than `0`
   - Handled by API design

Validations for `vkInvalidateMappedMemoryRanges`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pMemoryRanges` must be a valid pointer to an array of `memoryRangeCount` valid `VkMappedMemoryRange` structures
   - Handled by API design
3. `memoryRangeCount` must be greater than `0`
   - Handled by API design

Validations for `VkMappedMemoryRange`:

1. `sType` must be `VK_STRUCTURE_TYPE_MAPPED_MEMORY_RANGE`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `memory` must be a valid `VkDeviceMemory` handle
   - Handled by API design

Descriptors

Validations for `vkCreateDescriptorSetLayout`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkDescriptorSetLayoutCreateInfo` structure
   - Handled by API design
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pSetLayout` must be a valid pointer to a `VkDescriptorSetLayout` handle
   - Handled by API design (ash)

Validations for `VkDescriptorSetLayoutCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_DESCRIPTOR_SET_LAYOUT_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL` or a pointer to a valid instance of `VkDescriptorSetLayoutBindingFlagsCreateInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkDescriptorSetLayoutCreateFlagBits` values
   - Handled by API design
5. If `bindingCount` is not `0`, `pBindings` must be a valid pointer to an array of `bindingCount` valid `VkDescriptorSetLayoutBinding` structures
   - Handled by API design

Validations for `VkDescriptorSetLayoutBinding`:

1. `descriptorType` must be a valid `VkDescriptorType` value
   - Handled by API design

Validations for `vkCreateDescriptorPool`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkDescriptorPoolCreateInfo` structure
   - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pDescriptorPool` must be a valid pointer to a `VkDescriptorPool` handle
   - Handled by API design (ash)

Validations for `VkDescriptorPoolCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_DESCRIPTOR_POOL_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL` or a pointer to a valid instance of `VkDescriptorPoolInlineUniformBlockCreateInfoEXT`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkDescriptorPoolCreateFlagBits` values
   - Handled by API design (ash)
5. `pPoolSizes` must be a valid pointer to an array of `poolSizeCount` valid `VkDescriptorPoolSize` structures
   - Handled by API design (ash)
6. `poolSizeCount` must be greater than `0`
   - Guaranteed by the type system

Validations for `VkDescriptorPoolInlineUniformBlockCreateInfoEXT`:

1. `sType` must be `VK_STRUCTURE_TYPE_DESCRIPTOR_POOL_INLINE_UNIFORM_BLOCK_CREATE_INFO_EXT`
   - Handled by API design (ash)

Validations for `vkAllocateDescriptorSets`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pAllocateInfo` must be a valid pointer to a valid `VkDescriptorSetAllocateInfo` structure
   - Handled by API design
3. `pDescriptorSets` must be a valid pointer to an array of `pAllocateInfo`::descriptorSetCount `VkDescriptorSet` handles
   - Handled by API design (ash)
4. The value referenced by `pAllocateInfo`::`descriptorSetCount` must be greater than `0`
   - Guaranteed by the type system

Validations for `VkDescriptorSetAllocateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_DESCRIPTOR_SET_ALLOCATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL` or a pointer to a valid instance of `VkDescriptorSetVariableDescriptorCountAllocateInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `descriptorPool` must be a valid `VkDescriptorPool` handle
   - Handled by API design
5. `pSetLayouts` must be a valid pointer to an array of `descriptorSetCount` valid `VkDescriptorSetLayout` handles
   - Handled by API design
6. `descriptorSetCount` must be greater than `0`
   - Returns error
7. Both of `descriptorPool`, and the elements of `pSetLayouts` must have been created, allocated, or retrieved from the same `VkDevice`
   - Returns error

Validations for `vkCreateSampler`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkSamplerCreateInfo` structure
   - Handled by API design
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pSampler` must be a valid pointer to a `VkSampler` handle
   - Handled by API design (ash)

Validations for `VkSamplerCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_SAMPLER_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkSamplerReductionModeCreateInfo` or `VkSamplerYcbcrConversionInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkSamplerCreateFlagBits` values
   - Handled by API design
5. `magFilter` must be a valid `VkFilter` value
   - Handled by API design
6. `minFilter` must be a valid `VkFilter` value
   - Handled by API design
7. `mipmapMode` must be a valid `VkSamplerMipmapMode` value
   - Handled by API design
8. `addressModeU` must be a valid `VkSamplerAddressMode` value
   - Handled by API design
9. `addressModeV` must be a valid `VkSamplerAddressMode` value
   - Handled by API design
10. `addressModeW` must be a valid `VkSamplerAddressMode` value
    - Handled by API design

Validations for `VkDescriptorBufferInfo`:

1. `buffer` must be a valid `VkBuffer` handle
   - Handled by API design

Validations for `VkDescriptorImageInfo`:

1. Both of `imageView`, and `sampler` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkDevice`
   - Returns error

Validations for `VkWriteDescriptorSetInlineUniformBlockEXT`:

1. `sType` must be `VK_STRUCTURE_TYPE_WRITE_DESCRIPTOR_SET_INLINE_UNIFORM_BLOCK_EXT`
   - Handled by API design (ash)
2. `pData` must be a valid pointer to an array of `dataSize` bytes
   - Handled by API design
3. `dataSize` must be greater than `0`
   - Returns error

Validations for `VkWriteDescriptorSet`:

1. `sType` must be `VK_STRUCTURE_TYPE_WRITE_DESCRIPTOR_SET`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkWriteDescriptorSetAccelerationStructureKHR` or `VkWriteDescriptorSetInlineUniformBlockEXT`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `descriptorType` must be a valid `VkDescriptorType` value
   - Handled by API design
5. `descriptorCount` must be greater than `0`
   - Returns error
6. Both of `dstSet`, and the elements of `pTexelBufferView` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkDevice`

Validations for `VkCopyDescriptorSet`:

1. `sType` must be `VK_STRUCTURE_TYPE_COPY_DESCRIPTOR_SET`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `srcSet` must be a valid `VkDescriptorSet` handle
   - Handled by API design
4. `dstSet` must be a valid `VkDescriptorSet` handle
   - Handled by API design
5. Both of `dstSet`, and `srcSet` must have been created, allocated, or retrieved from the same `VkDevice`

Validations for `vkUpdateDescriptorSets`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. If `descriptorWriteCount` is not `0`, `pDescriptorWrites` must be a valid pointer to an array of `descriptorWriteCount` valid `VkWriteDescriptorSet` structures
   - Handled by API design
3. If `descriptorCopyCount` is not `0`, `pDescriptorCopies` must be a valid pointer to an array of `descriptorCopyCount` valid `VkCopyDescriptorSet` structures
   - Handled by API design

Render pass

Validations for `vkCreateRenderPass`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkRenderPassCreateInfo` structure
   - Handled by API design
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pRenderPass` must be a valid pointer to a `VkRenderPass` handle
   - Handled by API design (ash)

Validations for `VkRenderPassCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_RENDER_PASS_CREATE_INFO`
   - Handled by API design (ash)
2. Each `pNext` member of any structure (including this one) in the `pNext` chain must be either `NULL` or a pointer to a valid instance of `VkRenderPassFragmentDensityMapCreateInfoEXT`, `VkRenderPassInputAttachmentAspectCreateInfo`, or `VkRenderPassMultiviewCreateInfo`
   - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
   - Handled by API design
4. `flags` must be a valid combination of `VkRenderPassCreateFlagBits` values
   - Handled by API design
5. If `attachmentCount` is not `0`, `pAttachments` must be a valid pointer to an array of `attachmentCount` valid `VkAttachmentDescription` structures
   - Handled by API design
6. `pSubpasses` must be a valid pointer to an array of `subpassCount` valid `VkSubpassDescription` structures
   - Handled by API design
7. If `dependencyCount` is not `0`, `pDependencies` must be a valid pointer to an array of `dependencyCount` valid `VkSubpassDependency` structures
   - Handled by API design
8. `subpassCount` must be greater than `0`
   - Returns error

Validations for `VkAttachmentDescription`:

1. `flags` must be a valid combination of `VkAttachmentDescriptionFlagBits` values
   - Handled by API design
2. `format` must be a valid `VkFormat` value
   - Handled by API design (ash)
3. `samples` must be a valid `VkSampleCountFlagBits` value
   - Handled by API design (ash)
4. `loadOp` must be a valid `VkAttachmentLoadOp` value
   - Handled by API design (ash)
5. `storeOp` must be a valid `VkAttachmentStoreOp` value
   - Handled by API design (ash)
6. `stencilLoadOp` must be a valid `VkAttachmentLoadOp` value
   - Handled by API design (ash)
7. `stencilStoreOp` must be a valid `VkAttachmentStoreOp` value
   - Handled by API design (ash)
8. `initialLayout` must be a valid `VkImageLayout` value
   - Handled by API design (ash)
9. `finalLayout` must be a valid `VkImageLayout` value
   - Handled by API design

Validations for `VkSubpassDescription`:

1. `flags` must be a valid combination of `VkSubpassDescriptionFlagBits` values
   - Handled by API design
2. `pipelineBindPoint` must be a valid `VkPipelineBindPoint` value
   - Handled by API design (ash)
3. If `inputAttachmentCount` is not `0`, `pInputAttachments` must be a valid pointer to an array of `inputAttachmentCount` valid `VkAttachmentReference` structures
   - Handled by API design
4. If `colorAttachmentCount` is not `0`, `pColorAttachments` must be a valid pointer to an array of `colorAttachmentCount` valid `VkAttachmentReference` structures
   - Handled by API design
5. If `colorAttachmentCount` is not `0`, and `pResolveAttachments` is not `NULL`, `pResolveAttachments` must be a valid pointer to an array of `colorAttachmentCount` valid `VkAttachmentReference` structures
   - Returns error
6. If `pDepthStencilAttachment` is not `NULL`, `pDepthStencilAttachment` must be a valid pointer to a valid `VkAttachmentReference` structure
   - Handled by API design
7. If `preserveAttachmentCount` is not `0`, `pPreserveAttachments` must be a valid pointer to an array of `preserveAttachmentCount` `uint32_t` values
   - Handled by API design

Validations for `VkSubpassDependency`:

1. `srcStageMask` must be a valid combination of `VkPipelineStageFlagBits` values
   - Handled by API design (ash)
2. `srcStageMask` must not be `0`
   - Returns error
3. `dstStageMask` must be a valid combination of `VkPipelineStageFlagBits` values
   - Handled by API design (ash)

4. `dstStageMask` must not be `0`
    - Returns error

5. `srcAccessMask` must be a valid combination of `VkAccessFlagBits` values
    - Handled by API design (ash)
6. `dstAccessMask` must be a valid combination of `VkAccessFlagBits` values
    - Handled by API design (ash)
7. `dependencyFlags` must be a valid combination of `VkDependencyFlagBits` values
    - Handled by API design (ash)

Framebuffer

Validations for `vkCreateFramebuffer`:

1. `device` must be a valid `VkDevice` handle
    - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkFramebufferCreateInfo` structure
    - Handled by API design (ash)
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
    - Handled by API design
4. `pFramebuffer` must be a valid pointer to a `VkFramebuffer` handle
    - Handled by API design (ash)

Validations for `VkFramebufferCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_FRAMEBUFFER_CREATE_INFO`
    - Handled by API design (ash)
2. `pNext` must be `NULL` or a pointer to a valid instance of `VkFramebufferAttachmentsCreateInfo`
    - Handled by API design (ash)
3. The `sType` value of each struct in the `pNext` chain must be unique
    - Handled by API design
4. `flags` must be a valid combination of `VkFramebufferCreateFlagBits` values
    - Handled by API design
5. `renderPass` must be a valid `VkRenderPass` handle
    - Handled by API design
6. Both of `renderPass`, and the elements of `pAttachments` that are valid handles of non-ignored parameters must have been created, allocated, or retrieved from the same `VkDevice`

Pipeline

Validations for `vkCreatePipelineLayout`:

1. `device` must be a valid `VkDevice` handle
   - Handled by API design
2. `pCreateInfo` must be a valid pointer to a valid `VkPipelineLayoutCreateInfo` structure
   - Handled by API design
3. If `pAllocator` is not `NULL`, `pAllocator` must be a valid pointer to a valid `VkAllocationCallbacks` structure
   - Handled by API design
4. `pPipelineLayout` must be a valid pointer to a `VkPipelineLayout` handle
   - Handled by API design (ash)

Validations for `VkPipelineLayoutCreateInfo`:

1. `sType` must be `VK_STRUCTURE_TYPE_PIPELINE_LAYOUT_CREATE_INFO`
   - Handled by API design (ash)
2. `pNext` must be `NULL`
   - Handled by API design (ash)
3. `flags` must be `0`
   - Handled by API design (ash)
4. If `setLayoutCount` is not `0`, `pSetLayouts` must be a valid pointer to an array of `setLayoutCount` valid `VkDescriptorSetLayout` handles
   - Handled by API design
5. If `pushConstantRangeCount` is not `0`, `pPushConstantRanges` must be a valid pointer to an array of `pushConstantRangeCount` valid `VkPushConstantRange` structures
   - Handled by API design

Validations for `VkPushConstantRange`:

1. `stageFlags` must be a valid combination of `VkShaderStageFlagBits` values
   - Handled by API design (ash)
2. `stageFlags` must not be `0`
   - Returns error

Creation validation

Validations of correct usage in create functions as dictated by the Vulkan specification.

Instance

Validations for `vkCreateInstance`:

1. All required extensions for each extension in the `VkInstanceCreateInfo`::`ppEnabledExtensionNames` list must also be present in that list.

Device

Validations for `vkCreateDevice`:

1. All required extensions for each extension in the `VkDeviceCreateInfo`::`ppEnabledExtensionNames` list must also be present in that list.

Validations for `VkDeviceCreateInfo`:

1. The queueFamilyIndex member of each element of pQueueCreateInfos must be unique within pQueueCreateInfos, except that two members can share the same queueFamilyIndex if one is a protected-capable queue and one is not a protected-capable queue
2. If the pNext chain includes a VkPhysicalDeviceFeatures2 structure, then pEnabledFeatures must be NULL
   - Handled by API design
3. ppEnabledExtensionNames must not contain VK_AMD_negative_viewport_height
4. ppEnabledExtensionNames must not contain both VK_KHR_buffer_device_address and VK_EXT_buffer_device_address
5. If the pNext chain includes a VkPhysicalDeviceVulkan11Features structure, then it must not include a VkPhysicalDevice16BitStorageFeatures, VkPhysicalDeviceMultiviewFeatures, VkPhysicalDeviceVariablePointersFeatures, VkPhysicalDeviceProtectedMemoryFeatures, VkPhysicalDeviceSamplerYcbcrConversionFeatures, or VkPhysicalDeviceShaderDrawParametersFeatures structure
   - Handled by API design
6. If the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then it must not include a VkPhysicalDevice8BitStorageFeatures, VkPhysicalDeviceShaderAtomicInt64Features, VkPhysicalDeviceShaderFloat16Int8Features, VkPhysicalDeviceDescriptorIndexingFeatures, VkPhysicalDeviceScalarBlockLayoutFeatures, VkPhysicalDeviceImagelessFramebufferFeatures, VkPhysicalDeviceUniformBufferStandardLayoutFeatures, VkPhysicalDeviceShaderSubgroupExtendedTypesFeatures, VkPhysicalDeviceSeparateDepthStencilLayoutsFeatures, VkPhysicalDeviceHostQueryResetFeatures, VkPhysicalDeviceTimelineSemaphoreFeatures, VkPhysicalDeviceBufferDeviceAddressFeatures, or VkPhysicalDeviceVulkanMemoryModelFeatures structure
   - Handled by API design
7. If ppEnabledExtensions contains "VK_KHR_draw_indirect_count" and the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then VkPhysicalDeviceVulkan12Features::drawIndirectCount must be VK_TRUE
   - Handled by API design
8. If ppEnabledExtensions contains "VK_KHR_sampler_mirror_clamp_to_edge" and the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then VkPhysicalDeviceVulkan12Features::samplerMirrorClampToEdge must be VK_TRUE
   - Handled by API design
9. If ppEnabledExtensions contains "VK_EXT_descriptor_indexing" and the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then VkPhysicalDeviceVulkan12Features::descriptorIndexing must be VK_TRUE
   - Handled by API design
10. If ppEnabledExtensions contains "VK_EXT_sampler_filter_minmax" and the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then VkPhysicalDeviceVulkan12Features::samplerFilterMinmax must be VK_TRUE
    - Handled by API design
11. If ppEnabledExtensions contains "VK_EXT_shader_viewport_index_layer" and the pNext chain includes a VkPhysicalDeviceVulkan12Features structure, then VkPhysicalDeviceVulkan12Features::shaderOutputViewportIndex and VkPhysicalDeviceVulkan12Features::shaderOutputLayer must both be VK_TRUE
    - Handled by API design

Queue

Validations for VkDeviceQueueCreateInfo:

1. `queueFamilyIndex` must be less than `pQueueFamilyPropertyCount` returned by `vkGetPhysicalDeviceQueueFamilyProperties`
2. `queueCount` must be less than or equal to the `queueCount` member of the `VkQueueFamilyProperties` structure, as returned by `vkGetPhysicalDeviceQueueFamilyProperties` in the `pQueueFamilyProperties`[queueFamilyIndex]
3. Each element of `pQueuePriorities` must be between `0.0` and `1.0` inclusive
4. If the protected memory feature is not enabled, the `VK_DEVICE_QUEUE_CREATE_PROTECTED_BIT` bit of `flags` must not be set.
   - Handled by API design

Swapchain

Validations for `VkSwapchainCreateInfoKHR`:

1. `surface` must be a surface that is supported by the device as determined using `vkGetPhysicalDeviceSurfaceSupportKHR`
2. `minImageCount` must be less than or equal to the value returned in the `maxImageCount` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface if the returned `maxImageCount` is not zero
3. If `presentMode` is not `VK_PRESENT_MODE_SHARED_DEMAND_REFRESH_KHR` nor `VK_PRESENT_MODE_SHARED_CONTINUOUS_REFRESH_KHR`, then `minImageCount` must be greater than or equal to the value returned in the `minImageCount` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface
4. `minImageCount` must be `1` if `presentMode` is either `VK_PRESENT_MODE_SHARED_DEMAND_REFRESH_KHR` or `VK_PRESENT_MODE_SHARED_CONTINUOUS_REFRESH_KHR`
5. `imageFormat` and `imageColorSpace` must match the `format` and `colorSpace` members, respectively, of one of the `VkSurfaceFormatKHR` structures returned by `vkGetPhysicalDeviceSurfaceFormatsKHR` for the surface
6. `imageExtent` must be between `minImageExtent` and `maxImageExtent`, inclusive, where `minImageExtent` and `maxImageExtent` are members of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface
7. `imageExtent` members `width` and `height` must both be non-zero
   - Guaranteed by the type system
8. `imageArrayLayers` must be greater than `0` and less than or equal to the `maxImageArrayLayers` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface
   - Lower bound guaranteed by the type system
9. If `presentMode` is `VK_PRESENT_MODE_IMMEDIATE_KHR`, `VK_PRESENT_MODE_MAILBOX_KHR`, `VK_PRESENT_MODE_FIFO_KHR` or `VK_PRESENT_MODE_FIFO_RELAXED_KHR`, `imageUsage` must be a subset of the supported usage flags present in the `supportedUsageFlags` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for `surface`
10. If `presentMode` is `VK_PRESENT_MODE_SHARED_DEMAND_REFRESH_KHR` or `VK_PRESENT_MODE_SHARED_CONTINUOUS_REFRESH_KHR`, `imageUsage` must be a subset of the supported usage flags present in the `sharedPresentSupportedUsageFlags` member of the `VkSharedPresentSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilities2KHR` for `surface`

11. If `imageSharingMode` is `VK_SHARING_MODE_CONCURRENT`, `pQueueFamilyIndices` must be a valid pointer to an array of `queueFamilyIndexCount` `uint32_t` values
    - Guaranteed by the type system
12. If `imageSharingMode` is `VK_SHARING_MODE_CONCURRENT`, `queueFamilyIndexCount` must be greater than `1`
    - Guaranteed by the type system
13. If `imageSharingMode` is `VK_SHARING_MODE_CONCURRENT`, each element of `pQueueFamilyIndices` must be unique and must be less than `pQueueFamilyPropertyCount` returned by either `vkGetPhysicalDeviceQueueFamilyProperties` or `vkGetPhysicalDeviceQueueFamilyProperties2` for the `physicalDevice` that was used to create `device`
14. `preTransform` must be one of the bits present in the `supportedTransforms` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface
15. `compositeAlpha` must be one of the bits present in the `supportedCompositeAlpha` member of the `VkSurfaceCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilitiesKHR` for the surface
16. `presentMode` must be one of the `VkPresentModeKHR` values returned by `vkGetPhysicalDeviceSurfacePresentModesKHR` for the surface
17. If the logical device was created with `VkDeviceGroupDeviceCreateInfo`::`physicalDeviceCount` equal to 1, `flags` must not contain `VK_SWAPCHAIN_CREATE_SPLIT_INSTANCE_BIND_REGIONS_BIT_KHR`
    - Handled by API design
18. If `oldSwapchain` is not `VK_NULL_HANDLE`, `oldSwapchain` must be a non-retired swapchain associated with native window referred to by `surface`
    - Handled by API design
19. The implied image creation parameters of the swapchain must be supported as reported by `vkGetPhysicalDeviceImageFormatProperties`
20. If `flags` contains `VK_SWAPCHAIN_CREATE_MUTABLE_FORMAT_BIT_KHR` then the `pNext` chain must include a `VkImageFormatListCreateInfo` structure with a `viewFormatCount` greater than zero and `pViewFormats` must have an element equal to `imageFormat`
    - Handled by API design
21. If `flags` contains `VK_SWAPCHAIN_CREATE_PROTECTED_BIT_KHR`, then `VkSurfaceProtectedCapabilitiesKHR`::`supportsProtected` must be `VK_TRUE` in the `VkSurfaceProtectedCapabilitiesKHR` structure returned by `vkGetPhysicalDeviceSurfaceCapabilities2KHR` for `surface`
    - Handled by API design
22. If the `pNext` chain includes a `VkSurfaceFullScreenExclusiveInfoEXT` structure with its `fullScreenExclusive` member set to `VK_FULL_SCREEN_EXCLUSIVE_APPLICATION_CONTROLLED_EXT`, and `surface` was created using `vkCreateWin32SurfaceKHR`, a `VkSurfaceFullScreenExclusiveWin32InfoEXT` structure must be included in the `pNext` chain
    - Handled by API design

Command buffer

Validations for `vkCreateCommandPool`:

1. `pCreateInfo→queueFamilyIndex` must be the index of a queue family available in the logical device `device`.
    - Handled by API design

Validations for `VkCommandPoolCreateInfo`:

1. If the protected memory feature is not enabled, the `VK_COMMAND_POOL_CREATE_PROTECTED_BIT` bit of `flags` must not be set.
    - Handled by API design

Validations for `VkCommandBufferAllocateInfo`:

1. `commandBufferCount` must be greater than `0`
    - Guaranteed by the type system

Sempahore

Validations for `VkSemaphoreTypeCreateInfo`:

1. If the `timelineSemaphore` feature is not enabled, `semaphoreType` must not equal `VK_SEMAPHORE_TYPE_TIMELINE`
2. If `semaphoreType` is `VK_SEMAPHORE_TYPE_BINARY`, `initialValue` must be zero.
    - Handled by API design

Image

Validations for `vkCreateImage`:

1. If the `flags` member of `pCreateInfo` includes `VK_IMAGE_CREATE_SPARSE_BINDING_BIT`, creating this `VkImage` must not cause the total required sparse memory for all currently valid sparse resources on the device to exceed `VkPhysicalDeviceLimits`::`sparseAddressSpaceSize`

Validations for `VkImageCreateInfo`:

1. Each of the following values (as described in Image Creation Limits) must not be undefined `imageCreateMaxMipLevels`, `imageCreateMaxArrayLayers`, `imageCreateMaxExtent`, and `imageCreateSampleCounts`.

2. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, `pQueueFamilyIndices` must be a valid pointer to an array of `queueFamilyIndexCount` `uint32_t` values
   - Handled by API design
3. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, `queueFamilyIndexCount` must be greater than `1`
   - Handled by API design
4. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, each element of `pQueueFamilyIndices` must be unique and must be less than `pQueueFamilyPropertyCount` returned by either `vkGetPhysicalDeviceQueueFamilyProperties` or `vkGetPhysicalDeviceQueueFamilyProperties2` for the `physicalDevice` that was used to create `device`
   - Lower bound handled by API design
5. If the `pNext` chain includes a `VkExternalFormatANDROID` structure, and its `externalFormat` member is non-zero the `format` must be `VK_FORMAT_UNDEFINED`.
   - Handled by API design
6. If the `pNext` chain does not include a `VkExternalFormatANDROID` structure, or does and its `externalFormat` member is `0`, the `format` must not be `VK_FORMAT_UNDEFINED`.
   - Handled by API design
7. `extent.width` must be greater than `0`.
   - Guaranteed by the type system
8. `extent.height` must be greater than `0`.
   - Guaranteed by the type system
9. `extent.depth` must be greater than `0`.
   - Guaranteed by the type system
10. `mipLevels` must be greater than `0`
    - Guaranteed by the type system
11. `arrayLayers` must be greater than `0`
    - Guaranteed by the type system
12. If `flags` contains `VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT`, `imageType` must be `VK_IMAGE_TYPE_2D`
    - Guaranteed by the type system
13. If `flags` contains `VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT`, `imageType` must be `VK_IMAGE_TYPE_2D`
    - Guaranteed by the type system
14. If `flags` contains `VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT`, `imageType` must be `VK_IMAGE_TYPE_3D`
    - Guaranteed by the type system
15. `extent.width` must be less than or equal to `imageCreateMaxExtent.width` (as defined in Image Creation Limits).
16. `extent.height` must be less than or equal to `imageCreateMaxExtent.height` (as defined in Image Creation Limits).
17. `extent.depth` must be less than or equal to `imageCreateMaxExtent.depth` (as defined in Image Creation Limits).
18. If `imageType` is `VK_IMAGE_TYPE_2D` and `flags` contains `VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT`, `extent.width` and `extent.height` must be equal and `arrayLayers` must be greater than or equal to 6
    - Guaranteed by the type system
19. If `imageType` is `VK_IMAGE_TYPE_1D`, both `extent.height` and `extent.depth` must be `1`
    - Guaranteed by the type system
20. If `imageType` is `VK_IMAGE_TYPE_2D`, `extent.depth` must be `1`
    - Guaranteed by the type system
21. `mipLevels` must be less than or equal to the number of levels in the complete mipmap chain based on `extent.width`, `extent.height`, and `extent.depth`.
    - Guaranteed by the type system

22. `mipLevels` must be less than or equal to `imageCreateMaxMipLevels` (as defined in Image Creation Limits).
23. `arrayLayers` must be less than or equal to `imageCreateMaxArrayLayers` (as defined in Image Creation Limits).
24. If `imageType` is `VK_IMAGE_TYPE_3D`, `arrayLayers` must be `1`.
    - Guaranteed by the type system
25. If `samples` is not `VK_SAMPLE_COUNT_1_BIT`, then `imageType` must be `VK_IMAGE_TYPE_2D`, `flags` must not contain `VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT`, `mipLevels` must be equal to `1`, and `imageCreateMaybeLinear` (as defined in Image Creation Limits) must be `false`,
    - Guaranteed by the type system
26. If `samples` is not `VK_SAMPLE_COUNT_1_BIT`, `usage` must not contain `VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT`
    - Guaranteed by the type system
27. If `usage` includes `VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT`, then bits other than `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, and `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT` must not be set
28. If `usage` includes `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT`, or `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT`, `extent.width` must be less than or equal to `VkPhysicalDeviceLimits`::`maxFramebufferWidth`
29. If `usage` includes `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT`, or `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT`, `extent.height` must be less than or equal to `VkPhysicalDeviceLimits`::`maxFramebufferHeight`
30. If `usage` includes `VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT`, `extent.width` must be less than or equal to $\lceil \frac{maxFramebufferWidth}{minFragmentDensityTexelSize_{width}} \rceil$
31. If `usage` includes `VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT`, `extent.height` must be less than or equal to $\lceil \frac{maxFramebufferHeight}{minFragmentDensityTexelSize_{height}} \rceil$
32. If `usage` includes `VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT`, `usage` must also contain at least one of `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`, `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, or `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT`.
33. `samples` must be a bit value that is set in `imageCreateSampleCounts` (as defined in Image Creation Limits).
34. If the multisampled storage images feature is not enabled, and `usage` contains `VK_IMAGE_USAGE_STORAGE_BIT`, `samples` must be `VK_SAMPLE_COUNT_1_BIT`
35. If the sparse bindings feature is not enabled, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_BINDING_BIT`
36. If the sparse aliased residency feature is not enabled, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_ALIASED_BIT`
37. If `imageType` is `VK_IMAGE_TYPE_1D`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
38. If the sparse residency for 2D images feature is not enabled, and `imageType` is `VK_IMAGE_TYPE_2D`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
39. If the sparse residency for 3D images feature is not enabled, and `imageType` is `VK_IMAGE_TYPE_3D`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
40. If the sparse residency for images with 2 samples feature is not enabled, `imageType` is `VK_IMAGE_TYPE_2D`, and `samples` is `VK_SAMPLE_COUNT_2_BIT`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`

41. If the sparse residency for images with 4 samples feature is not enabled, `imageType` is `VK_IMAGE_TYPE_2D`, and `samples` is `VK_SAMPLE_COUNT_4_BIT`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
42. If the sparse residency for images with 8 samples feature is not enabled, `imageType` is `VK_IMAGE_TYPE_2D`, and `samples` is `VK_SAMPLE_COUNT_8_BIT`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
43. If the sparse residency for images with 16 samples feature is not enabled, `imageType` is `VK_IMAGE_TYPE_2D`, and `samples` is `VK_SAMPLE_COUNT_16_BIT`, `flags` must not contain `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`
44. If `flags` contains `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT` or `VK_IMAGE_CREATE_SPARSE_ALIASED_BIT`, it must also contain `VK_IMAGE_CREATE_SPARSE_BINDING_BIT`
45. If any of the bits `VK_IMAGE_CREATE_SPARSE_BINDING_BIT`, `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`, or `VK_IMAGE_CREATE_SPARSE_ALIASED_BIT` are set, `VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT` must not also be set
46. If the protected memory feature is not enabled, `flags` must not contain `VK_IMAGE_CREATE_PROTECTED_BIT`.
47. If any of the bits `VK_IMAGE_CREATE_SPARSE_BINDING_BIT`, `VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT`, or `VK_IMAGE_CREATE_SPARSE_ALIASED_BIT` are set, `VK_IMAGE_CREATE_PROTECTED_BIT` must not also be set.
48. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfoNV` structure, it must not contain a `VkExternalMemoryImageCreateInfo` structure.
    - Handled by API design
49. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfo` structure, its `handleTypes` member must only contain bits that are also in `VkExternalImageFormatProperties`::`externalMemoryProperties.compatibleHandleTypes`, as returned by `vkGetPhysicalDeviceImageFormatProperties2` with `format`, `imageType`, `tiling`, `usage`, and `flags` equal to those in this structure, and with a `VkPhysicalDeviceExternalImageFormatInfo` structure included in the `pNext` chain, with a `handleType` equal to any one of the handle types specified in `VkExternalMemoryImageCreateInfo`::`handleTypes`
    - Handled by API design
50. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfoNV` structure, its `handleTypes` member must only contain bits that are also in `VkExternalImageFormatPropertiesNV`::`externalMemoryProperties.compatibleHandleTypes`, as returned by `vkGetPhysicalDeviceExternalImageFormatPropertiesNV` with `format`, `imageType`, `tiling`, `usage`, and `flags` equal to those in this structure, and with `externalHandleType` equal to any one of the handle types specified in `VkExternalMemoryImageCreateInfoNV`::`handleTypes`
    - Handled by API design
51. If the logical device was created with `VkDeviceGroupDeviceCreateInfo`::`physicalDeviceCount` equal to 1, `flags` must not contain `VK_IMAGE_CREATE_SPLIT_INSTANCE_BIND_REGIONS_BIT`
52. If `flags` contains `VK_IMAGE_CREATE_SPLIT_INSTANCE_BIND_REGIONS_BIT`, then `mipLevels` must be one, `arrayLayers` must be one, `imageType` must be `VK_IMAGE_TYPE_2D`. and `imageCreateMaybeLinear` (as defined in Image Creation Limits) must be `false`.
53. If `flags` contains `VK_IMAGE_CREATE_BLOCK_TEXEL_VIEW_COMPATIBLE_BIT`, then `format` must be a block-compressed image format, an ETC compressed image format, or an ASTC compressed image format.
54. If `flags` contains `VK_IMAGE_CREATE_BLOCK_TEXEL_VIEW_COMPATIBLE_BIT`, then `flags` must also contain `VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT`.
55. `initialLayout` must be `VK_IMAGE_LAYOUT_UNDEFINED` or `VK_IMAGE_LAYOUT_PREINITIALIZED`.
    - Guaranteed by the type system
56. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfo` or `VkExternalMemoryImageC
    - Handled by API design

57. If the image `format` is one of those listed in Formats requiring sampler Y?CBCRconversion forVK_IMAGE_ASPECT_COLOR_BITimage views, then `mipLevels` must be 1
58. If the image `format` is one of those listed in Formats requiring sampler Y?CBCRconversion forVK_IMAGE_ASPECT_COLOR_BITimage views, `samples` must be `VK_SAMPLE_COUNT_1_BIT`
59. If the image `format` is one of those listed in Formats requiring sampler Y?CBCRconversion forVK_IMAGE_ASPECT_COLOR_BITimage views, `imageType` must be `VK_IMAGE_TYPE_2D`
60. If the image `format` is one of those listed in Formats requiring sampler Y?CBCRconversion forVK_IMAGE_ASPECT_COLOR_BITimage views, and the `ycbcrImageArrays` feature is not enabled, `arrayLayers` must be 1
61. If `format` is a *multi-planar* format, and if `imageCreateFormatFeatures` (as defined in Image Creation Limits) does not contain `VK_FORMAT_FEATURE_DISJOINT_BIT`, then `flags` must not contain `VK_IMAGE_CREATE_DISJOINT_BIT`
62. If `format` is not a *multi-planar* format, and `flags` does not include `VK_IMAGE_CREATE_ALIAS_BIT`, `flags` must not contain `VK_IMAGE_CREATE_DISJOINT_BIT`
63. If `tiling` is `VK_IMAGE_TILING_DRM_FORMAT_MODIFIER_EXT`, then the `pNext` chain must include exactly one of `VkImageDrmFormatModifierListCreateInfoEXT` or `VkImageDrmFormatModifierExplicitCreateInfoEXT` structures
64. If the `pNext` chain includes a `VkImageDrmFormatModifierListCreateInfoEXT` or `VkImageDrmFormatModifierExplicitCreateInfoEXT` structure, then `tiling` must be `VK_IMAGE_TILING_DRM_FORMAT_MODIFIER_EXT`
    - Handled by API design
65. If `tiling` is `VK_IMAGE_TILING_DRM_FORMAT_MODIFIER_EXT` and `flags` contains `VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT`, then the `pNext` chain must include a `VkImageFormatListCreateInfo` structure with non-zero `viewFormatCount`.
66. If `flags` contains `VK_IMAGE_CREATE_SAMPLE_LOCATIONS_COMPATIBLE_DEPTH_BIT_EXT` `format` must be a depth or depth/stencil format
67. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfo` structure whose `handleTypes` member includes `VK_EXTERNAL_MEMORY_HANDLE_TYPE_ANDROID_HARDWARE_BUFFER_BIT_ANDROID`, `imageType` must be `VK_IMAGE_TYPE_2D`.
    - Handled by API design
68. If the `pNext` chain includes a `VkExternalMemoryImageCreateInfo` structure whose `handleTypes` member includes `VK_EXTERNAL_MEMORY_HANDLE_TYPE_ANDROID_HARDWARE_BUFFER_BIT_ANDROID`, `mipLevels` must either be `1` or equal to the number of levels in the complete mipmap chain based on `extent.width`, `extent.height`, and `extent.depth`.
    - Handled by API design
69. If the `pNext` chain includes a `VkExternalFormatANDROID` structure whose `externalFormat` member is not `0`, `flags` must not include `VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT`.
    - Handled by API design
70. If the `pNext` chain includes a `VkExternalFormatANDROID` structure whose `externalFormat` member is not `0`, `usage` must not include any usages except `VK_IMAGE_USAGE_SAMPLED_BIT`.
    - Handled by API design
71. If the `pNext` chain includes a `VkExternalFormatANDROID` structure whose `externalFormat` member is not `0`, `tiling` must be `VK_IMAGE_TILING_OPTIMAL`.
    - Handled by API design
72. If `format` is a depth-stencil format, `usage` includes `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, and the `pNext` chain includes a `VkImageStencilUsageCreateInfo` structure, then its `VkImageStencilUsageCreateInfo`::`stencilUsage` member must also include `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`
73. If `format` is a depth-stencil format, `usage` does not include `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`, and the `pNext` chain includes a

VkImageStencilUsageCreateInfo structure, then its VkImageStencilUsageCreateInfo::stencilUsage member must also not include VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT

74. If format is a depth-stencil format, usage includes VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT, and the pNext chain includes a VkImageStencilUsageCreateInfo structure, then its VkImageStencilUsageCreateInfo::stencilUsage member must also include VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT
75. If format is a depth-stencil format, usage does not include VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT, and the pNext chain includes a VkImageStencilUsageCreateInfo structure, then its VkImageStencilUsageCreateInfo::stencilUsage member must also not include VK_IMAGE_USAGE_TRANSIENT_ATTACHMENT_BIT
76. If Format is a depth-stencil format and the pNext chain includes a VkImageStencilUsageCreateInfo structure with its stencilUsage member including VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT, extent.width must be less than or equal to VkPhysicalDeviceLimits::maxFramebufferWidth
77. If format is a depth-stencil format and the pNext chain includes a VkImageStencilUsageCreateInfo structure with its stencilUsage member including VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT, extent.height must be less than or equal to VkPhysicalDeviceLimits::maxFramebufferHeight
78. If the multisampled storage images feature is not enabled, format is a depth-stencil format and the pNext chain includes a VkImageStencilUsageCreateInfo structure with its stencilUsage including VK_IMAGE_USAGE_STORAGE_BIT, samples must be VK_SAMPLE_COUNT_1_BIT
79. If flags contains VK_IMAGE_CREATE_CORNER_SAMPLED_BIT_NV, imageType must be VK_IMAGE_TYPE_2D or VK_IMAGE_TYPE_3D
80. If flags contains VK_IMAGE_CREATE_CORNER_SAMPLED_BIT_NV, it must not contain VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT and the format must not be a depth/stencil format
81. If flags contains VK_IMAGE_CREATE_CORNER_SAMPLED_BIT_NV and imageType is VK_IMAGE_TYPE_2D, extent.width and extent.height must be greater than 1
82. If flags contains VK_IMAGE_CREATE_CORNER_SAMPLED_BIT_NV and imageType is VK_IMAGE_TYPE_3D, extent.width, extent.height, and extent.depth must be greater than 1
83. If usage includes VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, imageType must be VK_IMAGE_TYPE_2D.
84. If usage includes VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, samples must be VK_SAMPLE_COUNT_1_BIT.
85. If usage includes VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, tiling must be VK_IMAGE_TILING_OPTIMAL.
86. If flags contains VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT, tiling must be VK_IMAGE_TILING_OPTIMAL
87. If flags contains VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT, imageType must be VK_IMAGE_TYPE_2D
88. If flags contains VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT, flags must not contain VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT
89. If flags contains VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT, mipLevels must be 1

Validations for VkImageViewCreateInfo:

1. If image was not created with VK_IMAGE_CREATE_CUBE_COMPATIBLE_BIT then viewType must not be VK_IMAGE_VIEW_TYPE_CUBE or VK_IMAGE_VIEW_TYPE_CUBE_ARRAY
2. If the image cubemap arrays feature is not enabled, viewType must not be VK_IMAGE_VIEW_TYPE_CUBE_ARRAY
3. If image was created with VK_IMAGE_TYPE_3D but without

VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT set then viewType must not be VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY

4. image must have been created with a usage value containing at least one of VK_IMAGE_USAGE_SAMPLED_BIT, VK_IMAGE_USAGE_STORAGE_BIT, VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT, VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT, VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT, VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, or VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT
5. The format features of the resultant image view must contain at least one bit.
6. If usage contains VK_IMAGE_USAGE_SAMPLED_BIT, then the format features of the resultant image view must contain VK_FORMAT_FEATURE_SAMPLED_IMAGE_BIT.
7. If usage contains VK_IMAGE_USAGE_STORAGE_BIT, then the image view's format features must contain VK_FORMAT_FEATURE_STORAGE_IMAGE_BIT.
8. If usage contains VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT, then the image view's format features must contain VK_FORMAT_FEATURE_COLOR_ATTACHMENT_BIT.
9. If usage contains VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT, then the image view's format features must contain VK_FORMAT_FEATURE_DEPTH_STENCIL_ATTACHMENT_BIT.
10. If usage contains VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT, then the image view's format features must contain at least one of VK_FORMAT_FEATURE_COLOR_ATTACHMENT_BIT or VK_FORMAT_FEATURE_DEPTH_STENCIL_ATTACHMENT_BIT.
11. subresourceRange.baseMipLevel must be less than the mipLevels specified in VkImageCreateInfo when image was created
12. If subresourceRange.levelCount is not VK_REMAINING_MIP_LEVELS, subresourceRange.baseMipLevel+subresourceRange.levelCount must be less than or equal to the mipLevels specified in VkImageCreateInfo when image was created
13. If image was created with usage containing VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT, subresourceRange.levelCount must be 1
14. If image is not a 3D image created with VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT set, or viewType is not VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY, subresourceRange.baseArrayLayer must be less than the arrayLayers specified in VkImageCreateInfo when image was created
15. If subresourceRange.layerCount is not VK_REMAINING_ARRAY_LAYERS, image is not a 3D image created with VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT set, or viewType is not VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY, subresourceRange.layerCount must be non-zero and subresourceRange.baseArrayLayer+subresourceRange.layerCount must be less than or equal to the arrayLayers specified in VkImageCreateInfo when image was created
16. If image is a 3D image created with VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT set, and viewType is VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY, subresourceRange.baseArrayLayer must be less than the depth computed from baseMipLevel and extent.depth specified in VkImageCreateInfo when image was created, according to the formula defined in Image Miplevel Sizing.
17. If subresourceRange.layerCount is not VK_REMAINING_ARRAY_LAYERS, image is a 3D image created with VK_IMAGE_CREATE_2D_ARRAY_COMPATIBLE_BIT set, and viewType is VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY, subresourceRange.layerCount must be non-zero and subresourceRange.baseArrayLayer+subresourceRange.layerCount must be less than or equal to the depth computed from baseMipLevel and extent.depth specified in VkImageCreateInfo when image was created, according to the formula defined in Image Miplevel Sizing.
18. If image was created with the VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT flag, but without the VK_IMAGE_CREATE_BLOCK_TEXEL_VIEW_COMPATIBLE_BIT flag, and if the format of the image is not a multi-planar format, format must be compatible with the format used to create image, as defined in Format Compatibility Classes

19. If image was created with the VK_IMAGE_CREATE_BLOCK_TEXEL_VIEW_COMPATIBLE_BIT flag, format must be compatible with, or must be an uncompressed format that is size-compatible with, the format used to create image.
20. If image was created with the VK_IMAGE_CREATE_BLOCK_TEXEL_VIEW_COMPATIBLE_BIT flag, the levelCount and layerCount members of subresourceRange must both be 1.
21. If a VkImageFormatListCreateInfo structure was included in the pNext chain of the VkImageCreateInfo structure used when creating image and the viewFormatCount field of VkImageFormatListCreateInfo is not zero then format must be one of the formats in VkImageFormatListCreateInfo::pViewFormats.
22. If image was created with the VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT flag, if the format of the image is a multi-planar format, and if subresourceRange.aspectMask is one of VK_IMAGE_ASPECT_PLANE_0_BIT, VK_IMAGE_ASPECT_PLANE_1_BIT, or VK_IMAGE_ASPECT_PLANE_2_BIT, then format must be compatible with the VkFormat for the plane of the image format indicated by subresourceRange.aspectMask, as defined in Compatible formats of planes of multi-planar formats
23. If image was not created with the VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT flag, or if the format of the image is a multi-planar format and if subresourceRange.aspectMask is VK_IMAGE_ASPECT_COLOR_BIT, format must be identical to the format used to create image
24. If the pNext chain includes a VkSamplerYcbcrConversionInfo structure with a conversion value other than VK_NULL_HANDLE, all members of components must have the value VK_COMPONENT_SWIZZLE_IDENTITY.
25. If image is non-sparse then it must be bound completely and contiguously to a single VkDeviceMemory object
26. subresourceRange and viewType must be compatible with the image, as described in the compatibility table
27. If image has an external format, format must be VK_FORMAT_UNDEFINED.
28. If image has an external format, the pNext chain must include a VkSamplerYcbcrConversionInfo structure with a conversion object created with the same external format as image.
29. If image has an external format, all members of components must be VK_COMPONENT_SWIZZLE_IDENTITY.
30. If image was created with usage containing VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, viewType must be VK_IMAGE_VIEW_TYPE_2D or VK_IMAGE_VIEW_TYPE_2D_ARRAY
31. If image was created with usage containing VK_IMAGE_USAGE_SHADING_RATE_IMAGE_BIT_NV, format must be VK_FORMAT_R8_UINT
32. If dynamic fragment density map feature is not enabled, flags must not contain VK_IMAGE_VIEW_CREATE_FRAGMENT_DENSITY_MAP_DYNAMIC_BIT_EXT
33. If dynamic fragment density map feature is not enabled and image was created with usage containing VK_IMAGE_USAGE_FRAGMENT_DENSITY_MAP_BIT_EXT, flags must not contain any of VK_IMAGE_CREATE_PROTECTED_BIT, VK_IMAGE_CREATE_SPARSE_BINDING_BIT, VK_IMAGE_CREATE_SPARSE_RESIDENCY_BIT, or VK_IMAGE_CREATE_SPARSE_ALIASED_BIT
34. If the pNext chain includes a VkImageViewUsageCreateInfo structure, and image was not created with a VkImageStencilUsageCreateInfo structure included in the pNext chain of VkImageCreateInfo, its usage member must not include any bits that were not set in the usage member of the VkImageCreateInfo structure used to create image

35. If the `pNext` chain includes a `VkImageViewUsageCreateInfo` structure, `image` was created with a `VkImageStencilUsageCreateInfo` structure included in the `pNext` chain of `VkImageCreateInfo`, and `subResourceRange.aspectMask` includes `VK_IMAGE_ASPECT_STENCIL_BIT`, the `usage` member of the `VkImageViewUsageCreateInfo` instance must not include any bits that were not set in the `usage` member of the `VkImageStencilUsageCreateInfo` structure used to create `image`
    - Handled by API design
36. If the `pNext` chain includes a `VkImageViewUsageCreateInfo` structure, `image` was created with a `VkImageStencilUsageCreateInfo` structure included in the `pNext` chain of `VkImageCreateInfo`, and `subResourceRange.aspectMask` includes bits other than `VK_IMAGE_ASPECT_STENCIL_BIT`, the `usage` member of the `VkImageViewUsageCreateInfo` structure must not include any bits that were not set in the `usage` member of the `VkImageCreateInfo` structure used to create `image`
    - Handled by API design
37. If `viewType` is `VK_IMAGE_VIEW_TYPE_CUBE` and `subresourceRange.layerCount` is not `VK_REMAINING_ARRAY_LAYERS`, `subresourceRange.layerCount` must be `6`
    - Handled by API design
38. If `viewType` is `VK_IMAGE_VIEW_TYPE_CUBE_ARRAY` and `subresourceRange.layerCount` is not `VK_REMAINING_ARRAY_LAYERS`, `subresourceRange.layerCount` must be a multiple of `6`
39. If `viewType` is `VK_IMAGE_VIEW_TYPE_CUBE` and `subresourceRange.layerCount` is `VK_REMAINING_ARRAY_LAYERS`, the remaining number of layers must be `6`
40. If `viewType` is `VK_IMAGE_VIEW_TYPE_CUBE_ARRAY` and `subresourceRange.layerCount` is `VK_REMAINING_ARRAY_LAYERS`, the remaining number of layers must be a multiple of `6`

Validations for `VkImageSubresourceRange`:

1. If `levelCount` is not `VK_REMAINING_MIP_LEVELS`, it must be greater than `0`
    - Guaranteed by the type system
2. If `layerCount` is not `VK_REMAINING_ARRAY_LAYERS`, it must be greater than `0`
    - Guaranteed by the type system
3. If `aspectMask` includes `VK_IMAGE_ASPECT_COLOR_BIT`, then it must not include any of `VK_IMAGE_ASPECT_PLANE_0_BIT`, `VK_IMAGE_ASPECT_PLANE_1_BIT`, or `VK_IMAGE_ASPECT_PLANE_2_BIT`
4. `aspectMask` must not include `VK_IMAGE_ASPECT_MEMORY_PLANE_i_BIT_EXT` for any index `i`

Buffer

Validations for `vkCreateBuffer`:

1. If the `flags` member of `pCreateInfo` includes `VK_BUFFER_CREATE_SPARSE_BINDING_BIT`, creating this `VkBuffer` must not cause the total required sparse memory for all currently valid sparse resources on the device to exceed `VkPhysicalDeviceLimits`::`sparseAddressSpaceSize`

Validations for `VkBufferCreateInfo`:

1. `size` must be greater than `0`
    - Guaranteed by the type system
2. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, `pQueueFamilyIndices` must be a valid pointer to an array of `queueFamilyIndexCount` `uint32_t` values
    - Handled by API design
3. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, `queueFamilyIndexCount` must be greater than `1`
    - Handled by API design
4. If `sharingMode` is `VK_SHARING_MODE_CONCURRENT`, each element of `pQueueFamilyIndices` must be unique and must be less than `pQueueFamilyPropertyCount` returned by either `vkGetPhysicalDeviceQueueFamilyProperties` or `vkGetPhysicalDeviceQueueFamilyProperties2` for the `physicalDevice` that was used to create `device`
    - Handled by API design
5. If the sparse bindings feature is not enabled, `flags` must not contain `VK_BUFFER_CREATE_SPARSE_BINDING_BIT`
6. If the sparse buffer residency feature is not enabled, `flags` must not contain `VK_BUFFER_CREATE_SPARSE_RESIDENCY_BIT`
7. If the sparse aliased residency feature is not enabled, `flags` must not contain `VK_BUFFER_CREATE_SPARSE_ALIASED_BIT`
8. If `flags` contains `VK_BUFFER_CREATE_SPARSE_RESIDENCY_BIT` or `VK_BUFFER_CREATE_SPARSE_ALIASED_BIT`, it must also contain `VK_BUFFER_CREATE_SPARSE_BINDING_BIT`
9. If the `pNext` chain includes a `VkExternalMemoryBufferCreateInfo` structure, its `handleTypes` member must only contain bits that are also in `VkExternalBufferProperties`::`externalMemoryProperties.compatibleHandleTypes`, as returned by `vkGetPhysicalDeviceExternalBufferProperties` with `pExternalBufferInfo`→`handleType` equal to any one of the handle types specified in `VkExternalMemoryBufferCreateInfo`::`handleTypes`
10. If the protected memory feature is not enabled, `flags` must not contain `VK_BUFFER_CREATE_PROTECTED_BIT`
11. If any of the bits `VK_BUFFER_CREATE_SPARSE_BINDING_BIT`, `VK_BUFFER_CREATE_SPARSE_RESIDENCY_BIT`, or `VK_BUFFER_CREATE_SPARSE_ALIASED_BIT` are set, `VK_BUFFER_CREATE_PROTECTED_BIT` must not also be set
12. If the `pNext` chain includes a `VkDedicatedAllocationBufferCreateInfoNV` structure, and the `dedicatedAllocation` member of the chained structure is `VK_TRUE`, then `flags` must not include `VK_BUFFER_CREATE_SPARSE_BINDING_BIT`, `VK_BUFFER_CREATE_SPARSE_RESIDENCY_BIT`, or `VK_BUFFER_CREATE_SPARSE_ALIASED_BIT`
13. If `VkBufferDeviceAddressCreateInfoEXT`::`deviceAddress` is not zero, `flags` must include `VK_BUFFER_CREATE_DEVICE_ADDRESS_CAPTURE_REPLAY_BIT`
14. If `VkBufferOpaqueCaptureAddressCreateInfo`::`opaqueCaptureAddress` is not zero, `flags` must include `VK_BUFFER_CREATE_DEVICE_ADDRESS_CAPTURE_REPLAY_BIT`
15. If `flags` includes `VK_BUFFER_CREATE_DEVICE_ADDRESS_CAPTURE_REPLAY_BIT`, the `bufferDeviceAddressCaptureReplay` or `VkPhysicalDeviceBufferDeviceAddressFeaturesEXT` :: `bufferDeviceAddressCaptureReplay` feature must be enabled

Validations for `VkBufferViewCreateInfo`:

1. `offset` must be less than the size of `buffer`
2. If `range` is not equal to `VK_WHOLE_SIZE`, `range` must be greater than `0`
    - Guaranteed by the type system
3. If `range` is not equal to `VK_WHOLE_SIZE`, `range` must be an integer multiple of the texel block size of `format`

4. If `range` is not equal to `VK_WHOLE_SIZE`, `range` divided by the texel block size of `format`, multiplied by the number of texels per texel block for that format (as defined in the Compatible Formats table), must be less than or equal to `VkPhysicalDeviceLimits`::`maxTexelBufferElements`
5. If `range` is not equal to `VK_WHOLE_SIZE`, the sum of `offset` and `range` must be less than or equal to the size of `buffer`
6. `buffer` must have been created with a `usage` value containing at least one of `VK_BUFFER_USAGE_UNIFORM_TEXEL_BUFFER_BIT` or `VK_BUFFER_USAGE_STORAGE_TEXEL_BUFFER_BIT`
7. If `buffer` was created with `usage` containing `VK_BUFFER_USAGE_UNIFORM_TEXEL_BUFFER_BIT`, `format` must be supported for uniform texel buffers, as specified by the `VK_FORMAT_FEATURE_UNIFORM_TEXEL_BUFFER_BIT` flag in `VkFormatProperties`::`bufferFeatures` returned by `vkGetPhysicalDeviceFormatProperties`
8. If `buffer` was created with `usage` containing `VK_BUFFER_USAGE_STORAGE_TEXEL_BUFFER_BIT`, `format` must be supported for storage texel buffers, as specified by the `VK_FORMAT_FEATURE_STORAGE_TEXEL_BUFFER_BIT` flag in `VkFormatProperties`::`bufferFeatures` returned by `vkGetPhysicalDeviceFormatProperties`
9. If `buffer` is non-sparse then it must be bound completely and contiguously to a single `VkDeviceMemory` object
10. If the `texelBufferAlignment` feature is not enabled, `offset` must be a multiple of `VkPhysicalDeviceLimits`::`minTexelBufferOffsetAlignment`
11. If the `texelBufferAlignment` feature is enabled and if `buffer` was created with `usage` containing `VK_BUFFER_USAGE_STORAGE_TEXEL_BUFFER_BIT`, `offset` must be a multiple of the lesser of `VkPhysicalDeviceTexelBufferAlignmentPropertiesEXT`::`storageTexelBufferOffsetAlignmentBytes` or, if `VkPhysicalDeviceTexelBufferAlignmentPropertiesEXT`::`storageTexelBufferOffsetSingleTexelAlig` is `VK_TRUE`, the size of a texel of the requested `format`. If the size of a texel is a multiple of three bytes, then the size of a single component of `format` is used instead
12. If the `texelBufferAlignment` feature is enabled and if `buffer` was created with `usage` containing `VK_BUFFER_USAGE_UNIFORM_TEXEL_BUFFER_BIT`, `offset` must be a multiple of the lesser of `VkPhysicalDeviceTexelBufferAlignmentPropertiesEXT`::`uniformTexelBufferOffsetAlignmentBytes` or, if `VkPhysicalDeviceTexelBufferAlignmentPropertiesEXT`::`uniformTexelBufferOffsetSingleTexelAlig` is `VK_TRUE`, the size of a texel of the requested `format`. If the size of a texel is a multiple of three bytes, then the size of a single component of `format` is used instead

Descriptor

Validations for `VkDescriptorSetLayoutCreateInfo`:

1. The `VkDescriptorSetLayoutBinding`::`binding` members of the elements of the `pBindings` array must each have different values.
   - Handled by API design
2. If `flags` contains `VK_DESCRIPTOR_SET_LAYOUT_CREATE_PUSH_DESCRIPTOR_BIT_KHR`, then all elements of `pBindings` must not have a `descriptorType` of `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC` or `VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC`
3. If `flags` contains `VK_DESCRIPTOR_SET_LAYOUT_CREATE_PUSH_DESCRIPTOR_BIT_KHR`, then all elements of `pBindings` must not have a `descriptorType` of

VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT

4. If flags contains VK_DESCRIPTOR_SET_LAYOUT_CREATE_PUSH_DESCRIPTOR_BIT_KHR, then the total number of elements of all bindings must be less than or equal to VkPhysicalDevicePushDescriptorPropertiesKHR::maxPushDescriptors
5. If any binding has the VK_DESCRIPTOR_BINDING_UPDATE_AFTER_BIND_BIT bit set, flags must include VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT
6. If any binding has the VK_DESCRIPTOR_BINDING_UPDATE_AFTER_BIND_BIT bit set, then all bindings must not have descriptorType of VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC or VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC

Validations for VkDescriptorSetLayoutBinding:

1. If descriptorType is VK_DESCRIPTOR_TYPE_SAMPLER or VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, and descriptorCount is not 0 and pImmutableSamplers is not NULL, pImmutableSamplers must be a valid pointer to an array of descriptorCount valid VkSampler handles
   - Handled by API design
2. If descriptorType is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT then descriptorCount must be a multiple of 4
   - Handled by API design
3. If descriptorType is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT then descriptorCount must be less than or equal to VkPhysicalDeviceInlineUniformBlockPropertiesEXT::maxInlineUniformBlockSize
4. If descriptorCount is not 0, stageFlags must be a valid combination of VkShaderStageFlagBits values
5. If descriptorType is VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT and descriptorCount is not 0, then stageFlags must be 0 or VK_SHADER_STAGE_FRAGMENT_BIT
   - Handled by API design

Validations for VkDescriptorPoolCreateInfo:

1. maxSets must be greater than 0
   - Guaranteed by the type system

Validations for VkSamplerCreateInfo:

1. The absolute value of mipLodBias must be less than or equal to VkPhysicalDeviceLimits::maxSamplerLodBias
2. maxLod must be greater than or equal to minLod
3. If the anisotropic sampling feature is not enabled, anisotropyEnable must be VK_FALSE
   - Handled by API design
4. If anisotropyEnable is VK_TRUE, maxAnisotropy must be between 1.0 and VkPhysicalDeviceLimits::maxSamplerAnisotropy, inclusive
5. If sampler YCBCRconversion is enabled and the sampler YCBCRconversion's features do not support VK_FORMAT_FEATURE_SAMPLED_IMAGE_YCBCR_CONVERSION_SEPARATE_RECONSTRUCTION_FILTER_BIT, minFilter and magFilter must be equal to the sampler YCC conversion's chromaFilter

6. If `unnormalizedCoordinates` is `VK_TRUE`, `minFilter` and `magFilter` must be equal
   - Handled by API design
7. If `unnormalizedCoordinates` is `VK_TRUE`, `mipmapMode` must be `VK_SAMPLER_MIPMAP_MODE_NEAREST`
   - Handled by API design
8. If `unnormalizedCoordinates` is `VK_TRUE`, `minLod` and `maxLod` must be zero
   - Handled by API design
9. If `unnormalizedCoordinates` is `VK_TRUE`, `addressModeU` and `addressModeV` must each be either `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_EDGE` or `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_BORDER`
   - Handled by API design
10. If `unnormalizedCoordinates` is `VK_TRUE`, `anisotropyEnable` must be `VK_FALSE`
    - Handled by API design
11. If `unnormalizedCoordinates` is `VK_TRUE`, `compareEnable` must be `VK_FALSE`
    - Handled by API design
12. If any of `addressModeU`, `addressModeV` or `addressModeW` are `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_BORDER`, `borderColor` must be a valid `VkBorderColor` value
13. If sampler Y?CBCRconversion is enabled, `addressModeU`, `addressModeV`, and `addressModeW` must be `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_EDGE`, `anisotropyEnable` must be `VK_FALSE`, and `unnormalizedCoordinates` must be `VK_FALSE`
14. The sampler reduction mode must be set to `VK_SAMPLER_REDUCTION_MODE_WEIGHTED_AVERAGE` if sampler Y?CBCRconversion is enabled
15. If `samplerMirrorClampToEdge` is not enabled, and if the `VK_KHR_sampler_mirror_clamp_to_e
16. If `compareEnable` is `VK_TRUE`, `compareOp` must be a valid `VkCompareOp` value
17. If either `magFilter` or `minFilter` is `VK_FILTER_CUBIC_EXT`, `anisotropyEnable` must be `VK_FALSE`
18. If `compareEnable` is `VK_TRUE`, the `reductionMode` member of `VkSamplerReductionModeCreateInfo` must be `VK_SAMPLER_REDUCTION_MODE_WEIGHTED_AVERAGE`
19. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `minFilter` and `magFilter` must be equal.
    - Handled by API design
20. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `mipmapMode` must be `VK_SAMPLER_MIPMAP_MODE_NEAREST`.
    - Handled by API design
21. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `minLod` and `maxLod` must be zero.
    - Handled by API design
22. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `addressModeU` and `addressModeV` must each be either `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_EDGE` or `VK_SAMPLER_ADDRESS_MODE_CLAMP_TO_BORDER`.
    - Handled by API design
23. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `anisotropyEnable` must be `VK_FALSE`.
    - Handled by API design
24. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `compareEnable` must be `VK_FALSE`.
    - Handled by API design
25. If `flags` includes `VK_SAMPLER_CREATE_SUBSAMPLED_BIT_EXT`, then `unnormalizedCoordinates` must be `VK_FALSE`.
    - Handled by API design

Render pass

Validations for VkRenderPassCreateInfo:

1. If the attachment member of any element of pInputAttachments, pColorAttachments, pResolveAttachments or pDepthStencilAttachment, or any element of pPreserveAttachments in any element of pSubpasses is not VK_ATTACHMENT_UNUSED, it must be less than attachmentCount
2. For any member of pAttachments with a loadOp equal to VK_ATTACHMENT_LOAD_OP_CLEAR, the first use of that attachment must not specify a layout equal to VK_IMAGE_LAYOUT_SHADER_READ_ONLY_OPTIMAL or VK_IMAGE_LAYOUT_DEPTH_STENCIL_READ_ONLY_OPTIMAL.
3. For any member of pAttachments with a stencilLoadOp equal to VK_ATTACHMENT_LOAD_OP_CLEAR, the first use of that attachment must not specify a layout equal to VK_IMAGE_LAYOUT_SHADER_READ_ONLY_OPTIMAL or VK_IMAGE_LAYOUT_DEPTH_STENCIL_READ_ONLY_OPTIMAL.
4. For any member of pAttachments with a loadOp equal to VK_ATTACHMENT_LOAD_OP_CLEAR, the first use of that attachment must not specify a layout equal to VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_STENCIL_ATTACHMENT_OPTIMAL.
5. For any member of pAttachments with a stencilLoadOp equal to VK_ATTACHMENT_LOAD_OP_CLEAR, the first use of that attachment must not specify a layout equal to VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_STENCIL_READ_ONLY_OPTIMAL.
6. If the pNext chain includes a VkRenderPassInputAttachmentAspectCreateInfo structure, the subpass member of each element of its pAspectReferences member must be less than subpassCount
7. If the pNext chain includes a VkRenderPassInputAttachmentAspectCreateInfo structure, the inputAttachmentIndex member of each element of its pAspectReferences member must be less than the value of inputAttachmentCount in the member of pSubpasses identified by its subpass member
8. If the pNext chain includes a VkRenderPassInputAttachmentAspectCreateInfo structure, for any element of the pInputAttachments member of any element of pSubpasses where the attachment member is not VK_ATTACHMENT_UNUSED, the aspectMask member of the corresponding element of VkRenderPassInputAttachmentAspectCreateInfo::pAspectReferences must only include aspects that are present in images of the format specified by the element of pAttachments at attachment
9. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, and its subpassCount member is not zero, that member must be equal to the value of subpassCount
10. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, if its dependencyCount member is not zero, it must be equal to dependencyCount
11. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, for each non-zero element of pViewOffsets, the srcSubpass and dstSubpass members of pDependencies at the same index must not be equal
12. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, for any element of pDependencies with a dependencyFlags member that does not include VK_DEPENDENCY_VIEW_LOCAL_BIT, the corresponding element of the pViewOffsets member of that VkRenderPassMultiviewCreateInfo instance must be 0
13. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, elements of its pViewMasks member must either all be 0, or all not be 0
14. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, and each element of its pViewMasks member is 0, the dependencyFlags member of each element of pDependencies must not include VK_DEPENDENCY_VIEW_LOCAL_BIT
15. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, and each element of its pViewMasks member is 0, correlatedViewMaskCount must be 0
16. If the pNext chain includes a VkRenderPassMultiviewCreateInfo structure, each element of its pViewMask member must not have a bit set at an index greater than or equal to

VkPhysicalDeviceLimits::maxFramebufferLayers
17. For any element of pDependencies, if the srcSubpass is not VK_SUBPASS_EXTERNAL, all stage flags included in the srcStageMask member of that dependency must be a pipeline stage supported by the pipeline identified by the pipelineBindPoint member of the source subpass
18. For any element of pDependencies, if the dstSubpass is not VK_SUBPASS_EXTERNAL, all stage flags included in the dstStageMask member of that dependency must be a pipeline stage supported by the pipeline identified by the pipelineBindPoint member of the destination subpass
19. The srcSubpass member of each element of pDependencies must be less than subpassCount
20. The dstSubpass member of each element of pDependencies must be less than subpassCount

Validations for VkAttachmentDescription:

1. finalLayout must not be VK_IMAGE_LAYOUT_UNDEFINED or VK_IMAGE_LAYOUT_PREINITIALIZED
   - Guaranteed by the type system
2. If format is a color format, initialLayout must not be VK_IMAGE_LAYOUT_DEPTH_STENCIL_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_STENCIL_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_STENCIL_READ_ONLY_OPTIMAL, or VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_STENCIL_ATTACHMENT_OPTIMAL
3. If format is a depth/stencil format, initialLayout must not be VK_IMAGE_LAYOUT_COLOR_ATTACHMENT_OPTIMAL
4. If format is a color format, finalLayout must not be VK_IMAGE_LAYOUT_DEPTH_STENCIL_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_STENCIL_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_STENCIL_READ_ONLY_OPTIMAL, or VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_STENCIL_ATTACHMENT_OPTIMAL
5. If format is a depth/stencil format, finalLayout must not be VK_IMAGE_LAYOUT_COLOR_ATTACHMENT_OPTIMAL
6. If the separateDepthStencilLayouts feature is not enabled, initialLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
7. If the separateDepthStencilLayouts feature is not enabled, finalLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
8. If format is a color format, initialLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
9. If format is a color format, finalLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
10. If format is a depth/stencil format which includes both depth and stencil aspects, initialLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL,

VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
11. If format is a depth/stencil format which includes both depth and stencil aspects, finalLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL, VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL, VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL, or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
12. If format is a depth/stencil format which includes only the depth aspect, initialLayout must not be VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
13. If format is a depth/stencil format which includes only the depth aspect, finalLayout must not be VK_IMAGE_LAYOUT_STENCIL_ATTACHMENT_OPTIMAL or VK_IMAGE_LAYOUT_STENCIL_READ_ONLY_OPTIMAL
14. If format is a depth/stencil format which includes only the stencil aspect, initialLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL or VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL
15. If format is a depth/stencil format which includes only the stencil aspect, finalLayout must not be VK_IMAGE_LAYOUT_DEPTH_ATTACHMENT_OPTIMAL or VK_IMAGE_LAYOUT_DEPTH_READ_ONLY_OPTIMAL

Validations for VkSubpassDescription:

1. pipelineBindPoint must be VK_PIPELINE_BIND_POINT_GRAPHICS
2. colorAttachmentCount must be less than or equal to VkPhysicalDeviceLimits::maxColorAttachments
   - Handled by API design
3. If the first use of an attachment in this render pass is as an input attachment, and the attachment is not also used as a color or depth/stencil attachment in the same subpass, then loadOp must not be VK_ATTACHMENT_LOAD_OP_CLEAR
4. If pResolveAttachments is not NULL, for each resolve attachment that is not VK_ATTACHMENT_UNUSED, the corresponding color attachment must not be VK_ATTACHMENT_UNUSED
5. If pResolveAttachments is not NULL, for each resolve attachment that is not VK_ATTACHMENT_UNUSED, the corresponding color attachment must not have a sample count of VK_SAMPLE_COUNT_1_BIT
6. If pResolveAttachments is not NULL, each resolve attachment that is not VK_ATTACHMENT_UNUSED must have a sample count of VK_SAMPLE_COUNT_1_BIT
7. If pResolveAttachments is not NULL, each resolve attachment that is not VK_ATTACHMENT_UNUSED must have the same VkFormat as its corresponding color attachment
8. All attachments in pColorAttachments that are not VK_ATTACHMENT_UNUSED must have the same sample count
9. All attachments in pInputAttachments that are not VK_ATTACHMENT_UNUSED must have formats whose features contain at least one of VK_FORMAT_FEATURE_COLOR_ATTACHMENT_BIT or VK_FORMAT_FEATURE_DEPTH_STENCIL_ATTACHMENT_BIT.
10. All attachments in pColorAttachments that are not VK_ATTACHMENT_UNUSED must have formats whose features contain VK_FORMAT_FEATURE_COLOR_ATTACHMENT_BIT
11. All attachments in pResolveAttachments that are not VK_ATTACHMENT_UNUSED must have formats whose features contain VK_FORMAT_FEATURE_COLOR_ATTACHMENT_BIT
12. If pDepthStencilAttachment is not NULL and the attachment is not VK_ATTACHMENT_UNUSED then it must have a format whose features contain VK_FORMAT_FEATURE_DEPTH_STENCIL_ATTACHMENT_BIT
13. If the VK_AMD_mixed_attachment_samples extension is enabled, and all attachments in pColorAttachments that are not VK_ATTACHMENT_UNUSED must have a sample count that is smaller than or equal to the sample count of pDepthStencilAttachment if it is not

VK_ATTACHMENT_UNUSED
14. If neither the VK_AMD_mixed_attachment_samples nor the VK_NV_framebuffer_mixed_samples extensions are enabled, and if pDepthStencilAttachment is not VK_ATTACHMENT_UNUSED and any attachments in pColorAttachments are not VK_ATTACHMENT_UNUSED, they must have the same sample count
15. The attachment member of each element of pPreserveAttachments must not be VK_ATTACHMENT_UNUSED
16. Each element of pPreserveAttachments must not also be an element of any other member of the subpass description
17. If any attachment is used by more than one VkAttachmentReference member, then each use must use the same layout
18. If flags includes VK_SUBPASS_DESCRIPTION_PER_VIEW_POSITION_X_ONLY_BIT_NVX, it must also include VK_SUBPASS_DESCRIPTION_PER_VIEW_ATTRIBUTES_BIT_NVX.
19. If the render pass is created with VK_RENDER_PASS_CREATE_TRANSFORM_BIT_QCOM each of the elements of pInputAttachments must be VK_ATTACHMENT_UNUSED.

Validations for VkSubpassDependency:

1. If the geometry shaders feature is not enabled, srcStageMask must not contain VK_PIPELINE_STAGE_GEOMETRY_SHADER_BIT
2. If the geometry shaders feature is not enabled, dstStageMask must not contain VK_PIPELINE_STAGE_GEOMETRY_SHADER_BIT
3. If the tessellation shaders feature is not enabled, srcStageMask must not contain VK_PIPELINE_STAGE_TESSELLATION_CONTROL_SHADER_BIT or VK_PIPELINE_STAGE_TESSELLATION_EVALUATION_SHADER_BIT
4. If the tessellation shaders feature is not enabled, dstStageMask must not contain VK_PIPELINE_STAGE_TESSELLATION_CONTROL_SHADER_BIT or VK_PIPELINE_STAGE_TESSELLATION_EVALUATION_SHADER_BIT
5. srcSubpass must be less than or equal to dstSubpass, unless one of them is VK_SUBPASS_EXTERNAL, to avoid cyclic dependencies and ensure a valid execution order
6. srcSubpass and dstSubpass must not both be equal to VK_SUBPASS_EXTERNAL
7. If srcSubpass is equal to dstSubpass and not all of the stages in srcStageMask and dstStageMask are framebuffer-space stages, the logically latest pipeline stage in srcStageMask must be logically earlier than or equal to the logically earliest pipeline stage in dstStageMask
8. Any access flag included in srcAccessMask must be supported by one of the pipeline stages in srcStageMask, as specified in the table of supported access types
9. Any access flag included in dstAccessMask must be supported by one of the pipeline stages in dstStageMask, as specified in the table of supported access types
10. If srcSubpass equals dstSubpass, and srcStageMask and dstStageMask both include a framebuffer-space stage, then dependencyFlags must include VK_DEPENDENCY_BY_REGION_BIT
11. If dependencyFlags includes VK_DEPENDENCY_VIEW_LOCAL_BIT, srcSubpass must not be equal to VK_SUBPASS_EXTERNAL
12. If dependencyFlags includes VK_DEPENDENCY_VIEW_LOCAL_BIT, dstSubpass must not be equal to VK_SUBPASS_EXTERNAL
13. If srcSubpass equals dstSubpass and that subpass has more than one bit set in the view mask, then dependencyFlags must include VK_DEPENDENCY_VIEW_LOCAL_BIT
14. If the mesh shaders feature is not enabled, srcStageMask must not contain VK_PIPELINE_STAGE_MESH_SHADER_BIT_NV
15. If the task shaders feature is not enabled, srcStageMask must not contain VK_PIPELINE_STAGE_TASK_SHADER_BIT_NV
16. If the mesh shaders feature is not enabled, dstStageMask must not contain VK_PIPELINE_STAGE_MESH_SHADER_BIT_NV
17. If the task shaders feature is not enabled, dstStageMask must not contain VK_PIPELINE_STAGE_TASK_SHADER_BIT_NV

Framebuffer

Validations for `vkCreateFramebuffer`:

1. If `pCreateInfo→flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, and `attachmentCount` is not `0`, each element of `pCreateInfo→pAttachments` must have been created on `device`

Validations for `VkFramebufferCreateInfo`:

1. `attachmentCount` must be equal to the attachment count specified in `renderPass`
2. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, and `attachmentCount` is not `0`, `pAttachments` must be a valid pointer to an array of `attachmentCount` valid `VkImageView` handles
3. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` that is used as a color attachment or resolve attachment by `renderPass` must have been created with a `usage` value including `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`
4. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` that is used as a depth/stencil attachment by `renderPass` must have been created with a `usage` value including `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`
5. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` that is used as a depth/stencil resolve attachment by `renderPass` must have been created with a `usage` value including `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`
6. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` that is used as an input attachment by `renderPass` must have been created with a `usage` value including `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT`
7. Each element of `pAttachments` that is used as a fragment density map attachment by `renderPass` must not have been created with a `flags` value including `VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT`.
8. If `renderPass` has a fragment density map attachment and non-subsample image feature is not enabled, each element of `pAttachments` must have been created with a `flags` value including `VK_IMAGE_CREATE_SUBSAMPLED_BIT_EXT` unless that element is the fragment density map attachment.
9. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` must have been created with a `VkFormat` value that matches the `VkFormat` specified by the corresponding `VkAttachmentDescription` in `renderPass`
10. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` must have been created with a `samples` value that matches the `samples` value specified by the corresponding `VkAttachmentDescription` in `renderPass`
11. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, each element of `pAttachments` must have dimensions at least as large as the corresponding framebuffer dimension except for any element that is referenced by `fragmentDensityMapAttachment`
12. If `renderPass` was specified with non-zero view masks, each element of `pAttachments` that is not referenced by `fragmentDensityMapAttachment` must have a `layerCount` greater than the index of the most significant bit set in any of those view masks
13. If `renderPass` was specified with non-zero view masks, each element of `pAttachments` that is referenced by `fragmentDensityMapAttachment` must have a `layerCount` equal to `1` or greater than the index of the most significant bit set in any of those view masks
14. If `renderPass` was not specified with non-zero view masks, each element of `pAttachments` that is referenced by `fragmentDensityMapAttachment` must have a `layerCount` equal to `1`
15. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, an element of `pAttachments` that is referenced by `fragmentDensityMapAttachment` must have a width at least as large as $\lceil \frac{width}{maxFragmentDensityTexelSize_{width}} \rceil$
16. If `flags` does not include `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, an element of

pAttachments that is referenced by fragmentDensityMapAttachment must have a height at least as large as $\lceil \frac{height}{maxFragmentDensityTexelSize_{height}} \rceil$

17. If flags does not include VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, each element of pAttachments must only specify a single mip level
18. If flags does not include VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, each element of pAttachments must have been created with the identity swizzle
19. width must be greater than 0.
    - Guaranteed by the type system
20. width must be less than or equal to VkPhysicalDeviceLimits::maxFramebufferWidth
21. height must be greater than 0.
    - Guaranteed by the type system
22. height must be less than or equal to VkPhysicalDeviceLimits::maxFramebufferHeight
23. layers must be greater than 0.
    - Guaranteed by the type system
24. layers must be less than or equal to VkPhysicalDeviceLimits::maxFramebufferLayers
25. If renderPass was specified with non-zero view masks, layers must be 1
26. If flags does not include VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, each element of pAttachments that is a 2D or 2D array image view taken from a 3D image must not be a depth/stencil format
27. If flags does not include VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, and attachmentCount is not 0, pAttachments must be a valid pointer to an array of attachmentCount valid VkImageView handles
28. If the imageless framebuffer feature is not enabled, flags must not include VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT
29. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the pNext chain must include a VkFramebufferAttachmentsCreateInfo structure
30. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the attachmentImageInfoCount member of a VkFramebufferAttachmentsCreateInfo structure included in the pNext chain must be equal to either zero or attachmentCount
31. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the width member of any element of the pAttachmentImageInfos member of a VkFramebufferAttachmentsCreateInfo structure included in the pNext chain must be greater than or equal to width, except for any element that is referenced by VkRenderPassFragmentDensityMapCreateInfoEXT::fragmentDensityMapAttachment in renderPass
32. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the height member of any element of the pAttachmentImageInfos member of a VkFramebufferAttachmentsCreateInfo structure included in the pNext chain must be greater than or equal to height, except for any element that is referenced by VkRenderPassFragmentDensityMapCreateInfoEXT::fragmentDensityMapAttachment in renderPass
33. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the width member of any element of the pAttachmentImageInfos member of a VkFramebufferAttachmentsCreateInfo structure included in the pNext chain that is referenced by VkRenderPassFragmentDensityMapCreateInfoEXT::fragmentDensityMapAttachment in renderPass must be greater than or equal to $\lceil \frac{width}{maxFragmentDensityTexelSize_{width}} \rceil$
34. If flags includes VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT, the height member of any element of the pAttachmentImageInfos member of a VkFramebufferAttachmentsCreateInfo structure included in the pNext chain that is referenced by VkRenderPassFragmentDensityMapCreateInfoEXT::fragmentDensityMapAttachment in

`renderPass` must be greater than or equal to $\left\lceil \frac{height}{maxFragmentDensityTexelSize_{height}} \right\rceil$

35. If multiview is enabled for `renderPass`, and `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `layerCount` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain must be greater than the maximum bit index set in the view mask in the subpasses in which it is used in `renderPass`
36. If multiview is not enabled for `renderPass`, and `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `layerCount` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain must be greater than or equal to `layers`
37. If `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `usage` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain that refers to an attachment used as a color attachment or resolve attachment by `renderPass` must include `VK_IMAGE_USAGE_COLOR_ATTACHMENT_BIT`
38. If `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `usage` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain that refers to an attachment used as a depth/stencil attachment by `renderPass` must include `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`
39. If `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `usage` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain that refers to an attachment used as a depth/stencil resolve attachment by `renderPass` must include `VK_IMAGE_USAGE_DEPTH_STENCIL_ATTACHMENT_BIT`
40. If `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, the `usage` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain that refers to an attachment used as an input attachment by `renderPass` must include `VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT`
41. If `flags` includes `VK_FRAMEBUFFER_CREATE_IMAGELESS_BIT`, at least one element of the `pViewFormats` member of any element of the `pAttachmentImageInfos` member of a `VkFramebufferAttachmentsCreateInfo` structure included in the `pNext` chain must be equal to the corresponding value of `VkAttachmentDescription`::`format` used to create `renderPass`

Pipeline

Validations for `VkPipelineLayoutCreateInfo`:

1. `setLayoutCount` must be less than or equal to `VkPhysicalDeviceLimits`::`maxBoundDescriptorSets`
2. The total number of descriptors in descriptor set layouts created without the `VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT` bit set with a `descriptorType` of `VK_DESCRIPTOR_TYPE_SAMPLER` and `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER` accessible to any given shader stage across all elements of `pSetLayouts` must be less than or equal to `VkPhysicalDeviceLimits`::`maxPerStageDescriptorSamplers`
3. The total number of descriptors in descriptor set layouts created without the `VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT` bit set with a `descriptorType` of `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER` and `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC` accessible to any given shader stage across all elements of `pSetLayouts` must be less than or equal to `VkPhysicalDeviceLimits`::`maxPerStageDescriptorUniformBuffers`

4. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_BUFFER and VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxPerStageDescriptorStorageBuffers
5. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE, and VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxPerStageDescriptorSampledImages
6. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_IMAGE, and VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxPerStageDescriptorStorageImages
7. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxPerStageDescriptorInputAttachments
8. The total number of bindings in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceInlineUniformBlockPropertiesEXT::maxPerStageDescriptorInlineUniformBlocks
9. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_SAMPLER and VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindSamplers
10. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER and VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindUniformB
11. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_BUFFER and VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindStorageB
12. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE, and VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindSampledI
13. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_IMAGE, and VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindStorageI
14. The total number of descriptors with a descriptorType of VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to

VkPhysicalDeviceDescriptorIndexingProperties::maxPerStageDescriptorUpdateAfterBindInputAtt

15. The total number of bindings with a descriptorType of VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT accessible to any given shader stage across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceInlineUniformBlockPropertiesEXT::maxPerStageDescriptorUpdateAfterBindInlin
16. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_SAMPLER and VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetSamplers
17. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetUniformBuffers
18. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetUniformBuffersDynamic
19. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetStorageBuffers
20. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetStorageBuffersDynamic
21. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE, and VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetSampledImages
22. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_STORAGE_IMAGE, and VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetStorageImages
23. The total number of descriptors in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceLimits::maxDescriptorSetInputAttachments
24. The total number of bindings in descriptor set layouts created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT bit set with a descriptorType of VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceInlineUniformBlockPropertiesEXT::maxDescriptorSetInlineUniformBlocks
25. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_SAMPLER and VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER accessible across all shader stages and

across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindSamplers
26. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindUniformBuffe
27. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindUniformBuffe
28. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_STORAGE_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindStorageBuffe
29. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindStorageBuffe
30. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE, and VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindSampledImages
31. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_STORAGE_IMAGE, and VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindStorageImages
32. The total number of descriptors of the type VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceDescriptorIndexingProperties::maxDescriptorSetUpdateAfterBindInputAttachme
33. The total number of bindings with a descriptorType of VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceInlineUniformBlockPropertiesEXT::maxDescriptorSetUpdateAfterBindInlineUnif
34. Any two elements of pPushConstantRanges must not include the same stage in stageFlags
35. pSetLayouts must not contain more than one descriptor set layout that was created with VK_DESCRIPTOR_SET_LAYOUT_CREATE_PUSH_DESCRIPTOR_BIT_KHR set
36. The total number of bindings with a descriptorType of VK_DESCRIPTOR_TYPE_ACCELERATION_STRUCTURE_KHR accessible across all shader stages and across all elements of pSetLayouts must be less than or equal to VkPhysicalDeviceRayTracingPropertiesKHR::maxDescriptorSetAccelerationStructures

Validations for VkPushConstantRange:

1. offset must be less than VkPhysicalDeviceLimits::maxPushConstantsSize
2. offset must be a multiple of 4
   - Handled by API design
3. size must be greater than 0
   - Guaranteed by the type system
4. size must be a multiple of 4
   - Handled by API design
5. size must be less than or equal to VkPhysicalDeviceLimits::maxPushConstantsSize minus offset

Usage validations

Validations of correct unsage in other functions as dictated by the Vulkan specification.

Queue

Validations for `vkGetDeviceQueue`:

1. `queueFamilyIndex` must be one of the queue family indices specified when `device` was created, via the `VkDeviceQueueCreateInfo` structure
   - Handled by API design
2. `queueIndex` must be less than the number of queues created for the specified queue family index when `device` was created, via the `queueCount` member of the `VkDeviceQueueCreateInfo` structure
   - Handled by API design
3. `VkDeviceQueueCreateInfo`::`flags` must have been set to zero when `device` was created
   - Handled by API design

Validations for `vkQueueSubmit`:

1. If `fence` is not `VK_NULL_HANDLE`, `fence` must be unsignaled
2. If `fence` is not `VK_NULL_HANDLE`, `fence` must not be associated with any other queue command that has not yet completed execution on that queue
3. Any calls to `vkCmdSetEvent`, `vkCmdResetEvent` or `vkCmdWaitEvents` that have been recorded into any of the command buffer elements of the `pCommandBuffers` member of any element of `pSubmits`, must not reference any `VkEvent` that is referenced by any of those commands in a command buffer that has been submitted to another queue and is still in the *pending state*
4. Any stage flag included in any element of the `pWaitDstStageMask` member of any element of `pSubmits` must be a pipeline stage supported by one of the capabilities of `queue`, as specified in the table of supported pipeline stages
5. Each element of the `pSignalSemaphores` member of any element of `pSubmits` must be unsignaled when the semaphore signal operation it defines is executed on the device
6. When a semaphore wait operation referring to a binary semaphore defined by any element of the `pWaitSemaphores` member of any element of `pSubmits` executes on `queue`, there must be no other queues waiting on the same semaphore
7. All elements of the `pWaitSemaphores` member of all elements of `pSubmits` created with a `VkSemaphoreType` of `VK_SEMAPHORE_TYPE_BINARY` must reference a semaphore signal operation that has been submitted for execution and any semaphore signal operations on which it depends (if any) must have also been submitted for execution
8. Each element of the `pCommandBuffers` member of each element of `pSubmits` must be in the pending or executable state
9. If any element of the `pCommandBuffers` member of any element of `pSubmits` was not recorded with the `VK_COMMAND_BUFFER_USAGE_SIMULTANEOUS_USE_BIT`, it must not be in the pending state
10. Any secondary command buffers recorded into any element of the `pCommandBuffers` member of any element of `pSubmits` must be in the pending or executable state
11. If any secondary command buffers recorded into any element of the `pCommandBuffers` member of any element of `pSubmits` was not recorded with the `VK_COMMAND_BUFFER_USAGE_SIMULTANEOUS_USE_BIT`, it must not be in the pending state
12. Each element of the `pCommandBuffers` member of each element of `pSubmits` must have been allocated from a `VkCommandPool` that was created for the same queue family `queue` belongs to
    - Returns error
13. If any element of `pSubmits`→`pCommandBuffers` includes a Queue Family Transfer Acquire Operation, there must exist a previously submitted Queue Family Transfer Release Operation on a

queue in the queue family identified by the acquire operation, with parameters matching the acquire operation as defined in the definition of such acquire operations, and which happens-before the acquire operation
14. If a command recorded into any element of pCommandBuffers was a vkCmdBeginQuery whose queryPool was created with a queryType of VK_QUERY_TYPE_PERFORMANCE_QUERY_KHR, the profiling lock must have been held continuously on the VkDevice that queue was retrieved from, throughout recording of those command buffers
15. Any resource created with VK_SHARING_MODE_EXCLUSIVE that is read by an operation specified by pSubmits must not be owned by any queue family other than the one which queue belongs to, at the time it is executed

Validations for VkSubmitInfo:

1. Each element of pCommandBuffers must not have been allocated with VK_COMMAND_BUFFER_LEVEL_SECONDARY
2. If the geometry shaders feature is not enabled, each element of pWaitDstStageMask must not contain VK_PIPELINE_STAGE_GEOMETRY_SHADER_BIT
3. If the tessellation shaders feature is not enabled, each element of pWaitDstStageMask must not contain VK_PIPELINE_STAGE_TESSELLATION_CONTROL_SHADER_BIT or VK_PIPELINE_STAGE_TESSELLATION_EVALUATION_SHADER_BIT
4. Each element of pWaitDstStageMask must not include VK_PIPELINE_STAGE_HOST_BIT.
5. If any element of pWaitSemaphores or pSignalSemaphores was created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE, then the pNext chain must include a VkTimelineSemaphoreSubmitInfo structure
6. If the pNext chain of this structure includes a VkTimelineSemaphoreSubmitInfo structure and any element of pWaitSemaphores was created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE, then its waitSemaphoreValueCount member must equal waitSemaphoreCount
7. If the pNext chain of this structure includes a VkTimelineSemaphoreSubmitInfo structure and any element of pSignalSemaphores was created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE, then its signalSemaphoreValueCount member must equal signalSemaphoreCount
8. For each element of pSignalSemaphores created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE the corresponding element of VkTimelineSemaphoreSubmitInfo::pSignalSemaphoreValues must have a value greater than the current value of the semaphore when the semaphore signal operation is executed
9. For each element of pWaitSemaphores created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE the corresponding element of VkTimelineSemaphoreSubmitInfo::pWaitSemaphoreValues must have a value which does not differ from the current value of the semaphore or the value of any outstanding semaphore wait or signal operation on that semaphore by more than maxTimelineSemaphoreValueDifference.
10. For each element of pSignalSemaphores created with a VkSemaphoreType of VK_SEMAPHORE_TYPE_TIMELINE the corresponding element of VkTimelineSemaphoreSubmitInfo::pSignalSemaphoreValues must have a value which does not differ from the current value of the semaphore or the value of any outstanding semaphore wait or signal operation on that semaphore by more than maxTimelineSemaphoreValueDifference.
11. If the mesh shaders feature is not enabled, each element of pWaitDstStageMask must not contain VK_PIPELINE_STAGE_MESH_SHADER_BIT_NV
12. If the task shaders feature is not enabled, each element of pWaitDstStageMask must not contain VK_PIPELINE_STAGE_TASK_SHADER_BIT_NV

Swapchain

Validations for vkAcquireNextImageKHR:

1. `swapchain` must not be in the retired state
2. If `semaphore` is not `VK_NULL_HANDLE` it must be unsignaled
3. If `semaphore` is not `VK_NULL_HANDLE` it must not have any uncompleted signal or wait operations pending
4. If `fence` is not `VK_NULL_HANDLE` it must be unsignaled and must not be associated with any other queue command that has not yet completed execution on that queue
5. `semaphore` and `fence` must not both be equal to `VK_NULL_HANDLE`
    - Handled by API design
6. If the number of currently acquired images is greater than the difference between the number of images in `swapchain` and the value of `VkSurfaceCapabilitiesKHR::minImageCount` as returned by a call to `vkGetPhysicalDeviceSurfaceCapabilities2KHR` with the `surface` used to create `swapchain`, `timeout` must not be `UINT64_MAX`
7. `semaphore` must have a `VkSemaphoreType` of `VK_SEMAPHORE_TYPE_BINARY`
    - Guaranteed by the type system

Validations for `vkQueuePresentKHR`:

1. Each element of `pSwapchains` member of `pPresentInfo` must be a swapchain that is created for a surface for which presentation is supported from `queue` as determined using a call to `vkGetPhysicalDeviceSurfaceSupportKHR`
2. If more than one member of `pSwapchains` was created from a display surface, all display surfaces referenced that refer to the same display must use the same display mode
3. When a semaphore wait operation referring to a binary semaphore defined by the elements of the `pWaitSemaphores` member of `pPresentInfo` executes on `queue`, there must be no other queues waiting on the same semaphore.
4. All elements of the `pWaitSemaphores` member of `pPresentInfo` must be semaphores that are signaled, or have semaphore signal operations previously submitted for execution.
5. All elements of the `pWaitSemaphores` member of `pPresentInfo` must be created with a `VkSemaphoreType` of `VK_SEMAPHORE_TYPE_BINARY`.
    - Handled by API design
6. All elements of the `pWaitSemaphores` member of `pPresentInfo` must reference a semaphore signal operation that has been submitted for execution and any semaphore signal operations on which it depends (if any) must have also been submitted for execution.

Validations for `VkPresentInfoKHR`:

1. Each element of `pImageIndices` must be the index of a presentable image acquired from the swapchain specified by the corresponding element of the `pSwapchains` array, and the presented image subresource must be in the `VK_IMAGE_LAYOUT_PRESENT_SRC_KHR` or `VK_IMAGE_LAYOUT_SHARED_PRESENT_KHR` layout at the time the operation is executed on a `VkDevice`
    - Guaranteed by the type system
2. All elements of the `pWaitSemaphores` must have a `VkSemaphoreType` of `VK_SEMAPHORE_TYPE_BINARY`

Fence

Validations for `vkResetFences`:

1. Each element of `pFences` must not be currently associated with any queue command that has not yet completed execution on that queue

Image

Validations for vkBindImageMemory:

1. image must not have been created with the VK_IMAGE_CREATE_DISJOINT_BIT set.
2. image must not already be backed by a memory object
   - Handled by API design
3. image must not have been created with any sparse memory binding flags
4. memoryOffset must be less than the size of memory
   - Handled by API design
5. memory must have been allocated using one of the memory types allowed in the memoryTypeBits member of the VkMemoryRequirements structure returned from a call to vkGetImageMemoryRequirements with image
   - Handled by API design
6. memoryOffset must be an integer multiple of the alignment member of the VkMemoryRequirements structure returned from a call to vkGetImageMemoryRequirements with image
   - Handled by API design
7. The difference of the size of memory and memoryOffset must be greater than or equal to the size member of the VkMemoryRequirements structure returned from a call to vkGetImageMemoryRequirements with the same image
   - Handled by API design
8. If image requires a dedicated allocation (as reported by vkGetImageMemoryRequirements2 in VkMemoryDedicatedRequirements::requiresDedicatedAllocation for image), memory must have been created with VkMemoryDedicatedAllocateInfo::image equal to image
9. If the dedicated allocation image aliasing feature is not enabled, and the VkMemoryAllocateInfo provided when memory was allocated included a VkMemoryDedicatedAllocateInfo structure in its pNext chain, and VkMemoryDedicatedAllocateInfo::image was not VK_NULL_HANDLE, then image must equal VkMemoryDedicatedAllocateInfo::image and memoryOffset must be zero.
10. If the dedicated allocation image aliasing feature is enabled, and the VkMemoryAllocateInfo provided when memory was allocated included a VkMemoryDedicatedAllocateInfo structure in its pNext chain, and VkMemoryDedicatedAllocateInfo::image was not VK_NULL_HANDLE, then memoryOffset must be zero, and image must be either equal to VkMemoryDedicatedAllocateInfo::image or an image that was created using the same parameters in VkImageCreateInfo, with the exception that extent and arrayLayers may differ subject to the following restrictions: every dimension in the extent parameter of the image being bound must be equal to or smaller than the original image for which the allocation was created; and the arrayLayers parameter of the image being bound must be equal to or smaller than the original image for which the allocation was created.
11. If image was created with the VK_IMAGE_CREATE_PROTECTED_BIT bit set, the image must be bound to a memory object allocated with a memory type that reports VK_MEMORY_PROPERTY_PROTECTED_BIT
12. If image was created with the VK_IMAGE_CREATE_PROTECTED_BIT bit not set, the image must not be bound to a memory object created with a memory type that reports VK_MEMORY_PROPERTY_PROTECTED_BIT
13. If image was created with VkDedicatedAllocationImageCreateInfoNV::dedicatedAllocation equal to VK_TRUE, memory must have been created with VkDedicatedAllocationMemoryAllocateInfoNV::image equal to an image handle created with identical creation parameters to image and memoryOffset must be zero
14. If the value of VkExportMemoryAllocateInfo::handleTypes used to allocate memory is not 0, it must include at least one of the handles set in VkExternalMemoryImageCreateInfo::handleTypes when image was created

15. If memory was created by a memory import operation, the external handle type of the imported memory must also have been set in VkExternalMemoryImageCreateInfo::handleTypes when image was created

Buffer

Validations for vkBindBufferMemory:

1. buffer must not already be backed by a memory object
   - Handled by API design
2. buffer must not have been created with any sparse memory binding flags
3. memoryOffset must be less than the size of memory
   - Handled by API design
4. memory must have been allocated using one of the memory types allowed in the memoryTypeBits member of the VkMemoryRequirements structure returned from a call to vkGetBufferMemoryRequirements with buffer
   - Handled by API design
5. memoryOffset must be an integer multiple of the alignment member of the VkMemoryRequirements structure returned from a call to vkGetBufferMemoryRequirements with buffer
   - Handled by API design
6. The size member of the VkMemoryRequirements structure returned from a call to vkGetBufferMemoryRequirements with buffer must be less than or equal to the size of memory minus memoryOffset
   - Handled by API design
7. If buffer requires a dedicated allocation(as reported by vkGetBufferMemoryRequirements2 in VkMemoryDedicatedRequirements::requiresDedicatedAllocation for buffer), memory must have been created with VkMemoryDedicatedAllocateInfo::buffer equal to buffer
8. If the VkMemoryAllocateInfo provided when memory was allocated included a VkMemoryDedicatedAllocateInfo structure in its pNext chain, and VkMemoryDedicatedAllocateInfo::buffer was not VK_NULL_HANDLE, then buffer must equal VkMemoryDedicatedAllocateInfo::buffer, and memoryOffset must be zero.
9. If buffer was created with the VK_BUFFER_CREATE_PROTECTED_BIT bit set, the buffer must be bound to a memory object allocated with a memory type that reports VK_MEMORY_PROPERTY_PROTECTED_BIT
10. If buffer was created with the VK_BUFFER_CREATE_PROTECTED_BIT bit not set, the buffer must not be bound to a memory object created with a memory type that reports VK_MEMORY_PROPERTY_PROTECTED_BIT
11. If buffer was created with VkDedicatedAllocationBufferCreateInfoNV::dedicatedAllocation equal to VK_TRUE, memory must have been created with VkDedicatedAllocationMemoryAllocateInfoNV::buffer equal to a buffer handle created with identical creation parameters to buffer and memoryOffset must be zero
12. If the value of VkExportMemoryAllocateInfo::handleTypes used to allocate memory is not 0, it must include at least one of the handles set in VkExternalMemoryBufferCreateInfo::handleTypes when buffer was created
13. If memory was created by a memory import operation, the external handle type of the imported memory must also have been set in VkExternalMemoryBufferCreateInfo::handleTypes when buffer was created
14. If the VkPhysicalDeviceBufferDeviceAddressFeatures::bufferDeviceAddress feature is enabled and buffer was created with the VK_BUFFER_USAGE_SHADER_DEVICE_ADDRESS_BIT bit set, memory must have been allocated with the VK_MEMORY_ALLOCATE_DEVICE_ADDRESS_BIT bit set

Validations for `vkMapMemory`:

1. `memory` must not be currently host mapped
   - Handled by API design
2. `offset` must be less than the size of `memory`
3. If `size` is not equal to `VK_WHOLE_SIZE`, `size` must be greater than `0`
   - Guaranteed by the type system
4. If `size` is not equal to `VK_WHOLE_SIZE`, `size` must be less than or equal to the size of the `memory` minus `offset`
5. `memory` must have been created with a memory type that reports `VK_MEMORY_PROPERTY_HOST_VISIBLE_BIT`
6. `memory` must not have been allocated with multiple instances.

Validations for `VkMappedMemoryRange`:

1. `memory` must be currently host mapped
   - Handled by API design
2. If `size` is not equal to `VK_WHOLE_SIZE`, `offset` and `size` must specify a range contained within the currently mapped range of `memory`
   - Handled by API design
3. If `size` is equal to `VK_WHOLE_SIZE`, `offset` must be within the currently mapped range of `memory`
   - Handled by API design
4. If `size` is equal to `VK_WHOLE_SIZE`, the end of the current mapping of `memory` must be a multiple of `VkPhysicalDeviceLimits`::`nonCoherentAtomSize` bytes from the beginning of the memory object.
5. `offset` must be a multiple of `VkPhysicalDeviceLimits`::`nonCoherentAtomSize`
6. If `size` is not equal to `VK_WHOLE_SIZE`, `size` must either be a multiple of `VkPhysicalDeviceLimits`::`nonCoherentAtomSize`, or `offset` plus `size` must equal the size of `memory`.

Descriptor

Validations for `VkDescriptorSetAllocateInfo`:

1. Each element of `pSetLayouts` must not have been created with `VK_DESCRIPTOR_SET_LAYOUT_CREATE_PUSH_DESCRIPTOR_BIT_KHR` set
2. If any element of `pSetLayouts` was created with the `VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT` bit set, `descriptorPool` must have been created with the `VK_DESCRIPTOR_POOL_CREATE_UPDATE_AFTER_BIND_BIT` flag set

Validations for `VkDescriptorBufferInfo`:

1. `offset` must be less than the size of `buffer`
2. If `range` is not equal to `VK_WHOLE_SIZE`, `range` must be greater than `0`
   - Guaranteed by the type system
3. If `range` is not equal to `VK_WHOLE_SIZE`, `range` must be less than or equal to the size of `buffer` minus `offset`

Validations for `VkDescriptorImageInfo`:

1. imageView must not be 2D or 2D array image view created from a 3D image
2. If imageView is created from a depth/stencil image, the aspectMask used to create the imageView must include either VK_IMAGE_ASPECT_DEPTH_BIT or VK_IMAGE_ASPECT_STENCIL_BIT but not both.
3. imageLayout must match the actual VkImageLayout of each subresource accessible from imageView at the time this descriptor is accessed as defined by the image layout matching rules
4. If sampler is used and the VkFormat of the image is a multi-planar format, the image must have been created with VK_IMAGE_CREATE_MUTABLE_FORMAT_BIT, and the aspectMask of the imageView must be VK_IMAGE_ASPECT_PLANE_0_BIT, VK_IMAGE_ASPECT_PLANE_1_BIT or (for three-plane formats only) VK_IMAGE_ASPECT_PLANE_2_BIT

Validations for VkWriteDescriptorSetInlineUniformBlockEXT:

1. dataSize must be an integer multiple of 4
   - Returns error

Validations for VkWriteDescriptorSet:

1. dstBinding must be less than or equal to the maximum value of binding of all VkDescriptorSetLayoutBinding structures specified when dstSet's descriptor set layout was created
2. dstBinding must be a binding with a non-zero descriptorCount
3. All consecutive bindings updated via a single VkWriteDescriptorSet structure, except those with a descriptorCount of zero, must have identical descriptorType and stageFlags.
4. All consecutive bindings updated via a single VkWriteDescriptorSet structure, except those with a descriptorCount of zero, must all either use immutable samplers or must all not use immutable samplers.
5. descriptorType must match the type of dstBinding within dstSet
6. dstSet must be a valid VkDescriptorSet handle
   - Handled by API design
7. The sum of dstArrayElement and descriptorCount must be less than or equal to the number of array elements in the descriptor set binding specified by dstBinding, and all applicable consecutive bindings, as described by consecutive binding updates
8. If descriptorType is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT, dstArrayElement must be an integer multiple of 4
9. If descriptorType is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT, descriptorCount must be an integer multiple of 4
   - Returns error

10. If `descriptorType` is `VK_DESCRIPTOR_TYPE_SAMPLER`, `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER`, `VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE`, `VK_DESCRIPTOR_TYPE_STORAGE_IMAGE`, or `VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT`, `pImageInfo` must be a valid pointer to an array of `descriptorCount` valid `VkDescriptorImageInfo` structures
    - Handled by API design
11. If `descriptorType` is `VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER` or `VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER`, `pTexelBufferView` must be a valid pointer to an array of `descriptorCount` valid `VkBufferView` handles
    - Handled by API design
12. If `descriptorType` is `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER`, `VK_DESCRIPTOR_TYPE_STORAGE_BUFFER`, `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC`, or `VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC`, `pBufferInfo` must be a valid pointer to an array of `descriptorCount` valid `VkDescriptorBufferInfo` structures
    - Handled by API design
13. If `descriptorType` is `VK_DESCRIPTOR_TYPE_SAMPLER` or `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER`, and `dstSet` was not allocated with a layout that included immutable samplers for `dstBinding` with `descriptorType`, the `sampler` member of each element of `pImageInfo` must be a valid `VkSampler` object
14. If `descriptorType` is `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER`, `VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE`, `VK_DESCRIPTOR_TYPE_STORAGE_IMAGE`, or `VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT`, the `imageView` and `imageLayout` members of each element of `pImageInfo` must be a valid `VkImageView` and `VkImageLayout`, respectively
    - Handled by API design
15. If `descriptorType` is `VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT`, the `pNext` chain must include a `VkWriteDescriptorSetInlineUniformBlockEXT` structure whose `dataSize` member equals `descriptorCount`
    - Handled by API design
16. If `descriptorType` is `VK_DESCRIPTOR_TYPE_ACCELERATION_STRUCTURE_KHR`, the `pNext` chain must include a `VkWriteDescriptorSetAccelerationStructureKHR` structure whose `accelerationStructureCount` member equals `descriptorCount`
17. If `descriptorType` is `VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE`, then the `imageView` member of each `pImageInfo` element must have been created without a `VkSamplerYcbcrConversionInfo` structure in its `pNext` chain
18. If `descriptorType` is `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER`, and if any element of `pImageInfo` has a `imageView` member that was created with a `VkSamplerYcbcrConversionInfo` structure in its `pNext` chain, then `dstSet` must have been allocated with a layout that included immutable samplers for `dstBinding`, and the corresponding immutable sampler must have been created with an *identically defined* `VkSamplerYcbcrConversionInfo` object
19. If `descriptorType` is `VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER`, and `dstSet` was allocated with a layout that included immutable samplers for `dstBinding`, then the `imageView` member of each element of `pImageInfo` which corresponds to an immutable sampler that enables sampler Y□CBCRconversion must have been created with a `VkSamplerYcbcrConversionInfo` structure in its `pNext` chain with an *identically defined* `VkSamplerYcbcrConversionInfo` to the corresponding immutable sampler
20. If `descriptorType` is `VK_DESCRIPTOR_TYPE_STORAGE_IMAGE`, for each descriptor that will be accessed via load or store operations the `imageLayout` member for corresponding elements of `pImageInfo` must be `VK_IMAGE_LAYOUT_GENERAL`
21. If `descriptorType` is `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER` or `VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC`, the `offset` member of each element of `pBufferInfo` must be a multiple of `VkPhysicalDeviceLimits`::`minUniformBufferOffsetAlignment`

22. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_BUFFER or VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC, the offset member of each element of pBufferInfo must be a multiple of VkPhysicalDeviceLimits::minStorageBufferOffsetAlignment
23. If descriptorType is VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER, VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC, VK_DESCRIPTOR_TYPE_STORAGE_BUFFER, or VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC, and the buffer member of any element of pBufferInfo is the handle of a non-sparse buffer, then that buffer must be bound completely and contiguously to a single VkDeviceMemory object
24. If descriptorType is VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER or VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC, the buffer member of each element of pBufferInfo must have been created with VK_BUFFER_USAGE_UNIFORM_BUFFER_BIT set
25. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_BUFFER or VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC, the buffer member of each element of pBufferInfo must have been created with VK_BUFFER_USAGE_STORAGE_BUFFER_BIT set
26. If descriptorType is VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER or VK_DESCRIPTOR_TYPE_UNIFORM_BUFFER_DYNAMIC, the range member of each element of pBufferInfo, or the effective range if range is VK_WHOLE_SIZE, must be less than or equal to VkPhysicalDeviceLimits::maxUniformBufferRange
27. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_BUFFER or VK_DESCRIPTOR_TYPE_STORAGE_BUFFER_DYNAMIC, the range member of each element of pBufferInfo, or the effective range if range is VK_WHOLE_SIZE, must be less than or equal to VkPhysicalDeviceLimits::maxStorageBufferRange
28. If descriptorType is VK_DESCRIPTOR_TYPE_UNIFORM_TEXEL_BUFFER, the VkBuffer that each element of pTexelBufferView was created from must have been created with VK_BUFFER_USAGE_UNIFORM_TEXEL_BUFFER_BIT set
29. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_TEXEL_BUFFER, the VkBuffer that each element of pTexelBufferView was created from must have been created with VK_BUFFER_USAGE_STORAGE_TEXEL_BUFFER_BIT set
30. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_IMAGE or VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT, the imageView member of each element of pImageInfo must have been created with the identity swizzle
31. If descriptorType is VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE or VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, the imageView member of each element of pImageInfo must have been created with VK_IMAGE_USAGE_SAMPLED_BIT set
32. If descriptorType is VK_DESCRIPTOR_TYPE_SAMPLED_IMAGE or VK_DESCRIPTOR_TYPE_COMBINED_IMAGE_SAMPLER, the imageLayout member of each element of pImageInfo must be a member of the list given in Sampled Image or Combined Image Sampler, corresponding to its type
33. If descriptorType is VK_DESCRIPTOR_TYPE_INPUT_ATTACHMENT, the imageView member of each element of pImageInfo must have been created with VK_IMAGE_USAGE_INPUT_ATTACHMENT_BIT set
34. If descriptorType is VK_DESCRIPTOR_TYPE_STORAGE_IMAGE, the imageView member of each element of pImageInfo must have been created with VK_IMAGE_USAGE_STORAGE_BIT set
35. All consecutive bindings updated via a single VkWriteDescriptorSet structure, except those with a descriptorCount of zero, must have identical VkDescriptorBindingFlagBits.
36. If descriptorType is VK_DESCRIPTOR_TYPE_SAMPLER, then dstSet must not have been allocated with a layout that included immutable samplers for dstBinding

Validations for VkCopyDescriptorSet:

1. srcBinding must be a valid binding within srcSet
2. The sum of srcArrayElement and descriptorCount must be less than or equal to the number of array elements in the descriptor set binding specified by srcBinding, and all applicable consecutive bindings, as described by consecutive binding updates

3. dstBinding must be a valid binding within dstSet
4. The sum of dstArrayElement and descriptorCount must be less than or equal to the number of array elements in the descriptor set binding specified by dstBinding, and all applicable consecutive bindings, as described by consecutive binding updates
5. The type of dstBinding within dstSet must be equal to the type of srcBinding within srcSet
6. If srcSet is equal to dstSet, then the source and destination ranges of descriptors must not overlap, where the ranges may include array elements from consecutive bindings as described by consecutive binding updates
7. If the descriptor type of the descriptor set binding specified by srcBinding is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT, srcArrayElement must be an integer multiple of 4
8. If the descriptor type of the descriptor set binding specified by dstBinding is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT, dstArrayElement must be an integer multiple of 4
9. If the descriptor type of the descriptor set binding specified by either srcBinding or dstBinding is VK_DESCRIPTOR_TYPE_INLINE_UNIFORM_BLOCK_EXT, descriptorCount must be an integer multiple of 4
10. If srcSet's layout was created with the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT flag set, then dstSet's layout must also have been created with the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT flag set
11. If srcSet's layout was created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT flag set, then dstSet's layout must also have been created without the VK_DESCRIPTOR_SET_LAYOUT_CREATE_UPDATE_AFTER_BIND_POOL_BIT flag set
12. If the descriptor pool from which srcSet was allocated was created with the VK_DESCRIPTOR_POOL_CREATE_UPDATE_AFTER_BIND_BIT flag set, then the descriptor pool from which dstSet was allocated must also have been created with the VK_DESCRIPTOR_POOL_CREATE_UPDATE_AFTER_BIND_BIT flag set
13. If the descriptor pool from which srcSet was allocated was created without the VK_DESCRIPTOR_POOL_CREATE_UPDATE_AFTER_BIND_BIT flag set, then the descriptor pool from which dstSet was allocated must also have been created without the VK_DESCRIPTOR_POOL_CREATE_UPDATE_AFTER_BIND_BIT flag set
14. If the descriptor type of the descriptor set binding specified by dstBinding is VK_DESCRIPTOR_TYPE_SAMPLER, then dstSet must not have been allocated with a layout that included immutable samplers for dstBinding

Validations for vkUpdateDescriptorSets:

1. Descriptor bindings updated by this command which were created without the VK_DESCRIPTOR_BINDING_UPDATE_AFTER_BIND_BIT or VK_DESCRIPTOR_BINDING_UPDATE_UNUSED_WHILE_PENDING_BIT bits set must not be used by any command that was recorded to a command buffer which is in the pending state.

Statistics

Category	Statically solved	Dynamically solved	Left to user	Total
Implicit	306	27	3	336
Creation	90	0	307	397
Usage	29	3	116	148
Total	425	30	426	881