Vulnlog Specification

Table of Contents

1. Overview . . . 2
   1.1. Scope . . . 2
   1.2. Design Principles . . . 2
   1.3. File Convention . . . 3
   1.4. Multi-Branch Workflow . . . 3
2. File Structure . . . 3
3. Sections . . . 4
   3.1. `version` . . . 4
   3.2. `project` . . . 4
   3.3. `tags` . . . 4
   3.4. `releases` . . . 5
      3.4.1. PURL Entry . . . 5
   3.5. `vulnerabilities` . . . 5
      3.5.1. Report Entry . . . 6
      3.5.2. Suppress Entry . . . 7
4. Enumerations . . . 7
   4.1. Verdict Values . . . 7
   4.2. Severity Values . . . 7
   4.3. Justification Values (OpenVEX) . . . 8
   4.4. Reporter Type Values . . . 8
5. Defaults and Implicit Behavior . . . 8
6. Suppression Behavior . . . 9
   6.1. Suppression Rules . . . 9
   6.2. Suppression Identifier Resolution . . . 9
7. VEX Generation . . . 9
   7.1. Field Mapping . . . 9
   7.2. Product Scoping via Tags . . . 10
   7.3. VEX Document Versioning . . . 10
8. HTML Report Generation . . . 10
   8.1. Detail Pages (Future) . . . 10
9. Validation Rules . . . 11
10. CLI Design . . . 11
   10.1. Usage . . . 11
   10.2. Global Flags . . . 11
   10.3. Filtering Flags . . . 12
   10.4. Commands . . . 12

10.4.1. `vulnlog init` . . . 12
10.4.2. `vulnlog validate` . . . 12
10.4.3. `vulnlog lint` . . . 12
10.4.4. `vulnlog stats` . . . 13
10.4.5. `vulnlog report` . . . 13
10.4.6. `vulnlog suppress` . . . 13
10.4.7. `vulnlog vex` . . . 14
10.4.8. `vulnlog sarif` (Future) . . . 14
10.5. Exit Codes . . . 14
11. Future Directions . . . 14
11.1. Multi-File Support . . . 14
11.2. SARIF Export . . . 14
11.3. Per-Vulnerability HTML Detail Pages . . . 14
12. Examples . . . 15
12.1. Quick Start . . . 15
12.2. Full Example . . . 15

1. Overview

Vulnlog is a YAML-based format for tracking, analyzing, and managing software vulnerabilities reported by one or multiple Software Composition Analysis (SCA) scanners. Each Vulnlog file is scoped to a single release branch. The lifecycle of the file follows the lifecycle of the release branch — when a release branch reaches end of life (EoL), its Vulnlog file becomes a natural historical archive.

A Vulnlog file serves as a human-authored decision ledger. From this file, the Vulnlog CLI generates machine-readable outputs: SCA scanner suppression files, HTML reports, and OpenVEX statements.

1.1. Scope

Vulnlog is focused on security vulnerabilities reported by SCA scanners. License compliance findings, configuration issues, and other informational findings are out of scope for this version of the specification.

1.2. Design Principles

Compact and readable

The format prioritizes ease of writing and reading over exhaustive detail. The common case — reporting a finding and recording a verdict — should require minimal boilerplate.

IDE-supported

A JSON Schema published to SchemaStore provides validation, autocompletion, and inline documentation in editors.

Git-friendly

The file is designed for version control. Changes are tracked via Git history rather than in-file audit trails.

Data-oriented

Entries are plain data records with no behavior. The CLI applies transformations and business logic.

1.3. File Convention

Vulnlog files use the naming convention `<project-name>.vl.yaml` (or `.vl.yml`). The `.vl.` infix identifies Vulnlog files and enables automatic JSON Schema association in IDEs via glob pattern matching. Simple projects may use `vulnlog.yaml` (or `vulnlog.yml`).

The file location within the repository is not prescribed. The CLI requires an explicit file path as a positional argument; it does not search for files automatically.

1.4. Multi-Branch Workflow

The recommended approach for teams managing multiple release branches is to maintain multiple Vulnlog files on the main branch, one per release branch:

```
demo-project-8.1.vl.yaml    # Release branch 8.1.x
demo-project-8.2.vl.yaml    # Release branch 8.2.x
demo-project-8.3.vl.yaml    # Release branch 8.3.x
```

Each file is self-contained. The CLI operates on one file at a time. This approach avoids cherry-picking vulnerability analysis to older Git branches.

It remains possible to maintain a Vulnlog file directly on each release branch. Both approaches can coexist.

2. File Structure

```
version: "1"

project:
  # Project metadata

tags:
  # Tag definitions (optional)

releases:
  # Release definitions (chronological order)

vulnerabilities:
```

```
# Vulnerability entries
```

Required top-level sections: `version`, `project`, `releases`, `vulnerabilities`. Optional top-level sections: `tags`.

`vulnerabilities` may be an empty array.

3. Sections

3.1. `version`

Field	Type	Required	Description
`version`	String	Yes	Schema version of the Vulnlog file. For this specification it is `"1"`.

3.2. `project`

Project-level metadata. Used in report generation and as author information in VEX documents.

Field	Type	Required	Description
`organization`	String	Yes	Name of the organization or vendor.
`name`	String	Yes	Name of the software project.
`security_team`	String	No	Name of the responsible security team. Used as the author in VEX documents.
`security_team_email`	String (email)	No	Contact email for the security team. Used as the author contact in VEX documents.

3.3. `tags`

Optional. Defines labels for categorizing and scoping vulnerability entries. Tags provide a flexible, team-defined taxonomy that can represent customer-facing deliverables (`binary`, `container`, `sdk`), internal usage contexts (`build-dep`, `test-infra`), compliance scopes (`pci`, `hipaa`, `sox`), or any other categorization.

Field	Type	Required	Description
`id`	String	Yes	Unique identifier for the tag. Referenced by vulnerability entries and release purl entries.
`description`	String	No	Human-readable description of what this tag represents.

3.4. `releases`

Defines the releases tracked in this Vulnlog file. Releases must be listed in chronological order (oldest first). This ordering is used by the CLI to resolve `--release` filtering.

Field	Type	Required	Description
`id`	String	Yes	Unique release identifier (e.g., `8.1.1`, `2.0.0-SNAPSHOT`).
`published_at`	String (date, `YYYY-MM-DD`)	No	Publication date of the release. Absence indicates the release is not yet published.
`purls`	Array of PURL Entry	No	Versioned Package URLs identifying the release artifacts. Used as product identifiers in VEX documents.

3.4.1. PURL Entry

A release artifact identified by its Package URL, optionally tagged for scoping.

Field	Type	Required	Description
`purl`	String (Package URL)	Yes	The versioned Package URL for this artifact in this release.
`tags`	Array of String	No	Tags associated with this purl. Used to match vulnerability tags for scoped VEX generation. Must reference tags defined in the `tags` section.

When a vulnerability entry has tags that match a purl's tags, only the matching purls are included as products in the VEX statement. Purls without tags are included in VEX statements regardless of vulnerability tags.

3.5. `vulnerabilities`

Each entry represents a single vulnerability finding and the human verdict about it. The verdict reflects the most severe impact across all listed packages.

Field	Type	Required	Description
`id`	String	Yes	Primary identifier. Preferably a CVE ID. May be a scanner-specific ID if no CVE exists.
`name`	String	No	Common name if one exists (e.g., "Log4Shell", "Heartbleed"). Displayed prominently in reports.
`aliases`	Array of String	No	Alternative identifiers (e.g., GHSA IDs, scanner-specific IDs). Used for cross-referencing in reports.
`releases`	Array of String	Yes	Release identifiers affected. Must reference IDs from the `releases` section.

Field	Type	Required	Description
`description`	String	No	Brief human-readable description. Optional to allow quick stub entries during triage.
`packages`	Array of String (Package URL)	Yes	Package URLs of affected dependencies.
`reports`	Array of Report Entry	Yes	Scanner reports that identified this vulnerability.
`tags`	Array of String	No	Tags for categorizing and scoping. Must reference tags defined in the `tags` section. Used for CLI filtering and VEX product scoping.
`analysis`	String	No	Free-text analysis and rationale for the triage decision. Maps to `impact_statement` in VEX for `not_affected` and `action_statement` for `risk_acceptable`.
`analyzed_at`	String (date, `YYYY-MM-DD`)	No	Date the analysis was performed. Must not be before the earliest report date.
`comment`	String	No	Additional information not related to the analysis itself. May include evidence references, methodology notes, decision-making context, or reminders for future review. Not used in any output generation.
`severity`	String (enum)	Conditional	Severity assessment. Required when `verdict` is `affected` or `risk_acceptable`. See Severity Values.
`verdict`	String (enum)	No	The human triage decision. See Verdict Values. Absence indicates under investigation.
`justification`	String (enum)	Conditional	Required when `verdict` is `not_affected`. See Justification Values (OpenVEX).
`fixed_in`	String	Conditional	Required when `verdict` is `fixed`. References the release with the fix.
`fixed_at`	String (date, `YYYY-MM-DD`)	No	Date the fix was applied. Only meaningful when `verdict` is `fixed`.
`fix_ref`	String (URI)	No	Reference to the issue or ticket tracking the fix.
`fix_note`	String	No	Brief description of how the vulnerability was fixed.

3.5.1. Report Entry

Field	Type	Required	Description
`reporter`	String (enum)	Yes	The scanner or source type. See Reporter Type Values.

Field	Type	Required	Description
`at`	String (date, `YYYY-MM-DD`)	Yes	Date the vulnerability was reported.
`source`	String	No	Description of the report source. Optional for scanner reporters. Required by the CLI for reporter type `other`.
`vuln_id`	Array of String	No	Scanner-specific vulnerability identifiers. Used for scanner-specific suppression files.
`suppress`	Suppress Entry	No	Scanner-specific suppression configuration.

3.5.2. Suppress Entry

Field	Type	Required	Description
`expires_at`	String (date, `YYYY-MM-DD`)	Yes	Expiration date. After this date, the entry is excluded from the generated suppression file.

4. Enumerations

4.1. Verdict Values

The term "verdict" is used deliberately to distinguish from automated scanner statuses — it reflects a deliberate human judgment.

Value	Description	OpenVEX Mapping
`affected`	The vulnerability affects this release and action is required.	`affected`
`not_affected`	The vulnerability does not affect this release. Requires `justification`.	`not_affected`
`fixed`	The vulnerability has been resolved. Requires `fixed_in`.	`fixed`
`risk_acceptable`	The vulnerability affects this release but the risk has been assessed and accepted.	`affected` (with `action_statement` from `analysis`)
(absent)	Not yet triaged.	`under_investigation`

4.2. Severity Values

Value	Description
`critical`	Immediate action required. Exploitable with severe impact.
`high`	Action required. Significant impact if exploited.
`medium`	Action recommended. Moderate impact.

Value	Description
`low`	Low priority. Minimal impact or difficult to exploit.

4.3. Justification Values (OpenVEX)

Value	Description
`component_not_present`	The vulnerable component is not included in the deliverable.
`vulnerable_code_not_present`	The vulnerable code is present but the specific vulnerable function or code path is not included.
`vulnerable_code_not_in_execute_path`	The vulnerable code is present but cannot be reached during execution.
`vulnerable_code_cannot_be_controlled_by_adversary`	The vulnerable code is reachable but cannot be triggered by an attacker.
`inline_mitigations_already_exist`	The vulnerability is mitigated by existing controls (e.g., WAF, input validation).

4.4. Reporter Type Values

Value	Scanner	Default Suppression Path	Suppression Support
`trivy`	Trivy	`.trivyignore`	Yes
`snyk`	Snyk	`.snyk`	Yes
`dependency_check`	OWASP Dependency Check	`dependency-check-suppressions.xml`	Yes
`grype`	Grype	`.grype.yaml`	Yes
`rust_audit`	Cargo Audit (Rust)	`.cargo-audit.toml`	Yes
`semgrep`	Semgrep	—	No
`npm_audit`	npm audit	—	No
`github_advisory`	GitHub Advisory Database	—	No
`other`	Generic / non-scanner source	—	No

For reporters of type `other`, the `source` field on report entries is required by the CLI.

5. Defaults and Implicit Behavior

Omitted `tags` section

The file has no tag definitions. Vulnerability entries cannot use tags. VEX generation includes all purls as products.

Omitted `verdict`

Treated as `under_investigation`. The CLI warns about entries without a verdict.

Omitted `releases[].published_at`

The release is considered unpublished.

Omitted `analyzed_at`

No analysis date is recorded.

Omitted `vulnerabilities[].tags`

The vulnerability is not scoped. Included in all unfiltered outputs.

Omitted `releases[].purls[].tags`

The purl is included in VEX statements regardless of vulnerability tags.

6. Suppression Behavior

6.1. Suppression Rules

Entries where `verdict` is `fixed` are **never** included in suppression files.

Entries where `verdict` is `not_affected` are always included.

For all other verdicts (`affected`, `risk_acceptable`, absent), suppression requires an explicit, non-expired `suppress` block on the report entry.

6.2. Suppression Identifier Resolution

1. `vuln_id` values from the report entry for the target reporter type, if present.
2. The vulnerability's `id` field.

`aliases` are not used for suppression.

7. VEX Generation

OpenVEX documents are generated via the CLI. Vulnlog tags + release purls map to OpenVEX products. Vulnlog packages map to OpenVEX subcomponents.

7.1. Field Mapping

OpenVEX Field	Vulnlog Source
`author`	`project.security_team` and `project.security_team_email`
`statement.vulnerability`	`vulnerabilities[].id`

OpenVEX Field	Vulnlog Source
`statement.products`	`releases[].purls[].purl` for the target release, filtered by matching tags
`statement.products[].subcomponents`	`vulnerabilities[].packages[]`
`statement.status`	`vulnerabilities[].verdict` (mapped per Verdict Values)
`statement.justification`	`vulnerabilities[].justification`
`statement.impact_statement`	`vulnerabilities[].analysis` (when verdict is `not_affected`)
`statement.action_statement`	`vulnerabilities[].analysis` (when verdict is `risk_acceptable`)

7.2. Product Scoping via Tags

When a vulnerability has tags, the VEX generator matches those tags against purl entries on the target release. Only purls with matching tags are included as products. Purls without tags are always included. Vulnerabilities without tags are associated with all purls.

7.3. VEX Document Versioning

The OpenVEX `version` field is an incrementing integer. Since the CLI is stateless, the version is determined from the existing output file:

1. If the output path points to an existing VEX file, parse the current `version`.
2. New version = previous + 1.
3. If no existing file, start at version 1.

8. HTML Report Generation

The primary output is a self-contained HTML file with a summary table. Each vulnerability entry is a single row.

`name` (if present) is displayed prominently. `aliases` shown as secondary identifiers. Tags are displayed for filtering context. `comment` is not included in HTML reports (it is internal-only metadata).

8.1. Detail Pages (Future)

A future version will generate per-vulnerability detail pages alongside the summary:

```
vulnlog-report/
  index.html                    # Summary table with links
  CVE-2021-44228.html           # Detail page
```

```
...
```

9. Validation Rules

1. `releases` in vulnerability entries must reference IDs defined in `releases`.
2. `tags` in vulnerability entries must reference IDs defined in `tags` (when `tags` section exists).
3. `tags` in release purl entries must reference IDs defined in `tags`.
4. `fixed_in` must reference a release ID defined in `releases`.
5. `reporter` must be a valid reporter type enum value.
6. `justification` is required when `verdict` is `not_affected` and forbidden otherwise.
7. `severity` is required when `verdict` is `affected` or `risk_acceptable`.
8. `fixed_in` is required when `verdict` is `fixed` and forbidden otherwise.
9. `source` is required on report entries when `reporter` is `other`.
10. All `id` fields within their respective sections must be unique.
11. `suppress.expires_at` must be a valid future or present date at CLI execution time.
12. `analyzed_at`, when present, must not be before the earliest `at` date across reports.
13. Entries in `releases` must be in chronological order.
14. All entries in `packages` must be valid Package URLs.

10. CLI Design

10.1. Usage

```
vulnlog <command> <file> [flags]
```

Every command except `init` requires a Vulnlog file as a positional argument. No automatic file detection.

10.2. Global Flags

Flag	Description
`-q, --quiet`	Suppress non-essential output.
`-v, --verbose`	Verbose output.
`--no-color`	Disable colored output.
`--format <f>`	Output format for structured output: `yaml` (default). Future: `json`, `text`.

Flag	Description
`--version`	Print version and exit.
`--help`	Print help.

10.3. Filtering Flags

Available on `stats`, `report`, `suppress`, and `vex` commands.

Flag	Description
`--release <id>`	Include vulnerabilities affecting all releases up to and including this release.
`--tags <id>`	Filter by tag (repeatable).

10.4. Commands

10.4.1. `vulnlog init`

Scaffolds a minimal Vulnlog file containing only the required sections (`version`, `project`, `releases`, `vulnerabilities`).

```
vulnlog init [flags]
```

Flag	Description
`-o, --output <path>`	Output file path (default: `vulnlog.yaml`).
`--project <n>`	Project name. Prompted if not provided.
`--organization <n>`	Organization name. Prompted if not provided.

10.4.2. `vulnlog validate`

```
vulnlog validate <file> [--strict]
```

`--strict` treats warnings as errors (e.g., missing verdict, missing description).

10.4.3. `vulnlog lint`

```
vulnlog lint <file> [--fix]
```

Enforces:

Top-level section order

`version`, `project`, `tags`, `releases`, `vulnerabilities`.

Vulnerability field order

`id`, `name`, `aliases`, `releases`, `description`, `packages`, `reports`, `tags`, `analysis`, `analyzed_at`, `comment`, `severity`, `verdict`, `justification`, `fixed_in`, `fixed_at`, `fix_ref`, `fix_note`.

Release chronological order

Oldest first.

10.4.4. `vulnlog stats`

```
vulnlog stats <file> [filter flags]
```

Example output:

```
project: Demo Project
total: 7
by_verdict:
  affected: 0
  not_affected: 2
  fixed: 2
  risk_acceptable: 1
  under_investigation: 2
by_severity:
  critical: 2
  high: 0
  medium: 0
  low: 2
  unrated: 1
suppressions:
  active: 2
  expired: 1
```

10.4.5. `vulnlog report`

```
vulnlog report <file> [filter flags] [--format html] [-o <path>]
```

Default output: `vulnlog-report.html`.

10.4.6. `vulnlog suppress`

```
vulnlog suppress <file> [--reporter <type>] [filter flags] [-o <path>]
```

When `--reporter` is specified, generates a single suppression file. When omitted, generates for all reporter types found in the vulnerability reports.

Output path: `--output` flag or default for the reporter type. `--output` is only valid with `--reporter`.

10.4.7. `vulnlog vex`

```
vulnlog vex <file> [filter flags] [-o <path>]
```

Default output: `vex.json`.

10.4.8. `vulnlog sarif` (Future)

Generates a SARIF document from Vulnlog data.

```
vulnlog sarif <file> [filter flags] [-o <path>]
```

Default output: `vulnlog.sarif.json`.

10.5. Exit Codes

Code	Name	Description
`0`	Success	Command completed successfully.
`1`	General error	Unexpected error (I/O failure, unhandled exception).
`2`	Validation error	The Vulnlog file contains validation errors.
`3`	File not found	The specified Vulnlog file does not exist.
`4`	Lint violation	The file has lint violations (without `--fix`).
`5`	Missing required flag	A required flag was not provided.
`6`	Invalid flag value	A flag references an unknown entity or unsupported type.

11. Future Directions

11.1. Multi-File Support

A future version will introduce an `imports` directive for splitting a Vulnlog file.

11.2. SARIF Export

See `vulnlog sarif` (Future).

11.3. Per-Vulnerability HTML Detail Pages

See HTML Report Generation.

12. Examples

12.1. Quick Start

```
version: "1"

project:
  organization: Acme Corp
  name: Acme Web App

releases:
  - id: 1.0.0
    published_at: 2026-01-15

vulnerabilities:

  - id: CVE-2026-1234
    releases: [ 1.0.0 ]
    description: Remote code execution in example-lib
    packages:
      - "pkg:npm/example-lib@2.3.0"
    reports:
      - reporter: trivy
        at: 2026-01-20
    analysis: >
      The vulnerable code path is not reachable in our application
      because we only use the safe subset of the API.
    verdict: not_affected
    justification: vulnerable_code_not_in_execute_path
```

12.2. Full Example

```
version: "1"

project:
  organization: Demo Project Inc
  name: Demo Project
  security_team: Demo Security Team
  security_team_email: security@demo.com

tags:
  - id: binary
    description: Demo Project binary file
  - id: container
    description: Demo Project container image
  - id: sdk
    description: Demo Project SDK
```

```
  - id: build-dep
    description: Internal build dependency
  - id: pci
    description: PCI DSS compliance scope

releases:
  - id: 8.1.0
    published_at: 2021-01-15
    purls:
      - purl: "pkg:generic/demo-project@8.1.0"
        tags: [ binary ]
      - purl: "pkg:docker/demo-project@8.1.0"
        tags: [ container ]
  - id: 8.1.1
    published_at: 2021-02-11
    purls:
      - purl: "pkg:generic/demo-project@8.1.1"
        tags: [ binary ]
      - purl: "pkg:docker/demo-project@8.1.1"
        tags: [ container ]
  - id: 8.1.2

vulnerabilities:

  # No verdict - under investigation, with temporary suppression
  - id: CVE-2020-099
    releases: [ 8.1.0 ]
    description: Path traversal vulnerability in random-dependency
    packages:
      - "pkg:maven/org.random/random-core@1.33.7"
    reports:
      - reporter: trivy
        at: 2020-12-28
        suppress:
          expires_at: 2021-01-02
    tags: [ build-dep ]
    analysis: >
      Vulnerability in internal build dependency.
      No fixed library available at the moment. Re-check later.
    comment: >
      Checked upstream issue tracker - fix expected in random-core 1.33.8.
      Monitor https://github.com/random/random-core/issues/421
    severity: low

  # Stub entry - quick triage, no description, no verdict yet
  - id: CVE-2021-007
    releases: [ 8.1.1 ]
    packages:
      - "pkg:maven/com.example/some-lib@4.0.0"
    reports:
      - reporter: trivy
```

```
      at: 2021-03-10
    tags: [ binary ]

  # Verdict: not_affected - vulnerability does not impact this project
  - id: CVE-2021-002
    aliases: [ GHSA-xxxx-yyyy ]
    releases: [ 8.1.1 ]
    description: Deserialization vulnerability in some-dependency
    packages:
      - "pkg:maven/example.org/some-dependency@1.1.2"
    reports:
      - reporter: trivy
        at: 2021-03-03
      - reporter: snyk
        at: 2021-03-03
        vuln_id: [ SNYK-2021-002 ]
    tags: [ binary, container ]
    analysis: >
      Demo project does not utilize some-dependency
      and therefore is not affected.
    analyzed_at: 2021-03-03
    verdict: not_affected
    justification: vulnerable_code_not_present

  # Verdict: fixed - resolved in a subsequent release (named vulnerability)
  - id: CVE-2021-44228
    name: Log4Shell
    aliases: [ GHSA-jfh8-c2jp-5v3q ]
    releases: [ 8.1.1 ]
    description: RCE vulnerability in Log4J via JNDI lookup
    packages:
      - "pkg:maven/org.apache.logging.log4j/log4j-core@2.14.1"
    reports:
      - reporter: trivy
        at: 2021-12-10
    tags: [ binary, pci ]
    analysis: >
      Demo project utilizes Log4J and a PoC showed that
      the project is vulnerable to this RCE vulnerability.
    analyzed_at: 2021-12-10
    comment: >
      PoC exploit confirmed by Jane (security team) on 2021-12-10.
      See internal report attached to SEC-42.
    severity: critical
    verdict: fixed
    fixed_in: 8.1.2
    fixed_at: 2021-12-12
    fix_ref: "https://jira.example.com/browse/SEC-42"
    fix_note: "Updated Log4J from 2.14.1 to 2.17.1"

  # Verdict: not_affected - OS-level vulnerability in container base image
```

```
  - id: CVE-2024-5535
    releases: [ 8.1.1 ]
    description: Buffer overread in OpenSSL SSL_select_next_proto
    packages:
      - "pkg:apk/alpine/openssl@3.1.4-r0"
    reports:
      - reporter: trivy
        at: 2024-06-28
    tags: [ container ]
    analysis: >
      Vulnerable OpenSSL is present in the container base image
      but the affected NPN/ALPN negotiation code path is never
      invoked by our application.
    analyzed_at: 2024-06-29
    verdict: not_affected
    justification: vulnerable_code_not_in_execute_path

  # Verdict: risk_acceptable - vulnerability present but risk accepted
  - id: SNYK-2021-003
    releases: [ 8.1.2 ]
    description: DoS vulnerability in some-other-dependency
    packages:
      - "pkg:maven/com.some.other/some-other-dependency@3.11.0"
    reports:
      - reporter: snyk
        at: 2022-04-28
    tags: [ binary, container ]
    analysis: >
      Demo project utilizes some-other-dependency but only in rare cases.
      Therefore the risk is considered low and a fix would potentially
      be breaking for customer setups.
    analyzed_at: 2022-04-29
    comment: >
      Risk accepted by project lead (decision documented in RISK-12).
      Revisit when some-other-dependency 4.0 is released.
    severity: low
    verdict: risk_acceptable

  # Report from a non-scanner source (Oracle CPU)
  - id: CVE-2022-21449
    name: Psychic Signatures
    releases: [ 8.1.2 ]
    description: ECDSA signature verification bypass in Java SE
    packages:
      - "pkg:maven/com.oracle/jdk@17.0.2"
    reports:
      - reporter: other
        at: 2022-04-19
        source: "Oracle Critical Patch Update April 2022"
    tags: [ binary, container, pci ]
    analysis: >
```

```
      The project uses Java 17 and ECDSA signatures for
      JWT token verification. Confirmed exploitable.
    analyzed_at: 2022-04-20
    severity: critical
    verdict: fixed
    fixed_in: 8.1.2
    fixed_at: 2022-04-22
    fix_ref: "https://jira.example.com/browse/SEC-55"
    fix_note: "Updated JDK from 17.0.2 to 17.0.3"
```