2WFB-16.5 WALL TO WALL FIRE BARRIER 2 HOUR RATED - 100% MOVEMENT MAXIMUM OPENING 33" (838mm) 1'-4" A MINIMUM WALL THICKNESS OF 406mm 12" (305mm) IS REQ'D FOR THIS SYSTEM 2 3/4" FABRIC FLAP MAY BE 70mm **FOLDED BENEATH** HOLD DOWN, IF REQ'D 2" 51mm 2WFB-16.5 WSD82-O @ | 12" (305mm) O.C. w/20 GA. GALVANIZED -/ NOTE 1: HOLD DOWN 2WFB WALL FIRE BARRIER (CONTINUOUS) MUST BE INSTALLED ON BOTH SIDES OF WALL, METACAULK OR WITH DOUBLE PACKAGES 9901 INSTALLED FROM ONE SIDE OF JOINT, TO MAINTAIN 2 HOUR RATING. NOTE 2: THE FIRE RATING FOR THIS AND SIMILAR CONDITIONS IS DETERMINED BY THE PERFORMANCE CAPABILITIES OF THE SURROUNDING CONSTRUCTION RATHER THAN THE METAFLEX FIRE BARRIER. **Project** Customer SO# Date Length Qty. Color 1/24/02 ŏ BALCO INC Page_ 2626 S. Sheridan PO Box 17249 Scale: NTS Wichita, Kansas 67217-0249 USA P: +1-316-945-9328 F: +1-316-945-0789 K:\FireBarrier\Metaflex2000\Wall\2WFB-16.5.dwg Jan 24, 2002 - 1:41pm