

# PRODUCT DATA SHEET

## CAP527 LOW SHEEN TOP COAT

<b>PRODUCT</b>	CAP527 low sheen acrylic top coat
<b>DESCRIPTION/USES</b>	CAP527 is a low VOC, water based coating for use over CAP508 in wet, humid and damp areas, or to achieve Group 1 to AS3837 on wood substrates.
<b>SURFACE PREPARATION</b>	All surfaces should be clean, dry, and free of dust, grease or other contaminants.

---

### APPLICATION INFORMATION

<b>MATERIAL PREPARATION</b>	Mix thoroughly before application
<b>METHOD</b>	Airless spray, brush or roller.
<b>DRYING TIME</b>	Dry to Touch: 1/2 hour at 24°C and 50% relative humidity (RH) Re-Coat: 2 to 4 hours at 24°C and 50% relative humidity (RH) Full Cure: 20 days
<b>THINNING</b>	Do NOT thin
<b>CLEAN UP</b>	Water
<b>HMIS</b>	Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: E.
<b>ENVIRONMENTAL</b>	Consult with local regulatory and governmental agencies for methods of disposal.

---

### SPECIFICATIONS

<b>COLOUR</b>	White, can be tinted.
<b>SOLIDS BY VOLUME</b>	43%
<b>WEIGHT PER LITRE</b>	1.12 kg
<b>GLOSS</b>	Low sheen
<b>COVERAGE</b>	10m <sup>2</sup> /litre on smooth sealed surfaces per coat
<b>SHELF LIFE</b>	One year
<b>MAXIMUM VOCs</b>	60 grams/litre
<b>CAUTION</b>	Protect from freezing. Do not apply when temperature of paint or surface is below 18°C or above 25°C or relative humidity is above 75%.