

PRODUCT SPECIFICATION

Surface-mounted automatic hand dryer, Bobrick Model B-700 (white), B-7007 (color).

Surface-mounted hand dryer shall have a one-piece cast iron cover with (select one: white or color) vitreous enamel finish. Nozzle shall adjust for hand and face drying. Nozzle shall automatically return to hand drying position; and cannot be used as a vessel to hold liquids. International operating symbols shall be permanently fused into vitreous enamel cover. Motor shall be 1/10 hp, 6200 rpm, with automatic thermal overload switch. Centrifical fan shall direct air flow through heating element at 150 cfm. Heating element shall be rated at 2300 watts, shall be located on inlet side of fan, shall heat air without hot spots, and be inaccessible to vandals. Electronic sensor shall automatically turn dryer on when hands or self-returning nozzle are held under the air-outlet opening and will shut off automatically when hands are removed or self-returning nozzle is released. Sensor shall shut off automatically after 90 seconds if an inanimate object is used to activate dryer and resets itself after inanimate object is removed. Unit shall be cULus Listed, and or VDE approved, CE marked. Unit shall comply with EU Directive "Restriction of Hazardous Substance" (ROHS) requirements for non-use of certain hazardous substances in the production of electronic products. Unit shall be protected by a limited 10-year warranty on all parts except motor brushes. Motor brushes shall be warranted for a period of three years from date of purchase.

