## PRODUCT SPECIFICATION

## Surface-mounted convertible paper towel dispenser and waste receptacle, Bobrick Model B-39619.

Surface-mounted convertible touch-free roll towel dispenser and waste receptacle shall be constructed of type-304 stainless steel with satin finish and all-welded construction. Flange shall be 22-gauge (0.8mm), drawn and beveled, one-piece, seamless construction. Cabinet shall be equipped with an interior stainless steel shelf. Door shall be 18-gauge (1.2mm) stainless steel and shall be secured to cabinet with a full-length, stainless steel piano-hinge and equipped with two tumbler locks. Touch-free. pull-towel mechanism dispenses one 12" (300mm) length of towel per pull. Accommodates 8" (205mm) wide, up to 8" (205mm) diameter rolls, 800 ft (244m) long. Roll paper towel mechanism shall have automatic towel transfer system to dispense towels from stub roll up to 3-1/2" (90mm) diameter before new roll starts to dispense. Lever shall be operable with one hand and with less than 5 lb of force (22.2 N) to comply with barrier-free accessibility guidelines (including ADAAG in U. S. A.). Removable stainless steel waste receptacle shall be equipped with a tumbler lock. Front and side edges of bottom and all top edges of waste receptacle shall be hemmed for safe handling. Waste receptacle minimum capacity: 12-gal. (45.5-L).

