2WFB-7.5 WALL TO WALL FIRE BARRIER 2 HOUR RATED - 100% MOVEMENT MAXIMUM OPENING 15" (381mm) 3" FABRIC FLAP MAY BE 76mm FOLDED BENEATH HOLD DOWN, IF REQ'D 51mm 2WFB-7.5 WSD82-O @ 12" (305mm) O.C. w/20 GA. GALVANIZED NOTE 1: **HOLD DOWN 2WFB WALL FIRE BARRIER** (CONTINUOUS) MUST BE INSTALLED ON BOTH SIDES OF WALL, METACAULK OR WITH DOUBLE PACKAGES 9901 INSTALLED FROM ONE SIDE OF JOINT. TO MAINTAIN 2 HOUR RATING. NOTE 2: THE FIRE RATING FOR THIS AND SIMILAR CONDITIONS IS DETERMINED BY THE PERFORMANCE CAPABILITIES **Project** OF THE SURROUNDING CONSTRUCTION RATHER THAN THE Customer METAFLEX FIRE BARRIER. SO# Date Length Qty. Color 4/4/03 178mm ŏ BALCO INC Page 2626 S. Sheridan PO Box 17249 Scale: NTS Wichita, Kansas 67217-0249 USA P: +1-316-945-9328 F: +1-316-945-0789 K:\FireBarrier\Metaflex2000\Wall\2WFB-7.5.dwg Apr 04, 2003 - 3:08pm