

Lesson 9

MICROSERVICES

SERVICE DEPLOYMENT


Service deployment

- Service are written using different languages, frameworks, framework versions
- Run multiple service instances of a service for throughput and availability
- Building and deploying should be fast
- Instances need to be isolated
- Constrain the resources a service may consume (CPU, memory, etc.)
- Deployment should be reliable

Multiple service instances per host

- Benefits

- Efficient resource utilization
- Fast deployment



- Drawbacks

- Poor isolation
- Poor visibility of resource utilization
- Difficult to constrain resource utilization
- Risk of dependency version conflicts
- Poor encapsulation of implementation technology


Service per VM

- Benefits

- Great isolation
- Great manageability
- VM encapsulates implementation technology
- Leverage cloud infrastructure for auto scaling/load balancing

- Drawbacks

- Less efficient resource utilization
- Slow deployment




Service per container

■ Benefits

- Great isolation
- Great manageability
- Container encapsulates implementation technology
- Efficient resource utilization
- Fast deployment


■ Drawbacks

- Technology is not as mature as VM's
- Containers are not as secure as VM's




CONTAINERS


Monolith




Microservice








The challenge





Matrix from hell




	Static website	?	?	?	?	?	?	?
	Web frontend	?	?	?	?	?	?	?
	Background workers	?	?	?	?	?	?	?
	User DB	?	?	?	?	?	?	?
	Analytics DB	?	?	?	?	?	?	?
	Queue	?	?	?	?	?	?	?
		Development VM	QA Server	Single Prod Server	Onsite Cluster	Public Cloud	Contributor's laptop	Customer Servers




Cargo Transport Pre-1960



The solution



Docker is a shipping container for code




Separation of concern


- Dan the Developer
 - Worries about what's "inside" the container
 - His code
 - His Libraries
 - His Package Manager
 - His Apps
 - His Data
- Oscar the Ops Guy
 - Worries about what's "outside" the container
 - Logging
 - Remote access
 - Monitoring
 - Network config
 - All containers start, stop, copy, attach, migrate, etc. the same way

Containers


- Docker




Docker Container



Virtual Machine



Container management




CQRS

Command Query Responsibility Segregation (CQRS)

- Separates the querying from command processing by providing two models instead of one.
 - One model is built to handle and process commands
 - One model is built for presentation needs (queries)

Typical architecture

- One domain model that is used for commands and queries



One model for both commands and queries

- To support complex views and reporting
 - Required domain model becomes complex
 - Internal state needs to be exposed
 - Aggregates are merged for view requirements
 - Repositories often contain many extra methods to support presentation needs such as paging, querying, and free text searching
- Result: single model that is full of compromises

Example of complex aggregates

A Web Page

http://

Scott Millett
Edit Details

Gift Certificate Balance: \$30
Redeem Gift Certificate

Address Book
Home
Work
Parents
Edit Address
Add Address

Loyalty Status: Gold


Complex aggregate
because of UI needs

We don't need this
complexity for commands

```
public class Customer
{
    // ...
    public ContactDetails ContactDetails { get; private set; }
    public LoyaltyStatus LoyaltyStatus { get; private set; }
    public Money GiftCertBalance { get; private set; }
    public IEnumerable<Address> AddressBook { get; private set; }
}
```

CQRS

- Domain model is used for commands
- View model is used for queries



2 services instead of one

Traditional service

CustomerService

```
void MakeCustomerPreferred(CustomerId)
Customer GetCustomer(CustomerId)
CustomerSet GetCustomersWithName(Name)
CustomerSet GetPreferredCustomers()
void ChangeCustomerLocale(CustomerId, NewLocale)
void CreateCustomer(Customer)
void EditCustomerDetails(CustomerDetails)
```



Service with CQRS

CustomerWriteService

```
void MakeCustomerPreferred(CustomerId)
void ChangeCustomerLocale(CustomerId, NewLocale)
void CreateCustomer(Customer)
void EditCustomerDetails(CustomerDetails)
```

CustomerReadService


```
Customer GetCustomer(CustomerId)
CustomerSet GetCustomersWithName(Name)
CustomerSet GetPreferredCustomers()
```


Architectural properties

- Command and query side have different architectural properties
- Consistency
 - Command: needs consistency
 - Query: eventual consistency is mostly OK
- Data storage
 - Command: you want a normalized schema (3rd NF)
 - Query: denormalized (1st NF) is good for performance (no joins)
- Scalability
 - Command: commands happens not that often. Scalability is often not important.
 - Query: queries happen very often, scalability is important

Eventual consistency

- Views will become eventual consistent



CQRS advantages

- The query side is very simple
 - No transactions
- The query side can be optimized for performance
 - Fast noSQL database
 - Caching is easy
- Queries and commands can be scaled independently


When to use CQRS?

- When queries and commands have different scaling requirements
- When read performance is critical
- When your screens start to look very different then your tables
- When you apply event sourcing

When not to use CQRS

- Systems with simple CRUD functionality
- When you need strict consistency (instead of eventual consistency)

CQRS example




EVENT SOURCING

State based persistence

- You capture where you are, but not how you got there
- You don't know what happened in the past
- You cannot fix bad state because of bugs in the code


Audit log



- Now we know how we got there
- What if the audit log gets out of sync with the state due to a bug?
- Which is the source of truth? (Audit log)

Event sourcing

- Only capture how we got there



Event sourcing

- Bank account
 - Store all deposits and withdrawals
- Phone account
 - Store all phone calls
- Version control systems
 - Each commit or change is an event
- DBMS
 - Databases keep a transaction log of all inserts, deletes and updates

Storing state and storing events

- Store state

ID	status	data...
101	accepted	...

Store entity data

- Event sourcing

Entity ID	Entity type	Event ID	Event type	Event data...
101	Order	901	OrderCreated	...
101	Order	902	OrderApproved	...
101	Order	903	OrderShipped	...

Store state changing events

Store the state of a system



Structural representation

List of ordered goods

Payment information

Shipping information


Store the events of a system




Event representation

-  Add item #1
-  Add item #2
-  Add payment info
-  Update item #2
-  Remove item #1
-  Add shipping info


How do we get the state?



Snapshots




Event sourcing advantages



- You don't miss a thing
 - Business can analyze history of events
 - Bugs can be solved easier
- Creates a built-in audit log
- Allows for rewinding or undo changes
- Append is usually more efficient in databases
- No transactions needed

Event sourcing disadvantages



- You cannot easily see what your state is
 - You always have to replay the events first (lower read performance)
 - Always use CQRS when you apply event sourcing
- You need more storage
- What if events have to change?
 - We need event versioning
 - The logic needs to support all versions

When to consider event sourcing?


- When you need an audit log
- When you want to derive additional business value from the event history
- When you need fast performance on the command side

CENTRALIZED CONFIGURATION SERVICE

Configuration in microservices


- Remove settings from code
- Change runtime behavior
- Enforce consistency across elastic services

Local configuration




Local configuration challenges

- When we change the configuration we need to rebuild and redeploy the application
- Configuration may contain sensitive information
- Some of the properties are the same among services: lots of duplication




Spring cloud config server




Spring cloud config

- HTTP access to centralized configuration




Spring cloud config


- File based configuration



- Git based configuration



Spring cloud config example



Configuration server

```
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.cloud.config.server.EnableConfigServer;

@SpringBootApplication
@EnableConfigServer
public class ConfigServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ConfigServiceApplication.class, args);
    }
}
```

Do not use GIT,
but local files

application.properties


```
spring.profiles.active=active
server.port=8888
```

config/ServiceA.yml

```
greeting: Hello from Service A
```

config/ServiceB.yml

```
greeting: Hello from Service B
```




Configuration server



```
{
  "name": "ServiceA",
  "profiles": [
    "default"
  ],
  "label": null,
  "version": null,
  "state": null,
  "propertySources": [
    {
      "name": "classpath:/config/ServiceA.yml",
      "source": {
        "greeting": "Hello from Service A"
      }
    }
  ]
}
```



```
{
  "name": "ServiceB",
  "profiles": [
    "default"
  ],
  "label": null,
  "version": null,
  "state": null,
  "propertySources": [
    {
      "name": "classpath:/config/ServiceB.yml",
      "source": {
        "greeting": "Hello from Service B"
      }
    }
  ]
}
```




Configuration client: ServiceA

```
@SpringBootApplication
public class ServiceAApplication {

    public static void main(String[] args) {
        SpringApplication.run(ServiceAApplication.class, args);
    }
}
```

```
@RestController
public class ServiceAController {
    @Value("${greeting}")
    private String message;

    @RequestMapping("/")
    public String getName() {
        return message;
    }
}
```



application.yml

```
server:
  port: 8090
```

bootstrap.yml

```
spring:
  application:
    name: ServiceA
  cloud:
    config:
      url: http://localhost:8888
```

Spring cloud applications

- 2 configuration files

- bootstrap.yml

- Is loaded before applications.yml
 - Is needed when configuration is stored on a remote config server
 - Contains
 - The name of the application
 - Location of the configuration server

```
spring:                               bootstrap.yml
  application:
    name: ServiceA
  cloud:
    config:
      url: http://localhost:8888
```

- applications.yml

- Contains standard application configuration

application.yml

```
server:
  port: 8090
```


Configuration client: ServiceB

```
@SpringBootApplication
public class ServiceBApplication {

    public static void main(String[] args) {
        SpringApplication.run(ServiceBApplication.class, args);
    }
}
```

```
@RestController
public class ServiceBController {
    @Value("${greeting}")
    private String message;

    @RequestMapping("/")
    public String getName() {
        return message;
    }
}
```




application.yml

```
server:
  port: 8091
```


bootstrap.yml

```
spring:
  application:
    name: ServiceB
  cloud:
    config:
      url: http://localhost:8888
```


Use of the Config Server



Using Git (or GitHub)



Refreshing configuration

- Option 1: use `@RefreshScope` and “/actuator/refresh” event

`@RefreshScope`

```
@RestController
@RefreshScope
public class ServiceAController {
    @Value("${greeting}")
    private String message;

    @RequestMapping("/")
    public String getName() {
        return message;
    }
}
```

```
server:
  port: 8888
```


```
spring:
  cloud:
    config:
      server:
        git:
          uri:
            https://github.com/renespring/springcloud.git
```

Expose the /refresh actuator

```
management:
  endpoints:
    web:
      exposure:
        include: refresh
```


Refreshing configuration

- Option 1: use @RefreshScope and “/actuator/refresh” event




Refreshing configuration

- Option 2: use Spring cloud bus for broadcasting refresh events



Implementing microservices



Challenges of a microservice architecture

Challenge	Solution
Complex communication	Feign Registry API gateway
Performance	
Resilience	Registry replicas Load balancing between multiple service instances Circuit breaker
Security	
Transactions	
Keep data in sync	
Keep interfaces in sync	Spring cloud contract
Keep configuration in sync	Config server
Monitor health of microservices	ELK + beats
Follow/monitor business processes	Zipkin ELK