This version: 2017/08/10
Revising my paper before submitting for publication.

Syntactic Conditions for Antichain Property in CR-Prolog

Vu Phan
Texas Tech University

Abstract

We study syntactic conditions which guarantee when a Consistency Restoring Prolog program has antichain property (no answer set is a proper subset of another). A notable such condition is that the program's dependency graph being acyclic and having no directed path from one cr-rule head literal to another.

Contents

1 Introduction **1**

2 CR-Prolog **2**
2.1 Syntax . . . 2
2.2 Semantics . . . 2

3 Preliminary Results **3**
3.1 Antichain Condition: One CR-Rule . . . 4
3.2 Antichain Condition: Unique CR-Rule Head Literals . . . 4

4 Main Results **6**
4.1 Dependency Graphs . . . 6
4.2 Antichain Condition: Same Abductive Support Heads . . . 7
4.3 Antichain Condition: CR-Independence and Acyclicity . . . 9

5 Conclusion **12**

6 Acknowledgment **12**

1 Introduction

- Answer Set Prolog (A-Prolog) is a programming language for knowledge representation and reasoning (Gelfond and Lifschitz [1988]). An A-Prolog program comprises rules which determine the sets of beliefs that a logical agent can hold. A-Prolog relies on the stable model semantics of logic programs with negation.

- Consistency Restoring Prolog (CR-Prolog) extends A-Prolog with cr-rules (Balduccini and Gelfond [2003]). The cr-rules apply only when the regular rules alone result in a contradiction. These cr-rules are meant to represent exceptions which are very rare but still possible.

- A-Prolog and its extension CR-Prolog have been applied to solve problems in various fields (Erdem et al. [2016]). For instance, a logic program was used to guide multiple robots to collaboratively tidy up a house. Also, a tourism application suggested trips based on user preferences.

- In this paper, we investigate the antichain property that a logic program might have: no answer set is a proper subset of another. Every A-Prolog program has antichain property. However, there exist CR-Prolog programs without antichain property. We look at some syntactic conditions guaranteeing that a CR-Prolog program has this desired semantic property. Such conditions are specified in Theorem 4.3.12 (most notable) as well as Theorem 3.1.3, Corollary 3.1.6, and Propositions 3.2.10 & 4.2.11.

2 CR-Prolog

The complete specifications of A-Prolog and CR-Prolog can be found in [Gelfond and Kahl, 2014, Sections 2.1 & 2.2 & 5.5].

2.1 Syntax

Definition 2.1.1. An **atom** represents a boolean value. A **literal** is either an atom a or its **classical-negation** $\neg a$. An **extended literal** is either a literal l or its **default-negation** $not\ l$.

Definition 2.1.2 (Regular Rule)**.** A **regular rule** r has the form:

$$l_1\ or \ldots or\ l_k \longleftarrow l_{k+1}, \ldots, l_m,\ not\ l_{m+1}, \ldots, not\ l_n.$$

Each l_i above is a literal and $1 \leq k \leq m \leq n$. If $k = m = n$, then we call r a **fact** and write:

$$l_1\ or \ldots or\ l_k.$$

The **head** of the rule r is the disjunction of literals before the arrow "$\longleftarrow$". The **body** of r is the conjunction of extended literals after "$\longleftarrow$".

Definition 2.1.3 (CR-Rule)**.** Similar to a regular rule, a **cr-rule** has the form:

$$l_0 \stackrel{+}{\longleftarrow} l_1, \ldots, l_m,\ not\ l_{m+1}, \ldots, not\ l_n.$$

Definition 2.1.4 (A-Prolog Program)**.** An **A-Prolog program** is a finite set of regular rules.

Definition 2.1.5 (CR-Prolog Program)**.** A **CR-Prolog program** is a finite set of regular rules and cr-rules. Let Π^{reg} and Π^{cr} denote the corresponding subsets of regular rules and cr-rules.

Definition 2.1.6 (Applications of CR-Rules)**.** Let r be a cr-rule. The **application** $\alpha(r)$ is the regular rule obtained from r by replacing "$\stackrel{+}{\longleftarrow}$" with "$\longleftarrow$". If R is a set of cr-rules, then let $\alpha(R) = \{\alpha(r) : r \in R\}$. When $R \subseteq \Pi^{cr}$ (meaning R is a subset of cr-rules in a CR-Prolog program Π), define $\Pi_R = \Pi^{reg} \cup \alpha(R)$.

2.2 Semantics

Definition 2.2.1 (Context)**.** Literals l and l' are **complementary** if $l' = \neg l$ (one is the classical-negation of the other). A set S of literals is a **context** if S contains no pair of complementary literals. Note: for simplicity, we have slightly altered the original definition of a "context" in [Ben-Eliyahu and Dechter, 1994, page 55].

Definition 2.2.2 (Satisfiability)**.** A context S satisfies:

1. a literal l if $l \in S$
2. an extended literal $not\ l$ if $l \notin S$
3. a disjunction $l_1\ or \ldots or\ l_k$ if some $l_i \in S$

4. a conjunction $l_{k+1}, \ldots, l_m,\ not\ l_{m+1}, \ldots, not\ l_n$ if S satisfies all conjuncts (which are extended literals)

5. a rule r if S satisfies the head of r whenever S satisfies the body of r

6. a program Π if S satisfies every rule in Π

Definition 2.2.3 (A-Prolog Answer Set, part 1 of 2)**.** Let Π be an A-Prolog program without default-negation. Then a context S is an answer set of Π if:

1. S satisfies Π, and

2. S is minimal (wrt set-inclusion): no proper subset of S satisfies Π

Definition 2.2.4 (A-Prolog Answer Set, part 2 of 2)**.** Let Π be an A-Prolog program and S be a context. The **reduct** Π^S is the program obtained from Π by:

1. removing each rule containing *not* l such that $l \in S$

2. removing all other extended literals containing *not*

Then S is an answer set of Π if S is an answer set of Π^S. If Π has some answer set, then Π is said to be **consistent**.

Definition 2.2.5 (Abductive Support)**.** Let Π be a CR-Prolog program and $R \subseteq \Pi^{cr}$ (meaning R is a subset of cr-rules in Π). Then R is an **abductive support** of Π if:

1. the A-Prolog program $\Pi^{reg} \cup \alpha(R)$ is consistent, and

2. R is minimal (wrt cardinality): no $R' \subseteq \Pi^{cr}$ exists such that $\Pi^{reg} \cup \alpha(R')$ is consistent where $|R'| < |R|$

Definition 2.2.6 (CR-Prolog Answer Set)**.** Let Π be a CR-Prolog program and S be a context. Then S is an answer set of Π if S is an answer set of $\Pi^{reg} \cup \alpha(R)$ for some abductive support R of Π.

Definition 2.2.7 (Antichain Property)**.** Let Π be a CR-Prolog program. We say Π has **antichain property** if: for all answer sets S_1 and S_2 of Π, we have $S_1 \subseteq S_2 \Rightarrow S_1 = S_2$.

Example 2.2.8 (CR-Prolog Program without Antichain Property)**.** Consider the following program:

$$
\begin{aligned}
a.& \\
\neg a \longleftarrow\ & not\ b, not\ c. \\
b \longleftarrow\ & c. \\
b \xleftarrow{+}\ & . && (r_1) \\
c \xleftarrow{+}\ & . && (r_2)
\end{aligned}
$$

This program has answer sets $S_1 = \{a, b\}$ and $S_2 = \{a, b, c\}$. Observe that $S_1 \subset S_2$ (proper subset). The corresponding abductive supports are $R_1 = \{r_1\}$ and $R_2 = \{r_2\}$.

3 Preliminary Results

This section provides important lemmas.

3.1 Antichain Condition: One CR-Rule

Remark 3.1.1. Every inconsistent CR-Prolog program vacuously has antichain property. So only consistent programs are of interest.

Lemma 3.1.2. Let Π be an A-Prolog program and S_1 & S_2 be contexts. If $S_1 \subseteq S_2$, then $\Pi^{S_2} \subseteq \Pi^{S_1}$ (one reduct is a subset of the other).

Proof. Assume Π^{S_2} has an arbitrary rule r:

$$l_1 \ or \ldots or \ l_k \longleftarrow l_{k+1}, \ldots, l_m.$$

The corresponding rule in Π is:

$$l_1 \ or \ldots or \ l_k \longleftarrow l_{k+1}, \ldots, l_m, \ not \ l_{m+1}, \ldots, not \ l_n.$$

For each i in $\{m+1, \ldots, n\}$, we have $l_i \notin S_2$, so $l_i \notin S_1$ (as $S_1 \subseteq S_2$). Therefore, r is also a rule in Π^{S_1}. □

Theorem 3.1.3 (Antichain Property of A-Prolog Programs, proved by Dr. Michael Gelfond)**.** Let Π be an A-Prolog program and $S_1 \subseteq S_2$ be answer sets of Π. Then $S_1 = S_2$.

Proof. We will show $S_2 \subseteq S_1$.

1. First, S_2 is an answer set of Π^{S_2}. So S_2 is a minimal (wrt set-inclusion) context that satisfies Π^{S_2}. We shall prove $S_2 \subseteq S_1$ by showing S_1 also satisfies Π^{S_2}.

2. By 3.1.2, we have $\Pi^{S_2} \subseteq \Pi^{S_1}$. Because S_1 satisfies Π^{S_1}, we know S_1 also satisfies Π^{S_2}.

□

Definition 3.1.4 (Equivalence of CR-Prolog Programs)**.** Let Π_1 and Π_2 be CR-Prolog programs. We say Π_1 and Π_2 are **equivalent** when: S is an answer set of Π_1 iff S is an answer set of Π_2, for every context S.

Remark 3.1.5. Let Π be a CR-Prolog program. If Π^{reg} is consistent, then Π is equivalent to Π^{reg}, which has antichain property due to Theorem 3.1.3. The interesting case is when Π^{reg} is inconsistent.

Corollary 3.1.6. Let Π be a CR-Prolog program where Π^{reg} is inconsistent. If Π has only one cr-rule, then Π has antichain property.

Proof. Assume $\Pi^{cr} = \{r\}$ for some cr-rule r. Then Π is equivalent to the A-Prolog program $\Pi_{\{r\}} = \Pi^{reg} \cup \alpha(\{r\})$. Simply apply Theorem 3.1.3 to $\Pi_{\{r\}}$. □

3.2 Antichain Condition: Unique CR-Rule Head Literals

Definition 3.2.1 (Useless Regular Rule)**.** Let Π be an A-Prolog program containing some rule r. For an answer set S of Π, we say r is **useless** wrt S if S is an answer set of $\Pi \setminus \{r\}$.

Definition 3.2.2 (Regular Rule Firing)**.** Given a regular rule r and a context S, we say r **fires** wrt S if S satisfies the body of r.

Lemma 3.2.3. Let r be a regular rule and S be a context. Assume the reduct $\{r\}^S = \{r'\}$ for some default-negation-free rule r'. Then r fires iff r' fires, wrt S.

Proof. These two rules have the forms:

$$l_1 \ or \ldots or \ l_k \longleftarrow l_{k+1}, \ldots, l_m, \ not \ l_{m+1}, \ldots, not \ l_n. \tag{r}$$

$$l_1 \ or \ldots or \ l_k \longleftarrow l_{k+1}, \ldots, l_m. \tag{r'}$$

By construction of r' from r, we know $l_i \notin S$ for all $i \in \{m+1, \ldots, n\}$. Then r fires wrt S iff $l_i \in S$ for all $i \in \{k+1, \ldots, m\}$ iff r' fires wrt S. □

Remark 3.2.4. Let r be a regular default-negation-free rule and $S_1 \subseteq S_2$ be contexts. If r fires wrt S_1, then r fires wrt S_2.

Lemma 3.2.5. Let Π be an A-Prolog program containing some rule r and S be an answer set of Π. If r does not fire, then r is useless, wrt S.

Proof. Define the reducts $\Pi_1 = \Pi^S$ and $\Pi_2 = (\Pi \setminus \{r\})^S$. By Definition 2.2.4, S is an answer set of Π_1. We will prove S is an answer set of Π_2.

1. First, S satisfies Π_1. Notice $\Pi_2 \subseteq \Pi_1$. Then S satisfies Π_2.
2. Assume some context $S' \subseteq S$ also satisfies Π_2. We shall show $S' = S$.
   2.1. Case 1 of 2: $\{r\}^S = \varnothing$. Then $\Pi_1 = \Pi_2$, so S' satisfies Π_1.
   2.2. Case 2 of 2: $\{r\}^S = \{r'\}$ for some default-negation-free rule r'. Recall that r does not fire wrt S. By Lemma 3.2.3, r' does not fire wrt S. Since $S' \subseteq S$, using the contrapositive of Remark 3.2.4, we deduce that r' does not fire wrt S'. Then S' vacuously satisfies r'. So S' satisfies $\Pi_1 = \Pi_2 \cup \{r'\}$.

   In both cases, S' satisfies Π_1. As S is an answer set of Π_1, due to minimality, we know $S \subseteq S'$. Since we assumed $S' \subseteq S$, we can now conclude that $S' = S$.
3. We have shown that S is a minimal context which satisfies Π_2. Hence, S is an answer set of Π_2.

□

Lemma 3.2.6. Choose an arbitrary CR-Prolog program Π. Let S be an answer set of Π and R be a corresponding abductive support, meaning S is an answer set of the A-Prolog program $\Pi_R = \Pi^{reg} \cup \alpha(R)$. If cr-rule $r \in R$, then $\alpha(r)$ is not useless wrt S.

Proof. By way of contradiction, assume $\alpha(r)$ is useless wrt S. Then S is an answer set of $\Pi_R \setminus \{\alpha(r)\}$, whereas this program is precisely $\Pi_{R'} = \Pi^{reg} \cup \alpha(R')$ with $R' = R \setminus \{r\}$. So $\Pi_{R'}$ is consistent. By Definition 2.2.5, R is a minimal (wrt cardinality) set of cr-rules whose applications make Π consistent, we have $|R| \leq |R'|$. However, $|R'| = |R| - 1$ (recall $R' = R \setminus \{r\}$), contradiction. □

Lemma 3.2.7. Let Π be a CR-Prolog program with some answer set S and a corresponding abductive support R. If cr-rule $r \in R$, then the application $\alpha(r)$ fires wrt S.

Proof. First, S is an answer set of $\Pi_R = \Pi^{reg} \cup \alpha(R)$. By way of contradiction, assume there exists a cr-rule $r \in R$ such that $\alpha(r)$ does not fire wrt S. By Lemma 3.2.5, $\alpha(r)$ is useless wrt S. However, by Lemma 3.2.6, $\alpha(r)$ is not useless wrt S (as $r \in R$), contradiction. □

Definition 3.2.8 (Head)**.** If r is a rule, then let $head(r)$ denotes the set of literals which appear in the head of r. If R is a set of rules, then let $head(R) = \bigcup_{r \in R} head(r)$.

Definition 3.2.9 (Supported Literal)**.** Let r be a regular rule, l be a literal, and S be a context. We say l is **supported** by r wrt S if:

1. r fires wrt S, and
2. $head(r) \cap S = \{l\}$

[Gelfond and Kahl, 2014, page 43, Proposition 2.2.1]

Proposition 3.2.10. Let Π be a CR-Prolog program. If the literal in the head of each cr-rule does not appear in the head of any other rule, then Π has antichain property.

Proof. Let S_1 and S_2 be answer sets of Π. Assume $S_1 \subseteq S_2$. We will show $S_1 = S_2$.

1. Let R_1 and R_2 respectively be abductive supports for S_1 and S_2. We first prove $R_1 \subseteq R_2$. Choose an arbitrary cr-rule $r \in R_1$. By Lemma 3.2.7, r fires wrt S_1, and S_1 satisfies $head(r) = \{l\}$ where l is a literal. So $l \in S_1$, then $l \in S_2$ (as $S_1 \subseteq S_2$). By the hypothesized syntactic condition, r is the sole rule in Π whose head contains l. Then only r can support l wrt S_2 (in the sense of Definition 3.2.9). So $r \in R_2$.

2. Now that we have shown $R_1 \subseteq R_2$, recall $|R_1| = |R_2|$, as all abductive supports have the same minimal cardinality. Then $R_1 = R_2$, since they are finite sets. Consequently, $\Pi^{reg} \cup \alpha(R_1)$ is equal to $\Pi^{reg} \cup \alpha(R_2)$. So S_1 and S_2 are answer sets of the same A-Prolog program. By Theorem 3.1.3, $S_1 = S_2$.

□

4 Main Results

This section derives weaker syntactic conditions for antichain property.

4.1 Dependency Graphs

Definition 4.1.1 (Positive Body of Rule)**.** Let r be a rule. The **positive body** of r, denoted by $body_+(r)$, is the set of literals in the body of r which are default-negation-free.

Definition 4.1.2 (Dependency Graph)**.** Let Π be a CR-Prolog program. Let G_Π be a graph whose vertices are literals in Π. For each pair of vertices l_1 and l_2 of G_Π, there is a directed edge to l_1 from l_2 if Π has some rule r where $l_1 \in head(r)$ and $l_2 \in body_+(r)$. We say G_Π is the **dependency graph** of Π. Note: a self-loop forms a directed cycle; see Example 4.1.4.

Remark 4.1.3 (Answer Set of Acyclic Program)**.** Let Π be an acyclic A-Prolog program and S be a context. Then S is an answer set of Π iff:

1. S satisfies Π, and

2. every literal in S is supported by a rule in Π wrt S (in the sense of Definition 3.2.9)

[Ben-Eliyahu and Dechter, 1994, page 58, Theorem 2.7]

Example 4.1.4 (Self-Loop Forming Cycle)**.** To the contrary, assume a self-loop does not form a cycle. Consider this A-Prolog program containing the sole rule r:

$$l \longleftarrow l.$$

Let $S = \{l\}$. Notice that:

1. S satisfies Π, and

2. l is supported by r wrt S

However, S is not an answer set of Π. Then Remark 4.1.3 is wrong, contradiction.

Definition 4.1.5 (Head-Cycle)**.** Let Π be a CR-Prolog program with dependency graph G_Π. Let C be a directed cycle in G_Π. Assume:

1. vertices l_1 and l_2 are in C, and

2. there exists a rule $r \in \Pi$ where l_1 and l_2 are in $head(r)$

Then C is a **head-cycle** in Π [Ben-Eliyahu and Dechter, 1994, page 56].

Definition 4.1.6 (Dependent Literals)**.** Let l_1 and l_2 be two literals appearing in a CR-Prolog program Π. We say l_1 **depends** on l_2 if the dependency graph G_Π has a directed path to l_1 from l_2.

Definition 4.1.7 (CR-Literal)**.** Let Π be a CR-Prolog program with some cr-rule r where $head(r) = \{l\}$. We say l is a **cr-literal** in Π.

Definition 4.1.8 (CR-Independence)**.** Let Π be a CR-Prolog program. Then Π is called **cr-independent** if l_1 does not depend on l_2 for all cr-literals l_1 and l_2 in Π.

4.2 Antichain Condition: Same Abductive Support Heads

Remark 4.2.1. Let Π be a CR-Prolog program with some answer set S. Then $S \subseteq head(\Pi)$.

Remark 4.2.2. Let r be a regular rule and S be a context. If r fires wrt S, then the reduct $\{r\}^S \neq \varnothing$.

Remark 4.2.3. Let Π be a CR-Prolog program with some answer set S and a corresponding abductive support R. Let cr-rule $r \in R$. Then the reduct $\{\alpha(r)\}^S \neq \varnothing$ (by Lemma 3.2.7 and Remark 4.2.2).

Lemma 4.2.4. Let Π be a nondisjunctive default-negation-free A-Prolog program. If contexts S_1 and S_2 satisfy Π, then $S_0 = S_1 \cap S_2$ also satisfies Π.

Proof. Let r be a rule in Π. Assume r fires wrt S_0. Then r also fires wrt S_1 and S_2 (as Π is default-negation-free). So S_1 and S_2 satisfy $head(r) = \{l\}$ (since Π is nondisjunctive). Thus l is in S_1, S_2, and S_0. □

Lemma 4.2.5 (Proved by Dr. Michael Gelfond)**.** Let Π be a nondisjunctive default-negation-free A-Prolog program. Assume Π has rules $r_1 \neq r_2$ such that $head(r_1) = head(r_2)$. Let $\Pi_0 = \Pi \setminus \{r_1, r_2\}$, $\Pi_1 = \Pi_0 \cup \{r_1\}$, and $\Pi_2 = \Pi_0 \cup \{r_2\}$. If S is an answer set of Π, then S is also an answer set of either Π_1 or Π_2.

Proof. To the contrary, assume S is an answer set of neither Π_1 nor Π_2. Still, S satisfies both Π_1 and Π_2 (as S satisfies Π). So there exist two proper subsets of S, say S_1 and S_2, which respectively satisfy Π_1 and Π_2 (the programs are default-negation-free).

1. Case 1 of 2: either r_1 fires wrt S_1, or r_2 fires wrt S_2. WOLOG, assume the former. Then S_1 satisfies $head(r_1) = head(r_2)$. So S_1 also satisfies both the rule r_2 and the program $\Pi = \Pi_1 \cup \{r_2\}$. Recall that S is an answer set of Π whereas $S_1 \subset S$ (proper subset), contradicting Definition 2.2.3.

2. Case 2 of 2: neither r_1 fires wrt S_1, nor r_2 fires wrt S_2. So neither r_1 nor r_2 fires wrt $S_0 = S_1 \cap S_2$ (the rules are default-negation-free). Then S_0 vacuously satisfies r_1 and r_2. Because S_1 and S_2 satisfy Π_0, by Lemma 4.2.4, S_0 satisfies Π_0 too. Therefore, S_0 satisfies $\Pi = \Pi_0 \cup \{r_1, r_2\}$. But S is an answer set of Π, and $S_0 \subset S$, contradiction.

□

Lemma 4.2.6. Let Π be a nondisjunctive CR-Prolog program with some abductive support R. For all cr-rules r_1 and r_2 in R, if $head(r_1) = head(r_2)$, then r_1 and r_2 are the same rule.

Proof. By way of contradiction, assume there exist cr-rules $r_1 \neq r_2$ in R where $head(r_1) = head(r_2)$. Some notations:

1. Let $R_1 = R \setminus \{r_2\}$ and $R_2 = R \setminus \{r_1\}$.

2. Let $\Pi_1 = \Pi^{reg} \cup \alpha(R_1)$ and $\Pi_2 = \Pi^{reg} \cup \alpha(R_2)$.

3. Let S be an answer set of Π with a corresponding abductive support R.

4. Let $\Pi_a = (\Pi_1)^S$ and $\Pi_b = (\Pi_2)^S$.

By Lemma 4.2.5, S is an answer set of either Π_a or Π_b. WOLOG, assume the former. Then S is an answer set of Π_1. So R_1 is another abductive support of Π, but $|R_1| < |R|$ (recall $R_1 = R \setminus \{r_2\}$), contradicting Definition 2.2.5. □

Lemma 4.2.7. Let Π be an acyclic CR-Prolog program having some answer set S with a corresponding abductive support R. Let cr-rule $r \in R$ where $head(r) = \{l\}$. Then $\alpha(r)$ is the only rule in $\Pi_R = \Pi^{reg} \cup \alpha(R)$ which supports literal l wrt S.

Proof. By way of contradiction, assume l is also supported by a rule $r' \neq \alpha(r)$ in Π_R. Let $R' = R \setminus \{r\}$ and $\Pi' = \Pi^{reg} \cup \alpha(R')$. We will prove S is an answer set of Π':

1. First, S satisfies $\Pi' \subseteq \Pi_R$.
2. Let l' be an arbitrary literal in S. We show l' is supported wrt S by some rule in Π'. Recall that S is an answer set of Π_R. Applying Remark 4.1.3 to Π_R, we know l' is supported wrt S by some rule r_0 in Π_R.
   2.1. Case 1 of 2: $r_0 = \alpha(r)$. Recall $head(r) = \{l\}$. Then $l = l'$. Notice r' also supports $l' = l$ wrt S, and $r' \in \Pi'$.
   2.2. Case 2 of 2: $r_0 \neq \alpha(r)$. Then $r_0 \in \Pi'$ by construction.

   In both cases, l' is supported by some rule in Π' wrt S.

Applying Remark 4.1.3 to Π', we deduce that S is an answer set of Π'. So Π' is consistent, and R' is an abductive support of Π. But $|R'| < |R|$, contradiction. □

Definition 4.2.8 (Factified Rule)**.** For a regular rule r, let $\phi(r)$ denote the **factified rule** obtained from r by dropping its body. If R is a set of rules, then define $\phi(R) = \{\phi(r) : r \in R\}$.

Lemma 4.2.9. Let Π be a CR-Prolog program with some answer set S and a corresponding abductive support R. Then S is also an answer set of the A-Prolog program $\Pi' = \Pi^{reg} \cup \phi(\alpha(R))$.

Proof. We prove S is a minimal context which satisfies the reduct $(\Pi')^S$:

1. Let $\Pi_R = \Pi^{reg} \cup \alpha(R)$. Recall S is an answer set of and thus satisfies $(\Pi_R)^S = (\Pi^{reg})^S \cup (\alpha(R))^S$. Since R is a corresponding abductive support, $head(R) \subseteq S$. Of course, $head(\phi(\alpha(R))) = head(\alpha(R)) = head(R)$. Then S satisfies $(\Pi')^S = (\Pi^{reg})^S \cup \phi(\alpha(R))$.
2. Assume some context $S' \subseteq S$ also satisfies $(\Pi')^S$. Since $\phi(\alpha(R))$ contains only facts, we know $head(\alpha(R)) = head(\phi(\alpha(R))) \subseteq S'$. Then S' satisfies $(\Pi_R)^S$. So $S \subseteq S'$ (recall S is an answer set of Π_R). Therefore $S' = S$.

□

Lemma 4.2.10. Let Π be a CR-Prolog program with answer sets $S_1 \subseteq S_2$ and corresponding abductive supports R_1 & R_2, respectively. If $head(R_1) = head(R_2)$, then $S_1 = S_2$.

Proof. By Lemma 4.2.9, S_1 and S_2 are respectively answer sets of $\Pi^{reg} \cup \phi(\alpha(R_1))$ and $\Pi^{reg} \cup \phi(\alpha(R_2))$, which are the same A-Prolog program because $head(R_1) = head(R_2)$. By Theorem 3.1.3, $S_1 \subseteq S_2 \Rightarrow S_1 = S_2$. □

Proposition 4.2.11. Let Π be a CR-Prolog program. Then Π has antichain property if $head(R_1) = head(R_2)$ for all abductive supports R_1 and R_2 of Π.

Proof. Let S_1 and S_2 be arbitrary answer sets of Π corresponding to some abductive supports R_1 and R_2, respectively. By Lemma 4.2.10, $S_1 \subseteq S_2 \Rightarrow S_1 = S_2$. □

4.3 Antichain Condition: CR-Independence and Acyclicity

Definition 4.3.1 (Proof of Literal)**.** Let Π be an A-Prolog program, S be a context, and l be a literal. A **proof** of l wrt S in Π is a nonempty sequence of rules $p = \langle r_1, \ldots, r_n \rangle$ in Π such that:

1. for each rule r_i, there is a (sole) literal supported by r wrt S; we call this literal $h_S(r)$
2. $l = h_S(r_n)$
3. $body_+(r_1) = \varnothing$
4. for every rule r_i, each literal in $body_+(r_i)$ is $h_S(r_j)$ for some $j < i$

[Ben-Eliyahu and Dechter, 1994, page 57]

Note on point 3. Their original definition states: r_1 is a fact. However, there is an error in their Lemma B.5 on page 83. Consider the acyclic A-Prolog program $\{a \longleftarrow not\ b.\}$ with the answer set $\{a\}$.

Additional notations:

- $P(l, S, \Pi)$ denotes the set of all proofs p of l wrt S in Π; a proof $p \in P(l, S, \Pi)$ is called **minimal** if p is shortest (containing fewest rules)
- $h_S(p)$ denotes $\{h_S(r) : r \in p\}$
- $body_+(p)$ denotes $\{body_+(r) : r \in p\}$

Remark 4.3.2. Let $p = \langle r_1, \ldots, r_n \rangle$ be a proof in $P(l, S, \Pi)$; as usual, each r_i is a rule, l is a literal, S is a context, and Π is an A-Prolog program. We adopt the convention that the rules in p are pairwise distinct. Indeed, if there were rules $r_i = r_j$ where $i < j$, then $p' = \langle r_1, \ldots, r_{j-1} \rangle, \langle r_{j+1}, \ldots, r_n \rangle$ would be a shorter proof in $P(l, S, \Pi)$, and r_j would be redundant.

Remark 4.3.3. Let Π be a head-cycle-free A-Prolog program with an answer set S. Then each literal in S has a proof wrt S in Π [Ben-Eliyahu and Dechter, 1994, page 57, Theorem 2.3].

Definition 4.3.4 (Rank of Literal)**.** Let Π be a head-cycle-free A-Prolog program, S be a context, and l be a literal. The **rank** $rank(l, S, \Pi)$ of l wrt S in Π is $\min\{|p| : p \in P(l, S, \Pi)\}$, which is the length of a shortest proof p of l wrt S in Π.

Definition 4.3.5 (Ranking Function)**.** Let:

1. Π be a head-cycle-free A-Prolog program
2. S be an answer set of Π
3. f be a function from S to the set of positive integers

Then f is called the **ranking function** wrt S in Π if $f(l) = rank(l, S, \Pi)$ for all $l \in S$.

Definition 4.3.6 (Normal Proof of Literal)**.** Let:

1. Π be a head-cycle-free A-Prolog program
2. S be an answer set of Π
3. l be a literal in S
4. $p \in P(l, S, \Pi)$; recall that this notation means p is a proof of l wrt S in Π

5. f be the ranking function wrt S in Π

We say p is a **normal proof** of l wrt S in Π if: for each rule $r \in p$ and each literal $l' \in body_+(r)$, we have $f(h_S(r)) > f(l')$. This definition is inspired by [Ben-Eliyahu and Dechter, 1994, page 59, Theorem 2.8].

Remark 4.3.7. Let:

1. Π be a head-cycle-free A-Prolog program
2. S be an answer set of Π
3. f be the ranking function wrt S in Π
4. l be a literal in S
5. $p = \langle r_1, \ldots, r_n \rangle$ be a normal proof in $P(l, S, \Pi)$
6. r_i be a rule in p
7. l' be a literal in $body_+(r_i)$

Then:

1. $f(l) > f(l')$
2. $p_i = \langle r_1, \ldots, r_i \rangle$ is a normal proof of $h_S(r_i)$

Lemma 4.3.8. Let:

1. Π_1 and Π_2 be head-cycle-free A-Prolog programs with corresponding answer sets $S_1 \subset S_2$ (proper subset)
2. l be a literal in $S_2 \setminus S_1$
3. $p = \langle r_1, \ldots, r_n \rangle$ be a normal proof in $P(l, S_2, \Pi_2)$, so $h_{S_2}(r_n) = l$

Then there exists a rule $r \in p$ such that $r \in \Pi_2 \setminus \Pi_1$.

Proof. Let f be the ranking function wrt S_2 in Π_2. We employ induction on $f(l)$.

- Base step: $f(l) = \min\{f(l_0) : l_0 \in S_2 \setminus S_1\}$.
  1. To the contrary, assume: for every rule $r \in p$, we have $r \in \Pi_1 \cap \Pi_2$.
  2. Then $r_n \in \Pi_1$.
  3. Since p is a normal proof of l, for each literal $l' \in body_+(r_n)$, we have $f(l') < f(l) = \min\{f(l_0) : l_0 \in S_2 \setminus S_1\}$, so $l' \in S_1 \cap S_2$.
  4. Then r_n fires wrt S_1 (recall: r_n fires wrt S_2, and $S_1 \subset S_2$).
  5. As S_1 is an answer set of Π_1, we know S_1 satisfies $head(r_n)$.
  6. Let l' be a literal in $head(r_n)$.
     6.1. Case 1 of 2: $l' = l$. We already assumed $l \in S_2 \setminus S_1$.
     6.2. Case 2 of 2: $l' \neq l$. We have $l' \notin S_2$ (as only l is supported by r_n wrt S_2 in Π_2), so $l' \notin S_1$.

     In both cases, $l' \notin S_1$. So S_1 does not satisfy $head(r_n)$, contradiction.
- Induction step: $f(l) \leq \max\{f(l_0) : l_0 \in S_2 \setminus S_1\}$.

1. Induction hypothesis: for each literal $l' \in S_2 \setminus S_1$, let p' be a normal proof in $P(l', S_2, \Pi_2)$, if $f(l') < f(l)$, then there exists a rule $r \in p'$ such that $r \in \Pi_2 \setminus \Pi_1$.
2. To the contrary, assume for every rule $r \in p$, we have $r \in \Pi_1 \cap \Pi_2$.
   2.1. Case 1 of 2: there exists a literal $l' \in body_+(r_n)$ where $l' \in S_2 \setminus S_1$.
      2.1.1. Notice $f(l') < f(l) = h_{S_2}(r_n)$.
      2.1.2. Choose some positive integer $m < n$ where $h_{S_2}(r_m) = l'$.
      2.1.3. As $p = \langle r_1, \ldots, r_n \rangle$ is a normal proof of l, we know $p' = \langle r_1, \ldots, r_m \rangle$ is a normal proof of l', wrt S_2 in Π_2.
      2.1.4. By the induction hypothesis, p' contains some rule $r' \in \Pi_2 \setminus \Pi_1$.
      2.1.5. So p also contains r'.
      2.1.6. But we assumed $r \in \Pi_1 \cap \Pi_2$ for every rule $r \in p$, contradiction.
   2.2. Case 2 of 2: for every literal $l' \in body_+(r_n)$, we have $l' \in S_1 \cap S_2$.
      2.2.1. Then the rule r_n fires wrt S_1.
      2.2.2. By our assumption, $r_n \in \Pi_1$.
      2.2.3. As S_1 is an answer set of Π_1, we know S_1 satisfies $head(r_n)$.
      2.2.4. Let l' be a literal in $head(r_n)$.
         2.2.4.1. Subcase 1 of 2: $l' = l$. We already assumed $l \in S_2 \setminus S_1$.
         2.2.4.2. Subcase 2 of 2: $l' \neq l$. We have $l' \notin S_2$ (as only l is supported by r_n wrt S_2 in Π_2), so $l' \notin S_1$.

         In both subcases, $l' \notin S_1$. So S_1 does not satisfy $head(r_n)$, contradiction.

□

Remark 4.3.9. Let $p = \langle r_1, \ldots, r_n \rangle$ be a proof in $P(l, S, \Pi)$. If p is a minimal proof, then:

1. p is a normal proof
2. l depends on $h_S(r_i)$ for all $i < n$ (in the sense of Definition 4.1.6)

Lemma 4.3.10. Let Π be a nondisjunctive acyclic CR-Prolog program. If Π has answer sets $S_1 \subset S_2$, then there exist literals l_1 and l_2 in $head(\Pi^{cr})$ such that l_1 depends on l_2.

Proof. Some notations first:

1. By the contrapositive of Lemma 4.2.10, there exist abductive supports R_1 and R_2 (respectively corresponding to S_1 and S_2) where $head(R_1) \neq head(R_2)$.
2. Define two sets of facts: ${R_1}' = \phi(\alpha(R_1))$ and ${R_2}' = \phi(\alpha(R_2))$.
3. Introduce A-Prolog programs $\Pi_1 = \Pi^{reg} \cup {R_1}'$ and $\Pi_2 = \Pi^{reg} \cup {R_2}'$. By Lemma 4.2.9, S_1 and S_2 are respectively answer sets of Π_1 and Π_2.

We follow these steps:

1. Note that Π_1 and Π_2 are nondisjunctive. By the contrapositive of Lemma 4.2.6, the cr-literals appearing in R_1 are pairwise distinct. So are the cr-literals appearing in R_2. Then $|{R_1}'| = |R_1|$ and $|{R_2}'| = |R_2|$.
2. Notice $|R_1| = |R_2| > 0$. Then $|{R_1}'| = |{R_2}'| > 0$.
3. Observe $|head({R_1}')| = |{R_1}'|$ and $|head({R_2}')| = |{R_2}'|$. Thus $|head({R_1}')| = |head({R_2}')| > 0$.
4. Recall $head({R_1}') = head(R_1) \neq head(R_2) = head({R_2}')$. Then $head({R_1}') \setminus head({R_2}') \neq \varnothing$.

5. Select some literal $l_1 \in head(R_1{}') \setminus head(R_2{}')$. Let r_1 be the fact "l_1." in $R_1{}' \setminus R_2{}'$.

6. Since S_1 is an answer set of Π_1, we have $l_1 \in S_1$. Recall $S_1 \subset S_2$. Then $l_1 \in S_2$.

7. As S_2 is an answer set of Π_2, there exists a rule $r \in \Pi_2$ which supports l_1 wrt S_2. Note that $body_+(r) \subseteq S_2$.

   7.1. Case 1 of 2: there exists a literal $l \in body_+(r)$ where $l \in S_2 \setminus S_1$.

      7.1.1. Let p be a minimal proof in $P(l, S_2, \Pi_2)$.

      7.1.2. By Lemma 4.3.8, there exists a rule $r_2 \in p$ where $r_2 \in \Pi_2 \setminus \Pi_1$.

      7.1.3. Then $r_2 \in R_2{}' \setminus R_1{}' \subseteq \alpha(\Pi^{cr})$. Let literal $l_2 = h_{S_2}(r_2) \in head(\Pi^{cr})$.

      7.1.4. As p is a minimal proof, l depends on l_2.

      7.1.5. Recall l_1 depends on l in r. By transitivity, l_1 depends on l_2.

   7.2. Case 2 of 2: $body_+(r) \subseteq S_1 \subset S_2$. We show that this case is impossible.

      7.2.1. Subcase 1 of 2: $r \in \Pi_1 \cap \Pi_2$.

         7.2.1.1. Recall r supports l_1 wrt S_2. Since $body_+(r) \subseteq S_1 \subset S_2$, we know r also supports l_1 wrt S_1.

         7.2.1.2. Applying Lemma 4.2.7 to Π_1, we have $r = r_1$.

         7.2.1.3. However, $r \in \Pi_2$ whereas $r_1 \in \Pi_1 \setminus \Pi_2$, contradiction.

      7.2.2. Subcase 2 of 2: $r \in \Pi_2 \setminus \Pi_1$.

         7.2.2.1. So $r \in R_2{}' \setminus R_1{}'$. Then r is the fact "l_1.", which is exactly r_1.

         7.2.2.2. However, we selected r_1 from $R_1{}' \setminus R_2{}'$ while $r \in R_2{}'$, contradiction.

□

Remark 4.3.11. If a CR-Prolog program Π is acyclic, then there exists a nondisjunctive acyclic CR-Prolog program Π' equivalent to Π [Ben-Eliyahu and Dechter, 1994, page 73, Theorem 4.17].

Theorem 4.3.12 (Antichain Property of CR-Independent Acyclic CR-Prolog Programs)**.** Let Π be an acyclic CR-Prolog program. If Π is cr-independent, then Π has antichain property.

Proof. By Remark 4.3.11, there exists a nondisjunctive acyclic CR-Prolog Π' equivalent to Π. By the contrapositive of Lemma 4.3.10, Π' has antichain property. Therefore, Π has antichain property too. □

5 Conclusion

We have found a reasonably weak syntactic condition which guarantees that a CR-Prolog program has antichain property: the program being acyclic and cr-independent. The future goal is to further relax this sufficient condition to extend the class of CR-Prolog programs known to have antichain property.

6 Acknowledgment

We sincerely appreciate the significant guidance of Dr. Michael Gelfond. This paper includes his proofs of Theorem 3.1.3 and Lemma 4.2.5. We also thank Evgenii Balai for the informative discussions.

References

Marcello Balduccini and Michael Gelfond. Logic programs with consistency-restoring rules. In *International Symposium on Logical Formalization of Commonsense Reasoning, AAAI 2003 Spring Symposium Series*, volume 102, 2003.

Rachel Ben-Eliyahu and Rina Dechter. Propositional semantics for disjunctive logic programs. *Annals of Mathematics and Artificial intelligence*, 12(1):53–87, 1994.

Esra Erdem, Michael Gelfond, and Nicola Leone. Applications of answer set programming. *AI Magazine*, 37 (3):53–68, 2016.

Michael Gelfond and Yulia Kahl. *Knowledge representation, reasoning, and the design of intelligent agents: The answer-set programming approach*. Cambridge University Press, 2014.

Michael Gelfond and Vladimir Lifschitz. The stable model semantics for logic programming. In *ICLP/SLP*, volume 88, pages 1070–1080, 1988.