

1. What will the following code output to the screen?

```
def velocity(x):  
    return speed + x  
  
speed = 10  
new_speed = velocity(10)  
new_speed = velocity(speed)  
print(new_speed)
```

The code is erroneous and cannot be run.

30

20

10

2. What will the following code output to the screen?

```
def do_the_mess(parameter):  
    global variable  
    variable += parameter[0]  
    return variable  
  
the_list = [x for x in range(2, 3)]  
variable = 0  
do_the_mess(the_list)  
print(variable)
```

A. The code prints 1.

B. The code prints 0.

C. The code prints 2.

D. The code raises an unhandled exception.

3. What will the following code output to the screen?

```
def do_the_mess(parameter):  
    parameter[0] += variable  
    return variable  
  
the_list = [x for x in range(2, 3)]  
variable = -1  
do_the_mess(the_list)  
print(the_list[0])
```

E. The code prints 1.

F. The code prints 0.

G. The code prints 2.

H. The code raises an unhandled exception.

4. What will the following code output to the screen?

```
x = []  
x.insert(0, 2)  
x.append(3)  
duplicate = x  
duplicate.append(2)  
print(x[-1] + duplicate[-1])
```

A. 5

B. 6

C. 4

D. The code raises an exception and outputs nothing.

5. What will the following code output to the screen?

```
rates = (1.2,1.4,1.0)
new = rates[3: ]
for rate in rates [-2: ]:
    new+= (rate, )
print(len(new))
```

A. 1

B. 2

C. Error

D. 5

6. What will the following code output to the screen?

```
rates = (1.2,1.4,1.0)
new = rates[3: ]
for rate in rates [-2: ]:
    new+= (rate )
print(len(new))
```

A. 1

B. 2

C. Error.

D. 5

7. What is the result of the following code?

```
prices = { "pizza": 3.99 }  
try:  
    charge = prices["calzone"]  
    print("Charged")  
except KeyError:  
    print("Unavailable")  
except:  
    print("Out of bounds")
```

A. A. Charged

B. Unavailable

C. Out of bounds

D. The code raises an exception.

8. What is the result of the following code?

```
menu = {"syrniki": 12.8, "shashlik": 49.9, "borscht": 23.2}  
  
for value in menu.items():  
    print(value[1], end="")
```

A. The code is erroneous and cannot be run.

B. . yh

C. 12.849.923.2

D. 293

9. What is the result of the following code?

```
d = {'a': [1, 2, 3], 'b': (0, 1), 'c': [2, 3, 4, 5]}
```

```
for i in d.values():
```

```
    print(i[0])
```

A. 1

0

2

B. a1

b0

c2

C. 2

1

3

D. Error

10. What is the result of the following code?

```
d = {'a': [1, 2, 3], 'b': (0, 1), 'c': [2, 3, 4, 5]}
```

```
for i in d.keys():
```

```
    print(d[i][1])
```

E. 2

1

2

F. a1

b0

c2

G. 2

1

3

H. Error

11. What is the result of the following code?

```
equals = 0
```

```
for i in range(2):
```

```
    for j in range(2):
```

```
        if i == j:
```

```
            equals += 1
```

```
        else:
```

```
            equals += 1
```

```
print(equals)
```

A. The code outputs nothing.

B. 4

C. 1

D. 3

12. What is the result of the following code?

```
d={"a":1,"b":2,"c":3}
```

```
print(d.get("d","key not found"))
```

A. 1

B. Key not found

C. None

D. Error

13. Arrange the code boxes to create a valid line of code which retrieves Martin Eden's phone number and assigns it to the number variable.

```
phone_dir = {  
    "Martin Eden": "555-1234",  
    "Alice": "555-5678"  
}
```

Note: this dictionary doesn't come with the exam

A.	[	
B.	phone_dir	
C.	number	
D.	"Martin Eden"	
E.	=	
F.	]	

C

E

B

A

D

F

14.D

```
def i(end , foo=0):  
    if end>0:
```



```
        foo=i(end-1,foo+end)

    return foo

print(i(2))
```

- A. 3
- B. 0
- C. 1
- D. 2

15.D

```
total=0
for i in range(5):
    if i% 2==1:
        total +=1
    else:
        total -=1
print(total)
```

- A. the code output 3
- B. the code enter an infinte loop
- C. the code output 2
- D. the code output 1

16.What is the expected output of the following code?

```
def runner(brand, model="", year=2021, convertible=False):
    return (brand, str(year), str(convertible))

print(runner("Fermi")[2][2])
```

- A. ('Fermi', '2021', 'False')
- B. 1

- C. False
- D. The code raises an unhandled exception.

17. Assuming that Barry Lyndon has the following phone number: 555123447
Arrange the code boxes to create a valid line of code , which makes a relevant
phones directory entry within phone_dir dictionary

note ("Barry Lyndon" is the key)

A.	{	
B.	"5551234567"	
C.	number	
D.	"Barry Lyndon"	
E.	=	
F.	}	
G.	:	

- A. CEADGBF
- B. DEACGBF
- C. CEABGDF
- D. CEADGB

18. What is the expected output of the following code?

```
def runner(brand,model="",year=2021, convertible=True):  
    return brand+model+str(convertible)  
print(runner(model="Reluctance", 2019)[1])
```

- A. e
- B. The code raises an unhandled exception.
- C. Reluctance
- D. True

19. What will the following code output to the screen?

```
def velocity(x):  
    return speed + x  
  
speed = 0  
new_speed = velocity(10)  
new_speed = velocity(speed)  
print(new_speed)
```

- A. The code is erroneous and cannot be run.
- B. 30
- C. 20
- D. 10