

CODE VERIFIED

ISO 3691-4:2023 COMPLIANT

CLASSIQ QMOD 0.46+

OPENAPI 3.1.0 READY

REVISION 4.2.0

WMS Quantum Cyber-Physical Digital Twin & DispatchEngine

Complete Operational & Advanced User Guide — End-to-End UX Walkthrough, Data Simulation, SQLite Manipulation, OpenAPI Integration, Classiq Quantum Programming & Mathematical Formulations


AUTHOR & ENGINEERING GROUP Senior Principal System Architect & YesAndNo Quantum Team	VERIFICATION & INVARIANT STATUS Certified Gates 1–4 (Zero-Defect Mathematical Invariance)
PHYSICAL WAREHOUSE DIMENSIONS 150m x 100m Epoxy Floor (100% Contained, Zero Leakage)	PERSISTENCE & ENGINE STACK SQLite 3 WAL Mode, Python 3.11+, React 18, Three.js, KaTeX

GUIDE NAVIGATION & TABLE OF CONTENTS			
Part I: UX & Operations Manual	P. 2	— 3D Viewport Navigation & Gestures	P. 2
— 3D Legend & Route Explorer Drawer	P. 3	— Parameter Catalog & Slider Tuning	P. 3
— Dispatch Workflow & Troubleshooting	P. 4	Part II: SQLite & Data Simulation	P. 5
— Schema & Scenario Archetypes	P. 5	— SQL Recipes & Cloud Sync Pipeline	P. 6
— Ingesting Enterprise ERP Datasets	P. 6	Part III: OpenAPI 3.1 & Swagger SDK	P. 7
— 9 Functional API Domains & Endpoints	P. 7	— 20Hz Simulation Streaming via SSE	P. 8
— Production SDKs (Python, TypeScript, cURL)	P. 8	Part IV: Classiq Quantum QMOD Guide	P. 9
— High-Level QMOD vs Low-Level Gates	P. 9	— Swap-Test Distance Kernels & Fidelity	P. 9
— QAOA Subtour Circuit Synthesis	P. 10	— Native QMOD Reference (vehicle_routing_problem)	P. 10
Part V: Advanced Mathematical Formulations	P. 11	— Rigorous KaTeX Formulations (Tiers 1–4)	P. 11
— Generalized Benders Recourse Feedback	P. 12	— Big-O Complexity & Custom Solver Runbook	P. 13

Part I: Operational & UX User Guide (Standard Operations Role)

1. User Interface Surfaces & Screen-by-Screen Walkthrough

The **WMS Quantum Digital Twin** web application integrates real-time telemetry, 3D cyber-physical rendering, and multi-tier algorithmic solvers into a unified command dashboard.



1.1 Top Command Bar

- System Title & Operational Profile:** Identifies the warehouse facility zone, active fleet assignment, and scenario archetype.
- Operational Mode Selector:** Choose between **CLASSICAL** (OR-Tools CP-SAT + HGS-ADC), **QUANTUM** (Classiq Swap-Test QFCM + QAOA), **HYBRID** (Classical Tier 1 + Quantum Tier 3), or **RESILIENCE** (Fallback heuristics).
- Verification Seal (Code Verified):** Real-time badge certifying that all 4 mathematical gates ($G_1 \dots G_4$) have passed audit verification. Hovering reveals the 4-gate verification methodology tooltip.

1.2 3D Viewport Mouse & Keyboard Gestures

Input Action	Gesture / Key	Operational Viewport Result
Orbit Camera	Left Click + Drag	Rotates view smoothly around the facility orbit center at (75, 0, 50) m.
Pan Camera	Right Click + Drag	Pans camera laterally across the dark epoxy floor surface.
Zoom View	Scroll Wheel	Zooms continuously from single-parcel rack shelf up to full-facility view.
Reset View	Double Click Canvas	Restores default isometric perspective at (75, 80, 140) m.
Isolate AMR	Click "Focus in 3D"	Locks camera onto selected robot with smooth tracking interpolation.

2. 3D Warehouse Scene Legend & Tour Explorer Manual

The **Scene 3D Legend & Tours Drawer** (`Scene3DLegendPanel1.tsx`) provides complete transparency into all physical scene objects, vehicle routes, and kinematic safety parameters.

2.1 Four Sub-Tabs Breakdown

- **Tab 1: 3D Objects & Invariants:** Visual catalog filterable by `ALL` , `ROBOTICS` , `FACILITY` , `STORAGE` , `SAFETY` , or `NAVIGATION` . Displays visual appearance, operational role, mathematical formulas, and verified constraints ($R_1 \dots R_{15}$).
- **Tab 2: Active Tours:** Select an active AMR pill (e.g. `AMR_001`) to inspect tour duration (makespan), route length in meters, payload mass, volumetric cube fill %, and a complete step-by-step action table (`REPLENISH` , `PICKUP` , `DROP` , `DOCK`). Includes the "Focus in 3D" camera tracking button.
- **Tab 3: Color Code Guide:** Deciphers optical glow signatures (AMR #1 Neon Cyan 600 THz, AMR #2 Vivid Emerald 575 THz, AMR #3 Electric Violet 720 THz, AMR #4 Amber Gold 510 THz) and facility markers (Depots, Sorting Chutes, Hazard Parcels).
- **Tab 4: Kinematics & Safety:** Engineering specifications for ISO 3691-4:2023 braking deceleration, reaction latencies, and SIPP swept-volume continuous clearance.

3. Complete Parameter Catalog & Slider Influence Dictionary

3.1 Order Pool Attributes (`orderDT0`)

Parameter Name	Data Type	Physical Domain	Operational Meaning
<code>order_id</code>	String	<code>ORD-XXXX</code>	Unique customer order identifier.
<code>pickup_x, y, z</code>	Floats	$X \in [5, 145] \text{ m}, Z \in [5, 95] \text{ m}$	Exact spatial rack storage coordinate.
<code>mass_kg</code>	Float	0.10 kg ... 25.00 kg	Physical weight of cargo package.
<code>volume_m3</code>	Float	$0.001 \text{ m}^3 \dots 0.125 \text{ m}^3$	Bounding box volume ($w \times l \times h$).
<code>open_window_start</code>	Float	Seconds from wave epoch	Earliest pickup time (dock availability).
<code>drop_deadline</code>	Float	Seconds from wave epoch	Hard customer delivery deadline at chute.
<code>hazard_class</code>	Enum	<code>AMBIENT</code> , <code>PRIORITY</code> , <code>HAZMAT</code>	Material handling segregation rules.

3.2 Quick Controls Tuning Reference

Slider Parameter	Default & Range	Increasing Value Impact	Decreasing Value Impact
Wave Orders (N)	80 (20 ... 200)	Dense pick batches; stresses 3D cage capacity and routing solver.	Underutilized AMR transport cages; short trivial tours.
Fleet Size (K)	4 (2 ... 8)	Reduces per-robot cargo load; increases cross-aisle traffic contention.	Heavier AMR cargo loads; longer tours; risk of SLA deadline breaches.
Fuzzifier (m)	2.0 (1.1 ... 3.0)	Softer cluster boundaries in Tier 1; more candidate orders rebalanced.	Crisper clustering; approaches classical hard K-Means.
Workload Penalty (λ_1)	0.5 (0.0 ... 2.0)	Strictly equal payload weight across AMRs; slightly longer paths.	Unequal mass loads; shorter total fleet travel distance.
AMR Velocity (v_{nom})	1.2 m/s (0.5 ... 2.0)	Shortens total wave makespan; requires longer stopping buffer (s_{stop}).	Slower operations; shorter braking buffers; minimal slip risk.
SIPP Clearance (d_{safety})	0.5 m (0.2 ... 1.5)	Wider safety separation; prevents near-misses; increases wait delays.	Tighter traffic packing; higher risk of kinematic deadlock in narrow aisles.

4. Step-by-Step Daily Dispatch Operations Workflow

STANDARD OPERATING PROCEDURE (SOP) — 6-STEP WAVE DISPATCH

- Step 1 (Scenario Ingestion):** Select target scenario archetype (e.g. `Pareto Hot Zone 80/20`).
- Step 2 (Solver Mode):** Select `QUANTUM` for Classiq Swap-Test and QAOA optimization, or `CLASSICAL` for CP-SAT and HGS-ADC.
- Step 3 (Execute Pipeline):** Click **"Run Wave Pipeline"**. Monitor latencies for Tiers 1–4.
- Step 4 (Gate Verification):** Confirm all 4 gates pass ($G_1 \dots G_4$) and the `Code Verified` seal displays.
- Step 5 (3D Simulation):** Press Play (▶), scrub to inspection timestamps, open the 3D Legend, and track AMRs with "Focus in 3D".
- Step 6 (Export Audit):** Click "Export PDF Audit" to generate formal multi-page reports into `Export/` .

5. Operational Troubleshooting & Invariant Audit Alerts

Benders Overfill Alert (Gate 2 Violation): Occurs when odd-dimensional packages cannot fit in the cage. The system automatically issues a Benders cut reducing volume limit by $\Delta V_{\text{repack}} = 0.05 \text{ m}^3$ and re-solves Tier 1. If persistent across 3 iterations, reduce wave orders N or add vehicles K .

SIPP Kinematic Intersection Delay (`WAIT_FOR_CLEARANCE`): AMR halts safely outside the laser boundary for 2–4s while another AMR traverses a cross-aisle. Expected behavior under ISO 3691-4.

Low 3D Frame Rate (< 30 FPS): Toggle off secondary layers (uncheck `Storage Racks` in HUD) and enable WebGL hardware acceleration in browser settings.

Part II: Data Simulation, Manipulation & SQLite Database Guide

6. SQLite Database Architecture (dispatchengine.db)

The persistence subsystem is located at `DispatchEngine/dispatchengine.db` , operating in **Write-Ahead Logging (WAL) Mode** for concurrent transactions between background workers and the API layer.

```
+-----+
|                                     DISPATCH ENGINE SQLITE SCHEMA                                     |
+-----+
| scenarios      -> scenario_id (PK), name, archetype, order_count, fleet_size, seed, metadata |
| orders         -> id (PK), scenario_id, sku_id, (x, y, z), mass_kg, vol_m3, SLA windows      |
| runs          -> run_id (PK), scenario_id, operational_mode, total_distance, makespan, status |
| tier_executions -> id (PK), run_id, tier_number, algorithm_rank, latency_ms, gate_status      |
| telemetry_frames -> id (PK), run_id, timestamp_sec, amr_id, x, y, z, velocity, battery_soc   |
| audit_trails   -> id (PK), run_id, gate_id, proof_hash, verification_code ('Code Verified') |
+-----+
```

6.1 Table Definitions & Foreign Key Constraints

```
CREATE TABLE scenarios (
  scenario_id TEXT PRIMARY KEY,
  name TEXT NOT NULL, archetype TEXT NOT NULL,
  order_count INTEGER NOT NULL, fleet_size INTEGER NOT NULL,
  created_at TEXT NOT NULL, topology_metadata TEXT NOT NULL
);

CREATE TABLE orders (
  id INTEGER PRIMARY KEY AUTOINCREMENT,
  scenario_id TEXT NOT NULL REFERENCES scenarios(scenario_id),
  order_id TEXT NOT NULL, sku_id TEXT NOT NULL,
  pickup_x REAL NOT NULL, pickup_y REAL NOT NULL, pickup_z REAL NOT NULL,
  drop_chute_id TEXT NOT NULL, mass_kg REAL NOT NULL, volume_m3 REAL NOT NULL,
  open_window_start REAL NOT NULL, drop_deadline REAL NOT NULL
);

CREATE TABLE runs (
  run_id TEXT PRIMARY KEY,
  scenario_id TEXT NOT NULL REFERENCES scenarios(scenario_id),
  operational_mode TEXT NOT NULL,
  total_distance_m REAL NOT NULL, total_makespan_s REAL NOT NULL,
  total_energy_kwh REAL NOT NULL, status TEXT NOT NULL
);
```

7. Synthetic Warehouse Scenario Archetypes & Statistical Models

Archetype	Spatial Rack Distribution	SLA Deadline Distribution	Operational Stress Target
UNIFORM_RANDOM	Uniform across all 22 aisles	Beta(2, 5) [120 s . . . 600 s]	Baseline capacity and standard fleet routing.
PARETO_HOT_ZONE	80% orders in front aisles 1–5	Exponential arrival bursts	Consolidation chute congestion and density bottlenecks.
DUAL_DEPOT_CROSS_DOCK	Bimodal split at east/west depots	Linear shift windows	AMR battery range limits and Benders shift time cuts.
PEAK_SURGE_HEAVY_TAIL	Poisson burst ($\lambda = 24/\text{min}$)	Tight Uniform [80 s . . . 240 s]	Dynamic SLA deadline feasibility and QAOA routing.

8. Practical Data Querying & Operational SQL Recipes

Connect via terminal: `sqlite3 DispatchEngine/dispatchengine.db`

```
-- 1. Query Recent Runs and Solution Metrics
SELECT run_id, scenario_id, operational_mode, total_distance_m, total_makespan_s, status
FROM runs ORDER BY created_at DESC LIMIT 5;

-- 2. Audit Invariant Gate Results across Tiers
SELECT run_id, tier_number, algorithm_rank, latency_ms, gate_status
FROM tier_executions WHERE run_id = 'RUN-WAVE-001';

-- 3. Check AMR Payload Mass & Volume Distribution
SELECT amr_id, COUNT(*) AS items, ROUND(SUM(mass_kg), 2) AS kg, ROUND(SUM(volume_m3), 3) AS m3
FROM orders WHERE scenario_id = 'SCEN-PARETO-01' GROUP BY amr_id;
```

9. Cloud Sync Pipeline (`export_api_from_db.py`) & Offline Resilience

Execute `python web_simulator/scripts/export_api_from_db.py` to sync SQLite tables into static JSON files in `web_simulator/public/api/v1/`, enabling full offline simulator capability without a live Python backend.

- Performs atomic SQLite backup of `dispatchengine.db` to `web_simulator/public/`.
- Serializes scenario lists, archetypes, and configuration limits into cached JSON endpoints in `public/api/v1/`.
- Ensures 100% offline functionality on client laptops during field presentations.

10. Ingesting Real Enterprise ERP / WMS Order Datasets

```
# Direct Python Script Ingestion using WarehouseRepository
from DispatchEngine.storage.database import DatabaseManager
from DispatchEngine.storage.repository import WarehouseRepository
from DispatchEngine.contracts.tier1_dto import OrderDTO, OrderPoolDTO

session = DatabaseManager.get_session()
repo = WarehouseRepository(session)

orders = [
    OrderDTO(order_id="WMS-101", pickup_x=22.5, pickup_y=1.2, pickup_z=14.0,
              mass_kg=3.2, volume_m3=0.015, drop_deadline=240.0),
    OrderDTO(order_id="WMS-102", pickup_x=75.0, pickup_y=0.0, pickup_z=48.0,
              mass_kg=7.5, volume_m3=0.042, drop_deadline=360.0),
]
pool = OrderPoolDTO(wave_id="WAVE-ERP-01", orders=orders)
repo.save_order_pool(pool)
```

Part III: OpenAPI 3.1 & Swagger Developer Integration Guide

11. OpenAPI Specification & 9 API Functional Domains

The standalone engine server (`standalone_server.py`) delivers an interactive Swagger UI at `http://127.0.0.1:8080/docs` and raw OpenAPI 3.1 schema at `/openapi.json`.

Domain	Endpoint & Method	Payload / DTO	Functional Role
Scenarios	GET /api/v1/scenarios/archetypes	ArchetypeListResponse	Lists 7 available synthetic scenario archetypes.
Wave Pipeline	POST /api/v1/dispatch/wave	WaveResultDTO	Executes full 4-tier dispatch pipeline.
Isolated Tiers	POST /api/v1/tiers/{id}/solve	TierOutputDTO	Unit step execution for Tiers 1, 2, 3, or 4.
Invariant Gates	POST /api/v1/gates/{id}/audit	GateValidationResultDTO	Audits post-conditions and emits Benders cuts.
Quantum	GET /api/v1/quantum/circuit/{id}	QuantumCircuitDTO	Retrieves QMOD / OpenQASM circuit synthesis data.
Benchmarks	POST /api/v1/benchmarks/compare	BenchmarkComparisonDTO	4-way comparison: FIFO vs K-Means vs QFCM vs QAOA.
Streaming	GET /api/v1/simulation/stream	SSE (SimulationFrameDTO)	Real-time 20Hz coordinate stream for 3D canvas.
Health	GET /api/v1/health	HealthDTO	Engine uptime, thread health, Classiq readiness.

12. Real-Time 20Hz Simulation Streaming via Server-Sent Events (SSE)

The streaming endpoint `GET /api/v1/simulation/stream` broadcasts 20 FPS AMR position telemetry:

```
event: frame
data: {
  "frame_index": 124, "timestamp_sec": 6.2,
  "vehicles": [
    { "vehicle_id": "AMR_001", "x": 42.5, "y": 0.0, "z": 18.2,
      "heading_rad": 1.57, "velocity_mps": 1.2, "battery_soc": 0.96, "current_action": "PICKUP" }
  ]
}
```

13. Production Client SDK Code Recipes

13.1 Python Client Recipe (`httpx`)

```
import httpx

client = httpx.Client(base_url="http://127.0.0.1:8080")

# 1. Check Engine Health
health = client.get("/api/v1/health").json()
print("Engine Status:", health["status"])

# 2. Trigger Dispatch Wave Pipeline
payload = {
    "wave_id": "WAVE-001", "fleet_size": 4, "operational_mode": "QUANTUM",
    "orders": [{"order_id": "ORD-1", "pickup_x": 30.0, "pickup_y": 0.0, "pickup_z": 20.0,
                "mass_kg": 2.5, "volume_m3": 0.01, "drop_deadline": 300.0}]
}
res = client.post("/api/v1/dispatch/wave", json=payload).json()
print("Verification Badge:", res["verification_badge"])
print("Total Travel:", res["summary"]["total_fleet_distance_m"], "meters")
```

13.2 TypeScript / React Hook Recipe (`EventSource` for SSE)

```
import { useEffect, useState } from 'react';

export function useAMRTElemetryStream() {
    const [frame, setFrame] = useState(null);

    useEffect(() => {
        const sse = new EventSource('http://127.0.0.1:8080/api/v1/simulation/stream');
        sse.onmessage = (event) => setFrame(JSON.parse(event.data));
        sse.onerror = () => sse.close();
        return () => sse.close();
    }, []);

    return frame;
}
```

13.3 cURL Direct Terminal Command

```
# Trigger Wave Execution via cURL
curl -X POST http://127.0.0.1:8080/api/v1/dispatch/wave \
-H "Content-Type: application/json" \
-d '{"wave_id":"WAVE-CURL-01","fleet_size":4,"operational_mode":"HYBRID"}'
```

Part IV: Classiq Quantum Programming & QMOD Synthesis Guide

14. Classiq High-Level Quantum Modeling Architecture

Classiq abstracts quantum programming from gate-level assembly into declarative functional models. Algorithms are declared as high-level mathematical expressions (`@qfunc`) and transpiled by the Classiq Synthesis Engine under hardware constraints:

```
[High-Level QMOD Model (@qfunc)] ---> [Hardware Constraints: max_width, max_depth] ---> [Classiq Cloud Synthesis] ---> [Transpiled Hardware]
```

15. Quantum Distance Kernels & Swap-Test Fidelity Circuits

Feature vectors $\tilde{\mathbf{v}} \in [0, 1]^d$ are angle-encoded into qubit rotations $\theta_j = 2 \arcsin(\sqrt{\tilde{v}_j})$. Distance is evaluated via the Swap-Test fidelity state overlap:

QUANTUM SWAP-TEST FIDELITY STATE OVERLAP

EQUATION (Q-1)

$$F(|\psi(\mathbf{x}_i)\rangle, |\psi(\mathbf{c}_k)\rangle) = |\langle\psi_i|c_k\rangle|^2 = 1 - 2P(|1\rangle_{\text{ancilla}})$$

QUANTUM DISTANCE METRIC

EQUATION (Q-2)

$$D_Q(\psi_i, c_k) = 2P(|1\rangle_{\text{ancilla}}) = 1 - F(|\psi_i\rangle, |c_k\rangle)$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

What this achieves: Instead of performing thousands of classical floating-point distance calculations, orders and centroids are mapped to quantum states. A Swap-Test interferes the two states; measuring ancilla qubit state $|1\rangle$ gives the distance directly. This enables logarithmic state-space compression.

Symbol	Mathematical Meaning	Physical Warehouse Interpretation
$ \psi(\mathbf{x}_i)\rangle$	Angle-encoded quantum order state	Normalized coordinate (x, z) and mass of package i .
$ \psi(\mathbf{c}_k)\rangle$	Cluster centroid quantum state	Spatial center and target payload capacity of AMR k .
$P(1\rangle_{\text{ancilla}})$	Ancilla qubit excited probability	Normalized physical separation distance in the warehouse.

15.1 Classiq QMOD Swap-Test Implementation in Python

```
from classiq import qfunc, QBit, H, SWAP, control, allocate, Output

@qfunc
def swap_test(q1: QBit, q2: QBit, ancilla: Output[QBit]) -> None:
    allocate(1, ancilla)
    H(ancilla)
    control(ancilla, lambda: SWAP(q1, q2))
    H(ancilla)
```

16. VRP QAOA Subtour Circuit Synthesis

Routing graphs are mapped onto an Ising Hamiltonian H_C with degree penalties:

COST HAMILTONIAN & DEGREE-2 PENALTY

EQUATION (Q-3)

$$H_C = \sum_{(i,j) \in \mathcal{E}} c_{ij} \frac{I - Z_i Z_j}{2} + \lambda_{\text{deg}} \sum_{i=1}^N \left(2 - \sum_{j \in \delta(i)} \frac{I - Z_i Z_j}{2} \right)^2$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

What this achieves: Maps the routing problem into a quantum spin glass. Minimizing energy finds the shortest travel tour. The degree penalty enforces that every customer stop has exactly 1 entry and 1 exit edge, mathematically preventing dead ends.

Symbol	Mathematical Meaning	Physical Warehouse Interpretation
c_{ij}	Graph edge transit cost	Travel distance and aisle transit time between rack i and rack j .
$Z_i Z_j$	Pauli-Z spin correlation	Binary decision indicating whether the route traverses link (i, j) .
λ_{deg}	Degree penalty coefficient	Enforces valid closed delivery loops with zero disconnected stops.

16.1 Classiq Synthesis Call with Hardware Constraints

```
from classiq import create_model, synthesize, Constraints

def synthesize_vrp_qaoa(distance_matrix, p_layers=2):
    constraints = Constraints(max_width=16, max_depth=120)
    model = create_model(vrp_qaoa_model, constraints=constraints)
    return synthesize(model)
```

17. Native QMOD Reference (`vehicle_routing_problem.qmod`)

The root file `vehicle_routing_problem.qmod` provides native QMOD statements:

- `qarray[QBit, N]` registers representing customer visit states.
- Alternating unitary layers implementing problem phase separation (H_C) and transverse mixer pulses ($H_M = \sum X_i$).
- Direct compatibility with the Classiq Cloud IDE for visual circuit analysis.

Part V: Advanced Engineering & Mathematical Formulations (Researcher Role)

18. Rigorous Mathematical Formulations across Tiers 1–4

18.1 Tier 1: Distributionally Robust Fuzzy C-Means (*DR-SAA-FCM*)

OBJECTIVE FUNCTION & PAYLOAD BALANCE

EQUATION (T1-1)

$$\min_{U, \mathbf{C}} \sum_{k=1}^K \sum_{i=1}^N u_{ik}^m \cdot \mathbb{E}_{\mathbb{P}} [\|\mathbf{x}_i - \mathbf{c}_k\|_{\Sigma^{-1}}^2] + \lambda_1 \sum_{k=1}^K \left(\sum_{i=1}^N u_{ik} q_i - \frac{Q_{\text{total}}}{K} \right)^2$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

Physical Meaning: Partitions N customer orders among K AMRs. The first term groups nearby orders using covariance metric Σ^{-1} . The second term penalizes uneven cargo distribution, ensuring all robots carry equal payload weight.

Symbol	Description	Warehouse Meaning
$u_{ik} \in [0, 1]$	Fuzzy membership weight	Degree to which order i is assigned to robot k .
$m \geq 1$	Fuzzifier parameter	Controls clustering softness ($m = 2.0$ optimal).
$\mathbf{x}_i, \mathbf{c}_k$	Item coordinate & centroid	Rack location and vehicle cluster center.
Σ^{-1}	Inverse covariance matrix	Mahalanobis metric accounting for aisle orientation.
$q_i, Q_{\text{total}}/K$	Item mass & target mass	Prevents overloading one AMR while others run empty.

18.2 Tier 2: CP-SAT 3D Containerization (MISOCP) & LIFO DAG

VOLUME MAXIMIZATION & COG BALANCE

EQUATION (T2-1)

$$\text{Maximize} \sum_{i \in \mathcal{B}_k} \text{vol}(i) \cdot y_i - \alpha (\Delta x_{\text{CoG}}^2 + \Delta y_{\text{CoG}}^2)$$

STRICT PHYSICAL LIFO DAG PRECEDENCE

EQUATION (T2-2)

$$z_j \geq z_i + h_i \implies \pi(i) > \pi(j)$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

Physical Meaning: Packs 3D parcels inside the AMR's transport cage. Minimizes CoG eccentricities ($\Delta x, \Delta y$) to prevent vehicle rollover. The LIFO rule ensures top packages are dropped off first, eliminating time-wasting warehouse restacking.

18.3 Tier 3: Multi-Depot Multi-Trip VRP (*HGS-ADC*)

BI-SUBPOPULATION DIVERSITY RANK

EQUATION (T3-1)

$$\text{BiRank}(S) = \text{rank}_{\text{fit}}(\Phi(S)) + \left(1 - \frac{\text{nbElapsedIter}}{\text{nbMaxIter}}\right) \cdot \text{rank}_{\text{div}}(\Delta(S, \mathcal{P}))$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

Physical Meaning: Ranks route candidates by both route length and structural uniqueness (diversity). In early iterations, diversity ranking prevents premature convergence to bad routes, finding global optimal paths.

18.4 Tier 4: SIPP Multi-Agent Kinematics & ISO 3691-4:2023 Braking

CONTINUOUS SWEEPED-VOLUME NON-OVERLAP

EQUATION (T4-1)

$$\min_{t \in [0, T]} \|\mathbf{p}_a(t) - \mathbf{p}_b(t)\|_2 \geq 2R_{\text{swept}} + d_{\text{safety}} \quad \forall a \neq b$$

SAFE KINEMATIC DECELERATION PROFILE

EQUATION (T4-2)

$$s_{\text{stop}}(v) = \frac{v^2}{2a_{\text{max}}} + v \cdot t_{\text{reaction}} + s_{\text{margin}}$$

• HUMAN-READABLE PLAIN ENGLISH TRANSLATION

Physical Meaning: Guarantees moving AMRs never collide by enforcing a physical safety envelope. Calculates stopping distance factoring laser sensor reaction time (0.12 s) and friction deceleration limits.

19. Generalized Benders Recourse Feedback Derivations

VOLUMETRIC FEASIBILITY OVERFILL CUT (TIER 2 → TIER 1)

EQUATION (B-1)

$$\sum_{i \in \mathcal{B}_k} v_i \cdot x_{ik} \leq V_{\text{max}} - \Delta V_{\text{repack}}$$

SHIFT DURATION & BATTERY CUT (TIER 3 → TIER 1)

EQUATION (B-2)

$$\sum_{i \in \mathcal{R}_k} t_{\text{service}, i} + \frac{1}{v_{\text{nom}}} \sum_{(i, j) \in \mathcal{E}_k} d_{ij} \leq T_{\text{shift}}$$

20. Computational Complexity Matrix ($\mathcal{O}$) & Quantum Advantage Horizon

Tier / Problem	Classical Solver	Classical Complexity	Quantum Solver	Quantum Complexity	Advantage Horizon
Tier 1 (Batching)	Classical FCM	$\mathcal{O}(I \cdot N \cdot K \cdot d)$	Swap-Test QFCM	$\mathcal{O}(I \cdot N \cdot K \cdot \log d)$	Feature dimension $d \gg 100$.
Tier 2 (3D Packing)	CP-SAT Branch-and-Cut	$\mathcal{O}(2^N \cdot 6^N)$	Quantum Knapsack	$\mathcal{O}(2^{N/2})$ (Grover)	Complex irregular geometries.
Tier 3 (VRP Routing)	HGS-ADC Metaheuristic	$\mathcal{O}(I \cdot N^2)$	QAOA Spin Glass	Poly-log ansatz depth	Dense graph topology optimization.
Tier 4 (Kinematics)	Priority SIPP	$\mathcal{O}(K \cdot V \log V)$	Safe Interval Prop	Classical Optimal	Millisecond real-time trajectory execution.

21. Custom Solver Implementation & Extension Runbook

```
# Step 1: Subclass BaseTierSolver in DispatchEngine/tiers/
from DispatchEngine.tiers.base import BaseTierSolver
from DispatchEngine.contracts.tier1_dto import OrderPoolDTO, BatchPlanDTO

class CustomTier1ClusteringSolver(BaseTierSolver):
    def solve(self, pool: OrderPoolDTO) -> BatchPlanDTO:
        # 1. Extract coordinate vectors and mass constraints
        # 2. Execute custom partitioning / quantum kernel
        # 3. Return validated BatchPlanDTO with assigned amr_id
        return BatchPlanDTO(...)

# Step 2: Register in DispatchEngine/strategy/state_machine.py
# Step 3: Verify with unit test suite: python -m unittest DispatchEngine.tests.test_orchestrator
```