

Поиск файлов. Перенаправление ввода-вывода.
Просмотр запущенных процессов.

Мурашко В.В.

14.05.2021

Отчёт по лабораторной работе №7

Ознакомление с инструментами поиска файлов и фильтрации текстовых данных. Приобретение практических навыков: по управлению процессами (и заданиями), по проверке использования диска и обслуживанию файловых систем.

```
vvmurashko1@dk4n70 ~ $ ls /etc > file.txt  
vvmurashko1@dk4n70 ~ $ ls ~ >> file.txt
```

```
vvmurashko1@dk4n70 ~ $ grep .conf file.txt  
appstream.conf  
brltty.conf  
ca-certificates.conf  
cachefilesd.conf  
cfg-update.conf  
cpufreq-bench.conf  
dconf  
dhcpcd.conf  
dispatch-conf.conf  
dleyna-server-service.conf  
dnsmasq.conf  
e2fsck.conf  
e2scrub.conf  
etc-update.conf  
fluidsynth.conf
```

```
vvmurashko1@dk4n70 ~ $ grep .conf file.txt > conf.txt
```

Имена файлов в домашнем каталоге

```
vvmurashko1@dk4n70 ~ $ ls -l | grep c*  
-rw-r--r-- 1 vvmurashko1 studsci 1233 мая 14 10:13 conf.txt  
vvmurashko1@dk4n70 ~ $ find ~/c* -name "c*" -print  
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/conf.txt
```

Имена файлов из каталога /etc


```
vvmurashko1@dk4n70 ~ $ cd /etc
vvmurashko1@dk4n70 /etc $ ls -l | grep h* | less
grep: harbour: Это каталог
vvmurashko1@dk4n70 /etc $ cd
```

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1


```
vvmurashko1@dk4n70 ~ $ find ~ -name "log*" -print > ~/logfile &  
[1] 4208  
vvmurashko1@dk4n70 ~ $ rm -r logfile  
[1]+  Завершён      find ~ -name "log*" -print > ~/logfile
```

Запуск редактора

```
vvmurashko1@dk4n70 ~ $ gedit &  
[1] 4265
```



Идентификатор процессора

```
vvmurashko1@dk4n70 ~ $ ps aux | grep -i gedit
vmmuras+  3955  0.9  1.6 776192 135904 ?        Sl   10:08   0:06 /usr/bin/gedit --gapplication-service
vmmuras+  4323  0.0  0.0 14320  972 pts/3      S+   10:20   0:00 grep --colour=auto -i gedit
[1]+  Завершён          gedit
```

KILL(1)	User Commands	KILL(1)
NAME		
kill - send a signal to a process		
SYNOPSIS		
kill [options] <pid> [...]		
DESCRIPTION		
<p>The default signal for kill is TERM. Use <code>-l</code> or <code>-L</code> to list available signals. Particularly useful signals include HUP, INT, KILL, STOP, CONT, and 0. Alternate signals may be specified in three ways: <code>-9</code>, <code>-SIGKILL</code> or <code>-KILL</code>. Negative PID values may be used to choose whole process groups; see the PGID column in ps command output. A PID of <code>-1</code> is special; it indicates all processes except the kill process itself and init.</p>		
OPTIONS		
<pid> [...]		
Send signal to every <pid> listed.		
-<signal>		
-s <signal>		
--signal <signal>		
Specify the signal to be sent. The signal can be specified by using name or number. The behavior of signals is explained in signal(7) manual page.		
-l, --list [signal]		
List signal names. This option has optional argument, which will convert signal number to signal name, or other way round.		
-L, --table		
List signal names in a nice table.		

```
vvmurashko1@dk4n70 ~ $ kill -9 3955
```

Информация о команде df

DF(1)

User Commands

NAME

df - report file system disk space usage

SYNOPSIS

df [OPTION]... [FILE]...

DESCRIPTION

This manual page documents the GNU version of `df`. `df` displays the amount of disk space available on the file systems currently mounted on the system. Disk space is shown in 1K blocks by default, unless the `-k` option is used.

If an argument is the absolute file name of a disk device node containing a mounted file system, `df` shows the disk space available on that file system. This version of `df` cannot show the space available on unmounted file systems, because on most kinds of file systems, the space available is not known until the file system is mounted.

OPTIONS

Show information about the file system on which each FILE resides, or all file systems by default.

Mandatory arguments to long options are mandatory for short options too.

`-a, --all`

include pseudo, duplicate, inaccessible file systems

`-B, --block-size=SIZE`

scale sizes by SIZE before printing them; e.g., `'-BM'` prints sizes in units of 1,048,576 bytes; see `df --help` for more

`-h, --human-readable`

print sizes in powers of 1024 (e.g., 1023M)

`-H, --si`

print sizes in powers of 1000 (e.g., 1.1G)

`-i, --inodes`

list inode information instead of block usage

Информация о команде du

DU(1)

NAME

du - estimate file space usage

SYNOPSIS

```
du [OPTION]... [FILE]...
du [OPTION]... --files0-from=F
```

DESCRIPTION

Summarize disk usage of the set of FILES, recursively for directories.

Mandatory arguments to long options are mandatory for short options too.

-0, --null
end each output line with NUL, not newline

-a, --all
write counts for all files, not just directories

--apparent-size
print apparent sizes, rather than disk usage; although the apparent size is usually the like

-B, --block-size=SIZE
scale sizes by SIZE before printing them; e.g., '-BM' prints sizes in units of 1

-b, --bytes
equivalent to '--apparent-size --block-size=1'

-c, --total
produce a grand total

Команда df

```
vvmurashko1@dk4n70 ~ $ df
```

Файловая система	1К-блоков	Использовано	Доступно	Используй
none	4000164	12028	3988136	
udev	3924440	0	3924440	
tmpfs	4000164	77860	3922304	
/dev/sda8	491812356	59266468	407540144	
tmpfs	4096	0	4096	
tmpfs	4000164	59528	3940636	
/dev/sda6	91557952	816336	86067672	
mark.sci.pfu.edu.ru:/usr/portage	8388608	4369664	1790976	
mark.sci.pfu.edu.ru:/com/lib/portage	733747200	115402752	618344448	
mark.sci.pfu.edu.ru:/usr/local/share/portage	8388608	4369664	1790976	
AFS	2147483647	0	2147483647	
tmpfs	800032	248	799784	
mark.sci.pfu.edu.ru:/usr/local/share/portage	8388608	4369664	1790976	

```
vvmurashko1@dk4n70 ~ $ du
2      ./public/public_html
4      ./public
2      ../config/gnome-session/saved-session
4      ../config/gnome-session
3      ../config/ibus/bus
5      ../config/ibus
10     ../config/dconf
5      ../config/evolution/sources
7      ../config/evolution
74     ../config/libaccounts-glib
3      ../config/goa-1.0
2      ../config/gconf
44     ../config/gtk-3.0/assets
58     ../config/gtk-3.0
72     ../config/session
2      ../config/nautilus
2      ../config/mc/mcedit
8      ../config/mc
```


Справка команды find

FIND(1)

General Command:

NAME

find - search for files in a directory hierarchy

SYNOPSIS

find [-H] [-L] [-P] [-D debugopts] [-Olevel] [starting-point...] [expression]

DESCRIPTION

This manual page documents the GNU version of **find**. GNU **find** searches the directory tree rooted at the starting-point, following the rules of precedence (see section OPERATORS), until the outcome is known (the left hand side is false). If no starting-point is specified, '.' is assumed.

If you are using **find** in an environment where security is important (for example if you are using it in a shell script), see the 'security' chapter of the findutils documentation, which is called **Finding Files** and comes with findutils. This manual page is a more useful source of information.

OPTIONS

The **-H**, **-L** and **-P** options control the treatment of symbolic links. Command-line arguments following the starting-point are taken to be path names. If the argument begins with '-', or the argument '(' or '!', that argument and any following arguments are taken to be options. If no expression is given, the expression **-print** is used (but you should probably use **-exec** instead).

This manual page talks about 'options' within the expression list. These options control the behaviour of **find**. The options **-L**, **-P**, **-D** and **-O** must appear before the first path name, if at all. A double dash **--** can also be used to end the list of options. **-D** is generally safer if you use wildcards in the list of start points).

-P Never follow symbolic links. This is the default behaviour. When **find** examines or prints the properties of the symbolic link itself.

-L Follow symbolic links. When **find** examines or prints information about files, the information about the file itself (unless it is a broken symbolic link or **find** is unable to examine the file to which it points) is used. If **-L** is in effect and **find** discovers a symbolic link to a subdirectory, the search will still be in effect. If **-L** is in effect and **find** discovers a symbolic link to a subdirectory, the search will still be in effect.

Имена всех директорий

```
vvmurashko1@dk4n70 ~ $ find ~ -type d -print
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/public
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/public/public_html
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/gnome-session
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/gnome-session
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/ibus
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/ibus/bus
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/dconf
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/evolution
/afs/.dk.sci.pfu.edu.ru/home/v/v/vvmurashko1/.config/evolution/sc
```

Я ознакомилась с инструментами поиска файлов и фильтрации текстовых данных, приобрела практические навыки: по управлению процессами (и заданиями), по проверке использования диска и обслуживанию файловых систем.