

Fundamentals of Computer Vision

Dr. Venkataramana Veeramsetty
NVIDIA DLI Instructor & Faculty@CAIDL
Assistant Professor
Dept. of EEE
SR Engineering College

.vvr.research@gmail.com
ataramana Veeramsetty)

December 19, 2020



Computer Vision Problems

- Image Classification
 - You might take as input say a 64 by 64 image and try to figure out, is that a cat?
- Object Detection
 - If you're building a self-driving car, maybe you don't just need to figure out that there are other cars in this image. But instead, you need to figure out the position of the other cars in this picture so that your car can avoid them.
- Neural style transfer
 - Paint one image (Content Image) In another image style

mail : dr.vr.research@gmail.com
r. Venkataramana Veeamsetty



Why Convolution Operation Required

- Consider 64 X 64 gray scale image, number of features in input matrix are 4096
- Consider 64 X 64 RGB image, number of features in input matrix are 12288
- Consider 1000 X 1000 RGB image, number of features in input matrix are 30,00,000
- Consider FCN, with first hidden layer has 1000 hidden units. then size of the weight matrix is 30,00,000 x 1000 size.

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty



Problems and Approach



- It is difficult to get enough data to prevent neural network from over fitting
- Need more computation time
- Need more memory

To avoid these problem, use convolution operation which is fundamental building block for convolutional Neural Network (CNN)

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty



Vertical Edge Detection



na
r.



Table 1 : Gray Scale Image

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)

Table 2 : Filter for Vertical Edge Detection

1	0	-1
1	0	-1
1	0	-1

Table 3 : Convolution Operation

3(1)	0(0)	1(-1)	2	7	4
1(1)	5(0)	8(-1)	9	3	1
2(1)	7(0)	2(-1)	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

Email : dr.vr.research@gmail.com
(Dr. Venkataramana Veeramsetty)

Table 4 : Output

-5			

Table 5 : Output Image after Convolution

-5	-4	0	8
-10	-2	2	3
0	-2	-4	-7
-3	-2	-3	-16


- Python: conv_forward
- Tensorflow: tf.nn.conv2d
- keras: Conv2D

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



Email :
(Dr. Ve

10	10	10	0	0	0
10	10	10	0	0	0
10	10	10	0	0	0
10	10	10	0	0	0
10	10	10	0	0	0
10	10	10	0	0	0




*

1	0	-1
1	0	-1
1	0	-1



=

0	30	30	0
0	30	30	0
0	30	30	0
0	30	30	0




om
(y)



Email : dr.vvr.research@gmail.com
(Dr. Venkataraman Veeramsetty)

0	-30	-30	0
0	-30	-30	0
0	-30	-30	0
0	-30	-30	0




=

1	0	-1
1	0	-1
1	0	-1



*

0	0	0	10	10	10
0	0	0	10	10	10
0	0	0	10	10	10
0	0	0	10	10	10
0	0	0	10	10	10
0	0	0	10	10	10




Multiple Edge Detector

Table 6 : Vertical Edge Filter

1	0	-1
1	0	-1
1	0	-1

Table 7 : Horizontal Edge Filter

1	1	1
0	0	0
-1	-1	-1

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



Email :
(Dr. Ve

om
(ty)

10	10	10	0	0	0
10	10	10	0	0	0
10	10	10	0	0	0
0	0	0	10	10	10
0	0	0	10	10	10
0	0	0	10	10	10

*

1	1	1
0	0	0
-1	-1	-1

=

0	0	0	0
30	10	-10	-30
30	10	-10	-30
0	0	0	0



Sobel filter

Table 8 : Sobel filter for Vertical Edge Detection

1	0	-1
2	0	-2
1	0	-1

Table 9 : Sobel filter for Horizontal Edge Detection

1	2	1
0	0	0
-1	2	-1

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



Scharr filter

Table 10 : Scharr filter for Vertical Edge Detection

3	0	-3
10	0	-10
3	0	-3

Table 11 : Scharr filter for Horizontal Edge Detection

3	10	3
0	0	0
-3	-10	-3

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty



3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

*

w_1	w_2	w_3
w_4	w_5	w_6
w_7	w_8	w_9

=

n =number of pixels in input image
 f =number of pixels in filter
 o =number of pixels in output image
 $o=n-f+1$

For example

If input image size is 6×6 and filter size is 3×3
means $n=6$, $f=3$

ch@gmail.com
(Veeramsetty)

Number of parameters in one layer

If you have 10 filters that are $3 \times 3 \times 3$ in one layer of a neural network, how many parameters does that layer have?

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



Padding

- In order to build deep neural network one modification to the basic convolutional operation that needs to be use in **padding**

Limitations of standard convolution operation

- Can not detect edges or other feature without shrinking input image
- Throwing away a lot of the information near the edge of the image

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty



Middle pixel

Edge Pixel




Table 12 : Padding one layer ($p=1$)

0	0	0	0	0	0	0	0
0	3	0	1	2	7	4	0
0	1	5	8	9	3	1	0
0	2	7	2	5	1	3	0
0	0	1	3	1	7	8	0
0	4	2	1	6	2	8	0
0	2	4	5	2	3	9	0
0	0	0	0	0	0	0	0

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



Finding output image size

n = number of pixels in input image

f = number of pixels in filter

o = number of pixels in output image

p = number of layers in padding $o = n + 2p - f + 1$

For example

if input image size is 6×6 , filter size is 3×3 and padding with one layer

means $n=6$, $f=3$, $p=1$

Then output image size is $(n + 2p - f + 1) \times$

$$(n + 2p - f + 1) = (6 + 2 \cdot 1 - 3 + 1) \times (6 + 2 \cdot 1 - 3 + 1) = 6 \times 6$$

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty

Valid and Same Convolutions

- **Valid Convolutions:** No padding

$$n \times n * f \times f = n-f+1 \times n-f+1$$

- **Same Convolutions :** Pad such that size of input and output size must be same

$$n \times n * f \times f = n+2*p-f+1 \times n+2*p-f+1$$

In order to keep input image size same as output image size, padding parameter p is designed based on filter size (f)

$$n+2*p-f+1 = n \Rightarrow p = \frac{f-1}{2}$$

p value usually odd

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty

Striding Convolutions

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91		

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	

mail : dr.vr.research@gmail.com
r. Venkataramana Veeramsetty)

Striding parameter s=2



2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69		

Striding parameter s=2

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69	91	

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69	91	127

Striding parameter s=2

Email : dr.vr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69	91	127
44		

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69	91	127
44	72	

Striding parameter s=2

Email : dr.vr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

3	4	4
1	0	2
-1	0	3

=

91	100	83
69	91	127
44	72	74

Striding parameter s=2 and output size 3 X 3
Perform convolution only if all pixels in filter must overlap on image

Email : dr.vr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



Finding output image size

n=number of pixels in input image

f=number of pixels in filter

o=number of pixels in output image

p=number of layers in padding

s=striding parameter

$o = \frac{n+2p-f}{s} + 1$ if that fraction is integer

$o = \text{floor}\left(\frac{n+2p-f}{s} + 1\right)$ if that fraction is not integer

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty)



For example

if input image size is 7×7 , filter size is 3×3 ,
padding with no layer and striding parameter $s=2$
means $n=6$, $f=3$, $p=0$, $s=2$

Then output image size is $(n+2p-f+1) \times$
 $(n+2p-f+1) = (7+2*0-3)/2+1 \times$
 $(7+2*0-3)/2+1 = 3 \times 3$

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)



Cross - Correlation

2	3	7	4	6	2	9
6	6	9	8	7	4	3
3	4	8	3	8	9	7
7	8	3	6	6	3	4
4	2	1	8	3	4	6
3	2	4	1	9	8	3
0	1	3	9	2	1	4

*

Filter

3	4	4
1	0	2
-1	0	3

=

101		

Flip filter and DO

convolution operation

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



Convolution Over Volume

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

*

1	0	-1
1	0	-1
1	0	-1

=

-15	-12	0	24
-30	-6	6	9
0	-6	-12	-21
-9	-6	-9	-48

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

1	0	-1
1	0	-1
1	0	-1

1	0	-1
1	0	-1
1	0	-1

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

mail : dr.vr.research@gmail.com
r. Venkataramana Veeramsetty)



$$D(1,1) = R(1,1) * f_R(1,1) + G(1,1) * f_G(1,1) + B(1,1) * f_B(1,1)$$



3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

*

1	0	-1
1	0	-1
1	0	-1

1	0	-1
1	0	-1
1	0	-1

1	0	-1
1	0	-1
1	0	-1

1	1	1
0	0	0
-1	-1	-1

1	1	1
0	0	0
-1	0	-1

1	1	1
0	0	0
-1	-1	-1

=

-15	-12	0	24
-30	-6	6	9
0	-6	-12	-21
-9	-6	-9	-48

-21	-33	6	12
30	51	27	-9
12	15	-3	-21
-21	-18	3	6

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9

3	0	1	2	7	4
1	5	8	9	3	1
2	7	2	5	1	3
0	1	3	1	7	8
4	2	1	6	2	8
2	4	5	2	3	9


Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)

$$n \times n \times n_c \cdot f \times f \times n_c \times n_f = \frac{n+2p-f}{s} + 1 \times \frac{n+2p-f}{s} + 1 \times n_f$$

$$5 \times 6 \times 3 * 3 \times 3 \times 3 \times 2 = \frac{6+2*0-3}{1} + 1 \times 2$$



One Layer of Convolutional Neural Network




$$a[1] = g(w[1]a[0] + b)$$



Image * convolution operation + nonlinear operation = output of layer 1

Relu Activation Function



output = $\max(0, z)$

Whereas for Leaky Relu

output = $\max(0.1z, z)$

mail : dr.vr.research@gmail.com
Dr. Venkataramana Veeramsetty

f^l = Number of rows and columns in filter in layer 1

p^l = Padding size in layer 1

s^l = Striding size in layer 1

n_c = Number of channels of image

n_f^l = Number of Filters

Image size = $n_H^{l-1} \times n_W^{l-1} \times n_c$

Filter size = $f^l \times f^l \times n_c$

Output size = $n_H^l \times n_W^l \times n_c$

Where $n_H^l = n_W^l = \frac{n_H^{l-1} + 2p^l - f^l}{s^l} + 1$

Number of activations = $n_H^l * n_W^l * n_c$


Weights = $f^l * f^l * n_c * n_f^l$

bias parameters = n_f^l For one filter one bias

parameter

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)

Simple Convolutional Neural Network



mail: dr.vkr.research@gmail.com

Layers In CNN

- Convolution Layer
- Pooling Layer
- Fully Connected Layer

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



Pooling

Other than convolution layers, ConvNet also uses Pooling layers. The main purposes of using this pooling layer in ConvNet are

- To reduce the size of representation
- To speedup the computation
- It detects some of the features more robust
- No parameters to learn

mail : dr.vvr.research@gmail.com
Dr. Venkataramana Veeramsetty



Max Pooling

2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Max Pooling: $f=3$ and $S=3$



9	9
8	9

$$o=(6+0-3)/3+1: 2 \times 2$$

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Max Pooling: $f=3$ and $S=3$

First Channel

9	9
8	9



$2 \times 2 \times 2 \rightarrow$ No. of channels

2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Second Channel

9	9
8	9

$o=(6+0-3)/3+1: 2 \times 2$

(Dr. ...
Email : dr.vr.research@gmail.com
...)



Average Pooling

2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Average Pooling: $f=3$ and $S=3$

5.3	5.6
3.7	5.3

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)



2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Average Pooling: $f=3$ and $S=3$

5.3	5.6
3.7	5.3

5.3	5.6
3.7	5.3

2 X 2 X 2 \rightarrow No. of channels

2	3	7	4	6	2
6	6	9	8	7	4
3	4	8	3	8	9
7	8	3	6	6	3
4	2	1	8	3	4
3	2	4	1	9	8

Second Channel

5.3	5.6
3.7	5.3

$$o = (6 + 0 - 3) / 3 + 1 = 2 \times 2$$

(Dr.
Email : dr.vr.research@gmail.com
.. ,



Hyper Parameters

f: Filter Size

s: Striding

n: Size of image in previous layer

n_c : Number of channels


Size of Pooling Output: $\frac{n+2p-f}{s} + 1 \times \frac{n+2p-f}{s} + 1 \times n_c$

In pooling padding is usually zero. ($p=0$)

mail : dr.vvr.research@gmail.com
Dr. Venkataramana Veeramsetty



LENET




Number of parameters in convolution layer having filter size f , number of filters n_f and number of n_c is $(f*f*n_c+1)*n_f$

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)




1X1 convolutions



Dr. Ve
nkatarama




Inception Network



Dr. Venkatar
Dr. Venkatar



Computation Cost




$$\text{cost} = 5 * 5 * 192 * 28 * 28 * 32 = 12,04,22,400$$

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)

Computation Cost

Dr. Ven



28 × 28 × 192

28 × 28 × 16


28 × 28 × 32

$$(1 \times 1 \times 192 \times 28 \times 28 \times 16) + (5 \times 5 \times 16 \times 28 \times 28 \times 32) = 2408448 + 10035200 = 12443648$$




Computation Cost

Inception module



Transfer Learning



mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)

Object Detection



y

1

1

1

0

0



ConvNet

y

main

Data Augmentation

- Flip
- Rotation
- Scale
- Crop
- Translate
- Noise

mail : dr.vvr.research@gmail.com
r. Venkataramana Veeramsetty)





Thank you!

Email : dr.vvr.research@gmail.com
(Dr. Venkataramana Veeramsetty)

