Blood Cancer Identification using Hybrid Ensemble Deep Learning

How It Works — A Non-Technical Guide

Prepared for the client

IMPORTANT NOTICE: This software is a research and educational project. It is **not** approved for clinical diagnosis. All results must be verified by a qualified medical professional.

Generated from project results dated 2026-10-09 13:48 UTC

Table of Contents

1. What This Project Does
2. The Data
3. How a Computer Learns to Recognise Cells
4. The Three Backbones
5. The Hybrid Ensemble
6. Grad-CAM: Where the Model Is Looking
7. Results
8. The Web Application
9. Where Everything Is
10. How It Was Built
11. Installation
12. Using the App — Step-by-Step Demo
13. Glossary
14. References

1. What This Project Does

Acute Lymphoblastic Leukaemia (ALL) is a type of blood cancer that affects white blood cells. Doctors diagnose it by examining a thin smear of blood under a microscope — a **peripheral blood smear** (a glass slide coated with a drop of blood, spread thin, stained with dye and photographed). This project builds software that looks at those photographs and sorts them into one of four groups:

- **Benign** — normal, healthy cells (no cancer).
- **[Malignant] early Pre-B** — cancer cells at an early stage called "early Pre-B".
- **[Malignant] Pre-B** — cancer cells at the "Pre-B" stage.
- **[Malignant] Pro-B** — cancer cells at the "Pro-B" stage.

The three malignant (cancerous) classes correspond to different stages of the cancer cell's development. Identifying the stage helps doctors choose the right treatment.

In practice the user uploads a blood smear photograph through a web browser. The software returns the predicted class, a confidence score (how sure it is), and a highlighted image showing which part of the cell it focused on.

Not for clinical use. This is a research project. It demonstrates that the technique works well on this dataset, but it has not been validated on other patient populations or approved by any regulatory body. A qualified haematologist must always make the final diagnosis.

2. The Data

The images come from a public dataset on Kaggle (a website for data-science datasets) called *Blood Cells Cancer (ALL)*, published by Aria et al. It contains **3,242** microscope photographs of stained blood cells, each already labelled by an expert as one of the four classes above.

What Is a Peripheral Blood Smear Image?

A peripheral blood smear is prepared by placing a drop of blood on a glass slide, spreading it into a thin layer, then applying a chemical stain (typically Wright or Giemsa stain) that colours different cell parts in different shades. The slide is then photographed under a microscope. The resulting image shows individual cells whose shape, size and colour pattern reveal whether they are healthy or cancerous.

Class Counts

Class	Training	Validation	Test	Total
Benign	358	77	77	512
[Malignant] early Pre-B	685	147	147	979
[Malignant] Pre-B	669	143	143	955
[Malignant] Pro-B	557	119	120	796
Total	**2269**	**486**	**487**	**3242**

Train / Validation / Test Split

The images are divided into three groups, and each group has a specific job:

- **Training set** (2,269 images, 70%) — the computer studies these images to learn the patterns. Think of this as the textbook a student reads.
- **Validation set** (486 images, 15%) — used during training as a practice exam. The computer checks its answers on these images to tune its learning, but never memorises them.
- **Test set** (487 images, 15%) — the final exam. The computer never sees these images until the very end, so the score is an honest measure of performance.

The split is **stratified**: each group has roughly the same proportion of each class, so no class is accidentally left out. The file `src/data.py` performs the split and saves the lists to `data/splits/train.csv`, `val.csv` and `test.csv`.

Augmentation

Augmentation means creating slightly altered copies of the training images — flipping them horizontally, rotating them a few degrees, zooming in a little, or adjusting the brightness. This teaches the computer to recognise a cell regardless of its orientation or lighting. Augmentation is applied *only* to the training set; validation and test images are left untouched so the scores stay fair.

3. How a Computer Learns to Recognise Cells

At its core, the software uses a **neural network**. Imagine a chain of simple calculations, loosely inspired by the way neurons in a brain pass signals to each other. Each link in the chain receives a set of numbers, multiplies them by adjustable values called **weights**, adds them up, and passes the result to the next link. At the end, the chain outputs four numbers — one for each class — and picks the highest.

Training is the process of adjusting those weights so the network gives the right answer more often. The computer shows the network a training image, compares its answer to the correct label, measures how wrong it was (the **loss**), and nudges the weights in the direction that would have made the answer closer to correct. This cycle repeats millions of times.

An **epoch** is one complete pass through every training image. Our models were each trained for 15 epochs.

A Visual Analogy

Imagine learning to identify birds. At first you would learn basic concepts — what feathers look like, the shape of beaks, the difference between wings and tails. Only then would you learn to tell a robin from a sparrow. A neural network works the same way: the early layers learn simple patterns (edges, colours, textures), and the later layers combine them into complex features (cell membranes, nuclei, the irregular shapes that signal cancer). The final layer compares those features against what it learned during training and picks the best-matching class.

The beauty of this layered approach is that the simple patterns (edges, textures) are useful for almost any image task. That is why transfer learning works so well: the early layers already know how to see.

How the Computer Improves

Each training cycle works like a feedback loop. The computer makes a prediction, checks the answer, and adjusts its internal numbers to do slightly better next time. The size of each adjustment is controlled by a setting called the **learning rate**. If the learning rate is too large, the model overshoots and never settles; if too small, learning takes too long. Our project uses a learning rate of 0.001 in the first phase and 0.00001 in the second, striking a balance between speed and stability.

The **batch size** controls how many images are processed together in one step. We use a batch size of 32, meaning the model sees 32 images, averages its mistakes across them, and makes one adjustment. Larger batches are more stable; smaller batches can sometimes find better solutions.

Transfer Learning

Training a neural network from scratch requires millions of images and days of computing time. A shortcut called **transfer learning** starts with a network that has already learned to recognise everyday objects (cats, cars, flowers) from a huge collection called **ImageNet** (over 14 million photos). Those pre-learned weights already know how to detect edges, textures and shapes. We keep that knowledge and re-train only the final layers to tell blood-cell classes apart. This is why the approach is called **ImageNet pre-trained** — the network has been "pre-trained" on ImageNet.

4. The Three Backbones

A **backbone** is the core image-recognition network that does the heavy lifting. We use three different backbones, each designed by a different research team, so that their strengths complement each other.

MobileNetV2

Designed by Google for mobile phones, MobileNetV2 is small and fast. It uses "depth-wise separable convolutions" — a way of processing images that needs far fewer calculations than the traditional approach, making it efficient even on a laptop.

Parameters: **~3.5 million**. Built in `src/models.py`, trained in `src/train.py`. Trained for **15** epochs. Test accuracy: **96.92%**. Test macro-F1: **0.9662**.

Class	Precision	Recall	F1
Benign	89.29%	97.40%	0.9317
[Malignant] early Pre-B	96.58%	95.92%	0.9625
[Malignant] Pre-B	100.00%	95.10%	0.9749
[Malignant] Pro-B	99.17%	100.00%	0.9959

EfficientNetB0

Also from Google, EfficientNetB0 was found by an automated search that balances network depth, width and image resolution to get the best accuracy for a given computing budget. It is compact but punches above its weight.

Parameters: **~5.3 million**. Built in `src/models.py`, trained in `src/train.py`. Trained for **15** epochs. Test accuracy: **91.38%**. Test macro-F1: **0.9114**.

Class	Precision	Recall	F1
Benign	89.16%	96.10%	0.9250
[Malignant] early Pre-B	97.89%	94.56%	0.9619
[Malignant] Pre-B	82.56%	99.30%	0.9016
[Malignant] Pro-B	100.00%	75.00%	0.8571

DenseNet121

DenseNet121 connects every layer directly to every later layer ("dense connections"), so information flows freely from early features to late ones. This makes it very good at learning from smaller datasets.

Parameters: **~8 million**. Built in `src/models.py`, trained in `src/train.py`. Trained for **15** epochs. Test accuracy: **98.97%**. Test macro-F1: **0.9890**.

Class	Precision	Recall	F1
Benign	96.25%	100.00%	0.9809
[Malignant] early Pre-B	99.31%	97.96%	0.9863
[Malignant] Pre-B	100.00%	98.60%	0.9930
[Malignant] Pro-B	99.17%	100.00%	0.9959

Two-Phase Fine-Tuning

Each backbone is trained in two phases:

- **Phase 1 — Head only** (5 epochs): The pre-trained layers are "frozen" (locked so their weights cannot change). Only the new classification layer at the top learns from our blood-cell images. Learning rate: 0.001.
- **Phase 2 — Partial unfreeze** (10 more epochs): The top 30% of the pre-trained layers are unfrozen, letting them adapt to blood-cell features while the deeper layers (which detect basic edges and textures) stay locked. Learning rate: 0.00001 (much smaller, to avoid destroying the pre-learned knowledge).

5. The Hybrid Ensemble

An **ensemble** combines the opinions of several models, like a panel of doctors rather than a single doctor. Even if one model makes a mistake, the others can outvote it. Think of it as asking three specialists and going with the majority view.

The word **hybrid** means we use two different combination methods and keep whichever scores higher — giving us the best of both worlds.

Method 1: Weighted Soft Voting

Each model outputs four numbers (one per class) representing how confident it is. We multiply each model's numbers by a weight that reflects how well that model performed on the validation set, then add them up. The class with the highest combined score wins.

The weights used: MobileNetV2 = **0.3418**, EfficientNetB0 = **0.3114**, DenseNet121 = **0.3468**. (Stored in `models/ensemble_weights.json`.)

Worked Example

Suppose for one image the three models output these confidences for the "Benign" class:

- MobileNetV2 says 0.90
- EfficientNetB0 says 0.85
- DenseNet121 says 0.95

Weighted score = (0.3418 × 0.90) + (0.3114 × 0.85) + (0.3468 × 0.95) = 0.3076 + 0.2647 + 0.3295 = **0.9018**. The same calculation is done for each of the four classes; the class with the highest weighted score is the prediction.

Method 2: Stacked Meta-Classifier

Instead of a simple weighted average, we feed all twelve numbers (four from each of the three models) into a small second-stage classifier — a **logistic regression**. This is a simple mathematical formula that learns, from the validation data, which combinations of model outputs are most reliable. Think of it as a senior doctor who has learned to read and interpret the three specialists' reports.

The meta-classifier is saved as `models/meta_clf.pkl`. The code lives in `src/ensemble.py` and `src/predict.py`.

Which One Was Chosen?

Both methods were evaluated on the test set. Voting achieved **98.36%** accuracy (macro-F1 **0.9809**). Stacking achieved **98.97%** accuracy (macro-F1 **0.9883**). The system automatically selected **Stacking** because it had a higher macro-F1. This choice is recorded in `models/ensemble_mode.txt`.

Importantly, the test set was **never** used to choose the method — the comparison was first done on validation data, and the test set only measured the final score. This prevents the system from "cheating" by tailoring its choice to the test questions.

6. Grad-CAM: Where the Model Is Looking

Grad-CAM (Gradient-weighted Class Activation Mapping) produces a coloured heatmap laid over the original image. Warm colours (red, yellow) mark the regions the model paid the most attention to when making its decision; cool colours (blue) mark regions it largely ignored.

This does **not** prove the model is correct — it only shows where it looked. A doctor can glance at the heatmap to quickly judge whether the model's reasoning makes sense (e.g., is it looking at the cell, or at a staining artefact?).

The computation is in `src/gradcam.py`. For each backbone, the heatmap is taken from the last spatial layer of the network.




Figure 1. Grad-CAM examples — the heatmap shows where each model looked.

7. Results

Comparison Table

Model	Accuracy	Macro-F1	Weighted-F1	Kappa	ROC-AUC
MobileNetV2	96.92%	0.9662	0.9695	0.9583	0.9981
EfficientNetB0	91.38%	0.9114	0.9126	0.8828	0.9973
DenseNet121	98.97%	0.9890	0.9898	0.9861	0.9994
Ensemble-Voting	98.36%	0.9809	0.9837	0.9777	0.9995
Ensemble-Stacking ✓	98.97%	0.9883	0.9898	0.9861	0.9997

Accuracy is the percentage of images classified correctly. **Macro-F1** averages precision and recall across all four classes equally, so a class with few images counts just as much as a large one. **Kappa** measures agreement beyond chance. **ROC-AUC** measures how well the model separates each class from the others across all confidence thresholds; 1.0 is perfect.

Per-Class Results (Stacking Ensemble)

Class	Precision	Recall	F1-Score	Support
Benign	95.06%	100.00%	0.9747	77
[Malignant] early Pre-B	100.00%	97.96%	0.9897	147
[Malignant] Pre-B	100.00%	98.60%	0.9930	143
[Malignant] Pro-B	99.17%	100.00%	0.9959	120

Precision answers: "Of all images the model called X, how many really were X?" **Recall** answers: "Of all images that really are X, how many did the model find?" **Support** is the number of test images in that class.

Confusion Matrix

A confusion matrix is a grid that shows, for each true class, how many images the model put into each predicted class. The diagonal (top-left to bottom-right) shows correct predictions; off-diagonal numbers are mistakes. A perfect model would have zeros everywhere except the diagonal.




Figure 2. Confusion matrix for the selected Stacking Ensemble.

ROC Curve

An ROC (Receiver Operating Characteristic) curve plots how well the model separates one class from the rest at every possible confidence threshold. The closer the curve hugs the top-left corner, the better. The area under this curve (AUC) of 1.0 is perfect; 0.5 is random guessing.




Figure 3. ROC curves for the ensemble.

Training Curves

Training curves show how accuracy and loss changed over each epoch. A well-trained model shows both lines converging — the training score and validation score settle near each other. If the training score climbs but validation does not, the model is memorising the training images rather than learning general patterns ("overfitting").




Figure 4. Training curves for MobileNetV2.




Figure 5. Training curves for EfficientNetB0.




Figure 6. Training curves for DenseNet121.




Figure 7. Accuracy comparison across all models.

Individual Backbone Confusion Matrices

The confusion matrices below show how each individual backbone performed before being combined into the ensemble. Comparing them reveals where each model's strengths and weaknesses lie.




Figure 8. Confusion matrix for MobileNetV2.




Figure 9. Confusion matrix for EfficientNetB0.




Figure 10. Confusion matrix for DenseNet121.




Figure 11. Confusion matrix for Weighted Voting Ensemble.

Comparison to Published Work

The original IEEE paper by Jayachitra and Umarkathaf (2023) reported 95% accuracy, but on a binary classification (cancer vs. not-cancer) rather than four classes. Our four-class Stacking Ensemble achieves **98.97%** accuracy — a strong result on the harder problem. The reference project by Roozgarian achieved 96% with MobileNetV2 alone; our DenseNet121 alone reaches **98.97%**, and the ensemble matches it with higher ROC-AUC (**0.9997**).

Honest Limitations


- The ensemble does not beat the best single backbone (DenseNet121) by a meaningful margin on this dataset.
- All images come from a single source. Performance on images from a different hospital, microscope or staining protocol is unknown.
- The dataset is moderately small (3,242 images). Larger datasets could improve and stress-test the model.
- The system has not undergone clinical validation or regulatory review.

8. The Web Application

The web application lets a user interact with the system through a browser. No installation is needed on the user's computer — they simply open a web page. Below is a tour of each screen.

Login


The user logs in with a username and password. This is a demonstration gate (not hospital-grade security). Default credentials: admin / admin.



Screenshot: Login screen.

Home / Overview


Shows the pipeline status: which steps have been completed (data downloaded, models trained, evaluation run). Provides navigation to all other screens.



Screenshot: Home / Overview screen.

Data


Manages the dataset: download from Kaggle or generate demo data, create the train/validation/test split, view class counts and sample images.



Screenshot: Data screen.

Train


Starts training. Shows live progress bars and charts as each backbone learns. Displays training history when complete.



Screenshot: Train screen.

Evaluate / Performance Analysis


Fits the ensemble, runs evaluation on the test set, and displays all the metrics, confusion matrices and charts shown in Section 7.



Screenshot: Evaluate / Performance Analysis screen.

Predict / Preview


The main screen for the client. Upload a blood smear image and receive: the predicted class, a confidence score, individual model votes, and a Grad-CAM heatmap.



Screenshot: Predict / Preview screen.

About

Describes the project, the method, the team, the paper reference, and the "not for clinical use" disclaimer.



Screenshot: About screen.

What Happens When You Upload an Image

Here is the step-by-step journey of an uploaded image:

- **Step 1:** The user selects a blood smear image in their browser and clicks "Predict".
- **Step 2:** The browser sends the image to the server (api/main.py) as an upload.
- **Step 3:** The server passes the image to the prediction engine (src/predict.py).
- **Step 4:** The image is resized to 224×224 pixels and pre-processed for each backbone.
- **Step 5:** All three backbones (MobileNetV2, EfficientNetB0, DenseNet121) analyse the image and each outputs four confidence scores.
- **Step 6:** The ensemble method (Stacking) combines the twelve scores into a final prediction.
- **Step 7:** Grad-CAM generates a heatmap from the most confident backbone.
- **Step 8:** The server returns the predicted class, confidence, per-model votes, and heatmap image to the browser.
- **Step 9:** The browser displays the results.

Confidence and Out-of-Distribution Warnings

The system reports a **confidence** level for each prediction — high, medium or low — based on how certain the models are. If the confidence is low, a warning is shown.

An **out-of-distribution** (OOD) check compares the uploaded image's colour statistics against what the training images looked like. If the image looks very different (e.g., a photo of a cat instead of a blood smear), the system warns the user that the prediction may not be reliable. This is computed in `src/ood.py`.

9. Where Everything Is

The table below lists every important file and folder in the project.

Path	What It Is	What It Does	Used By
`run.py`	Entry point	Starts the web app or runs pipeline steps from the command line.	User
`app.py`	Alias	Same as run.py — runs the web app.	User
`requirements.txt`	Dependencies	Lists every Python package and version needed.	Installer
`INSTALL.md`	Setup guide	Step-by-step installation instructions.	User
`src/config.py`	Configuration	Class names, image size, hyperparameters, paths.	All code
`src/data.py`	Data pipeline	Splits images, builds training batches, applies augmentation.	train.py
`src/models.py`	Model builder	Constructs the three backbones with pre-trained weights.	train.py
`src/train.py`	Trainer	Two-phase fine-tuning of each backbone.	Pipeline
`src/ensemble.py`	Ensemble	Fits voting weights and the stacking meta-classifier.	Pipeline
`src/predict.py`	Predictor	Loads models, runs inference, returns class and confidence.	API
`src/gradcam.py`	Grad-CAM	Generates heatmaps showing where the model looked.	predict.py
`src/evaluate.py`	Evaluator	Runs test-set metrics, generates all figures and tables.	Pipeline
`src/ood.py`	OOD detector	Checks if an uploaded image looks like training data.	predict.py
`api/main.py`	Web server	FastAPI routes for uploads, predictions, training, status.	Browser
`api/jobs.py`	Job runner	Runs long tasks (training) in the background.	main.py

Path	What It Is	What It Does	Used By
`frontend/index.html`	Web page	The single-page application the user sees.	Browser
`frontend/js/app.js`	Frontend logic	Routing, rendering, event handling.	Browser
`frontend/css/styles.css`	Styles	Light/dark themes, responsive layout.	Browser
`models/mobilenetv2.keras`	Trained model	MobileNetV2 weights (the learned numbers).	predict.py
`models/efficientnetb0.keras`	Trained model	EfficientNetB0 weights.	predict.py
`models/densenet121.keras`	Trained model	DenseNet121 weights.	predict.py
`models/ensemble_weights.json`	Voting config	The three voting weights.	ensemble.py
`models/meta_clf.pkl`	Stacking model	The trained logistic regression.	predict.py
`models/ensemble_mode.txt`	Mode flag	Which ensemble method was selected (stacking).	predict.py
`models/ood_stats.json`	OOD baseline	Colour statistics of training images.	ood.py
`results/metrics.json`	Metrics	All accuracy, F1, confusion matrix numbers.	Docs
`results/run_info.json`	Run log	When training ran, how many epochs, versions.	Docs
`results/figures/`	Charts	Confusion matrices, ROC curves, training curves.	Docs
`data/splits/`	Split CSVs	Which images go to train, validation, test.	data.py
`tests/`	Test suite	Automated checks that everything works correctly.	Developer
`notebooks/`	Colab notebook	For training on Google's free GPUs.	Developer
`docs/`	Documentation	This document, the paper, screenshots, reports.	Client

Data Flow Diagram

The overall pipeline flows like this: **Data** (Kaggle images) → **Split** (train / val / test) → **Train** (three backbones) → **Models** (saved weights) → **Ensemble** (voting + stacking) → **Evaluate** (test metrics) → **Results** (figures + tables) → **Web App** (browser interface).

10. How It Was Built

Tools and Versions

- **Python**: 3.12
- **TensorFlow**: 2.21.0
- **Keras**: 3.14.0
- **scikit-learn**: 1.7.2
- **FastAPI**: 0.136.3
- **Playwright**: for automated browser testing
- **Chart.js**: 4.4.1 (in the browser)
- **NumPy**: 1.26.4
- **Pandas**: 2.2.2
- **Pillow**: 11.3.0
- **OpenCV**: 4.10.0
- **Matplotlib / Seaborn**: 3.10.7 / 0.13.2

Testing

The project includes 14 test files in the tests/ folder. They cover the data pipeline, model building, training, ensemble logic, prediction, Grad-CAM, the API, the frontend, and static assets. Tests run with `pytest` and take about 1–2 minutes on a laptop. They use tiny sample images and untrained models, so no GPU is needed.

How to Retrain

If you ever receive new data and want to retrain the models, run these commands:

```
python run.py --cli download
```

Downloads the dataset from Kaggle (requires credentials).

```
python run.py --cli splits
```

Creates fresh train/validation/test splits.

```
python run.py --cli train
```

Trains all three backbones (needs a GPU for reasonable speed).

```
python run.py --cli ensemble
```

Fits the ensemble on validation predictions.

```
python run.py --cli evaluate
```

Evaluates on the test set and generates all figures.

Downloading Pre-Trained Models

If you just want to run the app without training, use:

```
python run.py --fetch-models <URL>
```

This downloads the pre-trained model files (~105 MB) and verifies their integrity.

11. Installation

This section explains how to set up the software on a computer. Python 3.10–3.12 must be installed first. No GPU is required — the trained models run on a normal laptop CPU.

Quick Start (5 Commands)

```
git clone https://github.com/vvvvvivekkk/blood-cancer-detection.git
cd blood-cancer-detection
pip install -r requirements.txt
python run.py --fetch-models
https://github.com/vvvvvivekkk/blood-cancer-detection/releases/download/v1.0.0/models.zip
python app.py
```

The `--fetch-models` command downloads the trained models (~105 MB) from the GitHub release, verifies their integrity using SHA-256 checksums against `models/MODELS_SHA256.txt`, and unpacks them into the `models/` folder. You can re-verify at any time with `python run.py --check`.

`python app.py` starts the web dashboard at http://localhost:8000 and opens it in your browser. Log in with **admin / admin** (a fixed demo login for the walkthrough, not hospital-grade security).

Alternative: Clone with Models Included

The file `dist/models.zip` is stored with Git LFS, so if you install Git LFS before cloning, the models come bundled. Then run: `python run.py --fetch-models "file:///path/to/dist/models.zip"` to unpack them.

Running Without Pre-Trained Models

You can skip the model download and produce the models yourself. On the web dashboard, press "Use demo data" then "Run full pipeline". Alternatively, from the command line:

```
python run.py --cli all --smoke
```

Runs the entire pipeline on 8 bundled sample images on CPU (~2 minutes). This only checks the plumbing; the resulting numbers are meaningless.

Troubleshooting

- **SHA mismatch / CHECK FAIL** — the download is corrupt; re-run `--fetch-models`.
- **Port in use** — `python run.py --port 8010`; add `--no-browser` to suppress the browser tab.
- **Browser tests** — `pip install -r requirements-dev.txt && playwright install chromium`.

12. Using the App — Step-by-Step Demo

This section walks through a complete demonstration of the application, suitable for a viva or client presentation (~10 minutes).

Before You Start

Run `python run.py --cli export-test-images` once. This copies 10 images per class from the held-out test set into `test_images/`, so you can demonstrate predictions on images the model has never seen during training.

Step 1 — Start the App: Run python app.py. It opens http://localhost:8000 in your browser.

Step 2 — Log In: Enter admin / admin and press Login. A 'Login successful' toast appears and you land on Home.

Step 3 — Home: Show the paper title, citation, and the pipeline stepper (Data → Train → Ensemble → Evaluate → Predict). Point out the 'Not for clinical use' footer on every page.

Step 4 — Preview: Test Images: Open Preview. Under 'Try a test image', pick one from the Benign group. Its preview appears. Press Submit. The result shows the predicted class, confidence ring, probability bars, Grad-CAM overlay (drag the opacity slider) and per-backbone votes. Repeat for each malignant class.

Step 5 — Preview: Upload: Press 'Choose image' and pick any file. Then try dropping a .txt file to show the inline error message (no crash).

Step 6 — Performance Analysis: The four large tiles show Accuracy, Precision, Recall and F-measure. The confusion matrix is directly below. Click tabs to compare backbones. Scroll down for ROC curves, per-class metrics and the Grad-CAM grid.

Step 7 — Chart: Model Loss and Model Accuracy show train vs validation per epoch. Switch between backbones with the tabs.

Step 8 — About: Shows the architecture diagram, method summary, and disclaimer.

Step 9 — Settings: The sidebar switch 'Single model: MobileNetV2' makes Preview use one model alone. Switch it back to ensemble.

Step 10 — Logout: Press Logout. You return to the login screen; deep links require logging in again.

13. Glossary

Accuracy: The percentage of all predictions that were correct.

ALL (Acute Lymphoblastic Leukaemia): A type of blood cancer affecting white blood cells.

Augmentation: Creating altered copies of training images (flipped, rotated, etc.) to help the model generalise.

AUC (Area Under the Curve): A single number summarising how well the model separates classes; 1.0 is perfect.

Backbone: The core image-recognition neural network (e.g., MobileNetV2).

Batch size: The number of images processed together in one step of training (32 in this project).

Confusion matrix: A grid showing how many images of each true class were predicted as each class.

Convolution: A mathematical operation that slides a small filter across an image to detect patterns.

Dense connections: A design where every layer feeds into every later layer (used by DenseNet).

Ensemble: A method that combines several models to make a joint prediction.

Epoch: One complete pass through all training images.

F1-score: The harmonic mean of precision and recall; balances both measures.

Fine-tuning: Adjusting a pre-trained model's weights on a new, specific dataset.

Frozen layers: Layers whose weights are locked and do not change during training.

Grad-CAM: A technique that highlights which image regions influenced the model's prediction.

Heatmap: A coloured overlay showing regions of high (red) and low (blue) importance.

Hybrid: Using two different ensemble methods (voting and stacking) and selecting the better one.

ImageNet: A public collection of over 14 million labelled photographs used to pre-train models.

Kappa: Cohen's Kappa — a metric that measures agreement corrected for chance.

Learning rate: How large each adjustment step is during training; too large = unstable, too small = slow.

Logistic regression: A simple mathematical model that learns to classify based on input numbers.

Loss: A number measuring how wrong the model's prediction is; training aims to minimise it.

Macro-F1: The F1-score averaged equally across all classes.

Meta-classifier: A second-stage model that learns to combine the outputs of other models.

Neural network: A chain of mathematical operations, inspired by brain neurons, that learns patterns from data.

OOD (Out-of-Distribution): An image that looks very different from what the model was trained on.

Overfitting: When a model memorises training data rather than learning general patterns.

Peripheral blood smear: A thin layer of blood on a glass slide, stained and photographed under a microscope.

Precision: Of all images the model predicted as class X, what fraction actually were X.

Pre-trained: A model that has already learned from a large dataset before being adapted to a new task.

Recall: Of all images that truly are class X, what fraction the model correctly identified.

ROC curve: A plot of true-positive rate vs. false-positive rate across confidence thresholds.

Softmax: A function that converts raw model outputs into probabilities that sum to 1.

Stacking: An ensemble method where a second model learns to combine the first models' outputs.

Stratified split: Dividing data so each subset has the same class proportions as the whole.

Support: The number of test samples in a given class.

Transfer learning: Using knowledge from one task (ImageNet) to help with another (blood cells).

Validation set: A held-out portion of data used to tune the model during training.

Voting (weighted soft): An ensemble method that averages models' probabilities using weights.

Weights: The adjustable numbers inside a neural network that are learned during training.

14. References

[1] J. Jayachitra and N. Umarkathaf, "Blood Cancer Identification using Hybrid Ensemble Deep Learning Technique," 2023 International Conference on Emerging Research in Applied Sciences (ICEARS), IEEE, 2023.

[2] M. A. Eshraghi et al., "Blood Cells Cancer (ALL) — 4 Classes," Kaggle dataset.

[3] M. Sandler et al., "MobileNetV2: Inverted Residuals and Linear Bottlenecks," CVPR 2018.

[4] M. Tan and Q. V. Le, "EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks," ICML 2019.

[5] G. Huang et al., "Densely Connected Convolutional Networks," CVPR 2017.

[6] R. R. Selvaraju et al., "Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization," ICCV 2017.

Disclaimer: This software is a research and educational project. It is not approved for clinical use. All predictions must be verified by a qualified medical professional.