#### **APEX TRIGGERS**

# GET STARTED WITH APEX TRIGGERS AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {
   for(Account account:Trigger.New){
      if(account.Match_Billing_Address__c == True) {
        account.ShippingPostalCode = account.BillingPostalCode;
    }
   }
}
```

#### **BULK APEX TRIGGERS**

# ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
   List<Task> tasklist = new List<Task>();

for(Opportunity opp: Trigger.New){
   if(opp.StageName == 'Closed won'){
     tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
   }
  }
  if(tasklist.size()>0){
   insert tasklist;
  }
}
```

#### APPEX TESTING

# GET STARTED WITH APEX UNIT TEST VerifyDate.apxc

```
return SetEndOfMonthDate(date1);
              }
       }
       //method to check if date2 is within the next 30 days of date1
                     private static Boolean DateWithin30Days(Date date1, Date date2) {
              //check for date2 being in the past
       if( date2 < date1) { return false; }
       //check that date2 is within (>=) 30 days of date1
       Date date30Days = date1.addDays(30); //create a date 30 days away from date1
              if( date2 >= date30Days ) { return false; }
              else { return true; }
       }
       //method to return the end of the month of a given date
 @TestVisible
                     private static Date SetEndOfMonthDate(Date date1) {
              Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
              Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
              return lastDay;
       }
}
TestVerifyDate.apxc
@isTest
public class TestVerifyDate {
  @isTest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'), D);
  @isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'), D);
  }
  @isTest static void Test_DateWithin30Days_case1(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
    System.assertEquals(false, flag);
   @isTest static void Test_DateWithin30Days_case2(){
```

```
Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2019'));
    System.assertEquals(false, flag);
  @isTest static void Test DateWithin30Days case3(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
    System.assertEquals(true, flag);
  @isTest static Void Test_SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
  }
}
                      TEST APEX TRIGGERS
RestrictContactByName.apxt
trigger RestrictContactByName on Contact (before insert, before update) {
//check contacts prior to insert or update for invalid data
For (Contact c : Trigger.New) {
if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
c.AddError('The Last Name "'+c.LastName+" is not allowed for DML');
}
}
         CREATE TEST DATA FOR APEX TESTS:
RandomContactFactory.apxc
public class RandomContactFactory {
public static List<Contact> generateRandomContacts(Integer nument, string lastname){
List<Contact> contacts=new List<Contact>();
for(Integer i=0;i<numcnt;i++){</pre>
Contact cnt=new Contact(FirstName='Test '+i, LastName=lastname);
contacts.add(cnt);
return contacts:
}
```

# TestRestrictContactByName.apxc

```
@isTest
public class TestRestrictContactByName {
```

```
@isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt, false);
    Test.stopTest();
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
}
                  ASYNCHRONOUS APEX
USE FUTURE METHODS:
AccountProcessor.apxc
public class AccountProcessor {
  @future
  public static void countContacts(List<Id> accountIds){
    List<Account> accountsToUpdate = new List<Account>();
    List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];
    For(Account acc:accounts){
       List<Contact> contactList = acc.Contacts;
       acc.Number_of_Contacts__c = contactList.size();
       accountsToUpdate.add(acc);
    update accountsToUpdate;
}
```

 ${\bf Account Processor Test. apxc}$ 

@IsTest

```
public class AccountProcessorTest {
 @IsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount;
    Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId =
newAccount.Id);
    insert newContact1;
     Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId =
newAccount.Id);
    insert newContact2;
    List<Id> accountIds = new List<Id>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
  }
}
                        USE BATCH APEX:
 LeadProcessor.apxc
global class LeadProcessor implements Database.Batchable<sObject> {
  global Integer count = 0;
  global Database.QueryLocator start(Database.BatchableContext bc){
    return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }
  global void execute (Database.BatchableContext bc, List<Lead> L_list){
     List<lead> L_list_new = new List<lead>();
     for(lead L:L_list){
       L.leadsource = 'Dreamforce';
       L_list_new.add(L);
       count += 1;
     update L_list_new;
  global void finish(Database.BatchableContext bc){
    system.debug('count =' + count);
```

# LeadProcessorTest.apxc

```
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit(){
     List<lead> L_list = new List<lead>();
    for(Integer i=0; i<200; i++){
       Lead L = new lead();
       L.LastName = 'name' + i;
       L.Company = 'Company';
       L.Status = 'Random Status';
       L_list.add(L);
       }
    insert L_list;
    Test.startTest();
    LeadProcessor lp = new LeadProcessor();
    id batchId = Database.executeBatch(lp);
    Test.stopTest();
  }
}
```

# CONTROL PROCESSES WITH QUEUEABLE APEX:

## AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable {
   public contact c;
   public String state;

public AddPrimaryContact(Contact c, String state) {
     this.c = c;
     this.state = state;
   }

public void execute(QueueableContext qc) {
     system.debug('this.c = '+this.c+' this.state = '+this.state);
     List<Account> acc_lst = new List<account>([select id, name, BillingState from account where account.BillingState = :this.state limit 200]);
     List<contact> c_lst = new List<contact>();
     for(account a: acc_lst) {
        contact c = new contact();
        c = this.c.clone(false, false, false, false);
}
```

```
c.AccountId = a.Id;
       c_lst.add(c);
    insert c_lst;
  }
}
AddPrimaryContactTest.apxc
@IsTest
public class AddPrimaryContactTest {
  @IsTest
  public static void testing() {
    List<account> acc_lst = new List<account>();
    for (Integer i=0; i<50;i++) {
       account a = new account(name=string.valueOf(i),billingstate='NY');
       system.debug('account a = '+a);
       acc_lst.add(a);
    for (Integer i=0; i<50;i++) {
       account a = new account(name=string.valueOf(50+i),billingstate='CA');
       system.debug('account a = '+a);
       acc_lst.add(a);
    insert acc_lst;
    Test.startTest();
    contact c = new contact(lastname='alex');
    AddPrimaryContact apc = new AddPrimaryContact(c,'CA');
    system.debug('apc = '+apc);
    System.enqueueJob(apc);
    Test.stopTest();
    List<contact> c_lst = new List<contact>([select id from contact]);
    Integer size = c_{lst.size}();
    system.assertEquals(50, size);
  }
}
         SCHEDULE JOBS USING APEX SCHEDULER:
DailyLeadProcessor.apxc
global class DailyLeadProcessor implements Schedulable {
  global void execute(SchedulableContext ctx) {
    //Retrieving the 200 first leads where lead source is in blank.
    List<Lead> leads = [SELECT ID, LeadSource FROM Lead where LeadSource = "
LIMIT 200];
```

```
//Setting the LeadSource field the 'Dreamforce' value.
    for (Lead lead: leads) {
       lead.LeadSource = 'Dreamforce';
    //Updating all elements in the list.
    update leads;
  }
}
DailyLeadProcessorTest.apxc
@isTest
private class DailyLeadProcessorTest {
  @isTest
  public static void testDailyLeadProcessor(){
    //Creating new 200 Leads and inserting them.
    List<Lead> leads = new List<Lead>();
    for (Integer x = 0; x < 200; x++) {
       leads.add(new Lead(lastname='lead number ' + x, company='company number ' + x));
    insert leads;
    //Starting test. Putting in the schedule and running the DailyLeadProcessor execute
method.
    Test.startTest();
    String jobId = System.schedule('DailyLeadProcessor', '0 0 12 * * ?', new
DailyLeadProcessor());
    Test.stopTest();
    //Once the job has finished, retrieve all modified leads.
    List<Lead> listResult = [SELECT ID, LeadSource FROM Lead where LeadSource =
'Dreamforce' LIMIT 200];
    //Checking if the modified leads are the same size number that we created in the start of
this method.
    System.assertEquals(200, listResult.size());
  }
}
```

#### **APEX INTEGRATION SERVICES**

**APEX REST CALLOUTS:** 

AnimalLocator.apxc

```
public class AnimalLocator
 public static String getAnimalNameById(Integer id)
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
      String strResp = ";
      system.debug('*****response '+response.getStatusCode());
      system.debug('*****response '+response.getBody());
    // If the request is successful, parse the JSON response.
    if (response.getStatusCode() == 200)
       // Deserializes the JSON string into collections of primitive data types.
      Map<String, Object> results = (Map<String, Object>)
JSON.deserializeUntyped(response.getBody());
       // Cast the values in the 'animals' key as a list
      Map<string,object> animals = (map<string,object>) results.get('animal');
       System.debug('Received the following animals:' + animals );
       strResp = string.valueof(animals.get('name'));
       System.debug('strResp >>>>' + strResp );
    return strResp;
AnimalLocatorMock.apxc
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  global HTTPResponse respond(HTTPRequest request) {
     HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken
food", "says": "cluck cluck" \} \);
    response.setStatusCode(200);
    return response;
  }
}
AnimalLocatorTest.apxc
@isTest
private class AnimalLocatorTest{
  @isTest static void AnimalLocatorMock1() {
    Test.SetMock(HttpCallOutMock.class, new AnimalLocatorMock());
```

```
string result=AnimalLocator.getAnimalNameById(3);
string expectedResult='chicken';
System.assertEquals(result, expectedResult);
}
```

#### **APEX SOAP CALLOUTS:**

### ParkService.apxc

```
//Generated by wsdl2apex
public class ParkService {
  public class byCountryResponse {
    public String[] return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field order type info = new String[]{'return x'};
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
     public String clientCert x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'};
    public String[] byCountry(String arg0) {
       ParkService.byCountry request_x = new ParkService.byCountry();
       request_x.arg0 = arg0;
       ParkService.byCountryResponse response_x;
       Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
       response_map_x.put('response_x', response_x);
       WebServiceCallout.invoke(
        this,
        request_x,
        response_map_x,
        new String[]{endpoint_x,
```

```
'http://parks.services/',
        'byCountry',
        'http://parks.services/',
        'byCountryResponse',
        'ParkService.byCountryResponse'}
       response x = response map x.get('response x');
       return response_x.return_x;
     }
  }
ParkLocatorTest.apxc
@isTest
private class ParkLocatorTest {
  @isTest static void testCallout() {
    // This causes a fake response to be generated
    Test.setMock(WebServiceMock.class, new ParkServiceMock());
    // Call the method that invokes a callout
    //Double x = 1.0;
    //Double result = AwesomeCalculator.add(x, y);
    String country = 'Germany';
    String[] result = ParkLocator.Country(country);
    // Verify that a fake result is returned
     System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park', 'Hainich
National Park', 'Bavarian Forest National Park', result);
}
ParkServiceMock.apxc
@isTest
global class ParkServiceMock implements WebServiceMock {
 global void doInvoke(
      Object stub,
      Object request,
      Map<String, Object> response,
      String endpoint,
      String soapAction,
      String requestName,
      String responseNS,
      String responseName,
      String responseType) {
    // start - specify the response you want to send
    parkService.byCountryResponse response_x = new parkService.byCountryResponse();
    response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park',
'Hainich National Park', 'Bavarian Forest National Park'};
```

```
//calculatorServices.doAddResponse response_x = new
calculatorServices.doAddResponse();
    //response_x.return_x = 3.0;
    // end
    response.put('response_x', response_x);
}
APEX WEB SERVICES:
AccountManager.apxc
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static account getAccount() {
    RestRequest request = RestContext.request;
    String accountId = request.requestURI.substring(request.requestURI.lastIndexOf('/')-18,
      request.requestURI.lastIndexOf('/'));
    List<Account> a = [select id, name, (select id, name from contacts) from account where
id = :accountId];
    List<contact> co = [select id, name from contact where account.id = :accountId];
    system.debug('** a[0] = '+ a[0]);
    return a[0];
  }
}
AccountManagerTest.apxc
@istest
public class AccountManagerTest {
@istest static void testGetContactsByAccountId() {
Id recordId = createTestRecord();
// Set up a test request
RestRequest request = new RestRequest();
request.requestUri =
'https://yourInstance.salesforce.com/services/apexrest/Accounts/'+ recordId+'/Contacts';
request.httpMethod = 'GET';
RestContext.request = request;
Account this Account = Account Manager.get Account();
System.assert(thisAccount!= null);
System.assertEquals('Test record', thisAccount.Name);
```

```
// Helper method
static Id createTestRecord() {
// Create test record
Account accountTest = new Account(
Name='Test record');
insert accountTest;
Contact contactTest = new Contact(
FirstName='John',
LastName='Doe',
AccountId=accountTest.Id
return accountTest.Id;
APEX SPECIALIST
AUTOMATE RECORD CREATION:
MaintenanceRequest.apxt
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
MaintenanceRequestHelper.apxc
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id>validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
         if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
           validIds.add(c.Id);
    }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
```

```
Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM Equipment_Maintenance_Item_c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance Request c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
         Case nc = new Case (
           ParentId = cc.Id,
         Status = 'New',
           Subject = 'Routine Maintenance',
           Type = 'Routine Maintenance',
           Vehicle c = cc. Vehicle c,
           Equipment_c = cc. Equipment_c,
           Origin = 'Web',
           Date\_Reported\_\_c = Date.Today()
         );
         If (maintenanceCycles.containskey(cc.Id)){
           nc.Date\_Due\_\_c = Date.today().addDays((Integer))
maintenanceCycles.get(cc.Id));
         newCases.add(nc);
      insert newCases;
      List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
         for (Equipment_Maintenance_Item_c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
           Equipment_Maintenance_Item__c wpClone = wp.clone();
           wpClone.Maintenance_Request__c = nc.Id;
           ClonedWPs.add(wpClone);
         }
      insert ClonedWPs;
```

SYNCHRONIZATION SALESFORCE DATA WITH AN EXTERNAL SYSTEM:

# WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
         Map<String,Object> mapJson = (Map<String,Object>)eq;
         Product2 myEq = new Product2();
         myEq.Replacement Part c = (Boolean) mapJson.get('replacement');
         myEq.Name = (String) mapJson.get('name');
         myEq.Maintenance Cycle c = (Integer) mapJson.get('maintenanceperiod');
         myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
         myEq.Cost__c = (Decimal) mapJson.get('lifespan');
         myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
         myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
         warehouseEq.add(myEq);
       }
      if (warehouseEq.size() > 0){
         upsert warehouseEq;
         System.debug('Your equipment was synced with the warehouse one');
         System.debug(warehouseEq);
    }
```

# SCHEDULE SYNCHRONIZATION USING APEX CODE: WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
  }
}
TEST AUTOMATION LOGIC:
MaintenanceRequestHelperTest.apxc
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                       lifespan months C = 10,
                       maintenance cycle C = 10,
                       replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
              Status=STATUS_NEW,
              Origin=REQUEST ORIGIN,
              Subject=REQUEST_SUBJECT,
              Equipment_c=equipmentId,
              Vehicle c=vehicleId);
    return cs;
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                           Maintenance_Request__c = requestId);
```

```
return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c, Vehicle_c,
Date_Due__c
             from case
            where status =: STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                            from Equipment_Maintenance_Item_c
                            where Maintenance_Request__c =: newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
```

```
insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                   from case];
    Equipment Maintenance Item c workPart = [select id
                              from Equipment_Maintenance_Item__c
                              where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle C> vehicleList = new list<Vehicle C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id>oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
       equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
       requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
       workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
```

```
insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.Id);
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                   from case
                   where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                                from Equipment_Maintenance_Item__c
                                where Maintenance_Request_c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
  }
}
MaintenanceRequestHelper.apxc
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id>validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
         if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
           validIds.add(c.Id);
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
```

FROM Case WHERE Id IN :validIds]);

```
Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM Equipment_Maintenance_Item_c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance Request c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
         Case nc = new Case (
           ParentId = cc.Id,
         Status = 'New',
           Subject = 'Routine Maintenance',
           Type = 'Routine Maintenance',
           Vehicle c = cc. Vehicle c,
           Equipment_c = cc. Equipment_c,
           Origin = 'Web',
           Date\_Reported\_\_c = Date.Today()
         );
         If (maintenanceCycles.containskey(cc.Id)){
           nc.Date\_Due\_\_c = Date.today().addDays((Integer))
maintenanceCycles.get(cc.Id));
         newCases.add(nc);
      insert newCases;
      List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
         for (Equipment_Maintenance_Item_c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
           Equipment_Maintenance_Item__c wpClone = wp.clone();
           wpClone.Maintenance_Request__c = nc.Id;
           ClonedWPs.add(wpClone);
         }
      insert ClonedWPs;
```

## MaintenanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {
   if(Trigger.isUpdate && Trigger.isAfter){
      MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
   }
}
```

#### **TEST CALLOUT LOGIC:**

#### WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
       List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
       System.debug(response.getBody());
       for (Object eq : jsonResponse){
         Map<String,Object> mapJson = (Map<String,Object>)eq;
         Product2 myEq = new Product2();
         myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
         myEq.Name = (String) mapJson.get('name');
         myEq.Maintenance Cycle c = (Integer) mapJson.get('maintenanceperiod');
         myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
         myEq.Cost c = (Decimal) mapJson.get('lifespan');
         myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
         myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
         warehouseEq.add(myEq);
       }
       if (warehouseEq.size() > 0){
         upsert warehouseEq;
```

```
System.debug('Your equipment was synced with the warehouse one');
         System.debug(warehouseEq);
    }
WarehouseCalloutServiceTest.apxc
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
  }
}
WarehouseCalloutServiceMock.apxc
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity
":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
}
```

## **TEST SCHEDULING LOGIC:**

WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
  }
}
WarehouseSyncScheduleTest.apxc
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job
on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule ');
  }
```