NAVIGATION / +C THROUGH +C5

Quick reference card

Select a pad and press **INFO twice** for parameters. **Select + INFO** opens supported modulation. Page numbers refer to the full guide.

Waveform / Stop · 2	Vertical pinch: 25-3200% amplitude; horizontal: 4x farther out than stock. Two-finger tap restores 100% amplitude + stock horizontal view. Hold a Trigger grid pad or detail Play button 3 s to stop.
Speed / Pitch · 3	**Sample > LFO/Spd > SPEED**: 50-200%. One stretch voice, shared with Smooth; Pitch is unrestricted. Waiting voices stay at 100% until restart or neutral-then-adjust.
Tone · 4	**Pad > Tone**: Fidelity, Drive, Filter 2, Res 2 and Slope 1. Select + INFO on Drive, Filter 2 or Res 2 for modulation.
Clip / Slicer · 5-6	**Clip > Pos**: Loop Fade, Shift, Play Len, Sync, Live Flip, Fill every. **Slicer > Pos**: Sync, Sync Grid, **Slice Fit > Cut / Tape / Smooth**.
GEN · 7-8	**Pad > Gen**: algorithm, steps and timing. **Cnf**: Cond, Proc, Resp Pad; all GEN controls for Granular. Enable **Tools > Mstr > Section > GEN Run > Run On**.
Delay / reverb · 9-10	**FX1 > INFO > More**: extra delay controls. **FX2 > INFO**: reverb; More for detail. Tap selected FX2 again to switch to FX3, then INFO.
Sends / Dry · 11, 19	**Pad > Pos**: FX1/2/3 Send and Dry Level; select + INFO to modulate. Dry 0% gives wet-only sound. **Tools > Rec > FX Out** routes returns; FX3 has its own Out selector.
Modulation · 11-12	KEY, ENV, CHAOS, RAND and NET join native sources. Up to 12 saved routes per pad. Double-tap numeric dials to reset base values without clearing routes.
CV / MIDI · 13, 16	**Tools > Rec > CV In**: Scale, Offset, Quantize, Root. **Tools > MIDI > Monitor**: incoming messages, Freeze, channel filter, Clear.
Master · 14-15	**Tools > Comp**: compressor. **Mstr > Section**: Comp env, Master FX, Dist Ctrl and Sweep Mod. Compressor in Main and Mstr is the same setting.
Overdub · 17	Empty destination > **Cnf > Dub source**: Manual or Pad 1-16. **Dub tap**: Pre / Post pad / Post+FX. Record with **In 1/2**; Length Custom ends at Stop.
Recording / Resam · 18	**Rec Input > Resam** prints the native mix. Tap destination on Pads to Stop; INFO then opens it. To reopen without stopping, select with a left encoder + INFO. Right encoders adjust live Gain.
Display / reset · 2, 14	**Tools > Disp**: saver, graphic, signal wake. Double-tap counter for next-bar renumbering. **Main > RESET**: Tools or FX; Tools preserves saver preferences.
Install / recover · 20	Use official 2.3.4 in the browser patcher. Back up the card. Name output **BITBOXMK2.bin**, copy to card root and power up holding INFO. Use the original file to return to stock.