

class12

Vince (PID: A15422556)

2/24/2022

Differential Expression Analysis

Work on a complete differential expression analysis project using DESeq2.

```
library(DESeq2)
library(ggplot2)
library(AnnotationDbi)
library(org.Hs.eg.db)
```

Input the count and metadata files

```
countData <- read.csv("GSE37704_featurecounts.csv", row.names = 1)
colData <- read.csv("GSE37704_metadata.csv", row.names = 1)

head(countData[, -1])
```

##	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
## ENSG00000186092	0	0	0	0	0	0
## ENSG00000279928	0	0	0	0	0	0
## ENSG00000279457	23	28	29	29	28	46
## ENSG00000278566	0	0	0	0	0	0
## ENSG00000273547	0	0	0	0	0	0
## ENSG00000187634	124	123	205	207	212	258

```
head(colData)
```

##	condition
## SRR493366	control_sirna
## SRR493367	control_sirna
## SRR493368	control_sirna
## SRR493369	hoxa1_kd
## SRR493370	hoxa1_kd
## SRR493371	hoxa1_kd

Q. Complete the code below to remove the troublesome first column from countData

```
countData <- as.matrix(countData[,-1])
head(countData)
```

```
##                SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000186092         0         0         0         0         0         0
## ENSG00000279928         0         0         0         0         0         0
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000278566         0         0         0         0         0         0
## ENSG00000273547         0         0         0         0         0         0
## ENSG00000187634       124       123       205       207       212       258
```

Check correspondence of colData and countData

```
all(colData$id == colnames(count))
```

```
## [1] TRUE
```

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
counts <- countData[rowSums(countData) !=0, ]
head(counts)
```

```
##                SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000187634       124       123       205       207       212       258
## ENSG00000188976      1637      1831      2383      1226      1326      1504
## ENSG00000187961       120       153       180       236       255       357
## ENSG00000187583        24        48        65        44        48        64
## ENSG00000187642         4         9        16        14        16        16
```

Run DESeq analysis

```
dds <- DESeqDataSetFromMatrix(countData=counts,
                              colData=colData,
                              design=~condition)
```

```
## Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
## design formula are characters, converting to factors
```

```
dds <- DESeq(dds)
```

```
## estimating size factors
```

```
## estimating dispersions
```

```
## gene-wise dispersion estimates
```

```
## mean-dispersion relationship

## final dispersion estimates

## fitting model and testing

res <- results(dds, contrast=c("condition", "hoxa1_kd", "control_sirna"))
```

Q. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff. 4349 up-regulated, 4396 down-regulated

```
summary(res)

##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)      : 4349, 27%
## LFC < 0 (down)    : 4396, 28%
## outliers [1]      : 0, 0%
## low counts [2]    : 1237, 7.7%
## (mean count < 0)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

Add annotation

```
columns(org.Hs.eg.db)

## [1] "ACCNUM"      "ALIAS"        "ENSEMBL"      "ENSEMBLPROT"  "ENSEMBLTRANS"
## [6] "ENTREZID"    "ENZYME"       "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"    "GO"           "GOALL"        "IPI"          "MAP"
## [16] "OMIM"        "ONTOLOGY"     "ONTOLOGYALL"  "PATH"         "PFAM"
## [21] "PMID"        "PROSITE"      "REFSEQ"       "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

Q. Use the `mapIDs()` function multiple times to add `SYMBOL`, `ENTREZID` and `GENENAME` annotation to our results by completing the code below.

```
library("AnnotationDbi")
library("org.Hs.eg.db")

columns(org.Hs.eg.db)

## [1] "ACCNUM"      "ALIAS"        "ENSEMBL"      "ENSEMBLPROT"  "ENSEMBLTRANS"
## [6] "ENTREZID"    "ENZYME"       "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"    "GO"           "GOALL"        "IPI"          "MAP"
## [16] "OMIM"        "ONTOLOGY"     "ONTOLOGYALL"  "PATH"         "PFAM"
## [21] "PMID"        "PROSITE"      "REFSEQ"       "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

```
res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="SYMBOL",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="GENENAME",
                  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

log2 fold change (MLE): condition hoxa1_kd vs control_sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

```
##           baseMean log2FoldChange      lfcSE      stat      pvalue
##           <numeric>      <numeric> <numeric> <numeric> <numeric>
## ENSG00000279457  29.913579      0.1792571 0.3248216  0.551863 5.81042e-01
## ENSG00000187634 183.229650      0.4264571 0.1402658  3.040350 2.36304e-03
## ENSG00000188976 1651.188076     -0.6927205 0.0548465 -12.630158 1.43990e-36
## ENSG00000187961 209.637938      0.7297556 0.1318599  5.534326 3.12428e-08
## ENSG00000187583  47.255123      0.0405765 0.2718928  0.149237 8.81366e-01
## ENSG00000187642  11.979750      0.5428105 0.5215598  1.040744 2.97994e-01
## ENSG00000188290 108.922128      2.0570638 0.1969053 10.446970 1.51282e-25
## ENSG00000187608 350.716868      0.2573837 0.1027266  2.505522 1.22271e-02
## ENSG00000188157 9128.439422      0.3899088 0.0467163  8.346304 7.04321e-17
## ENSG00000237330  0.158192      0.7859552 4.0804729  0.192614 8.47261e-01
##           padj      symbol      entrez      name
##           <numeric> <character> <character> <character>
## ENSG00000279457 6.86555e-01  WASH9P  102723897 WAS protein family h..
## ENSG00000187634 5.15718e-03  SAMD11  148398 sterile alpha motif ..
## ENSG00000188976 1.76549e-35  NOC2L   26155 NOC2 like nucleolar ..
## ENSG00000187961 1.13413e-07  KLHL17  339451 kelch like family me..
## ENSG00000187583 9.19031e-01  PLEKHN1 84069 pleckstrin homology ..
## ENSG00000187642 4.03379e-01  PERM1   84808 PPARGC1 and ESRR ind..
## ENSG00000188290 1.30538e-24  HES4    57801 hes family bHLH tran..
## ENSG00000187608 2.37452e-02  ISG15   9636 ISG15 ubiquitin like..
## ENSG00000188157 4.21963e-16  AGRN    375790 agrin
## ENSG00000237330 NA      RNF223  401934 ring finger protein ..
```


Volcano Plot

Try ggplot


```
tmp <- as.data.frame(res)
```

```
ggplot(tmp) +  
  aes(log2FoldChange, -log(padj)) +  
  geom_point()
```

```
## Warning: Removed 1237 rows containing missing values (geom_point).
```



```
plot(res$log2FoldChange, -log(res$padj))
```




Q. Improve this plot by completing the below code, which adds color and axis labels

```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log(P-value)" )
```



```
library(EnhancedVolcano)
```


```
x <- as.data.frame(res)
```

```
EnhancedVolcano(x,  
  lab = x$symbol,  
  x = 'log2FoldChange',  
  y = 'pvalue')
```

```
## Warning: One or more p-values is 0. Converting to 10^-1 * current lowest non-  
## zero p-value...
```

Volcano plot

Enhanced Volcano



Pathway Analysis and Gene Set Enrichment

Which pathways and functions feature heavily in our differentially expressed genes.

```
library(pathview)
library(gage)
library(gageData)

data(kegg.sets.hs)
data(sigmet.idx.hs)

# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]

# Examine the first 3 pathways
head(kegg.sets.hs, 3)

## $'hsa00232 Caffeine metabolism'
## [1] "10" "1544" "1548" "1549" "1553" "7498" "9"
##
## $'hsa00983 Drug metabolism - other enzymes'
## [1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
## [9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
## [17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
```



```
## [25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
## [33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
## [41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
## [49] "8824" "8833" "9" "978"
##
## $'hsa00230 Purine metabolism'
## [1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
## [9] "108" "10846" "109" "111" "11128" "11164" "112" "113"
## [17] "114" "115" "122481" "122622" "124583" "132" "158" "159"
## [25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
## [33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
## [41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
## [49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
## [57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
## [65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
## [73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
## [81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
## [89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
## [97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
## [105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
## [113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
## [121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
## [129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
## [137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
## [145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
## [153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
## [161] "9583" "9615"
```

Need a “vector of importance” as input for GAGE that has ENTREZ IDs set as the names attribute.

```
foldchanges <- res$log2FoldChange
names(foldchanges) <- res$entrez
```

GAGE Pathway Analysis

```
keggres <- gage(foldchanges, gsets=kegg.sets.hs)
attributes(keggres)
```

```
## $names
## [1] "greater" "less" "stats"
```

```
head(keggres$less)
```

```
##                p.geomean stat.mean      p.val
## hsa04110 Cell cycle      8.995727e-06 -4.378644 8.995727e-06
## hsa03030 DNA replication  9.424076e-05 -3.951803 9.424076e-05
## hsa03013 RNA transport    1.246882e-03 -3.059466 1.246882e-03
## hsa03440 Homologous recombination 3.066756e-03 -2.852899 3.066756e-03
## hsa04114 Oocyte meiosis    3.784520e-03 -2.698128 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 8.961413e-03 -2.405398 8.961413e-03
##                q.val set.size      exp1
## hsa04110 Cell cycle      0.001448312      121 8.995727e-06
```


```
## hsa03030 DNA replication          0.007586381      36 9.424076e-05
## hsa03013 RNA transport            0.066915974     144 1.246882e-03
## hsa03440 Homologous recombination 0.121861535      28 3.066756e-03
## hsa04114 Oocyte meiosis           0.121861535     102 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 0.212222694      53 8.961413e-03
```

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory C:/Users/vince/Desktop/UCSD/Academic Years/Fourth Year/BIMM143/class12
```

```
## Info: Writing image file hsa04110.pathview.png
```



Gene Ontology

```
data(go.sets.hs)
data(go.subs.hs)
```

```
# Focus on Biological Process subset of GO
```

```
gobpsets = go.sets.hs[go.subs.hs$BP]
```

```
gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)
```

```
lapply(gobpres, head)
```

```
## $greater
```

```
##
##          p.geomean stat.mean      p.val
## GO:0007156 homophilic cell adhesion 8.519724e-05 3.824205 8.519724e-05
## GO:0002009 morphogenesis of an epithelium 1.396681e-04 3.653886 1.396681e-04
## GO:0048729 tissue morphogenesis 1.432451e-04 3.643242 1.432451e-04
## GO:0007610 behavior 2.195494e-04 3.530241 2.195494e-04
```

```
## G0:0060562 epithelial tube morphogenesis 5.932837e-04 3.261376 5.932837e-04
## G0:0035295 tube development 5.953254e-04 3.253665 5.953254e-04
## q.val set.size exp1
## G0:0007156 homophilic cell adhesion 0.1951953 113 8.519724e-05
## G0:0002009 morphogenesis of an epithelium 0.1951953 339 1.396681e-04
## G0:0048729 tissue morphogenesis 0.1951953 424 1.432451e-04
## G0:0007610 behavior 0.2243795 427 2.195494e-04
## G0:0060562 epithelial tube morphogenesis 0.3711390 257 5.932837e-04
## G0:0035295 tube development 0.3711390 391 5.953254e-04
##
## $less
## p.geomean stat.mean p.val
## G0:0048285 organelle fission 1.536227e-15 -8.063910 1.536227e-15
## G0:0000280 nuclear division 4.286961e-15 -7.939217 4.286961e-15
## G0:0007067 mitosis 4.286961e-15 -7.939217 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.169934e-14 -7.797496 1.169934e-14
## G0:0007059 chromosome segregation 2.028624e-11 -6.878340 2.028624e-11
## G0:0000236 mitotic prometaphase 1.729553e-10 -6.695966 1.729553e-10
## q.val set.size exp1
## G0:0048285 organelle fission 5.841698e-12 376 1.536227e-15
## G0:0000280 nuclear division 5.841698e-12 352 4.286961e-15
## G0:0007067 mitosis 5.841698e-12 352 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.195672e-11 362 1.169934e-14
## G0:0007059 chromosome segregation 1.658603e-08 142 2.028624e-11
## G0:0000236 mitotic prometaphase 1.178402e-07 84 1.729553e-10
##
## $stats
## stat.mean exp1
## G0:0007156 homophilic cell adhesion 3.824205 3.824205
## G0:0002009 morphogenesis of an epithelium 3.653886 3.653886
## G0:0048729 tissue morphogenesis 3.643242 3.643242
## G0:0007610 behavior 3.530241 3.530241
## G0:0060562 epithelial tube morphogenesis 3.261376 3.261376
## G0:0035295 tube development 3.253665 3.253665
```

Reactome Analysis

Q: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods? Endosomal/Vacuolar pathway. The pathways differ from the previous KEGG results. Using different criteria to determine pathways could cause differences.

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
## [1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=FALSE)
```

Save results

```
write.csv(res, file="deseq_results.csv")
```