IN1006 Systems Architecture 2024_2025
Tutorial 4: Instruction Set Architecture and Assembly Programming

1. What are the components of a very simple computer?

   CPU, Memory, IO

2. Name some special purpose registers?

   Accumulator, Program Counter

3. What is the purpose of a clock in a computer processor?

   Every computer contains at least one clock that synchronises the activities of its components. A fixed number of clock cycles are required to carry out each data movement or computational operation

4. What is meant by an Instruction Set Architecture?

   A specification of the interface between software and hardware describing the operations and addressing format

5. What classes of instructions generally make up an ISA?

   Arithmetic, memory access, I/O, control

6. What are the advantages of assembly programming over machine code?
   Human friendly, extra structuring features

7. Write a MARIE assembly language program to:

   Read 3 values from memory addresses FA, FB, FC, sum them, display the value and write the value back to FD (assuming no overflow)

   LOAD FA

   ADD FB

   ADD FC

   OUTPUT

   STORE FD

8. Write a simple Marie program that reads 3 numbers from memory, add the first 2 together, subtract the third, output the result and store the result back to memory. i.e. result = X+Y-Z; print(result);

   ```
   LOAD X
   ADD Y
   SUBT Z
   ```

```
        OUTPUT
        STORE RESULT
        HALT
X,      DEC 6
Y,      DEC 3
Z,      DEC 4
RESULT, DEC 0
```

9. What does these Marie code do?

```
INPUT
STORE W
ADD W
STORE X
ADD X
STORE Y
ADD Y
STORE Z
ADD Z
OUTPUT
HALT
W, DEC 0
X, DEC 0
Y, DEC 0
Z, DEC 0
```

This program reads a value from input to the accumulator, store it in memory doubling it up 4 times, outputting the final value, e.g. if 1 is entered it does 1, 2, 4, 8, 16 and prints out 16

10. What does this Marie code print to the output

```
        ORG 100
        LOAD 104
        ADDI 105
        OUTPUT
        HALT
104     HEX  4
105     HEX  106
106     HEX  3
```

-This code add indirectly (through 105) the values in address 104 and 106. If there was not ADDI but just ADD, the result would be $010A_h$ which is 266 in decimal.

11. After executing the following Marie code, what value will be stored at address location 109?

```
        ORG 100
        LOAD 106
        ADD 107
        SUBT 108
        CLEAR
        STORE 109
        HALT
106  DEC  4
```

```
107     DEC  9
108     DEC  5
```

- Zero will be stored at address 109, as the CLEAR instruction will set the Accumulator to 0 before the store instruction.

12. Write a program in Marie that print/output the numbers from 1 to 10. In high level language it would look like:

```
for(int i = 0; i<=10; i++){
print(i);
}
```

```
LOOP,     LOAD COUNTER
          ADD ONE
          OUTPUT
          STORE COUNTER
          SUBT TEN
          SKIPCOND 400
          JUMP LOOP
          HALT
COUNTER,  DEC  0
ONE,      DEC  1
TEN,      DEC  10
```

13. Using a subroutine, write a program that reads two numbers from memory, multiply them and show the result in the output.

i.e C = AxB;

Using a routine would look like this in high level language:

result = multiply(2,3);

print(result);

```
          ORG 100
          LOAD A
          STORE X
          LOAD B
          STORE Y
          JnS multiply      /Jump to multiplication subroutine
          LOAD RESULT       /Get result
          OUTPUT
          HALT
A,        Dec  2
B,        Dec  3
X,        Dec 0             /First parameter
Y,        Dec 0             /Second parameter
```

```
//****Subroutine to multiply***

multiply, Hex 0          /Store return address here
          Load X         /Load first parameter to be used as counter
          Store Counter  /Counter = X
Loop,     Load result    /Load the sum
          Add Y          /Add second parameter
          Store result   /Store result in result
          Load Counter   /load to AC the value in Counter
          Subt One       /Decrement counter
          Store Counter  /Store counter
          SkipCond 400   /If AC == 0 skip next line
          Jump Loop      /jump to label loop
          JumpI multiply /return or jump from subroutine to value stored in multiply which
          will indirectly jump back to instruction after Jns in main program.

          Counter, Dec 0  /Counter for looping
          One,     Dec 1  /Constant with value 1
          Result,  Dec 0  /return value for multiplication subroutine
```

14. Write a MARIE assembly language program to:

    Calculate A x B + C x D

    Hint: treat multiplication as a series of additions. Use the commands Skipcond together with Jump to loop. Use the multiply subroutine from Question 13 or look at the examples in the MARIE simulator directory that you downloaded when you installed the simulator.

15. Consider the following MARIE assembly language program. What does the program do?

```
          INPUT
LOOP,     STORE COUNTER
          OUTPUT
          SUBT ONE
          SKIPCOND 000
          JUMP LOOP
          HALT
COUNTER, DEC 0
ONE,     DEC 1
```

-This takes a number *n* from the input and prints all the numbers in reverse order from *n* down to 0.

16. Describe the F-D-E cycle for a simple machine.

    *The **fetch-decode-execute cycle** is the series of steps that a computer carries out when it runs a program.*
    We first have to fetch an instruction from memory, and place it into the IR.
    Once in the IR, it is decoded to determine what needs to be done next.

If a memory value (operand) is involved in the operation, it is retrieved and placed into the MBR.
With everything in place, the instruction is executed.