The VM20 valve is an in-line 1/8 BSP Ported 5/2 valve. Having a Ball operated, spring return function, the VM20 valve is interchangeable with the Capsula 1/8 valves.



. (III) PORTS 1/8 BSP 働

TECHNICAL SPECIFICATIONS

General

Maximum Pressure Flow to Atmosphere Permissible Mediums Ambient Temperature Range 0 - 8 Bar 450l/min at 7 Bar Air, inert gas, vacuumj Nitrile Seals: -10 - +50°C Viton Seals: 0 - +100°C

MATERIALS

Housing **End Caps** Spool

Anodised Aluminium Anodised Aluminium Aluminium

PRODUCT ORDERING CODE

VM20—4007—00—00V PRODUCT FAMILY VM20 - Capsula 1/8" Valve

ACTUATORS (SELECT BOTH ENDS) 07 - Spring

40 - Ball

VOLTAGE - SOLENOID *NO VOLTAGE*

<u>SEALS</u> 000 - Nitrile 00V - Viton

Mead Engineering Services Ltd.

Unit 9b, Parkland Business Centre, Chartwell Road, Lancing, West Sussex, United Kingdom, BN15 8UE

Tel: +44(0) 1903 854625

Fax: +44(0) 1903 851943

Email: sales@mead.co.uk

