Vyomi Appliance — Detailed Component Architecture

A full-stack component diagram of the appliance (v2.0.x). It shows the two request paths (console REST **and** native SOAP/JSON-RPC over), the provider + orchestrator core layers, the store **seams** with their in-memory vs real-backend implementations, the real backends, the compute/runtime path, support systems, and the Nanos/KVM substrate that issues the seam zones. `vyomi-local` (new v0.1) bundles FAKSIS dispatch.


Clients
Native SDK / CLI
boto3 · go-aws-sdk · aws-sdk-java-v2
(signs + talks AWS Query)
Browser — current creation
Vyomi Console (Next.js)
console.html
(FAKSIS — flask console redesign)
vyomi-launcher CLI
Entry — server.py · FaksIP app · RSS
SIGV4 AWS
app = FaksIP()
register_routes(app, providers, register)
FAKSIS_UNIFIED_SIGNING?
no
yes
AWS middleware
(SigV4 verify, region
ScopeEnforcer, RateLimiter,
CloudAudit, X-Ray/OTel,
IAM / StandardCarrier hop)
ID admin (not used; all
Console/CRUD goes vyomi-
ops)
device flow + principal
(`vyomi auth` / all tools)
Native dual-protocol (vyomi + some, to Eclipse)
vyomi-relay.* (external DB +
for tunnel)
Tenant Admin, Policies (ops)
Relay Node
Eclipse webclient
ec2_facts · Faksiks (EC2 API)
vyomi-bridge.* (external
NAT Gateway/Internet
vyomi-core* (credential-centric
AuthZ_core.py)
aws_sns_router
vyomi-provider-*_plugin.so
vyomi
(all consoles) + native
Native admin (vyomi) + some, to Eclipse
Native dual-protocol (vyomi + some, to Eclipse)