

# Writing middleware for use in Express apps

## Overview

**Middleware** functions are functions that have access to the request object (`req`), the response object (`res`), and the next function in the application's request-response cycle. The `next` function is a function in the Express router which, when invoked, executes the middleware succeeding the current middleware.

Middleware functions can perform the following tasks:

- Execute any code.
- Make changes to the request and the response objects.
- End the request-response cycle.
- Call the next middleware in the stack.

If the current middleware function does not end the request-response cycle, it must call `next()` to pass control to the next middleware function. Otherwise, the request will be left hanging.

The following figure shows the elements of a middleware function call:

```
var express = require('express');
var app = express();

app.get('/', function(req, res, next) {
  next();
})

app.listen(3000);
```


HTTP method for which the middleware function applies.

Path (route) for which the middleware function applies.

The middleware function.

Callback argument to the middleware function, called "next" by convention.

HTTP response argument to the middleware function, called "res" by convention.



**Using App Router**  
Features available in /app

- Getting Started
- Installation
- Project Structure
- Building Your Application
  - Routing
    - Defining Routes
    - Pages and Layouts
    - Linking and Navigating
    - Loading UI and Streaming
    - Error Handling
    - Redirecting
    - Route Groups
    - Project Organization
    - Dynamic Routes
    - Parallel Routes
    - Intercepting Routes
    - Route Handlers
    - Middleware
    - Internationalization

- Data Fetching >
- Rendering >
- Caching
- Styling >
- Optimizing >
- Configuring >
- Testing >

App Router > ... > Routing > **Middleware**

**Middleware** ←

Middleware allows you to run code before a request is completed. Then, based on the incoming request, you can modify the response by rewriting, redirecting, modifying the request or response headers, or responding directly.

Middleware runs before cached content and routes are matched. See [Matching Paths](#) for more details.

## Convention

Use the file `middleware.ts` (or `.js`) in the root of your project to define Middleware. For example, at the same level as `pages` or `app`, or inside `src` if applicable.

### Example

```
1 import { NextResponse } from 'next/server'
2 import type { NextRequest } from 'next/server'
3
4 // This function can be marked 'async' if using 'await' inside
5 export function middleware(request: NextRequest) {
6     return NextResponse.redirect(new URL('/home', request.url))
7 }
8
9 // See "Matching Paths" below to learn more
10 export const config = {
11     matcher: '/about/:path*',
12 }
```


## On this page

- Convention
- Example
- Matching Paths
  - Matcher
  - Conditional Statements
- NextResponse
- Using Cookies
- Setting Headers
- CORS
- Producing a Response
  - waitUntil and NextFetchEvent
- Advanced Middleware Flags
- Runtime
- Version History

---

Edit this page on GitHub ↗





Watch  
video 126

## Convention

Use the file `middleware.ts` (or `.js`) in the root of your project to define Middleware. For example, at the same level as `pages` or `app`, or inside `src` if applicable.

## Example

```
middleware.js
JavaScript
1 import { NextResponse } from 'next/server'
2
3 // This function can be marked 'async' if using 'await' inside
4 export function middleware(request) {
5   return NextResponse.redirect(new URL('/home', request.url))
6 }
7
8 // See "Matching Paths" below to learn more
9 export const config = {
10   matcher: '/about/:path*',
11 }
```

## Matching Paths

Middleware will be invoked for every route in your project. The following is the execution order:

1. `headers` from `next.config.js`
2. `redirects` from `next.config.js`
3. Middleware (`rewrites`, `redirects`, etc.)
4. `beforeFiles` (`rewrites`) from `next.config.js`

### On this page

- [Convention](#)
- [Example](#)
- [Matching Paths](#)
- [Matcher](#)
- [Conditional Statements](#)
- [NextResponse](#)
- [Using Cookies](#)
- [Setting Headers](#)
- [CORS](#)
- [Producing a Response](#)
- [waitUntil and NextFetchEvent](#)
- [Advanced Middleware Flags](#)
- [Runtime](#)
- [Version History](#)
- [Edit this page on GitHub](#)
- [Scroll to top](#)



nextjs.org/docs/app/building-your-application/routing/middleware

Sigma Web Developme...GitHub - CodeWithHarr...Learn to code online - C...EJs with ExpressRouting: Middleware | N...

▲NEXT.js

ShowcaseDocsBlogAnalyticsTemplatesEnterprise

Search documentation...CtrlKFeedbackLearn

Using App RouterFeatures available in /app

Getting StartedInstallationProject StructureBuilding Your ApplicationRoutingDefining RoutesPages and LayoutsLinking and NavigatingLoading UI and StreamingError HandlingRedirectingRoute GroupsProject OrganizationDynamic RoutesParallel RoutesIntercepting RoutesRoute HandlersMiddlewareInternationalizationData Fetching

You can set request and response headers using the `NextResponse` API (setting `request` headers is available since Next.js v13.0.0).

middleware.jsJavaScript

```
1 import { NextResponse } from 'next/server'
2
3 export function middleware(request) {
4   // Clone the request headers and set a new header 'x-hello-from-middleware'
5   const requestHeaders = new Headers(request.headers)
6   requestHeaders.set('x-hello-from-middleware1', 'hello')
7
8   // You can also set request headers in NextResponse.rewrite
9   const response = NextResponse.next({
10     request: {
11       // New request headers
12       headers: requestHeaders,
13     },
14   })
15
16   // Set a new response header 'x-hello-from-middleware2'
17   response.headers.set('x-hello-from-middleware2', 'hello')
18   return response
19 }
```

Good to know: Avoid setting large headers as it might cause [431 Request Header Fields Too Large](#) error depending on your backend web server configuration.

### CORS

You can set CORS headers in Middleware to allow cross-origin requests, including [simple](#) and [preflighted](#) requests.


On this page

ConventionExampleMatching PathsMatcherConditional StatementsNextResponseUsing CookiesSetting HeadersCORSProducing a ResponsewaitUntil and NextFetchEventAdvanced Middleware FlagsRuntimeVersion History

Edit this page on GitHub ↗

Scroll to top ⌴

# Setting Headers



20°C Cloudy

Search

19:22 Sat