ia_study1_computeMeasures

2026-03-11

Admin (Packages & Custom Functions)

```r
#setwd(dirname(rstudioapi::getActiveDocumentContext()$path))
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ------------------------ tidyverse 2.0.0 --
## v dplyr     1.1.4     v readr     2.1.5
## v forcats   1.0.0     v stringr   1.6.0
## v ggplot2   4.0.0     v tibble    3.3.0
## v lubridate 1.9.3     v tidyr     1.3.1
## v purrr     1.2.0
## -- Conflicts ------------------------------------------ tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()    masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

Load Data

```
data <- read_csv("ia_study1_anon_data.csv")
data <- data[ , -1]
```

Ten Item Personality Inventory (TIPI)

Next, we compute the composite scores of the participant-level TIPI variables. Specifically, we calculate:

1. participant's extraversion `tipi_ex`

- `tipi_1` (Extraverted, enthusiastic), `tipi_6` (reversed; Reserved, quiet)

2. participant's agreeableness, `tipi_a`

- `tipi_2` (reversed; Critical, quarrelsome), `tipi_7` (Sympathetic, warm)

3. participant's conscientiousness, `tipi_c`

- `tipi_3` (Dependable, self-disciplined), `tipi_8` (reversed; Disorganized, careless)

4. participant's emotoinal stability, `tipi_es`

- `tipi_4` (reversed; Anxious, easily upset), `tipi_9` (Calm, emotionally stable)

5. participant's openness to experience, `tipi_o`

- `tipi_5` (Open to new experiences, complex), `tipi_10` (reversed; Conventional, uncreative)

```
# compute tipi variables
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # reverse code tipi items
    tipi_6r = 8 - tipi_6,
    tipi_2r = 8 - tipi_2,
    tipi_8r = 8 - tipi_8,
    tipi_4r = 8 - tipi_4,
    tipi_10r = 8 - tipi_10
    ) %>%
  dplyr::mutate( # calculate tipi_ex, tipi_a, tipi_c, tipi_es, and tipi_o
    tipi_ex = mean(c(tipi_1, tipi_6r), na.rm = T),
    tipi_a = mean(c(tipi_2r, tipi_7), na.rm = T),
    tipi_c = mean(c(tipi_3, tipi_8r), na.rm = T),
    tipi_es = mean(c(tipi_4r, tipi_9), na.rm = T),
    tipi_o = mean(c(tipi_5, tipi_10r), na.rm = T)
    ) %>%
  ungroup()
```

```r
data %>%
  dplyr::select("tipi_1", "tipi_6r",
                "tipi_2r", "tipi_7",
                "tipi_3", "tipi_8r",
                "tipi_4r", "tipi_9",
                "tipi_5", "tipi_10r") %>%
  cor(use = "pairwise.complete.obs") %>%
  round(2)
```

```
##          tipi_1 tipi_6r tipi_2r tipi_7 tipi_3 tipi_8r tipi_4r tipi_9 tipi_5
## tipi_1     1.00    0.62   -0.23   0.10   0.04   -0.22   -0.01  -0.10   0.23
## tipi_6r    0.62    1.00   -0.09   0.02  -0.09   -0.15    0.04  -0.23   0.09
## tipi_2r   -0.23   -0.09    1.00   0.12  -0.04    0.26    0.14   0.08   0.02
## tipi_7     0.10    0.02    0.12   1.00   0.03    0.04   -0.15   0.00   0.15
## tipi_3     0.04   -0.09   -0.04   0.03   1.00    0.45    0.10   0.30   0.21
## tipi_8r   -0.22   -0.15    0.26   0.04   0.45    1.00    0.23   0.18  -0.07
## tipi_4r   -0.01    0.04    0.14  -0.15   0.10    0.23    1.00   0.43   0.00
## tipi_9    -0.10   -0.23    0.08   0.00   0.30    0.18    0.43   1.00   0.08
## tipi_5     0.23    0.09    0.02   0.15   0.21   -0.07    0.00   0.08   1.00
## tipi_10r   0.06    0.21    0.08   0.02   0.01    0.07    0.24  -0.14   0.27
##          tipi_10r
## tipi_1       0.06
## tipi_6r      0.21
## tipi_2r      0.08
## tipi_7       0.02
## tipi_3       0.01
## tipi_8r      0.07
## tipi_4r      0.24
## tipi_9      -0.14
## tipi_5       0.27
## tipi_10r     1.00
```

```r
# European American
data %>% dplyr::filter(cultureEA == 1) %>%
  dplyr::select("tipi_1", "tipi_6r",
                "tipi_2r", "tipi_7",
                "tipi_3", "tipi_8r",
                "tipi_4r", "tipi_9",
               "tipi_5", "tipi_10r") %>%
  cor(use = "pairwise.complete.obs") %>%
  round(2)
```

```
##          tipi_1 tipi_6r tipi_2r tipi_7 tipi_3 tipi_8r tipi_4r tipi_9 tipi_5
## tipi_1     1.00    0.58   -0.19   0.20   0.07   -0.16    0.09   0.14   0.24
## tipi_6r    0.58    1.00    0.02  -0.03  -0.05    0.08    0.22  -0.07   0.11
## tipi_2r   -0.19    0.02    1.00   0.14  -0.16    0.18    0.16  -0.18   0.03
## tipi_7     0.20   -0.03    0.14   1.00   0.09    0.01   -0.24  -0.05   0.10
## tipi_3     0.07   -0.05   -0.16   0.09   1.00    0.36    0.12   0.41   0.05
## tipi_8r   -0.16    0.08    0.18   0.01   0.36    1.00    0.31   0.13  -0.17
## tipi_4r    0.09    0.22    0.16  -0.24   0.12    0.31    1.00   0.48  -0.01
## tipi_9     0.14   -0.07   -0.18  -0.05   0.41    0.13    0.48   1.00   0.11
## tipi_5     0.24    0.11    0.03   0.10   0.05   -0.17   -0.01   0.11   1.00
## tipi_10r  -0.04    0.22    0.25   0.03  -0.16    0.23    0.11  -0.26   0.18
```

```
##          tipi_10r
## tipi_1      -0.04
## tipi_6r      0.22
## tipi_2r      0.25
## tipi_7       0.03
## tipi_3      -0.16
## tipi_8r      0.23
## tipi_4r      0.11
## tipi_9      -0.26
## tipi_5       0.18
## tipi_10r     1.00
```

```
# Taiwanese
data %>% dplyr::filter(cultureEA == 0) %>%
  dplyr::select("tipi_1", "tipi_6r",
                "tipi_2r", "tipi_7",
                "tipi_3", "tipi_8r",
                "tipi_4r", "tipi_9",
                "tipi_5", "tipi_10r")%>%
  cor(use = "pairwise.complete.obs") %>%
  round(2)
```

```
##          tipi_1 tipi_6r tipi_2r tipi_7 tipi_3 tipi_8r tipi_4r tipi_9 tipi_5
## tipi_1     1.00    0.68   -0.28   0.00   0.02   -0.31   -0.13  -0.39   0.21
## tipi_6r    0.68    1.00   -0.18   0.07  -0.06   -0.32   -0.10  -0.39   0.11
## tipi_2r   -0.28   -0.18    1.00   0.10   0.08    0.37    0.14   0.32   0.02
## tipi_7     0.00    0.07    0.10   1.00  -0.05    0.06   -0.07   0.04   0.18
## tipi_3     0.02   -0.06    0.08  -0.05   1.00    0.42    0.00   0.27   0.28
## tipi_8r   -0.31   -0.32    0.37   0.06   0.42    1.00    0.10   0.26  -0.05
## tipi_4r   -0.13   -0.10    0.14  -0.07   0.00    0.10    1.00   0.38  -0.03
## tipi_9    -0.39   -0.39    0.32   0.04   0.27    0.26    0.38   1.00   0.06
## tipi_5     0.21    0.11    0.02   0.18   0.28   -0.05   -0.03   0.06   1.00
## tipi_10r   0.17    0.26   -0.02  -0.01  -0.02   -0.18    0.31  -0.03   0.31
##          tipi_10r
## tipi_1       0.17
## tipi_6r      0.26
## tipi_2r     -0.02
## tipi_7      -0.01
## tipi_3      -0.02
## tipi_8r     -0.18
## tipi_4r      0.31
## tipi_9      -0.03
## tipi_5       0.31
## tipi_10r     1.00
```

Interpersonal Reativity Index (IRI)

Next, we compute the composite scores of the participant-level IRI variables. Specifically, we calculate:

1. participant's perspective-taking `iri_pt`

- calculated by averaging `iri3`, `iri8`, `iri11`, `iri15`, `iri21`, `iri25`, & `iri28`

2. participant's fantasy, `iri_fs`

- calculated by averaging `iri1`, `iri5`, `iri7`, `iri12`, `iri16`, `iri23`, & `iri26`

3. participant's empathetic concern, `iri_ec`

- calculated by averaging `iri2`, `iri4`, `iri9`, `iri14`, `iri18`, `iri20`, & `iri22`

4. participant's personal distress, `iri_pd`

- calculated by averaging `iri6`, `iri10`, `iri13`, `iri17`, `iri19`, `iri24`, & `iri27`

```
# compute iri variables
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # reverse code iri items
    iri3r = 6 - iri3,
    iri4r = 6 - iri4,
    iri7r = 6 - iri7,
    iri12r = 6 - iri12,
    iri13r = 6 - iri13,
    iri14r = 6 - iri14,
    iri15r = 6 - iri15,
    iri18r = 6 - iri18,
    iri19r = 6 - iri19,
    ) %>%
  dplyr::mutate( # calculate iri_pt, iri_fs, iri_ec, iri_pd
    iri_pt = mean(
      c(iri3r, iri8, iri11, iri15r, iri21, iri25, iri28), na.rm = T),
    iri_fs = mean(
      c(iri1, iri5, iri7r, iri12r, iri16, iri23, iri26), na.rm = T),
    iri_ec = mean(
      c(iri2, iri4r, iri9, iri14r, iri18r, iri20, iri22), na.rm = T),
    iri_pd = mean(
      c(iri6, iri10, iri13r, iri17, iri19r, iri24, iri27), na.rm = T)
    ) %>%
  ungroup()
```

```
reliab_iri <- c("iri3r, iri8, iri11, iri15r, iri21, iri25, iri28",
               "iri1, iri5, iri7r, iri12r, iri16, iri23, iri26",
               "iri2, iri4r, iri9, iri14r, iri18r, iri20, iri22",
               "iri6, iri10, iri13r, iri17, iri19r, iri24, iri27")

reliab_iri_names <- c("iri_pt", "iri_fs", "iri_ec", "iri_pd")

all_alphas(data, items = reliab_iri, constructs = reliab_iri_names,
           sensitivity = sensitivity_analyses)
```

```
## # A tibble: 12 x 5
##    construct      `!is.na(subID)` `exclude_age != 1` `exclude_sd != 1`
##    <chr>                    <dbl>              <dbl>             <dbl>
##  1 iri_pt_overall            0.77               0.77              0.77
```

```
## 2 iri_fs_overall          0.8              0.8              0.78
## 3 iri_ec_overall          0.79             0.8              0.79
## 4 iri_pd_overall          0.8              0.8              0.79
## 5 iri_pt_EA               0.78             0.79             0.78
## 6 iri_fs_EA               0.83             0.84             0.82
## 7 iri_ec_EA               0.78             0.8              0.78
## 8 iri_pd_EA               0.84             0.84             0.84
## 9 iri_pt_TN               0.76             0.76             0.76
## 10 iri_fs_TN              0.76             0.76             0.76
## 11 iri_ec_TN              0.79             0.8              0.79
## 12 iri_pd_TN              0.75             0.75             0.71
## # i 1 more variable: `exclude_age != 1 & exclude_sd != 1` <dbl>
```

AVI - Ideal and Actual HAP & LAP

Now, we compute the composite scores of the participant-level AVI variables. Specifically, we calculate:

1. participant's actual HAP, `rHAP`

- calculated by averaging `r1_1` (enthusiastic), `r1_7` (excited), `r1_9` (elated), `r2_9` (euphoric)

2. participant's actual LAP, `rLAP`

- calculated by averaging `r1_6` (relaxed), `r3_3` (calm), `r3_9` (peaceful), `r3_10` (serene)

3. participant's ideal HAP, `iHAP`

- calculated by averaging `i1_1` (enthusiastic), `i1_7` (excited), `i1_9` (elated), `i2_9` (euphoric)

4. participant's ideal LAP, `iLAP`

- calculated by averaging `i1_6` (relaxed), `i3_3` (calm), `i3_9` (peaceful), `i3_10` (serene)

5. participant's ipsatized `rHAP`, `rLAP`, `iHAP`, and `iLAP` scores

- calculated by converting ratings using this formula: `ipsatized score = (raw score - individuals' mean ratings across all emotion items) / (individuals' sd across the ratings on all emotion items)`

```r
# compute AVI variables
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # create rHAP, rLAP, iHAP, iLAP
    rHAP = mean(c(r1_1, r1_7, r1_9, r2_9), na.rm = T),
    rLAP = mean(c(r1_6, r3_3, r3_9, r3_10), na.rm = T),
    iHAP = mean(c(i1_1, i1_7, i1_9, i2_9), na.rm = T),
    iLAP = mean(c(i1_6, i3_3, i3_9, i3_10), na.rm = T)) %>%
  dplyr::mutate( # create intermediate variables for ipsatize scores
    rMean = mean(c_across(matches("^r[1-4]_[1-9][0]*$")), na.rm = TRUE),
```

```r
    rSd = sd(c_across(matches("^r[1-4]_[1-9]$|^r4_10$")), na.rm = TRUE),
    iMean = mean(c_across(matches("^i[1-4]_[1-9][0]*$")), na.rm = TRUE),
    iSd = sd(c_across(matches("^i[1-4]_[1-9]$|^i4_10$")), na.rm = TRUE)) %>%
  dplyr::mutate( # create ipsatized item scores
    across(matches("^r[1-4]_[1-9][0]*$"),
           ~ as.numeric((.x - rMean) / rSd),
           .names = "{.col}_i"),
    across(matches("^i[1-4]_[1-9][0]*$"),
           ~ as.numeric((.x - iMean) / iSd),
           .names = "{.col}_i")) %>%
  dplyr::mutate( # create ipsatized rHAP, rLAP, iHAP, iLAP
    rHAP_i = mean(c(r1_1_i, r1_7_i, r1_9_i, r2_9_i), na.rm = T),
    rLAP_i = mean(c(r1_6_i, r3_3_i, r3_9_i, r3_10_i), na.rm = T),
    iHAP_i = mean(c(i1_1_i, i1_7_i, i1_9_i, i2_9_i), na.rm = T),
    iLAP_i = mean(c(i1_6_i, i3_3_i, i3_9_i, i3_10_i), na.rm = T)) %>%
  ungroup()
```

```r
# calculate cronbach alpha

reliab_avi <- c("r1_1, r1_7, r1_9, r2_9",
                "r1_6, r3_3, r3_9, r3_10",
                "i1_1, i1_7, i1_9, i2_9",
                "i1_6, i3_3, i3_9, i3_10")

reliab_avi_names <- c("rHAP", "rLAP", "iHAP", "iLAP")

all_alphas(data, items = reliab_avi, constructs = reliab_avi_names,
           sensitivity = sensitivity_analyses)
```

```
## # A tibble: 12 x 5
##    construct    `!is.na(subID)` `exclude_age != 1` `exclude_sd != 1`
##    <chr>                  <dbl>              <dbl>             <dbl>
##  1 rHAP_overall            0.83               0.81              0.8
##  2 rLAP_overall            0.85               0.85              0.84
##  3 iHAP_overall            0.79               0.79              0.76
##  4 iLAP_overall            0.76               0.77              0.75
##  5 rHAP_EA                 0.87               0.85              0.84
##  6 rLAP_EA                 0.85               0.86              0.83
##  7 iHAP_EA                 0.8                0.79              0.74
##  8 iLAP_EA                 0.73               0.75              0.69
##  9 rHAP_TN                 0.78               0.78              0.77
## 10 rLAP_TN                 0.86               0.86              0.85
## 11 iHAP_TN                 0.77               0.77              0.77
## 12 iLAP_TN                 0.81               0.81              0.81
## # i 1 more variable: `exclude_age != 1 & exclude_sd != 1` <dbl>
```

AVI - Maximizing Positivity

Now, we compute the composite scores of the participant-level AVI variables. Specifically, we calculate:

1. participant's actual PA, `rPA`

- calculated by averaging `r1_1` (enthusiastic), `r1_7` (excited), `r1_9` (elated), `r2_9` (euphoric), `r1_6` (relaxed), `r3_3` (calm), `r3_9` (peaceful), `r3_10` (serene), `r3_1` (happy), `r3_7` (satisfied), `r2_5` (content)

2. participant's actual NA, `rNA`

- calculated by averaging `r2_10` (fearful), `r3_6` (hostile), `r1_3` (nervous), `r2_8` (sad), `r2_2` (lonely), `r3_4` (unhappy), `r2_6` (sluggish), `r1_10` (sleepy), `r1_4` (dull)

3. participant's ideal PA, `iPA`

- calculated by averaging `i1_1` (enthusiastic), `i1_7` (excited), `i1_9` (elated), `i2_9` (euphoric), `i1_6` (relaxed), `i3_3` (calm), `i3_9` (peaceful), `i3_10` (serene), `i3_1` (happy), `i3_7` (satisfied), `i2_5` (content)

4. participant's ideal NA, `iNA`

- calculated by averaging `i2_10` (fearful), `i3_6` (hostile), `i1_3` (nervous), `i2_8` (sad), `i2_2` (lonely), `i3_4` (unhappy), `i2_6` (sluggish), `i1_10` (sleepy), `i1_4` (dull)

5. participant's ipsatized `rPA`, `rNA`, `iPA`, and `iNA` scores
6. participant's raw maximizing positivity scores `maxPos` and ipsatized maximizing positivity scores `maxPos_i`

- calculated by subtracting (ipsatized) ideal NA from ideal PA

```
# compute AVI variables
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # create rPA, rNA, iPA, iNA
    rPA = mean(
      c(r1_1, r1_7, r1_9, r2_9, r1_6, r3_3, r3_9, r3_10, r3_1, r3_7, r2_5),
      na.rm = T),
    rNA = mean(
      c(r2_10, r3_6, r1_3, r2_8, r2_2, r3_4, r2_6, r1_10, r1_4),
      na.rm = T),
    iPA = mean(
      c(i1_1, i1_7, i1_9, i2_9, i1_6, i3_3, i3_9, i3_10, i3_1, i3_7, i2_5),
      na.rm = T),
    iNA = mean(
      c(i2_10, i3_6, i1_3, i2_8, i2_2, i3_4, i2_6, i1_10, i1_4),
      na.rm = T),

    rPA_i = mean(
      c(r1_1_i, r1_7_i, r1_9_i, r2_9_i, r1_6_i, r3_3_i, r3_9_i, r3_10_i,
        r3_1_i, r3_7_i, r2_5_i), na.rm = T),
    rNA_i = mean(
      c(r2_10_i, r3_6_i, r1_3_i, r2_8_i, r2_2_i, r3_4_i, r2_6_i, r1_10_i,
        r1_4_i), na.rm = T),
    iPA_i = mean(
      c(i1_1_i, i1_7_i, i1_9_i, i2_9_i, i1_6_i, i3_3_i, i3_9_i, i3_10_i,
        i3_1_i, i3_7_i, i2_5_i), na.rm = T),
    iNA_i = mean(
```

```r
      c(i2_10_i, i3_6_i, i1_3_i, i2_8_i, i2_2_i, i3_4_i, i2_6_i, i1_10_i,
        i1_4_i), na.rm = T)) %>%
  dplyr::mutate(
    # create maxPos variables
    maxPos = iPA - iNA,
    maxPos_i = iPA_i - iNA_i) %>%
  ungroup()
```

```r
# calculate cronbach alpha

reliab_avimp <-
  c("r1_1, r1_7, r1_9, r2_9, r1_6, r3_3, r3_9, r3_10, r3_1, r3_7, r2_5",
    "r2_10, r3_6, r1_3, r2_8, r2_2, r3_4, r2_6, r1_10, r1_4",
    "i1_1, i1_7, i1_9, i2_9, i1_6, i3_3, i3_9, i3_10, i3_1, i3_7, i2_5",
    "i2_10, i3_6, i1_3, i2_8, i2_2, i3_4, i2_6, i1_10, i1_4")

reliab_avi_namesmp <- c("rPA", "rNA", "iPA", "iNA")

all_alphas(data, items = reliab_avimp, constructs = reliab_avi_namesmp,
           sensitivity = sensitivity_analyses)
```

```
## # A tibble: 12 x 5
##    construct   `!is.na(subID)` `exclude_age != 1` `exclude_sd != 1`
##    <chr>                 <dbl>              <dbl>             <dbl>
##  1 rPA_overall            0.87               0.87              0.86
##  2 rNA_overall            0.86               0.86              0.85
##  3 iPA_overall            0.84               0.84              0.84
##  4 iNA_overall            0.88               0.88              0.83
##  5 rPA_EA                 0.9                0.9               0.89
##  6 rNA_EA                 0.89               0.9               0.89
##  7 iPA_EA                 0.84               0.85              0.83
##  8 iNA_EA                 0.93               0.94              0.89
##  9 rPA_TN                 0.85               0.85              0.84
## 10 rNA_TN                 0.83               0.83              0.83
## 11 iPA_TN                 0.85               0.85              0.86
## 12 iNA_TN                 0.77               0.76              0.77
## # i 1 more variable: `exclude_age != 1 & exclude_sd != 1` <dbl>
```

Ipsatized giving scores

Finally, we compute the ipsatized scores of the trials. Alike the AVI variables, we calculate this by converting the amount of money given using this formula: `ipsatized score = (raw amoung given - individuals' mean amount given across all trials) / (individuals' sd across the amount of money given across all trials)`

```r
# compute ipsatized giving scores
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # create intermediate variables for calculating ipsatize scores
    givingMean = mean(
      c_across(matches("^raw[1-9][1-9]*[0]*$")), na.rm = TRUE),
```

```r
    givingSd = sd(
      c_across(matches("^raw[1-9][1-9]*[0]*$")), na.rm = TRUE)) %>%
  dplyr::mutate( # create ipsatized item scores
    across(matches("^raw[1-9][1-9]*[0]*$"),
           ~ as.numeric((.x - givingMean) / givingSd),
           .names = "{.col}_i")) %>%
  ungroup()
```

Ipsatized trait rating scores

Finally, we compute the ipsatized scores of the trait ratings for the faces (items that start with `trait`, `vale`, and `arou`).

All participants rated the faces on numerous traits. Specifically, they responded to the prompt "To what extent is this person…" (e.g., "Competent", "Trustworthy", etc.; 1 = *Not at all*, 4 = *Moderately*, 7 = *Extremely*) and how positive ("*How negative - positive do you feel when you see this face?*"; 1 = *Extremely negative*, 7 = *Extremely positive*) and aroused ("*How not-aroused - aroused do you feel when you see this face? Aroused means activated, charged, alert, or energized physically and mentally.*"; 1 = *Not at all aroused*, 7 = *Extremely aroused*) they feel when they see the face. For the repeated ratings, we only include the first rating they provide.

Alike the AVI and giving variables, we calculate this by converting the ratings given using this formula: `ipsatized score = (raw rating - individuals' mean rating across all traits and faces) / (individuals' sd rating across all traits and faces)`. Note that for valence (`vale`) and arousal (`arou`) ratings, they are ipsatized within the valence and arousal ratings only (i.e., `ipsatized valence = (raw valence rating - individuals' mean rating of valence across all faces) / (individuals' sd of valence across all faces)`.

```r
# compute ipsatized trait rating scores
data <- data %>%
  rowwise() %>%
  dplyr::mutate( # create intermediate variables for calculating ipsatize scores
    traitRatingMean = mean(
      c_across(matches("^trait[1-9][0-9]*_")), na.rm = TRUE),
    traitRatingSd = sd(
      c_across(matches("^trait[1-9][0-9]*_")), na.rm = TRUE),
    valeRatingMean = mean(
      c_across(matches("^vale[1-9][0-9]*$")), na.rm = TRUE),
    valeRatingSd = sd(
      c_across(matches("^vale[1-9][0-9]*$")), na.rm = TRUE),
    arouRatingMean = mean(
      c_across(matches("^arou[1-9][0-9]*$")), na.rm = TRUE),
    arouRatingSd = sd(
      c_across(matches("^arou[1-9][0-9]*$")), na.rm = TRUE)) %>%
  dplyr::mutate(
    # create ipsatized item scores
    across(matches("^trait[1-9][0-9]*_"),
           ~ as.numeric((.x - traitRatingMean) / traitRatingSd),
           .names = "{.col}_i")) %>%
  dplyr::mutate( # create ipsatized item scores
    across(matches("^vale[1-9][0-9]*$"),
           ~ as.numeric((.x - valeRatingMean) / valeRatingSd),
           .names = "{.col}_i")) %>%
```

```r
  dplyr::mutate( # create ipsatized item scores
    across(matches("^arou[1-9][0-9]*$"),
           ~ as.numeric((.x - arouRatingMean) / arouRatingSd),
           .names = "{.col}_i")) %>%
  ungroup()
```

Save data computed frame

```r
write.csv(data, "ia_study1_anon_data_computed.csv")
```

```r
table(data$cultureEA)
```

```
##
##   0   1
## 117 103
```

```r
colnames(data)
```

```
##   [1] "subID"                      "cultureEA"
##   [3] "avatar_ori"                 "prac1"
##   [5] "prac1_rt_Page.Submit"       "raw1"
##   [7] "raw1_rt_Page.Submit"        "raw2"
##   [9] "raw2_rt_Page.Submit"        "raw3"
##  [11] "seq3_rt_Page.Submit"        "raw4"
##  [13] "raw4_rt_Page.Submit"        "raw5"
##  [15] "raw5_rt_Page.Submit"        "raw6"
##  [17] "raw6_rt_Page.Submit"        "raw7"
##  [19] "raw7_rt_Page.Submit"        "raw8"
##  [21] "raw8_rt_Page.Submit"        "raw9"
##  [23] "raw9_rt_Page.Submit"        "raw10"
##  [25] "raw10_rt_Page.Submit"       "raw11"
##  [27] "raw11_rt_Page.Submit"       "raw12"
##  [29] "raw12_rt_Page.Submit"       "raw13"
##  [31] "raw13_rt_Page.Submit"       "raw14"
##  [33] "raw14_rt_Page.Submit"       "raw15"
##  [35] "raw15_rt_Page.Submit"       "raw16"
##  [37] "raw16_rt_Page.Submit"       "raw17"
##  [39] "raw17_rt_Page.Submit"       "raw18"
##  [41] "raw18_rt_Page.Submit"       "raw19"
##  [43] "raw19_rt_Page.Submit"       "raw20"
##  [45] "raw20_rt_Page.Submit"       "raw21"
##  [47] "raw21_rt_Page.Submit"       "raw22"
##  [49] "raw22_rt_Page.Submit"       "raw23"
##  [51] "raw23_rt_Page.Submit"       "raw24"
##  [53] "raw24_rt_Page.Submit"       "raw25"
##  [55] "raw25_rt_Page.Submit"       "raw26"
##  [57] "raw26_rt_Page.Submit"       "raw27"
##  [59] "raw27_rt_Page.Submit"       "raw28"
##  [61] "raw28_rt_Page.Submit"       "raw29"
```

```
##  [63] "raw29_rt_Page.Submit"       "raw30"
##  [65] "raw30_rt_Page.Submit"       "raw31"
##  [67] "raw31_rt_Page.Submit"       "raw32"
##  [69] "raw32_rt_Page.Submit"       "raw33"
##  [71] "raw33_rt_Page.Submit"       "raw34"
##  [73] "raw34_rt_Page.Submit"       "raw35"
##  [75] "raw35_rt_Page.Submit"       "raw36"
##  [77] "raw36_rt_Page.Submit"       "vale1"
##  [79] "arou1"                      "trait1_Competent"
##  [81] "trait1_Trustworthy"         "trait1_FinanciallyNeedy"
##  [83] "trait1_Dominant"            "trait1_Selfish"
##  [85] "trait1_Friendly"            "trait1_aGoodPerson"
##  [87] "vale2"                      "arou2"
##  [89] "trait2_Competent"           "trait2_Trustworthy"
##  [91] "trait2_FinanciallyNeedy"    "trait2_Dominant"
##  [93] "trait2_Selfish"             "trait2_Friendly"
##  [95] "trait2_aGoodPerson"         "vale3"
##  [97] "arou3"                      "trait3_Competent"
##  [99] "trait3_Trustworthy"         "trait3_FinanciallyNeedy"
## [101] "trait3_Dominant"            "trait3_Selfish"
## [103] "trait3_Friendly"            "trait3_aGoodPerson"
## [105] "vale4"                      "arou4"
## [107] "trait4_Competent"           "trait4_Trustworthy"
## [109] "trait4_FinanciallyNeedy"    "trait4_Dominant"
## [111] "trait4_Selfish"             "trait4_Friendly"
## [113] "trait4_aGoodPerson"         "vale5"
## [115] "arou5"                      "trait5_Competent"
## [117] "trait5_Trustworthy"         "trait5_FinanciallyNeedy"
## [119] "trait5_Dominant"            "trait5_Selfish"
## [121] "trait5_Friendly"            "trait5_aGoodPerson"
## [123] "vale6"                      "arou6"
## [125] "trait6_Competent"           "trait6_Trustworthy"
## [127] "trait6_FinanciallyNeedy"    "trait6_Dominant"
## [129] "trait6_Selfish"             "trait6_Friendly"
## [131] "trait6_aGoodPerson"         "vale7"
## [133] "arou7"                      "trait7_Competent"
## [135] "trait7_Trustworthy"         "trait7_FinanciallyNeedy"
## [137] "trait7_Dominant"            "trait7_Selfish"
## [139] "trait7_Friendly"            "trait7_aGoodPerson"
## [141] "vale8"                      "arou8"
## [143] "trait8_Competent"           "trait8_Trustworthy"
## [145] "trait8_FinanciallyNeedy"    "trait8_Dominant"
## [147] "trait8_Selfish"             "trait8_Friendly"
## [149] "trait8_aGoodPerson"         "vale9"
## [151] "arou9"                      "trait9_Competent"
## [153] "trait9_Trustworthy"         "trait9_FinanciallyNeedy"
## [155] "trait9_Dominant"            "trait9_Selfish"
## [157] "trait9_Friendly"            "trait9_aGoodPerson"
## [159] "vale10"                     "arou10"
## [161] "trait10_Competent"          "trait10_Trustworthy"
## [163] "trait10_FinanciallyNeedy"   "trait10_Dominant"
## [165] "trait10_Selfish"            "trait10_Friendly"
## [167] "trait10_aGoodPerson"        "vale11"
## [169] "arou11"                     "trait11_Competent"
```

```
## [171] "trait11_Trustworthy"        "trait11_FinanciallyNeedy"
## [173] "trait11_Dominant"           "trait11_Selfish"
## [175] "trait11_Friendly"           "trait11_aGoodPerson"
## [177] "vale12"                     "arou12"
## [179] "trait12_Competent"          "trait12_Trustworthy"
## [181] "trait12_FinanciallyNeedy"   "trait12_Dominant"
## [183] "trait12_Selfish"            "trait12_Friendly"
## [185] "trait12_aGoodPerson"        "vale13"
## [187] "arou13"                     "trait13_Competent"
## [189] "trait13_Trustworthy"        "trait13_FinanciallyNeedy"
## [191] "trait13_Dominant"           "trait13_Selfish"
## [193] "trait13_Friendly"           "trait13_aGoodPerson"
## [195] "vale14"                     "arou14"
## [197] "trait14_Competent"          "trait14_Trustworthy"
## [199] "trait14_FinanciallyNeedy"   "trait14_Dominant"
## [201] "trait14_Selfish"            "trait14_Friendly"
## [203] "trait14_aGoodPerson"        "vale15"
## [205] "arou15"                     "trait15_Competent"
## [207] "trait15_Trustworthy"        "trait15_FinanciallyNeedy"
## [209] "trait15_Dominant"           "trait15_Selfish"
## [211] "trait15_Friendly"           "trait15_aGoodPerson"
## [213] "vale16"                     "arou16"
## [215] "trait16_Competent"          "trait16_Trustworthy"
## [217] "trait16_FinanciallyNeedy"   "trait16_Dominant"
## [219] "trait16_Selfish"            "trait16_Friendly"
## [221] "trait16_aGoodPerson"        "vale17"
## [223] "arou17"                     "trait17_Competent"
## [225] "trait17_Trustworthy"        "trait17_FinanciallyNeedy"
## [227] "trait17_Dominant"           "trait17_Selfish"
## [229] "trait17_Friendly"           "trait17_aGoodPerson"
## [231] "vale18"                     "arou18"
## [233] "trait18_Competent"          "trait18_Trustworthy"
## [235] "trait18_FinanciallyNeedy"   "trait18_Dominant"
## [237] "trait18_Selfish"            "trait18_Friendly"
## [239] "trait18_aGoodPerson"        "r1_1"
## [241] "r1_2"                       "r1_3"
## [243] "r1_4"                       "r1_5"
## [245] "r1_6"                       "r1_7"
## [247] "r1_8"                       "r1_9"
## [249] "r1_10"                      "r2_1"
## [251] "r2_2"                       "r2_3"
## [253] "r2_4"                       "r2_5"
## [255] "r2_6"                       "r2_7"
## [257] "r2_8"                       "r2_9"
## [259] "r2_10"                      "r3_1"
## [261] "r3_2"                       "r3_3"
## [263] "r3_4"                       "r3_5"
## [265] "r3_6"                       "r3_7"
## [267] "r3_8"                       "r3_9"
## [269] "r3_10"                      "r4_1"
## [271] "r4_2"                       "r4_3"
## [273] "r4_4"                       "r4_5"
## [275] "r4_6"                       "r4_7"
## [277] "r4_8"                       "r4_9"
```

```
## [279] "i1_1"                      "i1_2"
## [281] "i1_3"                      "i1_4"
## [283] "i1_5"                      "i1_6"
## [285] "i1_7"                      "i1_8"
## [287] "i1_9"                      "i1_10"
## [289] "i2_1"                      "i2_2"
## [291] "i2_3"                      "i2_4"
## [293] "i2_5"                      "i2_6"
## [295] "i2_7"                      "i2_8"
## [297] "i2_9"                      "i2_10"
## [299] "i3_1"                      "i3_2"
## [301] "i3_3"                      "i3_4"
## [303] "i3_5"                      "i3_6"
## [305] "i3_7"                      "i3_8"
## [307] "i3_9"                      "i3_10"
## [309] "i4_1"                      "i4_2"
## [311] "i4_3"                      "i4_4"
## [313] "i4_5"                      "i4_6"
## [315] "i4_7"                      "i4_8"
## [317] "i4_9"                      "value_1"
## [319] "value_2"                   "value_3"
## [321] "value_4"                   "value_5"
## [323] "value_6"                   "value_7"
## [325] "value_8"                   "value_9"
## [327] "iri1"                      "iri2"
## [329] "iri3"                      "iri4"
## [331] "iri5"                      "iri6"
## [333] "iri7"                      "iri8"
## [335] "iri9"                      "iri10"
## [337] "iri11"                     "iri12"
## [339] "iri13"                     "iri14"
## [341] "iri15"                     "iri16"
## [343] "iri17"                     "iri18"
## [345] "iri19"                     "iri20"
## [347] "iri21"                     "iri22"
## [349] "iri23"                     "iri24"
## [351] "iri25"                     "iri26"
## [353] "iri27"                     "iri28"
## [355] "tipi_1"                    "tipi_2"
## [357] "tipi_3"                    "tipi_4"
## [359] "tipi_5"                    "tipi_6"
## [361] "tipi_7"                    "tipi_8"
## [363] "tipi_9"                    "tipi_10"
## [365] "age"                       "Q509"
## [367] "Q509_8_TEXT"               "gender"
## [369] "gender_3_TEXT"             "sexualpref"
## [371] "sexualpref_5_TEXT"         "born1"
## [373] "born1_txt"                 "raise1"
## [375] "raise1_txt"                "born2"
## [377] "born2_txt"                 "raise2"
## [379] "raise2_txt"                "ethni2"
## [381] "ethni2_txt"                "born3"
## [383] "born3_txt"                 "raise3"
## [385] "raise3_txt"                "ethni3"
```

```
## [387] "ethni3_txt"                "born4"
## [389] "born4_txt"                 "raise4"
## [391] "raise4_txt"                "born5"
## [393] "born5_txt"                 "raise5"
## [395] "raise5_txt"                "born6"
## [397] "born6_txt"                 "raise6"
## [399] "raise6_txt"                "born7"
## [401] "born7_txt"                 "raise7"
## [403] "raise7_txt"                "econ1"
## [405] "econ2"                     "econ2_6_TEXT"
## [407] "ladder1"                   "ladder2"
## [409] "famises1"                  "famises2"
## [411] "econinde"                  "selfses1"
## [413] "selfses2"                  "didbefore"
## [415] "didbefore_"                "order"
## [417] "famises2_numbered"         "selfses2_numbered"
## [419] "gender_nonfemale"          "sexualpref_nonhetero"
## [421] "ethn_nonmajority"          "exclude_age"
## [423] "exclude_sd"                "tipi_6r"
## [425] "tipi_2r"                   "tipi_8r"
## [427] "tipi_4r"                   "tipi_10r"
## [429] "tipi_ex"                   "tipi_a"
## [431] "tipi_c"                    "tipi_es"
## [433] "tipi_o"                    "iri3r"
## [435] "iri4r"                     "iri7r"
## [437] "iri12r"                    "iri13r"
## [439] "iri14r"                    "iri15r"
## [441] "iri18r"                    "iri19r"
## [443] "iri_pt"                    "iri_fs"
## [445] "iri_ec"                    "iri_pd"
## [447] "rHAP"                      "rLAP"
## [449] "iHAP"                      "iLAP"
## [451] "rMean"                     "rSd"
## [453] "iMean"                     "iSd"
## [455] "r1_1_i"                    "r1_2_i"
## [457] "r1_3_i"                    "r1_4_i"
## [459] "r1_5_i"                    "r1_6_i"
## [461] "r1_7_i"                    "r1_8_i"
## [463] "r1_9_i"                    "r1_10_i"
## [465] "r2_1_i"                    "r2_2_i"
## [467] "r2_3_i"                    "r2_4_i"
## [469] "r2_5_i"                    "r2_6_i"
## [471] "r2_7_i"                    "r2_8_i"
## [473] "r2_9_i"                    "r2_10_i"
## [475] "r3_1_i"                    "r3_2_i"
## [477] "r3_3_i"                    "r3_4_i"
## [479] "r3_5_i"                    "r3_6_i"
## [481] "r3_7_i"                    "r3_8_i"
## [483] "r3_9_i"                    "r3_10_i"
## [485] "r4_1_i"                    "r4_2_i"
## [487] "r4_3_i"                    "r4_4_i"
## [489] "r4_5_i"                    "r4_6_i"
## [491] "r4_7_i"                    "r4_8_i"
## [493] "r4_9_i"                    "i1_1_i"
```

```
## [495] "i1_2_i"                    "i1_3_i"
## [497] "i1_4_i"                    "i1_5_i"
## [499] "i1_6_i"                    "i1_7_i"
## [501] "i1_8_i"                    "i1_9_i"
## [503] "i1_10_i"                   "i2_1_i"
## [505] "i2_2_i"                    "i2_3_i"
## [507] "i2_4_i"                    "i2_5_i"
## [509] "i2_6_i"                    "i2_7_i"
## [511] "i2_8_i"                    "i2_9_i"
## [513] "i2_10_i"                   "i3_1_i"
## [515] "i3_2_i"                    "i3_3_i"
## [517] "i3_4_i"                    "i3_5_i"
## [519] "i3_6_i"                    "i3_7_i"
## [521] "i3_8_i"                    "i3_9_i"
## [523] "i3_10_i"                   "i4_1_i"
## [525] "i4_2_i"                    "i4_3_i"
## [527] "i4_4_i"                    "i4_5_i"
## [529] "i4_6_i"                    "i4_7_i"
## [531] "i4_8_i"                    "i4_9_i"
## [533] "rHAP_i"                    "rLAP_i"
## [535] "iHAP_i"                    "iLAP_i"
## [537] "rPA"                       "rNA"
## [539] "iPA"                       "iNA"
## [541] "rPA_i"                     "rNA_i"
## [543] "iPA_i"                     "iNA_i"
## [545] "maxPos"                    "maxPos_i"
## [547] "givingMean"                "givingSd"
## [549] "raw1_i"                    "raw2_i"
## [551] "raw3_i"                    "raw4_i"
## [553] "raw5_i"                    "raw6_i"
## [555] "raw7_i"                    "raw8_i"
## [557] "raw9_i"                    "raw10_i"
## [559] "raw11_i"                   "raw12_i"
## [561] "raw13_i"                   "raw14_i"
## [563] "raw15_i"                   "raw16_i"
## [565] "raw17_i"                   "raw18_i"
## [567] "raw19_i"                   "raw20_i"
## [569] "raw21_i"                   "raw22_i"
## [571] "raw23_i"                   "raw24_i"
## [573] "raw25_i"                   "raw26_i"
## [575] "raw27_i"                   "raw28_i"
## [577] "raw29_i"                   "raw30_i"
## [579] "raw31_i"                   "raw32_i"
## [581] "raw33_i"                   "raw34_i"
## [583] "raw35_i"                   "raw36_i"
## [585] "traitRatingMean"           "traitRatingSd"
## [587] "valeRatingMean"            "valeRatingSd"
## [589] "arouRatingMean"            "arouRatingSd"
## [591] "trait1_Competent_i"        "trait1_Trustworthy_i"
## [593] "trait1_FinanciallyNeedy_i" "trait1_Dominant_i"
## [595] "trait1_Selfish_i"          "trait1_Friendly_i"
## [597] "trait1_aGoodPerson_i"      "trait2_Competent_i"
## [599] "trait2_Trustworthy_i"      "trait2_FinanciallyNeedy_i"
## [601] "trait2_Dominant_i"         "trait2_Selfish_i"
```

```
## [603] "trait2_Friendly_i"          "trait2_aGoodPerson_i"
## [605] "trait3_Competent_i"         "trait3_Trustworthy_i"
## [607] "trait3_FinanciallyNeedy_i"  "trait3_Dominant_i"
## [609] "trait3_Selfish_i"           "trait3_Friendly_i"
## [611] "trait3_aGoodPerson_i"       "trait4_Competent_i"
## [613] "trait4_Trustworthy_i"       "trait4_FinanciallyNeedy_i"
## [615] "trait4_Dominant_i"          "trait4_Selfish_i"
## [617] "trait4_Friendly_i"          "trait4_aGoodPerson_i"
## [619] "trait5_Competent_i"         "trait5_Trustworthy_i"
## [621] "trait5_FinanciallyNeedy_i"  "trait5_Dominant_i"
## [623] "trait5_Selfish_i"           "trait5_Friendly_i"
## [625] "trait5_aGoodPerson_i"       "trait6_Competent_i"
## [627] "trait6_Trustworthy_i"       "trait6_FinanciallyNeedy_i"
## [629] "trait6_Dominant_i"          "trait6_Selfish_i"
## [631] "trait6_Friendly_i"          "trait6_aGoodPerson_i"
## [633] "trait7_Competent_i"         "trait7_Trustworthy_i"
## [635] "trait7_FinanciallyNeedy_i"  "trait7_Dominant_i"
## [637] "trait7_Selfish_i"           "trait7_Friendly_i"
## [639] "trait7_aGoodPerson_i"       "trait8_Competent_i"
## [641] "trait8_Trustworthy_i"       "trait8_FinanciallyNeedy_i"
## [643] "trait8_Dominant_i"          "trait8_Selfish_i"
## [645] "trait8_Friendly_i"          "trait8_aGoodPerson_i"
## [647] "trait9_Competent_i"         "trait9_Trustworthy_i"
## [649] "trait9_FinanciallyNeedy_i"  "trait9_Dominant_i"
## [651] "trait9_Selfish_i"           "trait9_Friendly_i"
## [653] "trait9_aGoodPerson_i"       "trait10_Competent_i"
## [655] "trait10_Trustworthy_i"      "trait10_FinanciallyNeedy_i"
## [657] "trait10_Dominant_i"         "trait10_Selfish_i"
## [659] "trait10_Friendly_i"         "trait10_aGoodPerson_i"
## [661] "trait11_Competent_i"        "trait11_Trustworthy_i"
## [663] "trait11_FinanciallyNeedy_i" "trait11_Dominant_i"
## [665] "trait11_Selfish_i"          "trait11_Friendly_i"
## [667] "trait11_aGoodPerson_i"      "trait12_Competent_i"
## [669] "trait12_Trustworthy_i"      "trait12_FinanciallyNeedy_i"
## [671] "trait12_Dominant_i"         "trait12_Selfish_i"
## [673] "trait12_Friendly_i"         "trait12_aGoodPerson_i"
## [675] "trait13_Competent_i"        "trait13_Trustworthy_i"
## [677] "trait13_FinanciallyNeedy_i" "trait13_Dominant_i"
## [679] "trait13_Selfish_i"          "trait13_Friendly_i"
## [681] "trait13_aGoodPerson_i"      "trait14_Competent_i"
## [683] "trait14_Trustworthy_i"      "trait14_FinanciallyNeedy_i"
## [685] "trait14_Dominant_i"         "trait14_Selfish_i"
## [687] "trait14_Friendly_i"         "trait14_aGoodPerson_i"
## [689] "trait15_Competent_i"        "trait15_Trustworthy_i"
## [691] "trait15_FinanciallyNeedy_i" "trait15_Dominant_i"
## [693] "trait15_Selfish_i"          "trait15_Friendly_i"
## [695] "trait15_aGoodPerson_i"      "trait16_Competent_i"
## [697] "trait16_Trustworthy_i"      "trait16_FinanciallyNeedy_i"
## [699] "trait16_Dominant_i"         "trait16_Selfish_i"
## [701] "trait16_Friendly_i"         "trait16_aGoodPerson_i"
## [703] "trait17_Competent_i"        "trait17_Trustworthy_i"
## [705] "trait17_FinanciallyNeedy_i" "trait17_Dominant_i"
## [707] "trait17_Selfish_i"          "trait17_Friendly_i"
## [709] "trait17_aGoodPerson_i"      "trait18_Competent_i"
```

```
## [711] "trait18_Trustworthy_i"      "trait18_FinanciallyNeedy_i"
## [713] "trait18_Dominant_i"         "trait18_Selfish_i"
## [715] "trait18_Friendly_i"         "trait18_aGoodPerson_i"
## [717] "vale1_i"                    "vale2_i"
## [719] "vale3_i"                    "vale4_i"
## [721] "vale5_i"                    "vale6_i"
## [723] "vale7_i"                    "vale8_i"
## [725] "vale9_i"                    "vale10_i"
## [727] "vale11_i"                   "vale12_i"
## [729] "vale13_i"                   "vale14_i"
## [731] "vale15_i"                   "vale16_i"
## [733] "vale17_i"                   "vale18_i"
## [735] "arou1_i"                    "arou2_i"
## [737] "arou3_i"                    "arou4_i"
## [739] "arou5_i"                    "arou6_i"
## [741] "arou7_i"                    "arou8_i"
## [743] "arou9_i"                    "arou10_i"
## [745] "arou11_i"                   "arou12_i"
## [747] "arou13_i"                   "arou14_i"
## [749] "arou15_i"                   "arou16_i"
## [751] "arou17_i"                   "arou18_i"
```