Exasol Dashboard Setup Instructions

This guide explains how to configure the environment variables and start the frontend and Flask backend on Windows PowerShell.

1. Configure environment variables

Create a **.env** file in the **backend** folder (or the location expected by your Flask app). Use the template below. Replace each blank placeholder with the correct value on your own machine.

```
EXASOL_HOST="127.0.0.1"
EXASOL_PORT="8563"
EXASOL_USER="sys"
EXASOL_PASSWORD=""
EXASOL_SCHEMA="HACKATHON"
EXASOL_NOCERTCHECK="true"

FLASK_HOST="127.0.0.1"
FLASK_PORT="5000"
FRONTEND_URL="http://localhost:5173"

AZURE_TENANT_ID=""
AZURE_CLIENT_ID=""
AZURE_CLIENT_SECRET=""

AZURE_SUBSCRIPTION_ID=""
AZURE_RESOURCE_GROUP="opsnexus"
AZURE_DATA_FACTORY="opsnexus"

AZURE_MONTHLY_BUDGET_INR="1000"
COST_NORMAL_MAX_INR="10"
COST_ELEVATED_MAX_INR="50"

NORMAL_RUNS_MAX="5"
ELEVATED_RUNS_MAX="20"
```

Security: Credentials were intentionally left blank in this template. Add the real values locally; do not paste secrets into documentation, screenshots, GitHub, or shared PDFs. If a real Azure client secret has already been shared, rotate it in Azure and update your local .env file.

2. Start the frontend

Open PowerShell in the folder that contains the **exasol-dashboard** project, then run:

```
cd exasol-dashboard
npm install --force
npm run dev
```

When Vite starts, open the local URL printed in the terminal. The default URL in this configuration is usually **http://localhost:5173**.

3. Set up and start the backend

In a separate PowerShell terminal, go to the backend folder:

```
cd backend
py -m venv .venv
.\.venv\Scripts\Activate.ps1
python -m pip install --upgrade pip
pip install -r requirements.txt
python app.py
```

If PowerShell blocks virtual-environment activation, run this for the current terminal only, then activate again:

```
Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
.\.venv\Scripts\Activate.ps1
```

4. Check that both services are running

Frontend	Open http://localhost:5173 (or the URL shown by npm).
Backend	Check the Flask terminal for startup errors; the configured port is 5000.
Environment	Confirm the backend loads the .env file and that the Exasol and Azure values are correct.
Dependencies	Ensure backend/requirements.txt exists before running pip install -r requirements.txt.

Note: Run frontend and backend in two separate terminals. If your project folder is already named exasol-dashboard and your terminal is already inside it, do not run cd exasol-dashboard a second time.