

Table 1: BMP results over $T = 3$ experimental-design rounds. Higher EIG is better; lower L-C2ST and median distance are better. Results are mean $\pm$ standard error over three seeds. Wall-clock time was $2,235 \pm 9$ s for SBI-BOED and $7,095 \pm 2,519$ s for MINEBED-BO under the matched-budget sweep.

Method	EIG ($\uparrow$)	L-C2ST [†] ($\downarrow$)	Median dist. ($\downarrow$)
Random + NLE	0.02 ± 0.01	0.01 ± 0.01	11.49 ± 5.33
Random + InfoNCE- λ	0.46 ± 0.07	0.01 ± 0.01	10.86 ± 5.72
MINEBED-BO	14.23 ± 0.60	0.25 ± 0.00	0.82 ± 0.06
SBI-BOED ($\lambda = 1$)	10.39 ± 0.01	0.01 ± 0.01	0.61 ± 0.01
SBI-BOED ($\lambda = 0.1$)	10.38 ± 0.01	0.01 ± 0.01	0.60 ± 0.01
SBI-BOED ($\lambda = 0.01$)	10.39 ± 0.01	0.01 ± 0.01	0.61 ± 0.01

[†] L-C2ST values smaller than 0.01 are displayed as 0.01 for readability.