

Lecture notes

Vittorio Zaccaria

March 5, 2019

Contents

1 Lecture 0 - Specifying an API

1.1 Welcome

- You will learn how to finally deploy your *internet application* in the real world
- You will be *graded with a project assignment* which will consist of both *source code* and a *running instance of your app on a cloud service*.
 - The final goal of this part is to give a foundation for the construction of modern web applications
 - Almost all of Backend lessons will be hands-on, so *bring your own device* and a stable network connection.
 - This course is *not* a deep-dive into:
 - * Cloud Computing
 - * Distributed Systems
 - * Databases (we will take off from what you've already seen in that course)

1.2 Course project

Concerning the project there are a few important points:

- Every project should host its code on a *private* Git repository and provide a running application on cloud hosting platform.
- The team is composed of max. 3 students, where one of them will be elected as *team administrator*.

1.3 Web applications and web services

- This part is mostly an overview of the theoretical background behind web applications.
- This is just a recap about topics addressed in the *Information Systems* course.
- Let us start from the basics and see where this fits into the web application scenario.

We start by recalling what the term *service* means

- logically represents a business activity with a specified outcome which can be any kind of artifact
- is self-contained. Assuming that someone is offering the service, you don't need anything else to bring the activity to completion.
- is a black box for its consumers. Consumers only know the surface of the service. Otherwise it would result in a too tightly coupled communication.
- may consist of other underlying services.

1.3.1 Without a service oriented architecture

- Clients contain the application logic
- Might be replicated across them for common functionality. Obvious maintainability issues, violation of the DRY principle.
- Changing the structure of databases might imply rewriting the clients.

1.3.2 With a service oriented architecture

- Changing the structure of the database means rewriting only the remote application server.
- Clients are unimpacted by the change.
- In SOA you introduce a **service layer** where artifacts are provided by a single service invocation.
- You interact with it through an interface that does not expose implementation details (RPC or other high level language)
- SOA is the main architectural paradigm used to build web application today. Let's see why

1.3.3 Web service

- A Web service is a service built using web standards (we'll see in a few moments what does it mean) just consider:
 - Application layer → browser
 - Service layer → web server
- [A web service protocol](#) dictates how HTTP should be used to convey application requests.
- Services are really black boxes. The application knows only about "resources"

1.3.4 Activity pattern

- Now, a typical pattern of communication between web client and web server is shown here
- **First two arrows.** The request is typically initiated by the client (usually, first to get the assets needed to display the page).
- **Second two arrows.** The client requests the data to render and any other activity (that might also change the state of resources) happens next.

1.4 HTTP based networking

1.4.1 Anatomy

- HTTP is a **communication protocol**, i.e., a system of rules that specify how a request for a resource operation and the response should be formed (message negotiation and transmission).
- Much of HTTP1.1 standardization was guided by **a core set of principles and constraints** that today we call **REST**.
- You'll see a lot this term in these lectures because we are going to talk about **REST** compliant web services (there are other techniques, that you probably will see in other courses such as SOAP).
- Before addressing the most common practices, let's see what are the basic abstractions offered by HTTP.

1.4.2 Resource

- the **resource** is the first abstraction we are going to consider
- the **identifier** is a text string called uniform resource identifier - [URI](#).
- You can change the resource's state through a request using [HTTP verbs](#).
- a **representation** is a textual description of the actual state of the resource (JSON, XML and so on.).

1.4.3 HTTP verbs

- **Get:**
 - Request a copy of a *resource*
 - This is how the browser requests any HTML page or any other asset
 - The request should have no side-effects (i.e., doesn't change server state). That is why the second one is bad. This is because, there can be several layers of caching in the network.
- **Post:**
 - Example, chat app, add users to app etc..
 - Generally used to create a *resource* (in this case, a new message)
 - Has **side-effects**
 - **Not idempotent** (i.e., making the same request twice creates two separate, but similar resources)
- **Put:**
 - Often used to change or completely **replace an existing resource**.
 - Has **side-effects**
 - Should be idempotent (e.g., updating a resource twice should result in the same effect to the resource)
- **Delete:**
 - **Destroys** a resource
 - Has side effects
 - Should be idempotent

1.5 Demo D0.0 - using curl to interact with an HTTP service

- Prerequisites: curl, jq
- Remote API: <https://github.com/workforce-data-initiative/skills-api/wiki/API-Overview#introduction>

```
1 curl -X GET "http://api.dataatwork.org/v1/jobs" -v | jq .
2 curl -X GET "http://api.dataatwork.org/v1/jobs" | jq .
3 curl -X GET "http://api.dataatwork.org/v1/jobs?limit=2" | jq .
4 curl -X GET "http://api.dataatwork.org/v1/jobs/26bc4486dfd0f60b3bb0d8d64e001800/related_jobs" | jq .
5 curl -X GET "http://api.dataatwork.org/v1/jobs/26bc4486dfd0f60b3bb0d8d64e001800/related_skills" | jq .
6 curl -X GET /path/to/api/v1/jobs/autocomplete?contains="software"
```

- You do it! Search for the related skills of a baker

```
1 curl -X GET 'http://api.dataatwork.org/v1/jobs/autocomplete?contains="baker"' | jq .
```

and, choose and UUID and then use relatd skills

1.6 Demo D0.0bis - using the browser to interact with an HTTP service

Use the browser

```
1 fetch('http://api.dataatwork.org/v1/jobs?limit=2')
2   .then(function(response) {
3     return response.json();
4   })
5   .then(function(myJson) {
6     console.log(JSON.stringify(myJson));
7   });
```

1.7 Demo D0.1 - Using the swagger editor to document an API

1. Load up the Skills API in the swagger editor
2. Describe parameters
3. Describe responses

1.8 Demo D0.2 - Test the API with SwaggerHub

1. Load up the Skills API and try the same commands as above by using the interface

2 Lecture 1 - Javascript

2.1 Demos contained in the presentation

3 Lecture 2 - Implementation

3.1 Demo D2.0 - Generate the server

- Simply load up the bookstore API (only books) into the swagger editor, download and run the server.

3.2 Demo D2.1 - Serve static assets

- Add serve-static

```
1 let app = require('connect')();
2 /* .... */
3 let serveStatic = require('serve-static');
4 app().use(serveStatic(__dirname))
```

- Add example index.html (from 'vz-bookstore-alpha-2019', tag only.book.v0)
- Deploy on github

3.3 *Demo D2.2 - Deploy on Heroku*

Deploy on Heroku

Important:

- change swagger.yaml "host" to: `polimi-hyp-vz-demo.herokuapp.com` so that swagger user interface can work.
- change swagger.yaml "scheme" to `https`
- change the port in the code to `process.env.PORT || 8080`

Then:

1. Install the Heroku command line
2. Create an application with name `polimi-hyp-vz-demo` (region europe)
3. Connect to github
4. Find the Repo and press manual deploy
5. Press Open App

4 *Lecture 3 - Sessions and state*

4.1 *Demo D3.0 - Add a user with login and logout actions to the OpenAPI spec*

4.2 *Demo D3.1 - Add cookie-session*

4.3 *Handson D3.2 - Add a user/logout endpoint*

4.4 *Handson D3.3 - Add a user/register endpoint*