

MVC 5 (Model-View-Controller)

Helperi



Što su HTML Helper-i?

HTML helper-i se koriste da bi programski renderirali HTML markup unutar View-a. Oni vraćaju string tipa MvcHtmlHelper.

@Html.TextBox("Text1")

Klase HtmlHelper metoda:

- MvcForm ekstenzije renderiraju HTML forme.
- Input ekstenzije renderiraju HTML input elemente.
- Label ekstenzije renderiraju HTML label elemente.
- Link ekstenzije renderiraju HTML linkove.
- Select ekstenzije renderiraju drop-down liste i list-box-eve.
- TextArea ekstenzije renderiraju HTML TextArea.
- Validation ekstenzije renderiraju validacijske controle.



Korištenje Action Helpera

Html.ActionLink()

```
@Html.ActionLink("Click here to view photo 1",
   "Display", new { id = 1 })
```

```
<a href="/photo/display/1">
Click here to view photo 1
</a>
```

Url.Action()

```
<img alt="This image came from an action"
src="@Url.Action("GetImage", new { id = 1 })" />
```

```
<img
    alt="This image came from an action"
    src="/photo/getimage/1" })"
/>
```



Korištenje Display Helpera

Html.DisplayNameFor()

@Html.DisplayNameFor(model => model.DatumKreiranja)



Datum kreiranja

Html.DisplayFor()

@Html.DisplayFor(model => model.DatumKreiranja)



03/12/2012



Begin Form Helper

Html.BeginForm()

```
@using (Html.BeginForm("Create", "Photo",
   FormMethod.Post,
   new { enctype = "multipart/form-data" }))
{
   @* Place input controls here *@
}
```

```
<form action="/Photo/Create" method="post" enctype="multipart/form-data">
```

```
</form>
```



Korištenje Editor Helpera

Html.LabelFor()

@Html.LabelFor(model => model.ContactMe)

```
<label for="ContactMe">
    Contact Me
  </label>
```

Html.EditorFor()

@Html.EditorFor(model => model.ContactMe)

```
<input type="checkbox" name="Description">
```



Korištenje Validation Helpera

Html.ValidationSummary()

@Html.ValidationSummary()

Html.ValidationMessageFor()

@Html.ValidationMessageFor(model => model.Email)



Please enter a valid email address



Specijalni znakovi

Slijedeći specijalni znakovi su od važnosti prilikom pisanja helpera:

Znak	Naziv	Opis	Primjer
~	Tilda	Označava korijenski direktorij web aplikacije	~/Controller/Action
/	Slash (forward slash)	Označava korijenski direktorij site-a	/Content
./	Current directory	Označava trenutni direktorij u relativnom smislu, bez obzira gdje se nalazimo u aplikaciji	./Shared/_Layout.cshtml Ovo znači isto: Shared/_Layout.cshtml
/	Parent directory	Označava nad-direktorij (parent) u relativnom smislu, u odnosu na trenutni direktorij	/Script/app.js