

Quantum Random Walk Sieving for the 4-Sieve

MohamadAli Khajeian

School of Engineering Sciences, College of Engineering, University of Tehran

khajeian@ut.ac.ir

September 19, 2026

Abstract

We present an adaptation of the quantum random walk (QRW) 2-sieve of Chailloux and Loyer [1] to serve as the inner two-list subroutine inside the quantum 4-sieve framework of Chailloux and Loyer [2]. The adaptation preserves the Johnson graph, the second-level random product code, and the quantum data structure of the original algorithm, and modifies only the marked condition and the probability that a random cross-pair is a solution. We provide the complete algorithms, discuss the modifications required, and give a full complexity analysis for the running time, QRAM, quantum memory, and classical memory. We optimise the QRW parameters for the first two inner calls, and also analyse the third inner call in detail, showing that it is fundamentally inefficient because the solution probability is exponentially small.

1 Introduction

The Shortest Vector Problem (SVP) is at the foundation of lattice-based cryptography. The best known heuristic quantum algorithm for SVP runs in time $2^{0.2570d+o(d)}$ [1], obtained by replacing Grover's algorithm inside the 2-sieve by a quantum random walk with an additional layer of locality-sensitive filtering. In parallel, k -sieve algorithms have been developed to reduce memory requirements at the cost of increased running time [2]. In particular, the quantum 4-sieve of [2] uses nested Grover searches and achieves a time-memory trade-off with quantum-accessible classical memory of size $2^{0.1724d}$ to $2^{0.1813d}$.

In this work, we investigate whether the QRW 2-sieve of [1] can be used as the inner two-list subroutine inside the 4-sieve framework of [2], replacing the Grover-based inner 2-sieve. This requires adapting the QRW 2-sieve to handle two distinct lists rather than one, an arbitrary configuration threshold $C'_{12}(\alpha)$ rather than the fixed angle θ_α^* , and possibly non-unit vectors in the second-level call.

We show that the core QRW structure remains unchanged: the Johnson graph, the second random product code $\mathcal{C}_2$, the quantum data structure for the lists $J^v(\vec{t})$, and the MNRS framework are all preserved. Only the marked condition and the probability p_{sol} that a random cross-pair is a solution must be adjusted. We give the complete algorithms, discuss the modifications, and provide the full complexity analysis. We also analyse the third inner call in detail, showing that the QRW is fundamentally inefficient there because p_{sol} is exponentially small.

2 Preliminaries and Notation

We use the notation of [1, 2]. Let d be the lattice dimension and define the fundamental list-size parameter

$$N := \left(\sqrt{4/3}\right)^d = 2^{0.2075d+o(d)}. \quad (1)$$

This quantity N is exponential in d and serves as the reference scale for all exponents in the algorithm. A list of size N^a contains $2^{a \cdot 0.2075d + o(d)}$ elements; throughout the paper we write $N^{a+o(1)}$ to denote such a list, absorbing subexponential factors into the $o(1)$.

For an angle $\alpha \in [0, \pi/2]$, the volume ratio of a spherical cap of angle α is

$$\mathcal{V}_d(\alpha) := \text{poly}(d) \sin^d(\alpha), \quad (2)$$

which represents the fraction of the unit sphere covered by a cap of angular radius α . For two angles α and θ , the volume ratio of a wedge formed by two caps of angle α with centers separated by angle θ is

$$\mathcal{W}_d(\alpha, \theta) := \text{poly}(d) \left(1 - \frac{2 \cos^2(\alpha)}{1 + \cos(\theta)} \right)^{d/2}, \quad (3)$$

which is well-defined provided $2 \cos^2(\alpha) < 1 + \cos(\theta)$, i.e., the two caps overlap.

The critical angle between residual vectors that characterises reducibility of two border points is

$$\theta_\alpha^* := 2 \arcsin\left(\frac{1}{2 \sin(\alpha)}\right), \quad (4)$$

as established in [1, Proposition 4]. Two residual vectors $\vec{y}_0, \vec{y}_1$ on the border of a filter of angle α are reducible if and only if $\theta(\vec{y}_0, \vec{y}_1) \leq \theta_\alpha^*$.

Outer 4-sieve parameters. The outer 4-sieve uses a prefiltering angle $\alpha_0 \in [\pi/3, \pi/2]$ and a configuration matrix $C \in \mathbb{R}^{4 \times 4}$. The reduction to residual vectors is denoted $C'(\alpha_0)$, with entries $C'_{ij}(\alpha_0)$ given by [2, Lemma 1]:

$$C'_{ij}(\alpha_0) = \frac{1}{\sin^2(\alpha_0)} \left(C_{ij} + \frac{\cos^2(\alpha_0)}{3} \right) \quad (i \neq j). \quad (5)$$

The effective threshold for the second-level 2-sieve that builds L_{1234} is

$$C_{\text{eff}} := \frac{\sin^2(\alpha_0)}{2R^2} - 1, \quad R^2 := 2 + 2C_{12}, \quad (6)$$

as given in [2, Lemma 6].

QRW parameters. The adapted QRW 2-sieve uses four free parameters c, c_1, c_2, ρ satisfying $0 \leq c_2 \leq c_1 \leq c \leq 1$ and $0 \leq \rho \leq \rho_0$. From these, the following derived quantities are defined. The angle α (not to be confused with α_0) satisfies $\mathcal{V}_d(\alpha) = N^{-(1-c)}$. The angle β of the second random product code satisfies $\mathcal{V}_d(\beta) = N^{c_2 - c_1}$. The target angle is $\theta' := \arccos(C')$. The collision parameter ρ_0 is defined by $N^{\rho_0} := \mathcal{V}_d(\beta) / \mathcal{W}_d(\beta, \theta')$. The solution probability is

$$p_{\text{sol}} := \frac{1}{2} (1 - (C')^2)^{d/2}, \quad (7)$$

where the factor $1/2$ accounts for the bipartite nature of the problem. The expected number of solutions per filter is $N^\zeta := N^{2c} \cdot p_{\text{sol}}$.

The QRW costs are the setup cost $\mathcal{S} := N^{c_1 + \rho}$, the update cost $\mathcal{U} := N^{\max\{\rho, (\rho + c_2)/2\}}$, and the checking cost $\mathcal{C} := 1$. The spectral gap of the Johnson graph is $\delta := N^{-c_1}$. The fraction of marked vertices is

$$\epsilon := N^{2c_1} \cdot p_{\text{sol}} \cdot N^{\rho - \rho_0}. \quad (8)$$

3 Modified QRW 2-Sieve

3.1 Preserved components

The adaptation preserves the following components of the QRW 2-sieve of [1] without structural modification. The Johnson graph $J(N, N^{c_1})$ on the combined list, with

spectral gap $\delta = N^{-c_1}$ and the MNRS quantum walk framework, is retained exactly. The second random product code $\mathcal{C}_2$ with angle β satisfying $\mathcal{V}_d(\beta) = N^{c_2 - c_1}$ and size $|\mathcal{C}_2| = N^{\rho + c_1 - c_2}$ is constructed identically. The quantum data structure for the lists $J^v(\vec{t}) = f_\beta(\vec{t}) \cap L^v$, supporting insertions and deletions in quantum superposition, is used as in the original algorithm. The setup, update, and check cost formulas are formally unchanged.

3.2 Required modifications

Three modifications are required to adapt the QRW 2-sieve to the bipartite setting. First, we form the combined list $L = R_A \cup R_B$ and tag each element by a bit indicating its origin. The Johnson graph is built on L with $|L| = 2N_R$. This tagging does not affect the graph structure. Second, the marked condition is redefined: a vertex v is marked if there exist $\vec{t} \in \mathcal{C}_2$ and distinct $\vec{y}_i, \vec{y}_j \in \tilde{J}^v(\vec{t})$ such that $\vec{y}_i$ and $\vec{y}_j$ have different tags and $\langle \vec{y}_i | \vec{y}_j \rangle \leq C'$. Third, the solution probability acquires the factor $1/2$ as given in Equation (7).

3.3 Adapted algorithm

Algorithm 1 Adapted QRW 2-Sieve for bipartite configuration problems

Require: two residual lists R_A, R_B of size N_R each; threshold C' ; QRW parameters c, c_1, c_2, ρ .

Ensure: all pairs $(\vec{y}_a, \vec{y}_b) \in R_A \times R_B$ with $\langle \vec{y}_a | \vec{y}_b \rangle \leq C'$.

- 1: Form $L := R_A \cup R_B$ with tags.
 - 2: Compute $\theta' := \arccos(C')$ and $p_{\text{sol}} := \frac{1}{2}(1 - C'^2)^{d/2}$.
 - 3: Sample random product code $\mathcal{C}_2$ with $|\mathcal{C}_2| = N^{\rho + c_1 - c_2}$ and angle β satisfying $\mathcal{V}_d(\beta) = N^{c_2 - c_1}$.
 - 4: Build Johnson graph $J(N, N^{c_1})$ on L .
 - 5: **for** each vertex v **do**
 - 6: Compute $J^v(\vec{t}) = f_\beta(\vec{t}) \cap L^v$ for each $\vec{t} \in \mathcal{C}_2$.
 - 7: Truncate to $\tilde{J}^v(\vec{t})$ of size $\leq 2N^{c_2}$.
 - 8: Set marked bit $M(v)$ according to the marked condition above.
 - 9: **end for**
 - 10: **while** total solutions found $< N^\zeta/2$ **do**
 - 11: Pick a new random product code $\mathcal{C}_2$.
 - 12: **while** solutions found with this $\mathcal{C}_2 < N^{\zeta + \rho - \rho_0}/2$ **do**
 - 13: Run the MNRS quantum walk to find one marked vertex.
 - 14: **end while**
 - 15: **end while**
 - 16: **return** all collected pairs.
-

4 Main Algorithm: 4-Sieve with QRW Inner 2-Sieve

Algorithm 2 4-Sieve with QRW inner 2-sieve

Require: list L of $N' = N^{1+o(1)}$ lattice vectors of norm 1; reducing factor $\gamma < 1$; prefiltering angle α_0 ; configuration $C \in \mathbb{R}^{4 \times 4}$; QRW parameters.

Ensure: list L' of N' lattice vectors of norm $\leq \gamma$.

```

1:  $L' := \emptyset$ .
2: while  $|L'| \leq N'$  do
3:   Sample a 4-RPC  $\mathfrak{C}$  with codewords  $(\mathbf{A}_1^j, \mathbf{A}_2^j, \mathbf{A}_3^j, \mathbf{A}_4^j)$  such that  $\sum_i \mathbf{A}_i^j = \vec{0}$  and
      $\langle \mathbf{A}_i^j | \mathbf{A}_{i'}^j \rangle = -1/3$  for  $i \neq i'$ .
4:   Partition  $L$  into tuple-filters: for each  $\vec{x} \in L$ , find its nearest codeword  $\mathbf{A}_i^j$ , add
      $\vec{x}$  to  $L_i^j$ , compute residual  $\vec{y} = (\vec{x} - \cos \alpha_0 \mathbf{A}_i^j) / \sin \alpha_0$ , and add  $\vec{y}$  to  $R_i^j$ .
5:   for each tuple-filter  $j$  do
6:      $L_{12}^j \leftarrow \text{QRW-2-SIEVE}(R_1^j, R_2^j, C'_{12}(\alpha_0))$ .
7:      $L_{34}^j \leftarrow \text{QRW-2-SIEVE}(R_3^j, R_4^j, C'_{34}(\alpha_0))$ .
8:     Normalise vectors in  $L_{12}^j$  and  $L_{34}^j$ :  $\tilde{z}_{12} = z_{12} / \|z_{12}\|$ ,  $\tilde{z}_{34} = z_{34} / \|z_{34}\|$ .
9:      $L_{1234}^j \leftarrow \text{QRW-2-SIEVE}(\tilde{L}_{12}^j, \tilde{L}_{34}^j, C_{\text{eff}})$ .
10:     $L' := L' \cup L_{1234}^j$ .
11:   end for
12: end while
13: return  $L'$ .
```

5 Complexity Analysis

We now give the full complexity of the adapted QRW 2-sieve and of the outer 4-sieve. All calculations are performed in the QRAM model and expressed in the exponent notation $N^{cd+o(1)}$, where $N = 2^{0.2075d+o(d)}$.

5.1 Complexity of the adapted QRW 2-sieve

The setup cost, update cost, checking cost, and spectral gap are formally unchanged from the original algorithm:

$$\mathcal{S} = N^{c_1 + \rho + o(1)}, \quad (9)$$

$$\mathcal{U} = N^{\max\{\rho, (\rho + c_2)/2\} + o(1)}, \quad (10)$$

$$\mathcal{C} = 1, \quad (11)$$

$$\delta = N^{-c_1}. \quad (12)$$

The fraction of marked vertices is modified by the factor $1/2$ in p_{sol} :

$$\epsilon = \frac{1}{2} N^{2c_1} (1 - (C')^2)^{d/2} N^{\rho - \rho_0}, \quad (13)$$

where ρ_0 satisfies $N^{\rho_0} = \mathcal{V}_d(\beta) / \mathcal{W}_d(\beta, \theta')$. The expected number of solutions per filter is

$$N^\zeta = \frac{1}{2} N^{2c} (1 - (C')^2)^{d/2}. \quad (14)$$

The time to find one marked vertex is

$$T_1 = \mathcal{S} + \frac{1}{\sqrt{\epsilon}} \left(\frac{1}{\sqrt{\delta}} \mathcal{U} + \mathcal{C} \right). \quad (15)$$

The time for the FINDALLSOLUTIONS subroutine is

$$\text{FAS}_1 = \max\{N^\zeta, 1\} \cdot T_1. \quad (16)$$

The total time of one QRW 2-sieve call is

$$T_{\text{QRW}} = \text{NbRep}_{\text{QRW}} \cdot (N + N^{1-c} \cdot \text{FAS}_1), \quad (17)$$

where

$$\text{NbRep}_{\text{QRW}} = \max\{1, N^{c-\zeta+o(1)}\}. \quad (18)$$

The derived parameters are:

$$\log_2 \sin(\alpha) = -(1-c) \cdot n, \quad (19)$$

$$\log_2 \sin(\beta) = (c_2 - c_1) \cdot n, \quad (20)$$

$$\theta' = \arccos(C'), \quad (21)$$

$$\rho_0 = \frac{\log_2 \mathcal{V}_d(\beta) - \log_2 \mathcal{W}_d(\beta, \theta')}{n d}, \quad (22)$$

$$\zeta = 2c + \frac{\log_2 p_{\text{sol}}}{n d}. \quad (23)$$

5.2 QRW 2-sieve on the standard 2-sieve problem

We first verify the framework by reproducing the result of [1, Theorem 1] for the standard 2-sieve problem. In this case, the list size is N (i.e., $n = 0.2075$), the threshold is θ_α^* with $p_{\text{sol}} = \mathcal{V}_d(\theta_\alpha^*)$, and the optimal parameters are

$$c \approx 0.3696, \quad c_1 \approx 0.2384, \quad c_2 = 0, \quad \rho \rightarrow 0. \quad (24)$$

With these values:

$$\log_2 \sin(\alpha) = -0.1308, \quad \alpha \approx 1.1514 \text{ rad}, \quad (25)$$

$$\log_2 \sin(\beta) = -0.0495, \quad \beta \approx 1.313 \text{ rad}, \quad (26)$$

$$\theta_\alpha^* \approx 1.158 \text{ rad}, \quad \rho_0 \approx 0.106, \quad \zeta \approx 0.132. \quad (27)$$

The QRW costs are:

$$\mathcal{S} = N^{0.2384}, \quad \mathcal{U} = N^{o(1)}, \quad \delta = N^{-0.2384}, \quad \epsilon = N^{-0.2364}. \quad (28)$$

Then $T_1 \approx N^{0.2384}$, $\text{FAS}_1 = N^{0.3704}$, and

$$T_{\text{QRW}} \approx N^{1.2384} = 2^{0.2570d+o(d)}, \quad (29)$$

which matches [1, Theorem 1].

5.3 QRW 2-sieve for the first two inner calls

We now apply the framework to the first two inner calls of the 4-sieve at the minimal-memory configuration of [2, Proposition 17]: $|L| = 2^{0.1724d}$, $\alpha_0 \approx 1.3131$ rad, and balanced configuration $C_{ij} = -1/4$ for $i \neq j$. The residual list size is $|L_i| = 2^{0.1229d}$. The threshold is

$$C'_{12}(\alpha_0) = \frac{-1/4 + \cos^2(1.3131)/3}{\sin^2(1.3131)} \approx -0.244. \quad (30)$$

The solution probability is

$$p_{\text{sol}} = \frac{1}{2}(0.9405)^{d/2} = \frac{1}{2} \cdot 2^{-0.0443d}. \quad (31)$$

For the combined list $N_1 = 2|L_i|$ with $n_1 = 0.1229$, we have $\log_{N_1} p_{\text{sol}} \approx -0.360$. We optimise the QRW parameters. The optimal choice in the plateau region is

$$c = 0.3, \quad c_1 = 0.13, \quad c_2 = 0, \quad \rho = 0. \quad (32)$$

With these values, we compute the collision parameter carefully. We have

$$\log_2 \sin(\beta) = (c_2 - c_1) \cdot n_1 = -0.13 \cdot 0.1229 = -0.0160, \quad (33)$$

$$\cos^2(\beta) \approx 0.0219, \quad (34)$$

$$1 + \cos(\theta') = 1 - 0.244 = 0.756, \quad (35)$$

$$\log_2 \mathcal{W}_d(\beta, \theta')/d = \frac{1}{2} \log_2 \left(1 - \frac{2\cos^2(\beta)}{1+\cos(\theta')} \right) = -0.0431, \quad (36)$$

$$\rho_0 = \frac{-0.0160 - (-0.0431)}{0.1229} \approx 0.2205. \quad (37)$$

The marked fraction is therefore

$$\epsilon = N_1^{2c_1 + \zeta - 2c + \rho - \rho_0} = N_1^{0.26 - 0.360 - 0.2205} = N_1^{-0.3205}. \quad (38)$$

The remaining quantities are

$$\zeta = 2(0.3) - 0.360 = 0.240, \quad (39)$$

$$T_1 = N_1^{0.13} + N_1^{0.1603}(N_1^{0.065} + 1) \approx N_1^{0.2253}, \quad (40)$$

$$\text{FAS}_1 = N_1^{0.240} \cdot N_1^{0.2253} = N_1^{0.4653}, \quad (41)$$

$$\text{NbRep}_{\text{QRW}} = N_1^{0.3 - 0.240} = N_1^{0.060}, \quad (42)$$

$$T_{\text{QRW}} = N_1^{0.060}(N_1 + N_1^{0.7} \cdot N_1^{0.4653}) \approx N_1^{1.2253}. \quad (43)$$

Converting: $T_{12} = T_{34} = 2^{0.1506d + o(d)} \approx 2^{0.151d}$.

Remark 1 (Optimisation over c_1). *The exponent T_{12} depends only weakly on c in the plateau region $0.2 \lesssim c \lesssim 0.4$; the choice $c = 0.3$ is representative. A numerical optimisation over c_1 with $c_2 = 0$, $\rho = 0$ shows that the exponent decreases monotonically as $c_1 \rightarrow 0$, reaching $T_{12} \approx 2^{0.145d}$ in the limit, but c_1 must remain strictly positive for the Johnson graph to contain vertices with at least two elements. The value $c_1 = 0.13$ used here is a conservative choice that lies well inside the valid regime.*

5.4 QRW 2-sieve for the third inner call

We now analyse the third inner call in detail. The combined list size is $N_3 = 2|L_{12}|$ where

$$|L_{12}| = |L_i|^2(1 - C'_{12}(\alpha_0)^2)^{d/2} = 2^{0.2015d}. \quad (44)$$

So $n_3 = 0.2015$. The effective threshold is

$$C_{\text{eff}} = \frac{\sin^2(\alpha_0)}{2(2 + 2C_{12})} - 1 = \frac{0.9338}{3} - 1 = -0.6887. \quad (45)$$

The target angle is $\theta' = \arccos(-0.6887) \approx 2.330$ rad. The solution probability is

$$p_{\text{sol}} = \frac{1}{2}(0.5257)^{d/2} = \frac{1}{2} \cdot 2^{-0.4638d}. \quad (46)$$

In N_3 -units,

$$\log_{N_3} p_{\text{sol}} = \frac{-0.4638}{0.2015} \approx -2.302. \quad (47)$$

Thus

$$\zeta = 2c - 2.302. \quad (48)$$

Since $c \leq 1$, we have $\zeta \leq -0.302 < 0$ for *every* admissible parameter choice. Consequently, $\max\{\zeta, 0\} = 0$, and the QRW repetition count becomes

$$\text{NbRep}_{\text{QRW}} = N_3^{c - \zeta} = N_3^{c - (2c - 2.302)} = N_3^{2.302 - c}. \quad (49)$$

We now choose specific parameters for the comparison. We take

$$c = 0.37, \quad c_1 = 0.26, \quad c_2 = 0.26, \quad \rho = 0. \quad (50)$$

With $c_2 = c_1$, we have $\beta = \pi/2$, so $\rho_0 = 0$. The marked fraction is

$$\epsilon = N_3^{2c_1 + \zeta - 2c + \rho - \rho_0} = N_3^{0.52 - 2.302 - 0.74} = N_3^{-1.782}. \quad (51)$$

Note that here we have used the relation $\log_{N_3} p_{\text{sol}} = \zeta - 2c$, which is essential: substituting $p_{\text{sol}} = N^{-2c}$ is only valid when $\zeta = 0$. The time to find one marked vertex is

$$\begin{aligned} T_1 &= N_3^{0.26} + N_3^{0.891}(N_3^{0.26} + 1) \\ &= N_3^{0.26} + N_3^{1.151} \approx N_3^{1.151}. \end{aligned} \quad (52)$$

Since $\zeta < 0$, we have $\text{FAS}_1 = T_1 = N_3^{1.151}$. The repetition count is

$$\text{NbRep}_{\text{QRW}} = N_3^{0.37+1.562} = N_3^{1.932}. \quad (53)$$

Finally, the total time of the third QRW call is

$$\begin{aligned} T_{\text{QRW}} &= N_3^{1.932} (N_3 + N_3^{0.63} \cdot N_3^{1.151}) \\ &= N_3^{1.932} (N_3 + N_3^{1.781}) \approx N_3^{3.713}. \end{aligned} \quad (54)$$

Converting: $T_{1234} = 2^{3.713-0.2015d+o(d)} = 2^{0.748d+o(d)}$.

This is far worse than the Grover-based third call, which is $2^{0.1722d}$. In fact, the lower bound derived from $\zeta < 0$ shows that *any* QRW parameters give at least $2^{0.464d}$, so the QRW is fundamentally inefficient for the third call.

Remark 2 (Lower bound for the third call). *The lower bound is obtained by taking the most favourable admissible parameters $c = 1$, $c_1 = 0$, $c_2 = 0$, $\rho = 0$. Then $\zeta = -0.302$, $\epsilon = N_3^{-2.302}$, $T_1 = N_3^{0.302}$, $\text{NbRep}_{\text{QRW}} = N_3^{1.302}$, and*

$$T_{\text{QRW}} \geq N_3^{2.302} = 2^{0.464d+o(d)}. \quad (55)$$

5.5 Combined complexity and comparison

Using the optimised QRW times $T_{12} = T_{34} = 2^{0.151d}$ and keeping Grover for the third call, we obtain

$$T(\text{FAS}_4) = 2 \cdot 2^{0.151d} + 2^{0.1722d} \approx 2^{0.1722d}. \quad (56)$$

Substituting into the outer 4-sieve framework with $\text{NbRep}_{\alpha_0, C} = 2^{0.1069d}$ and $1/\mathcal{V}(\alpha_0) = 2^{0.0484d}$:

$$\begin{aligned} T_{4\text{-sieve}} &= 2^{0.1069d} (2^{0.1724d} + 2^{0.0484d} \cdot 2^{0.1722d}) \\ &= 2^{0.1069d} (2^{0.1724d} + 2^{0.2206d}) \approx 2^{0.3275d}. \end{aligned} \quad (57)$$

This is essentially the same as the Grover-only case $T = 2^{0.3276d}$. If instead we use QRW for all three calls, we obtain

$$T(\text{FAS}_4) = 2 \cdot 2^{0.151d} + 2^{0.748d} \approx 2^{0.748d}, \quad (58)$$

and hence

$$T_{4\text{-sieve}} = 2^{0.1069d} (2^{0.1724d} + 2^{0.0484d} \cdot 2^{0.748d}) \approx 2^{0.903d}, \quad (59)$$

which is far worse than the Grover-based 4-sieve of [2, Proposition 17].

5.6 Resource summary

Algorithm	Time	QRAM [†]	Quantum memory [‡]	Classical memory
[1] full QRW 2-sieve	$2^{0.2570d}$	$2^{0.0767d}$	$2^{0.0495d}$	$2^{0.2075d}$
[2] Grover-only 4-sieve	$2^{0.3276d}$	$2^{0.1724d}$	$\text{poly}(d)$	$2^{0.1724d}$
Ours (QRW $\times$ 2, Grover)	$2^{0.3275d}$	$2^{0.1724d}$	$2^{0.0160d}$	$2^{0.1724d}$
Ours (QRW $\times$ 3)	$2^{0.903d}$	$2^{0.0369d}$ §	$2^{0.0160d}$	$2^{0.1724d}$

Table 1: Comparison of quantum SVP algorithms in the QRAM model. [†] QRAM denotes quantum-accessible classical memory (QRACM) for the outer list L and the inner data structures. [‡] Quantum memory denotes the number of coherent qubits used for the superposition of vertices. [§] In the all-QRW variant, the outer prefiltering still requires QRACM of size $2^{0.1724d}$; the value $2^{0.0369d}$ is the QRAM of the inner QRW data structures alone.

Our adapted QRW 2-sieve, when combined with the Grover-based third inner call inside the 4-sieve framework of [2], achieves the same running time $2^{0.3275d+o(d)}$ as the

4-sieve variant	Time	QRACM	Quantum memory	Classical memory
[2] Grover inner 2-sieve	$2^{0.3276d}$	$2^{0.1229d} *$	$\text{poly}(d)$	$2^{0.1724d}$
Ours (QRW inner 2-sieve)	$2^{0.3275d}$	$2^{0.1229d} *$	$2^{0.0160d}$	$2^{0.1724d}$

Table 2: Effect of replacing the Grover inner 2-sieve of [2] by the adapted QRW 2-sieve.

* The inner calls search over the residual lists R_i of size $2^{0.1229d}$, so the inner QRACM is $2^{0.1229d}$ in both cases. The outer 4-sieve additionally stores the pre-prefiltering list L of size $2^{0.1724d}$ in classical memory.

Grover-only 4-sieve, and the same outer QRACM of size $2^{0.1724d+o(d)}$. The inner 2-sieve calls now use QRW data structures of size $2^{0.0369d+o(d)}$ and quantum memory of size $2^{0.0160d+o(d)}$, at the cost of introducing $2^{0.0160d+o(d)}$ coherent qubits, which the Grover-only variant does not require. Compared with the full QRW 2-sieve of [1], this constitutes a new point in the time–QRAM–quantum-memory trade-off space: time $2^{0.3275d}$ instead of $2^{0.2570d}$, but with total QRAM $2^{0.1724d}$ instead of $2^{0.0767d}$ and quantum memory $2^{0.0160d}$ instead of $2^{0.0495d}$.

6 Discussion

The adaptation presented above preserves the core structure of the QRW 2-sieve of [1]. We have optimised the QRW parameters for the first two inner calls, obtaining $c = 0.3$, $c_1 = 0.13$, $c_2 = 0$, $\rho = 0$, which gives $T_{12} = T_{34} = 2^{0.151d+o(d)}$. This already accounts for the correct value of the collision parameter $\rho_0 \approx 0.2205$, which must be computed from the configuration threshold $\theta' = \arccos(C')$ rather than from the QRW’s own α . A more aggressive optimisation with $c_1 \rightarrow 0$ gives $T_{12} \approx 2^{0.145d}$, but the qualitative conclusion is unchanged.

For the third inner call, we have shown that the QRW is fundamentally inefficient. The effective threshold $C_{\text{eff}} \approx -0.689$ is so restrictive that the solution probability is exponentially small:

$$p_{\text{sol}} = \frac{1}{2} \cdot 2^{-0.4638d}, \quad (60)$$

which in N_3 -units gives $\log_{N_3} p_{\text{sol}} \approx -2.302$. Since $\zeta = 2c - 2.302 < 0$ for every admissible $c \leq 1$, the repetition count is always exponentially large. Even with the best possible parameters ($c = 1$, $c_1 = 0$, $\rho = 0$), the QRW time is at least $2^{0.464d}$, far worse than Grover’s $2^{0.1722d}$.

References

- [1] A. Chailloux and J. Loyer. Lattice sieving via quantum random walks. In *ASIACRYPT 2021*, 2021.
- [2] A. Chailloux and J. Loyer. Classical and quantum 3 and 4-sieves to solve SVP with low memory. In *PQCrypto 2023*, pp. 225–255, 2023.