


# DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning

Chenye Wang

Feb 18, 2025

# Introduction to Reinforcement Learning

- Reinforcement Learning is concerned with how an intelligent **agent** should take actions in an **environment** to maximize the cumulative reward.



# RL example

**Agent:** the cat

**State:** the position of the cat (x, y) in the grid


**Action:** at each position, the cat can move to one of the 4-directionally connected cells. If a move is invalid, the cell will not move and remain in the same position. Every time the cat makes a move, it results in a new state and a reward.

**Reward model:**

- A move to another empty cell results in a reward of 0.
- A move towards the broom, will result in a reward of -1.
- A move towards the bathtub will result in a reward of -10 and the cat fainting (episode over). The cat will be respawned at the initial position again.
- A move towards the meat will result in a reward of +100

**Policy:** a policy rules how the agent selects the action to perform given the state it is in:  
 $a_t \sim \pi(\cdot | s_t)$

**The goal in RL is to select a policy that maximizes the expected return when the agent acts according to it.**



# RL: connection to language models

**Agent:** the language model itself


**State:** the prompt (input tokens)

**Action:** which token is selected as the next token

**Reward model:** the language model should be rewarded for generating "good responses" and should not receive any reward for generating "bad responses".


**Policy:** In the case of language models, the policy is the language model itself! Because it models the probability of the action space given the current state of the agent:  $a_t \sim \pi(\cdot | s_t)$

**Let's look at how we can define the reward model for our language model**




# DeepSeek-R1-Zero

- Our goal is to explore the potential of LLMs to develop reasoning capabilities **without any supervised fine-tuning(SFT) data(time-intensive to gather)**, focusing on their **self-evolution through a pure RL process**.
- This approach allows the model to explore chain-of-thought (CoT) for solving complex problems.



# RL Algorithm -- Group Relative Policy Optimization

- Value model brings a substantial memory and computational burden.



# RL Algorithm -- Group Relative Policy Optimization

Specifically, for each question  $q$ , GRPO samples a group of outputs  $\{o_1, o_2, \dots, o_G\}$  from the old policy  $\pi_{\theta_{old}}$  and then optimizes the policy model  $\pi_{\theta}$  by maximizing the following objective:

$$\mathcal{J}_{GRPO}(\theta) = \mathbb{E}[q \sim P(Q), \{o_i\}_{i=1}^G \sim \pi_{\theta_{old}}(O|q)]$$
$$\frac{1}{G} \sum_{i=1}^G \left( \min \left( \frac{\pi_{\theta}(o_i|q)}{\pi_{\theta_{old}}(o_i|q)} A_i, \text{clip} \left( \frac{\pi_{\theta}(o_i|q)}{\pi_{\theta_{old}}(o_i|q)}, 1 - \varepsilon, 1 + \varepsilon \right) A_i \right) - \beta \mathbb{D}_{KL}(\pi_{\theta} || \pi_{ref}) \right), \quad (1)$$

$$\mathbb{D}_{KL}(\pi_{\theta} || \pi_{ref}) = \frac{\pi_{ref}(o_i|q)}{\pi_{\theta}(o_i|q)} - \log \frac{\pi_{ref}(o_i|q)}{\pi_{\theta}(o_i|q)} - 1, \quad (2)$$

where  $\varepsilon$  and  $\beta$  are hyper-parameters, and  $A_i$  is the advantage, computed using a group of rewards  $\{r_1, r_2, \dots, r_G\}$  corresponding to the outputs within each group:

$$A_i = \frac{r_i - \text{mean}(\{r_1, r_2, \dots, r_G\})}{\text{std}(\{r_1, r_2, \dots, r_G\})}. \quad (3)$$

# Reward Modeling

- The reward is the source of the training signal, which decides the optimization direction of RL.
- DeepSeek-R1-Zero adopts a *rule-based* reward system that mainly consists of two types of rewards:
  - **Accuracy rewards:** math problems, LeetCode problems
  - **Format rewards:** avoid content-specific biases, align with human preferences




# Performance

- The findings underscore the model’s ability to learn and generalize effectively through RL alone.

Model	AIME 2024		MATH-500	GPQA Diamond	LiveCode Bench	CodeForces
	pass@1	cons@64	pass@1	pass@1	pass@1	rating
OpenAI-o1-mini	63.6	80.0	90.0	60.0	53.8	1820
OpenAI-o1-0912	74.4	83.3	94.8	77.3	63.4	1843
DeepSeek-R1-Zero	71.0	86.7	95.9	73.3	50.0	1444


Table 2 | Comparison of DeepSeek-R1-Zero and OpenAI o1 models on reasoning-related benchmarks.



# Self-evolution Process & Aha Moment

- To maximize the cumulative reward, RL drives a model to improve its reasoning capabilities autonomously.

DeepSeek-R1-Zero average length per response during training



---

Question: If  $a > 1$ , then the sum of the real solutions of  $\sqrt{a - \sqrt{a + x}} = x$  is equal to

---

Response: <think>

To solve the equation  $\sqrt{a - \sqrt{a + x}} = x$ , let's start by squaring both ...

$$\left(\sqrt{a - \sqrt{a + x}}\right)^2 = x^2 \implies a - \sqrt{a + x} = x^2.$$

Rearrange to isolate the inner square root term:

$$(a - x^2)^2 = a + x \implies a^2 - 2ax^2 + (x^2)^2 = a + x \implies x^4 - 2ax^2 - x + (a^2 - a) = 0$$

...

**Wait, wait. Wait. That's an aha moment I can flag here.**

Let's reevaluate this step-by-step to identify if the correct sum can be ...

We started with the equation:

$$\sqrt{a - \sqrt{a + x}} = x$$

First, let's square both sides:

$$a - \sqrt{a + x} = x^2 \implies \sqrt{a + x} = a - x^2$$

Next, I could square both sides again, treating the equation: ...

...

---

Table 3 | An interesting “aha moment” of an intermediate version of DeepSeek-R1-Zero. The model learns to rethink using an anthropomorphic tone. This is also an aha moment for us, allowing us to witness the power and beauty of reinforcement learning.

# DeepSeek-R1 pipeline

- **Cold Start:** construct and collect a small amount of long CoT data to fine-tune the model as the initial RL actor
- **Reasoning-oriented RL:** focus on enhancing the model's reasoning capabilities, particularly in reasoning-intensive tasks
- **Rejection Sampling and SFT:** incorporate data from other domains
- **RL for all Scenarios:** train the model using a combination of reward signals and diverse prompt distributions

# Distillation: Smaller Models Can Be Powerful Too

- Using the reasoning data generated by DeepSeek-R1 to fine-tuned small dense models yields excellent results.
- Smaller models relying on the large-scale RL require enormous computational power and may not even achieve the performance of distillation.

Model	AIME 2024		MATH-500	GPQA Diamond	LiveCodeBench
	pass@1	cons@64	pass@1	pass@1	pass@1
QwQ-32B-Preview	50.0	60.0	90.6	54.5	41.9
DeepSeek-R1-Zero-Qwen-32B	47.0	60.0	91.6	55.0	40.2
DeepSeek-R1-Distill-Qwen-32B	72.6	83.3	94.3	62.1	57.2

Table 6 | Comparison of distilled and RL Models on Reasoning-Related Benchmarks.

# Conclusion

- DeepSeek-R1 shows the power and beauty of RL: we simply provide models **with the right incentives**, they can **autonomously develops** advanced problem-solving strategies.
- Iterative training is a better way for reasoning models.
- While distillation is both economical and effective, advancing beyond the boundaries of intelligence may still require more powerful base models and larger\_scale reinforcement learning.